# INITIAL RUN-ON AND RUN-OFF CONTROL PLAN 40 C.F.R. PART 257.81 HUFFAKER ROAD (PLANT HAMMOND) PRIVATE INDUSTRIAL LANDFILL (HUFFAKER ROAD LANDFILL) GEORGIA POWER COMPANY

EPA's "Disposal of Coal Combustion Residuals from Electric Utilities" Final Rule (40 C.F.R. Part 257 and Part 261), §257.81, requires the owner or operator of an existing or new CCR landfill or any lateral expansion of a CCR landfill to prepare a run-on and run-off control system plan to document how these control systems have been designed and constructed to meet the applicable requirements of this section of the rule.

The CCR landfill known as the Huffaker Road Landfill is located in Floyd County, west of Rome, Georgia on Plant Hammond property. Huffaker Road Landfill is comprised of Active Cells A, B and E, and future Cells C & D. Cells A & B were recently retrofitted with composite liners. Cell E was permitted and constructed with a minimum 2-ft. compacted clay liner. The facility consists of the CCR storage cells, a leachate pond for Cells A&B, and separate storm water runoff ponds and clear pools. Future Cells C & D will also be constructed in the same manner as Cells A and B.

The storm water flows have been calculated using the Natural Resources Conservation Service (NRCS) method (also known as the Soil Conservation Service (SCS) method) using the 25-yr/100-yr, 24-hr storm event. The storm water detention system has been designed in accordance with the Georgia Soil and Water Conservation Commission requirements as well as other local, city, and government codes. The post developed storm water discharge was designed to be less than the pre-developed storm water discharge in accordance with the requirements of the State of Georgia.

Storm basin calculation data was determined from the existing topography and from the Urban Hydrology for Small Watersheds (TR-55). This site is located in a Type II Rainfall Distribution. Precipitation values were determined from Technical Paper No. 40 (TP-40), "Rainfall Frequency Atlas of the United States, 1961" and NOAA Atlas 14.

The NRCS provides information on soil characteristics and hydrologic groups present at the site. It was determined that the hydrological group "B" should be used to best reflect the characteristics of the soils

on site. This information was placed into Hydraflow Hydrographs 2011 and used to generate appropriate precipitation curves, runoff curve numbers and storm basin runoff values.

Huffaker Road Landfill Cells are designed and constructed with perimeter berms and drainage ditches around the cells that prevent stormwater run-on during the peak discharge of a 24-hr, 25-yr storm from flowing onto the active portion of the landfill. The leachate pond collects and controls the anticipated amount of leachate generated from the leachate collection system of Cells A&B over a period of 7 days as well as the quantity of rainfall from a 24-hr, 100-yr storm event that falls directly into the leachate pond. Storm water run-off from the Cells A&B and E is routed through sedimentation/clarifying ponds designed to handle the run-off from a 24-hr, 100-yr storm. This plan is supported by appropriate engineering calculations which are attached.

The facility is operated subject to and in accordance with § 257.3-3 of EPA's regulations.

I hereby certify that the run-on and run-off control system plan meets the requirements of 40 C.F.R. Part 257.81.

James C. Pegues, P.

Acensed State of Georgia, PE No. 17419

# Run-on and Run-off Control System Plan for Landfills: Calculation Summary

for

## Plant Hammond Huffaker Road Parcels A and B

Prepared by:

Southern Company Services Technical Services

Originator:

Curtis R. Upchurch

Date

Reviewer:

Jason S. Wilson

Date

Approval:

James C. Pegues

Date

## 1.0 Purpose of Calculation

The purpose of this report is to demonstrate the run-on and run-off controls of the Plant Hammond Huffaker Road Landfill Parcels A and B in order to prepare a run-on and run-off control system plan as required by the United States Environmental Protection Agency's (EPA) final rule for Disposal of Coal Combustion Residuals (CCR) from Electric Utilities (EPA 40 CFR 257).

## 2.0 Summary of Conclusions

#### 2.1 Site Overview

The Plant Hammond Huffaker Road Landfill Parcels A and B is located on Georgia Power Company property on Huffaker Road approximately 4 miles northeast of Plant Hammond and 1 mile northwest of Rome, Georgia. The total area occupied by Huffaker Road Landfill Parcels A and B is 37.8 acres. Table 1 below does not include the areas for perimeter ditches and roads which are included in the total area of 37.8 acres. There are no off-site areas draining into the parcels or the sediment pond and clear pool downstream and only stormwater run-off from rain falling directly in the cell, ponds and aggregate surfaced perimeter roads must be collected and controlled. Parcels A and B are lined with a 24 inch clay layer and 60 mil hdpe liner. Stormwater run-off from the active portion of the Parcels (ash contact water) is collected in an underdrain leachate system and sump and then pumped into a lined leachate collection pond. Water from this leachate pond is reused for ash conditioning in the active portion of the parcels or will be transported to the Plant for treatment. Stormwater run-off from the non-active areas of the parcels (aggregate roads, soil cover grassed areas above stacked ash and areas covered with an HDPE rain flap) is routed thru the cell and perimeter ditches into the sediment basin and clear pool. From the clear pool it is then discharged into a rip rap lined ditch at the southwest corner of the cell which outfalls into Smith Creek just east of the clear pool.

An overview of Huffaker Road Landfill Parcels A and B is provided in Table 1 below.

Table 1 – Huffaker Road Landfill Parcels A and B Site Characteristics

Pond	Storage Cells	Sedimentation	Clear Pool	Leachate Pond
Description		Pond		
Size (Acres)	29.1	4.6	0.6	0.7
Outlet Type	12' Flat bottom ditch, S=4.0%, w/2.5:1 S.S.	48" Riser with 36" dia. outlet pipe CMP	48" Riser w/ 36" dia. outlet pipe CMP	20' Trapezoidal Spillway, 6:1 S.S., (Control Structure – No Discharge)
Outlets To	Sedimentation Pond	Clear Pool	Ditch to Smith Creek	Ditch to Smith Creek

## 2.2 Run-on Control System Plan

There is no stormwater run-on into Parcels A and B due to the construction of perimeter berm/roads at the outer boundaries. Any run-off that was directed to the parcel areas was diverted by the initial design which now prevents any water

encroachment. For further information on this hydraulic design, see SCS Calculation No. C-HM-01208-01, Plant Hammond, Huffaker Road Coal Combustion By-Products Storage Site, 9/27/04.

## 2.3 Run-off Control System Plan

A hydrologic and hydraulic model was developed for the Huffaker Road Landfill Parcels A and B to determine the hydraulic capacity of the parcels. The design storm for the purposes of run-off control system plans is the 24-hour, 25-year rainfall event. The results of routing the design storm event through the landfill are presented in Table 2 below:

Table 2-Flood Routing Results for Huffaker Road Landfill Parcels A and B

Plant Hammond	Normal Pool El	Top of embankment	Peak Water Surface	Freeboard* (ft)	Peak Inflo	Peak Outflow
	(ft)	El (ft)	Elevation (ft)		w (cfs)	(cfs)
Parcels A and B	No pool	Varies Low Pt. @ EL. 654.75	N/A No ponding in cell	Parcel outlet d = 1.2 ft. Outlet to Sed. Pond d = 1.3 ft.	N/A	207 (Parcels) 254 (Parcels & Perim. Ditch)

<sup>\*</sup>Freeboard is measured from the top of embankment to the peak water surface elevation

## 3.0 Methodology

#### 3.1 HYDROLOGIC ANALYSES

The design storm for all run-on/run-off analyses is a 24-hour, 25-year rainfall event. A summary of the design storm parameters and rainfall distribution methodology for these calculations is summarized below in Table 3.

Table 3. Huffaker Road Landfill Parcels A and B Design Storm Distribution

Return	Storm	Rainfall	Rainfall	Storm
Frequency	Duration	Total	Source	Distribution
(years)	(hours)	(Inches)		
25	24	6.32	NOAA Atlas	SCS Type II
			14	• •

The drainage area for the Huffaker Road Landfill Parcels A and B was delineated based on LiDAR data acquired for the Plant in 2015. Run-off characteristics were developed based on the Soil Conservation Service (SCS) methodologies as outlined in TR-55. An overall SCS curve number for the drainage area was developed based on methods prescribed in TR-55. Soil types were obtained from the Natural Resources Conservation Service. Land use areas were delineated based on aerial photography. Time of

Concentration calculations were also developed based on methodologies prescribed in TR-55.

A table of the pertinent basin characteristics of the landfill is provided below in Table(s) 4(a) through 4(c).

Table 4(a) - Landfill Hydrologic Information (Parcels A and B)

Drainage Basin Area (acres)	26.7 (29.1 less active face area)
Hydrologic Curve Number, CN	96
Hydrologic Methodology	SCS Method
Time of Concentration (minutes)	8.9
Hydrologic Software	Hydraflow Hydrographs

Table 4(a) - Landfill Hydrologic Information (Perimeter Road & Ditches)

Drainage Basin Area (acres)	2.78
Hydrologic Curve Number, CN	74
Hydrologic Methodology	SCS Method
Time of Concentration (minutes)	21.3
Hydrologic Software	Hydraflow Hydrographs

Table 4(c) - Landfill Hydrologic Information (Sediment Pond & Clear Pool Areas)

Drainage Basin Area (acres)	5.2
Hydrologic Curve Number, CN	96
Hydrologic Methodology	SCS Method
Time of Concentration (minutes)	5.0
Hydrologic Software	Hydraflow Hydrographs

Run-off characteristics were developed based on the Soil Conservation Service (SCS) methodologies as outlined in TR-55. An overall SCS curve number for the drainage area was developed based on the National Engineering Handbook Part 630, Chapter 9 which provides a breakdown of curve numbers for each soil type and land use combination. Soil types were obtained from the USGS online soils database. Time of Concentration calculations were developed based on the overland flow method as described in the National Engineering Handbook Part 630, Chapter 15.

Run-off values were determined by importing the characteristics developed above into a hydrologic model in Hydraflow Hydrographs Extension of AutoCad Civil 3D, 2013.

## 3.2 HYDRAULIC ANALYSES

Storage values for the sediment pond, clear pool, and leachate pond were determined by developing a stage-storage relationship utilizing contour data. With the outlet spillway in the perimeter berm of Parcel A and B landfill water cannot pool in the storage area and therefore a stage storage curve was not developed for the landfill. Instead, the outlet was checked for depth of flow and velocity during the 25 year storm and the resultant freeboard noted. See section 4.4 of this summary. The spillway systems for both the Sediment Pond and the Clear Pool consist of a primary spillway and an auxiliary spillway. The primary spillways are 48" diameter vertical risers and have a sharp crested weir length of 12.6-feet. Each riser has a 36-inch diameter corrugated

metal outlet pipe. The auxiliary spillways are trapezoidal spillways in the dikes lined with Recyclex TRM matting and grassed. A summary of spillway information is presented below in Tables 5(a) and 5(b).

Table 5(a)—Sediment Pond Spillway Attribute Table

Spillway	US Invert	DS	Dimension	Slope	Length	Spillway
Component	El (feet)	Invert El		(ft/ft)	(ft)	Capacity
		(feet)				(cfs)
Primary	643.0	642.7	36" Dia. CMP (48" Dia. riser)	0.006	60.0	70.7
Auxiliary	648.5	648.5	Trapezoidal Crest L=20', 3:1 S.S.	0.000	20.0	122.4

Table 5(b)—Clear Pool Spillway Attribute Table


Spillway Component	US Invert El (feet)	DS Invert EI (feet)	Dimension	Slope (ft/ft)	Length (ft)	Spillway Capacity (cfs)
Primary	642.0	641.35	36" Dia. CMP (48" Dia. riser)	0.01	65.0	79.0
Auxiliary	648.0	648.0	Trapezoidal Crest L=20', 3:1 S.S.	0.000	20.0	188.4

Based on the spillway attributes listed above, a rating curve was developed and inserted into Hydraflow Hydrographs software to analyze pond performance during the design storm. Results are shown in Table 1.


## 4.0 SUPPORTING INFORMATION

## 4.1 CURVE NUMBER


## 4.1.1 PARCELS A AND B (RAINFLAP COVERED AREA)



## 4.1.2 PERIMETER DITCHES AND ROADS



## 4.1.3 POND AREAS



## 4.2 STAGE-STORAGE TABLE

## 4.2.1 SEDIMENT POND

Pond Name	Sediment Pond 1					X
Row	Stage	Elevation	Contour Area	Incremental Storage	Total Storage	Total Discharge
	(ft)	(ft)	(sqft)	(cuft)	(cuft)	(cfs)
0	0.00	642.00	3,113	0.000	0.000	0.000
1	1.00	643.00	30,855	16,984	16,984	0.000
2	2.00	644.00	80,928	55,892	72,876	0.000
3	3.00	645.00	137,926	109,427	182,303	0.000
4	4.00	646.00	162,280	150,103	332,406	0.000
5	5.00	647.00	168,474	165,377	497,783	0.000
6	6.00	648.00	174,708	171,591	669,374	0.000
7	7.00	649.00	180,981	177,845	847,218	60.24
8	8.00	650.00	187,294	184,138	1,031,356	166.26
9						
10						
11						
12						
13						
14						
15						
16						
17						
18						
19						
20						

## 4.2.2 CLEAR POOL

ond Name	Clear Pool #1					X
Row	Stage	Elevation	Contour Area	Incremental Storage	Total Storage	Total Discharge
	(ft)	(ft)	(sqft)	(cuft)	(cuft)	(cfs)
0	0.00	642.00	1,268	0.000	0.000	0.000
1	1.00	643.00	15,306	8,287	8,287	0.000
2	2.00	644.00	17,082	16,194	24,481	0.000
3	3.00	645.00	18,464	17,773	42,254	0.000
4	4.00	646.00	19,885	19,175	61,429	0.000
5	5.00	647.00	21,345	20,615	82,044	0.000
6	6.00	648.00	22,845	22,095	104,139	40.90
7	7.00	649.00	24,384	23,615	127,753	111.25
8	8.00	650.00	25,962	25,173	152,926	216.25
9						
10						
11						
12						
13						
14						
15						
16						
17						
18						
19						
20						

## 4.3 TIME OF CONCENTRATION

Sheet Flow Equation	Channel Flow Equation				
00021000000000000000000000000000000000	5000500035000503775K				
Tc = (0.007 * ((n * Lf)^0.8)) / ((P^0.5) * (Sf^0.4))	$V = (1.49 * (R^{(2/3)}) * (Sf^{0.5})) / n$				
	R = Aq / Wp				
Where:	Tc = (Lf / V) / (3600 sec/hr)				
Tc = Time of Concentration (hrs)					
n = Manning's Roughness	Where:				
Lf = Flow Length (ft)	Tc = Time of Concentration (hrs)				
P = 2 yr, 24 hr Rainfall (inches)	Lf = Flow Length (ft)				
Sf = Slope (ft/ft)	R = Hydraulic Radius (ft)				
	Aq = Flow Area (ft <sup>s</sup> )				
Shallow Concentrated Flow Equation	Wp = Wetted Perimeter (ft)				
	<pre>V = Velocity (ft/sec)</pre>				
V = 16.1345 * (Sf^0.5) (unpaved surface)	Sf = Slope (ft/ft)				
V = 20.3282 * (Sf^0.5) (paved surface)	n = Manning's Roughness				
V = 15.0 * (Sf^0.5) (grassed waterway surface)					
V = 10.0 * (Sf^0.5) (nearly bare & untilled surface)	Water Travel Velocity Equation				
V = 9.0 * (Sf^0.5) (cultivated straight rows surface)					
V = 7.0 * (Sf^0.5) (short grass pasture surface)	$V = (g*D)^0.5$				
V = 5.0 * (Sf^0.5) (woodland surface)	Tc = ((Lf / V) /60sec/min)				
V = 2.5 * (Sf^0.5) (forest w/heavy litter surface)					
Tc = (Lf / V) / (3600 sec/hr)	Where:				
	Tc = Time of Concentration (hrs)				
Where:	D = Mean Depth (ft)				
Tc = Time of Concentration (hrs)	g = Gravitational Constant (32.2 ft/sec)				
Lf = Flow Length (ft)	Lf = Flow Length (ft)				
V = Velocity (ft/sec)	R = Hydraulic Radius (ft)				
Sf = Slope (ft/ft)	V = Velocity (ft/sec)				

## 4.3.1 RAINFLAP COVERED AREA (PARCELS A AND B), Tc:

	Hydr	aflow H	lydrographs Ex	densid	on for AutoCAI	D® Civ	3DB 2013 by Autodesk, Inc. v10
Hyd. No. 1							
Post-Dev (RainFlap on Parcel	Bot.)						
Description	A		<u>B</u>		<u>c</u>		<u>Totals</u>
Sheet Flow							
Manning's n-value	= 0.013		0.011		0.011		
Flow length (ft)	= 0.0		0.0		0.0		
Two-year 24-hr precip. (in)	= 0.00		0.00		0.00		
Land slope (%)	= 0.00		0.00		0.00		
Travel Time (min)	= 0.00	+	0.00	+	0.00	=	0.00
Shallow Concentrated Flow							
Flow length (ft)	= 415.00		870.00		0.00		
Watercourse slope (%)	= 3.40		1.03		0.00		
Surface description	= Paved		Paved		Paved		
Average velocity (ft/s)	=3.75		2.06		0.00		
Travel Time (min)	= 1.85	+	7.03	+	0.00	=	8.87
Channel Flow							
X sectional flow area (sqft)	= 0.00		0.00		0.00		
Wetted perimeter (ft)	= 0.00		0.00		0.00		
Channel slope (%)	= 0.00		0.00		0.00		
Manning's n-value	= 0.015		0.015		0.015		
Velocity (ft/s)	=0.00						
			0.00				
					0.00		
Flow length (ft)	({0})0.0		0.0		0.0		
Travel Time (min)	= 0.00	+	0.00	+	0.00	=	0.00

## 4.3.2 PERIMETER ROADS AND DITCHES (PARCELS A AND B), Tc:

	Hydra	flow H	lydrographs E	xtensio	n for AutoCA	D® Civ	I 3D® 2013 by Autodesk, Inc. v1
Hyd. No. 2							
Post-Dev (Perim. Rd & Ditche	s)						
<u>Description</u>	A		В		<u>c</u>		<u>Totals</u>
Sheet Flow							
Manning's n-value	= 0.150		0.011		0.011		
Flow length (ft)	= 65.0		0.0		0.0		
Two-year 24-hr precip. (in)	= 3.80		0.00		0.00		
Land slope (%)	= 2.00		0.00		0.00		
Travel Time (min)	= 6.37	+	0.00	+	0.00	=	6.37
Shallow Concentrated Flow							
Flow length (ft)	= 0.00		0.00		0.00		
Watercourse slope (%)	= 0.00		0.00		0.00		
Surface description	= Paved		Paved		Paved		
Average velocity (ft/s)	=0.00		0.00		0.00		
Travel Time (min)	= 0.00	+	0.00	+	0.00	=	0.00
Channel Flow							
X sectional flow area (sqft)	= 1.75		0.00		0.00		
Wetted perimeter (ft)	= 5.65		0.00		0.00		
Channel slope (%)	= 1.40		0.00		0.00		
Manning's n-value	= 0.030		0.015		0.015		
Velocity (ft/s)	=2.68						
			0.00				
					0.00		
Flow length (ft)	({0})2405.0		0.0		0.0		
Travel Time (min)	= 14.94	+	0.00	+	0.00	=	14.94

## 4.3.3 POND AREAS (PARCELS A AND B), Tc:

	Hyd	raflow h	lydrographs E	xtensio	n for AutoCA	D® Civi	il 3D® 2013 by Autodesk, Inc. v1
Hyd. No. 3							
Post-Dev (Pond Areas)							2
<u>Description</u>	Δ		<u>B</u>		<u>c</u>		<u>Totals</u>
Sheet Flow							
Manning's n-value	= 0.000		0.000		0.000		
Flow length (ft)	= 0.0		0.0		0.0		
Two-year 24-hr precip. (in)	= 0.00		0.00		0.00		
Land slope (%)	= 0.00		0.00		0.00		
Travel Time (min)	= 0.00	+	0.00	+	0.00	=	0.00
Shallow Concentrated Flow							
Flow length (ft)	= 0.00		0.00		0.00		
Watercourse slope (%)	= 0.00		0.00		0.00		
Surface description	=						
Average velocity (ft/s)	=0.00		0.00		0.00		
Travel Time (min)	= 0.00	+	0.00	+	0.00	=	0.00
Channel Flow							
X sectional flow area (sqft)	= 0.00		0.00		0.00		
Wetted perimeter (ft)	= 0.00		0.00		0.00		
Channel slope (%)	= 0.00		0.00		0.00		
Manning's n-value	= 0.000		0.000		0.000		
Velocity (ft/s)	=0.00						
			0.00				
					0.00		
Flow length (ft)	({0})0.0		0.0		0.0		
Travel Time (min)	= 0.00	+	0.00	+	0.00	=	0.00

## 4.4.1 SEDIMENT POND REPORT WITH RATING CURVE:

Hydraflow H	ydrograph	s Extension f	or Auto	CAD® Civ	il 3D® 20	13 by Au	todesk, Inc. v	/10					Thursda	ay, 09 / 2	29 / 2016
all comme d	l. 4700 .	diment Po				i.									
Pond Dat	а														
		ed contour ar	eas. Ave	erage end	area me	thod used	for volume of	calculation	on. B	Begining E	Elevation = 6	342.00 ft			
Stage / St	torage I	able													
Stage (ft)	E	Elevation (ft)	y 3	Contour	area (sqf	t) In	cr. Storage	(cuft)	T	otal stor	age (cuft)				
0.00		642.00		3.11	3		0				0				
1.00		643.00		30,85	5		16,984			16,9	84				
2.00		644.00		80,92			55,892			72,8					
3.00		645.00		137,92			109,427			182,3					
4.00 5.00		646.00 647.00		162,28 168,47			150,103 165,377			332,4 497,7					
6.00		648.00		174,70			171,591			669,3					
7.00		649.00		180,98			177,845			847,2					
8.00		650.00		187,29	4		184,138			1,031,3	56				
Culvert /	Orifice !	Structures	•				Weir Str	ucture	s						
		[A]	[B]	[C]	[PrfF	Rsr]				[A]	[B]	[C]	[D]		
Rise (in)	= :	36.00	0.00	0.00	Ina	ctive	Crest Len	(ft)	= 1	2.57	20.00	0.00	0.00		
Span (in)	= :	36.00	0.00	0.00	1.00	)	Crest El. (	ft)	= 6	48.00	648.50	0.00	0.00		
No. Barrels	=	1	0	0	20		Weir Coef	f.	= 3	.33	3.33	3.33	3.33		
Invert El. (ft	) =	643.00	0.00	0.00	648	.00	Weir Type		= 1		Ciplti		-		
Length (ft)	= :	50.00	0.00	0.00	0.0	)	Multi-Stag		= Y	'es	No	No	No		
Slope (%)	= (	0.60	0.00	0.00	n/a										
N-Value	=	.022	.013	.013	n/a										
Orifice Coe	ff. = (	0.60	0.60	0.60	0.60	)	Exfil.(in/h	r)	= 0	0.000 (by	Contour)				
Multi-Stage	= 1	n/a	No	No	No		TW Elev.	5.00	= 0	.00					
					ce outflows	are analyze	d under inlet (ic) a	nd outlet (d	oc) cor	ntrol. Weir r	isers checked f	or orifice co	nditions (ic)	and subm	ergence (s).
		Discharge													
Stage	Storage	Elevation		v A	CIV B	CIV C	PrfRsr	Wr A		Wr B	Wr C	Wr D	Exfil	User	Total
ft	cuft	ft	cf	S	cfs	cfs	cfs	cfs		cfs	cfs	cfs	cfs	cfs	cfs
0.00	0	642.00	0.0	00			0.00	0.00		0.00					0.000
1.00	16,984	643.00	0.0				0.00	0.00		0.00					0.000
2.00	72,876	644.00	0.0			399	0.00	0.00		0.00	275.				0.000
3.00 4.00	182,303 332,406	645.00 646.00	0.0				0.00	0.00		0.00					0.000
5.00	497,783	647.00	0.0				0.00	0.00		0.00					0.000
6.00	669,374	648.00	0.0				0.00	0.00		0.00					0.000
7.00	847,218	649.00		.86 oc			0.00	41.86		23.55					65.40
8.00	1,031,356	650.00	70	.73 oc			0.00	70.73	S	122.35		2.22			193.08

## 4.4.2 CLEAR POOL POND REPORT WITH RATING CURVE:

## **Pond Report**

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2013 by Autodesk, Inc. v10

Thursday, 09 / 29 / 2016

## Pond No. 2 - Clear Pool #1

#### **Pond Data**

Contours -User-defined contour areas. Average end area method used for volume calculation. Begining Elevation = 642.00 ft

#### Stage / Storage Table

Stage (ft)	Elevation (ft)	Contour area (sqft)	Incr. Storage (cuft)	Total storage (cuft)
0.00	642.00	1,268	0	0
1.00	643.00	15,306	8,287	8,287
2.00	644.00	17,082	16,194	24,481
3.00	645.00	18,464	17,773	42,254
4.00	646.00	19,885	19,175	61,429
5.00	647.00	21,345	20,615	82,044
6.00	648.00	22,845	22,095	104,139
7.00	649.00	24,384	23,615	127,753
8.00	650.00	25,962	25,173	152,926

Culvert / Ori	fice Structur	es			Weir Structures					
	[A]	[B]	[C]	[PrfRsr]		[A]	[B]	[C]	[D]	
Rise (in)	= 36.00	0.00	0.00	0.00	Crest Len (ft)	= 12.57	20.00	0.00	0.00	
Span (in)	= 36.00	0.00	0.00	0.00	Crest El. (ft)	= 647.00	648.00	0.00	0.00	
No. Barrels	= 1	0	0	0	Weir Coeff.	= 3.33	3.33	3.33	3.33	
Invert El. (ft)	= 642.00	0.00	0.00	0.00	Weir Type	= 1	Ciplti		·	
Length (ft)	= 65.00	0.00	0.00	0.00	Multi-Stage	= Yes	No	No	No	
Slope (%)	= 1.00	0.00	0.00	n/a						
N-Value	= .022	.013	.013	n/a						
Orifice Coeff.	= 0.60	0.60	0.60	0.60	Exfil.(in/hr)	= 0.000 (by	Contour)			
Multi-Stage	= n/a	No	No	No	TW Elev. (ft)	= 0.00				

Note: Culvert/Orifice outflows are analyzed under inlet (ic) and outlet (oc) control. Weir risers checked for orifice conditions (ic) and submergence (s).

Stage /	Storage / I	Discharge 1	Γable										
Stage ft	Storage cuft	Elevation ft	CIV A	CIV B	CIV C cfs	PrfRsr cfs	Wr A cfs	Wr B cfs	Wr C cfs	Wr D cfs	Exfil cfs	User cfs	Total cfs
0.00	0	642.00	0.00				0.00	0.00					0.000
1.00	8,287	643.00	0.00				0.00	0.00					0.000
2.00	24,481	644.00	0.00				0.00	0.00					0.000
3.00	42,254	645.00	0.00				0.00	0.00					0.000
4.00	61,429	646.00	0.00				0.00	0.00					0.000
5.00	82,044	647.00	0.00				0.00	0.00					0.000
6.00	104,139	648.00	41.86 oc				41.86	0.00		1777			41.86
7.00	127,753	649.00	69.79 oc				69.78 s	66.60					136.38
8.00	152,926	650.00	78.99 oc				78.98 s	188.37					267.35

13

Pond	Rep	ort												16
Hydraflow Hy	drographs	Extension fo	or Auto	CAD® Civ	il 3D® 201	3 by Au	todesk, Inc. v	10				Thursda	ay, 09 / 2	29 / 2016
Pond No.	4 - Lea	chate Pon	d											
Pond Data	ı													
Pond storage	e is base	d on user-de	fined v	alues.										
Stage / Sto	orage T	able												
Stage (ft)	E	levation (ft)	9	Contour	area (sqft)	In	cr. Storage (	cuft)	Total sto	rage (cuft)				
0.00		652.50		n/	а		0			0				
0.50		653.00		n/			487			487				
1.50 2.25		654.00 654.75		n/			4,432			919				
2.25		655.00		n/			7,348 3,624			267 891				
3.50		656.00		n/			17,775			666				
4.50		657.00		n/			22,707			373				
5.50		658.00 658.50		n/			22,707 12,297			080 377				
6.50		659.00		n/			12,930		104.					
7.50		660.00		n/	a		27,785		132,	092				
Culvert / C	rifice S	tructures					Weir Str	ucture	s					
		[A]	[B]	[C]	[PrfR	sr]			[A]	[B]	[C]	[D]		
Rise (in)	= 0	.00	0.00	0.00	0.00		Crest Len	(ft)	= 20.00	0.00	0.00	0.00		
Span (in)	= 0	.00	0.00	0.00	0.00		Crest El. (f	ft)	= 658.50	0.00	0.00	0.00		
No. Barrels	= 0		0	0	0		Weir Coeff		= 3.33	3.33	3.33	3.33		
Invert El. (ft)	= 0	.00	0.00	0.00	0.00		Weir Type		= Ciplti		-			
Length (ft)	= 0		0.00	0.00	0.00		Multi-Stage	e	= No	No	No	No		
Slope (%)	= 0		0.00	0.00	n/a									
N-Value	= .(		.013	.013	n/a									
Orifice Coeff			0.60	0.60	0.60		Exfil.(in/hr	200	= 0.000 (b)	/ Wet area)				
Multi-Stage	= n	/a	No	No	No		TW Elev. (1	ft)	= 0.00					
Stage / Sto	orage /	Discharge			ice outflows an	e analyzed	d under inlet (ic) ar	nd outlet (d	oc) control. Weir	risers checked f	or orifice co	onditions (ic)	and subme	ergence (s).
Stage :	Storage	Elevation	CI	v A	CIV B	CIV C	PrfRsr	Wr A		Wr C	Wr D	Exfil	User	Total
ft (	cuft	ft	cf	S	cfs	cfs	cfs	cfs	cfs	cfs	cfs	cfs	cfs	cfs
0.00	0	652.50						0.00						0.000
0.50	487	653.00			-		_	0.00	-			-		0.000
1.50 2.25	4,919 12,267	654.00 654.75	-					0.00						0.000
2.50	15,891	655.00						0.00						0.000
3.50	33,666	656.00						0.00			2777	-	-	0.000
4.50	56,373	657.00						0.00					223	0.000
5.50	79,080	658.00						0.00						0.000
6.00	91,377	658.50						0.00						0.000
6.50	104,307	659.00						23.55	2 C					

#### 4.5 **RESULTS**:

## 4.5.1 Hydrograph Summary

2

# Hydrograph Summary Report Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2013 by Autodesk, Inc. v10

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	206.96	3	717	530,599	\$ <del></del>	-	·	Post-Dev (RainFlap on Parcel Bot.)
2	SCS Runoff	9.672	3	726	34,002	1000000			Post-Dev (Perim. Rd & Ditches)
3	SCS Runoff	40.43	3	717	103,653			100000	Post-Dev (Pond Areas)
4	Combine	46.65	3	717	137,655	2, 3			Add
5	Combine	253.61	3	717	668,254	1, 4			Add
6	Reservoir(i)	0.000	3	n/a	0	5	647.99	668,254	Post Dev. to Ponds
8	SCS Runoff	17.95	3	717	43,976	10 <del>0000</del> 1		( <del>1000 to</del>	Active Face/Area
9	Reservoir	0.000	3	n/a	0	8	656.45	43,976	Leachate Pond
Rui	n-on Run-off_	calcs any	v	i i	Return F	Period: 25	/ear	Thursday	09 / 29 / 2016

## 4.5.2 HYDROGRAPHS:

## Rain Flap Covered Area:

Hydrograph Report

3

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2013 by Autodesk, Inc. v10


Thursday, 09 / 29 / 2016

#### Hyd. No. 1

Post-Dev (RainFlap on Parcel Bot.)

Peak discharge Hydrograph type = SCS Runoff = 206.96 cfs Time to peak Storm frequency = 25 yrs = 11.95 hrs = 3 min = 530,599 cuft Time interval Hyd. volume Drainage area = 26.670 ac Curve number = 96\* = 0.0 % = 0 ftBasin Slope Hydraulic length Tc method = TR55 Time of conc. (Tc) = 8.90 min Total precip. = 6.32 inDistribution = Type II = 484 Storm duration = 24 hrs Shape factor

<sup>\*</sup> Composite (Area/CN) = [(26.670 x 96)] / 26.670



## **Hydrograph Report**


Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2013 by Autodesk, Inc. v10

Thursday, 09 / 29 / 2016

## Hyd. No. 5

Add

Hydrograph type= CombinePeak discharge= 253.61 cfsStorm frequency= 25 yrsTime to peak= 11.95 hrsTime interval= 3 minHyd. volume= 668,254 cuftInflow hyds.= 1, 4Contrib. drain. area= 26.670 ac



## **Hydrograph Report**

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2013 by Autodesk, Inc. v10


Thursday, 09 / 29 / 2016

Hyd. No. 6

Post Dev. to Ponds

Hydrograph type = Reservoir (Interconnected) Peak discharge = 0.000 cfsStorm frequency = 25 yrs Time to peak = n/aTime interval = 3 min Hyd. volume = 0 cuft Reservoir Other Inflow hyd. = Sediment Pond 1 = Clear Pool #1 Reservoir = 5 - Add = None Inflow hyd. = 642.00 ft Max. Elevation = 647.99 ft Max. Elevation = 0 cuft Max. Storage = 668,254 cuft Max. Storage

Interconnected Pond Routing. Storage Indication method used.



## **Hydrograph Report**

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2013 by Autodesk, Inc. v10


Thursday, 09 / 29 / 2016

Hyd. No. 9

Leachate Pond

Hydrograph type = Reservoir Peak discharge = 0.000 cfsStorm frequency Time to peak = 25 yrs = n/aTime interval = 3 min Hyd. volume = 0 cuft Inflow hyd. No. = 8 - Active Face/Area Max. Elevation = 656.45 ft Reservoir name = Leachate Pond Max. Storage = 43,976 cuft

Storage Indication method used.



## 4.5.3 PARCELS A AND B OUTLET SPILLWAY:

## **Channel Report**

Hydraflow Express Extension for AutoCAD® Civil 3D® 2013 by Autodesk, Inc.


Sunday, Sep 25 2016

## Parcels A&B Outlet

Trapezoidal Bottom Width (ft) = 12.00 Side Slopes (z:1) = 2.00, 2.00 Total Depth (ft) = 1.75 Invert Elev (ft) = 653.00 Slope (%) = 1.00 N-Value = 0.012

Calculations Compute by: Known Q (cfs) Known Q = 207.00 Highlighted

Depth (ft) = 1.18 = 207.00 Q (cfs) Area (sqft) = 16.94 Velocity (ft/s) Wetted Perim (ft) = 12.22 = 17.28 Crit Depth, Yc (ft) Top Width (ft) = 1.75 = 16.72 EGL (ft) = 3.50



# 4.5.4 PARCELS A AND B AND PERIMETER DITCH DISCHARGE DITCH TO SEDIMENT POND:


## Channel Report

Hydraflow Express Extension for AutoCAD® CIVII 3D® 2D13 by Autodesk, Inc. Sunday, Sep 25 2D16


#### Parcels A&B with Perim Dt. Outlet into Sediment Pond

Trapezoidal		Highlighted	
Bottom Width (ft)	= 16.00	Depth (ft)	= 1.16
Side Slopes (z:1)	= 2.50, 2.50	Q (cfs)	= 254.00
Total Depth (ft)	= 2.50	Area (sqft)	= 21.92
Invert Elev (ft)	= 649.00	Velocity (ft/s)	= 11.59
Slope (%)	= 5.60	Wetted Perim (ft)	= 22.25
N-Value	= 0.030	Crit Depth, Yc (ft)	= 1.80
		Top Width (ft)	= 21.80
Calculations		EGL (ft)	= 3.25

Compute by: Known Q Known Q (cfs) = 254.00



## 4.6 DRAINAGE BASIN



# Run-on and Run-off Control System Plan for Landfills: Calculation Summary

for

## Plant Hammond Huffaker Road Landfill Parcel E

Prepared by:

Southern Company Services Technical Services

Originator:

Curtis R. Upchurch

Date

Reviewer:

James C. Pegues

Date

## 1.0 Purpose of Calculation

The purpose of this report is to demonstrate the run-on and run-off controls of the Plant Hammond Huffaker Road Landfill in order to prepare a run-on and run-off control system plan as required by the United States Environmental Protection Agency's (EPA) final rule for Disposal of Coal Combustion Residuals (CCR) from Electric Utilities (EPA 40 CFR 257).

## 2.0 Summary of Conclusions

## 2.1 Site Overview

The Plant Hammond Huffaker Road Landfill Parcel E is located on Georgia Power Company property on Huffaker Road approximately 4 miles northeast of Plant Hammond and 1 mile northwest of Rome, Georgia. The total area occupied by the CCR landfill is 27.38 acres. There are no off-site areas draining into the cell or the sediment pond and clear pool downstream and only stormwater run-off from rain falling directly in the cell, ponds and aggregate surfaced perimeter roads must be collected and controlled. Stormwater is routed thru the cell and perimeter ditches into the sediment basin and clear pool and is then discharged into a ditch at the southwest corner of the cell. The ditch outfalls into Smith Creek located approximately 200 feet south of the clear pool.

An overview of Huffaker Road Landfill Parcel E is provided in Table 1 below.

Table I - Hulla	Nei Noau Lanunii	raicei L Sile Charac	teristics
Pond Description	Parcel E	Sedimentation	Clear Pool
		Pond	
Size (Acres)	23.42	2.87	1.09
Outlet Type	12' Flat bottom	48" Riser	48" Riser
	ditch, S=4.0%,	connected to a	connected to a
	w/2.5:1 S.S.	36" CMP	36" CMP
Outlets To	Sedimentation	Clear Pool	Ditch to Smith
	Pond		Creek

Table 1 – Huffaker Road Landfill Parcel E Site Characteristics

## 2.2 Run-on Control System Plan

There is no contributory stormwater run-on into Parcel E because a series of perimeter ditches, spillways, and roadways prevent overland flow from migrating into the Cell, Sediment Basin No. 3, and Clear Pool No. 3. Reference the Plant Hammond Huffaker Road CCB Storage Facility - Parcel E Run-on / Run-off Study calculations (Calc No. DC-HM-HAM16037-002) for information.

## 2.3 Run-off Control System Plan

A hydrologic and hydraulic model was developed for the Huffaker Road Landfill Parcel E to determine the hydraulic capacity of the Cell. The design storm for the purposes of run-off control system plans is the 24-hour, 25-year rainfall event. The results of routing the design storm event through the landfill are presented in Table 2 below:

Table 2-Flood Routing Results for Huffaker Road Landfill Parcel E

Plant	Normal	Top of	Peak Water	Freeboard	Peak	Peak
Hammond	Pool El	embankment	Surface	* (ft)	Inflow	Outflow
	(ft)	El (ft)	Elevation	, ,	(cfs)	(cfs)
	, ,	, ,	(ft)		, ,	
Parcel E	No pool	633.00	627.18	5.82	119.32	4.74

<sup>\*</sup>Freeboard is measured from the top of embankment to the peak water surface elevation

## 3.0 Methodology

#### 3.1 HYDROLOGIC ANALYSES

The design storm for all run-on/run-off analyses is a 24-hour, 25-year rainfall event. A summary of the design storm parameters and rainfall distribution methodology for these calculations is summarized below in Table 3.

Table 3. Huffaker Road Landfill Parcel E Design Storm Distribution

Return Frequency (years)	Storm Duration (hours)	Rainfall Total (Inches)	Rainfall Source	Storm Distribution
25	24	6.32	NOAA Atlas 14	SCS Type II

The drainage area for the Huffaker Road Landfill Parcel Ewas delineated based on LiDAR data acquired for the Plant in 2015. Run-off characteristics were developed based on the Soil Conservation Service (SCS) methodologies as outlined in TR-55. An overall SCS curve number for the drainage area was developed based on methods prescribed in TR-55. Soil types were obtained from the Natural Resources Conservation Service. Land use areas were delineated based on aerial photography. A conservative time of concentration was assumed as there are not any contributory drainage areas or overland flow beyond simply the footprint of the Cell, Sediment Basin No. 3 and Clear Pool No. 3.

A table of the pertinent basin characteristics of the landfill is provided below in Table.

Table 4—Landfill Hydrologic Information (Parcel E)

Drainage Basin Area (acres)	27.38
Hydrologic Curve Number, CN (weighted)	77
Hydrologic Methodology	SCS Method
Time of Concentration (minutes)	6
Hydrologic Software	Bentley Pond Pack

Run-off values were determined by importing the surface characteristics into a hydrologic model within Bentley's Pond Pack software.

#### 3.2 HYDRAULIC ANALYSES

Storage values for the landfill were determined by developing a stage-storage relationship utilizing contour data. The spillway system at the Huffaker Road Landfill Parcel E consists of a primary spillway from the Cell proper draining into Sediment Basin No. 3. The primary spillway is a trapezoidal rip rap weir that drains the Cell's perimeter ditch into Sediment Basin No. 3.

The Sediment Basin No. 3 drainage system consists of a primary 48" diameter corrugated metal riser (with trash rack) with a top elevation of 630.00. This riser is drained by a 60 foot long - 36" diameter corrugated metal culvert that discharges into Clear Pool No. 3. A 20-foot wide trapezoidal auxiliary spillway also handles overflow from Sediment Basin No. 3 into Clear Pool No. 3.

The Clear Pool No. 3 drainage system consists of a primary 48" diameter corrugated metal riser (with trash rack) with a top elevation of 629.00. This riser is drained by an 86 foot long - 36" diameter corrugated metal culvert that discharges into a swale that feeds into Smith Creek. A 20 foot wide emergency trapezoidal spillway also handles overflow from Clear Pool No. 3 into the same swale that feeds into Smith Creek.

A summary of spillway information is presented below in Table 5.

Table 5—Spillway Attribute Table\*

Spillway	US	DS	Dimension (ft)	Slope	Length	Spillway
Component	Invert	Invert El		(%)	(ft)	Capacity
	EI	(feet)				(cfs)
	(feet)					
Cell Spillway	632.00	630.00	12	4.0	20	N/A**
Sed. Basin No. 3	000.00	000.70	4 ft (diameter)	0.00	N 1 / A	N1/0
riser	630.00	623.70	6.75 ft (height)	0.00	N/A	N/A
Sed. Basin No. 3	00400	000.70	0 (1 / 1 )	0.50	00	N 1 / A
culvert	624.00	623.70	3 ft (diameter)	0.50	60	N/A
Sed. Basin No. 3			20 ft (Tap width)			
emergency	631.00	631.00	30 ft (Top width) 20 ft (Bottom Width)	0.00	15.5	N/A
spillway			20 it (20ttom Width)			
Clear Pool No. 3	629.00	622.00	4 ft (diameter)	0.00	N/A	N/A
riser	029.00	022.00	7 ft (height)	0.00	IN/A	IN/A
Clear Pool No. 3	622.00	620.00	3 ft (diameter)	2.33	86.0	N/A
culvert	022.00	020.00	on (diameter)	2.33	00.0	IN/A
Clear Pool No. 3			22 ft (Tap width)			
emergency	631.00	631.00	32 ft (Top width) 20 ft (Bottom Width)	0.00	20.5	N/A
spillway						

<sup>\*</sup>All spillway design information can be found on Drawing H9155.

Based on the spillway attributes listed above, a rating curve was developed and inserted into Pond Pack Detention Pond Design and Modeling Software, Haested Methods, Inc. to analyze pond performance during the design storm. Results are shown in Table 2.

<sup>\*\*</sup>N/A = Not available

## 4.0 SUPPORTING INFORMATION

## 4.1 CURVE NUMBER

## 4.1.1 CELL E AND SEDIMENT BASIN NO. 3

RUNOFF CURVE NUMBER DATA			::::::::::	:::::::::
		3	Impervious	* 33 a
Soil/Surface Description	CN	acres	Adjustment %C %UC	CN
Direct Pond Runoff & Drainage Area Stacking Area E	99	3.400		99.00 74.00
COMPOSITE AREA & WEIGHTED CN>			:::::::::	
S/N: 321F01F2E1C6 SOUTHERN COMPAN PondPack Ver: Com	NY pute Ti	me:	Date:	
Comp.	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		2444	
4.1.2 CLEAR POOL NO. 3				
RUNOFF CURVE NUMBER DATA				
***************************************				
Soil/Surface Description	CN		Impervious Adjustment %C %UC	
Direct Runoff to Clear Pool		1.000		99.00
COMPOSITE AREA & WEIGHTED CN>				99.00 (99)
S/N: 321F01F2E1C6 SOUTHERN COMPAN PondPack Ver: Comp	NY oute Ti	me:	Date:	

## 4.2 STAGE-STORAGE TABLE 4.2.1 SEDIMENT BASIN NO. 3

Type.... Vol: Elev-Volume Page 8.02

Name.... SED POND 3

File.... C:\Haestad\Huffaker1\SEDPOND3.PPW

## USER DEFINED VOLUME RATING TABLE

Elevation (ft)	Volume (ac-ft)
624.00	.130
625.00	.760
626.00	2.140
627.00	4.040
628.00	6.080
629.00	8.210
630.00	10.410
631.00	12.690
632.00	15.060
633.00	17.510

S/N: 321F01F2E1C6 SOUTHERN COMPANY

PondPack Ver: Compute Time: Date:

## 4.2.2 CLEAR POOL NO. 3

Type.... Vol: Elev-Volume Page 8.01

Name.... CLEAR POOL 3

File.... C:\Haestad\Huffaker1\SEDPOND3.PPW

## USER DEFINED VOLUME RATING TABLE

Elevation (ft)	Volume (ac-ft)
622.00	.000
623.00	.360
624.00	.910
625.00	1.510
626.00	2.140
627.00	2.810
628.00	3.530
629.00	4.290
630.00	5.090

S/N: 321F01F2E1C6 SOUTHERN COMPANY

PondPack Ver: Compute Time: Date:

#### 4.3 TIME OF CONCENTRATION

A conservative time of concentration was assumed as there are not any contributory drainage areas or overland flow impacting the Cell, Sediment Basin No. 3 and Clear Pool No. 3. A Time of Concentration of 6 minutes or 0.10 hours was assumed.

#### 4.4 **RESULTS**

4.4.1 PARCEL E

25-YEAR, 24-HOUR STORM EVENT

Type.... ICPM Node Routing Summary Page 10.10 Name.... SED POND 3 Tag: Dev 25 Event: 25 yr

File.... C:\Haestad\Huffaker1\SEDPOND3.PPW

Storm... TypeII 24hr Tag: Dev 25

#### ICPM POND ROUTING SUMMARY

HYG Dir = C:\Haestad\Huffaker1\ Inflow HYG file = SED POND 3 IN Dev 25 Outflow HYG file = SED POND 3 OUT Dev 25

Pond Node Data = SED POND 3 Pond Volume Data = SED POND 3 Pond Outlet Data = OUTLET 3

No Infiltration

INITIAL CONDITIONS

Starting WS Elev = 626.00 ft Target Convergence= .200 cfs +/Starting Volume = 2.140 ac-ft Max. Iterations = 35 loops
Starting Outflow = .00 cfs ICPM Time Step = .0500 hrs
Output Time Step = .0500 hrs
ICPM Ending Time = 35.0000 hrs

#### MAXIMUM STORAGE

14.7500 620 Tp, hrs Elev, ft Vol, ac-ft -----628.68 7.533

	FORWARD FI	LOW PEAKS	REVERSE FL	OW PEAKS
	Tp, hrs	Qp, cfs	Tp, hrs	Qp, cfs
Pond Inflow	12.0500	119.32	.0000	.00
Pond Outflow	13.5500	4.74	.0000	.00

	TOTAL VOLU	UME IN	TOTAL VOL	UME OUT
	Vol, ac-ft	Direction	Vol, ac-ft	Direction
Pond Inflow	8.517	Forward	.000	Reverse
Pond Outflow	.000	Reverse	6.264	Forward

#### MASS BALANCE (ac-ft)

+ Initial Vol	2.140		
+ Total Vol IN	8.517		
- Total Vol OUT	6.264		
<ul> <li>Ending Pond Vol.</li> </ul>	4.444	< (At 35.0000 hrs Elev.= 627.20 ft	:)

Difference..... -.050 ac-ft (.590% of Inflow Volume)

## 4.4.2 PARCEL E 100-YEAR, 24-HOUR STORM EVENT

+ Initial Vol.... 2.140 + Total Vol IN.... 11.117 - Total Vol OUT... 8.146 - Ending Pond Vol. 5.191

Difference.....

Type.... ICPM Node Routing Summary Page 10.12 Name.... SED POND 3 Tag: Dev100 Event: 100 yr File.... C:\Haestad\Huffaker1\SEDPOND3.PPW Storm... TypeII 24hr Tag: Dev100 ICPM POND ROUTING SUMMARY = C:\Haestad\Huffaker1\ Inflow HYG file = SED POND 3 IN Dev100 Outflow HYG file = SED POND 3 OUT Dev100 Pond Node Data = SED POND 3 Pond Volume Data = SED POND 3 Pond Outlet Data = OUTLET 3 No Infiltration INITIAL CONDITIONS CALCULATION TOLERANCES ----------Starting WS Elev = 626.00 ft Target Convergence= .200 cfs +/Starting Volume = 2.140 ac-ft Max. Iterations = 35 loops
Starting Outflow = .00 cfs ICPM Time Step = .0500 hrs
Output Time Step = .0500 hrs
ICPM Ending Time = 35.0000 hrs -----MAXIMUM STORAGE Tp, hrs Elev, ft Vol, ac-ft ------14.3000 629.44 9.177 FORWARD FLOW PEAKS REVERSE FLOW PEAKS Tp, hrs Qp, cfs Tp, hrs Qp, cfs 154.84 .0000 Pond Inflow.... 12.0500 .0000 .00 Pond Outflow.... 13.6000 6.59 .0000 .00 TOTAL VOLUME IN TOTAL VOLUME OUT Vol, ac-ft Direction Vol, ac-ft Direction ..... Pond Inflow..... 11.117 Forward .000 Reverse Pond Outflow.... .000 Reverse 8.146 Forward MASS BALANCE (ac-ft) -----

5.191 <-- (At 35.0000 hrs Elev.= 627.56 ft)

-.080 ac-ft (.723% of Inflow Volume)

## 4.5 DRAINAGE BASIN

