

**Georgia Power Company  
Plant Yates – Ash Pond 1**

**Newnan, Georgia  
Coweta County**

**2019 SEMIANNUAL  
GROUNDWATER MONITORING AND  
CORRECTIVE ACTION REPORT**



**ATLANTIC COAST  
CONSULTING, INC.**



## CERTIFICATION STATEMENT

This 2019 Second Semiannual Groundwater Monitoring & Corrective Action Report, Georgia Power Company - Plant Yates Ash Pond 1 has been prepared in compliance with Georgia Environmental Protection Division Rules for Solid Waste Management 39-3-41 (b) by a qualified groundwater scientist or engineer with:

**ATLANTIC COAST CONSULTING, INC.**

A handwritten signature in black ink that reads 'William M. Malone'.

William M. Malone  
Project Scientist



Evan B. Perry, P.E.  
Project Manager  
Date: 2019-02-27



## TABLE OF CONTENTS

| Section  | Page No. |
|--|----------|
| 1.0 INTRODUCTION .....   | 1        |
| 1.1 Site Description and Background .....                              | 1        |
| 1.2 Site Geology and Hydrogeologic Setting.....                        | 1        |
| 1.3 Groundwater Monitoring Well Network and CCR Unit Description ..... | 2        |
| 2.0 GROUNDWATER MONITORING ACTIVITIES.....                             | 2        |
| 2.1 Monitoring Well Installation/Maintenance.....                      | 3        |
| 2.2 Detection Monitoring Program .....                                 | 3        |
| 2.3 Initial Assessment Monitoring.....                                 | 3        |
| 3.0 SAMPLE METHODOLOGY AND ANALYSIS.....                               | 3        |
| 3.1 Groundwater Flow Direction, Gradient, and Velocity .....           | 3        |
| 3.2 Groundwater Sampling.....  | 4        |
| 3.3 Laboratory Analyses.....   | 4        |
| 3.4 Quality Assurance and Quality Control.....                         | 5        |
| 4.0 STATISTICAL ANALYSIS.....  | 5        |
| 4.1 Statistical Methods .....  | 6        |
| 4.2 Statistical Analyses Results – Appendix III.....                   | 6        |
| 4.3 Appendix IV Background Data .....                                  | 7        |
| 4.3 Statistical Analyses – Appendix IV .....                           | 7        |
| 5.0 MONITORING PROGRAM STATUS .....                                    | 7        |
| 6.0 CONCLUSIONS AND FUTURE ACTIONS.....                                | 7        |
| 7.0 REFERENCES .....   | 8        |

### Tables

- Table 1A – Monitoring Network Well Summary
- Table 1B – Non-Network Well Summary
- Table 2 – Groundwater Sampling Event Summary
- Table 3A – Summary of Groundwater Elevations – August 2019
- Table 3B – Summary of Groundwater Elevations – October 2019
- Table 4 – Groundwater Flow Velocity Calculations – October 2019
- Table 5 – Summary of Groundwater Monitoring Parameters
- Table 6A – Summary of Groundwater Analytical Data – August 2019
- Table 6B – Summary of Groundwater Analytical Data – October 2019
- Table 7 – Statistical Method Summary

## Figures

Figure 1 – Site Location Map

Figure 2 – AP-1 Well Location Map

Figure 3 – October 2019 Water Table Contour Map

## Appendices

Appendix A – Monitoring Well Installation Report

Appendix B – Laboratory Analytical and Field Sampling Reports

Appendix C – Statistical Analyses

## 1.0 INTRODUCTION

In accordance with the United States Environmental Protection Agency (US EPA) Coal Combustion Residuals (CCR) rule (Rule 40 Code of Federal Regulations [(CFR)] 257 Subpart D) and the Georgia Environmental Protection Division (GA EPD) Rules of Solid Waste Management 391-3-4-.10, Atlantic Coast Consulting, Inc. (ACC) has prepared this Semiannual Groundwater Monitoring Report to document groundwater monitoring activities at Georgia Power Company's (GPC's) Plant Yates AP-1 (Site). To specify groundwater monitoring requirements, GA EPD rule 391-3-4-.10(6)(a) incorporates by reference the United States Environmental Protection Agency (US EPA) Coal Combustion Residuals (CCR) Rule 40 Code of Federal Regulations (CFR) § 257 Subpart D. For ease of reference, the US EPA CCR rules are cited within this report. For ease of reference, the US EPA CCR rules are cited within this report.

Groundwater monitoring and reporting for CCR units is performed in accordance with the monitoring requirements §§ 257.90 through 257.95 of the Federal CCR rule and the Georgia EPD rule 391-3-4-.10(6)(a)-(c). This report documents the two monitoring events conducted during this monitoring period: (1) an initial assessment monitoring event in August 2019 as a result of statistical exceedances during the first detection monitoring event, and (2) the subsequent assessment event conducted in October 2019, which served as the second semiannual compliance monitoring event for the year.

### 1.1 Site Description and Background

Plant Yates is located at 708 Dyer Road, on the east bank of the Chattahoochee River in Coweta County, Georgia near the Coweta and Carroll County line, approximately 8 miles northwest of the city of Newnan and 13 miles southeast of the city of Carrollton. Plant Yates occupies approximately 2,400 acres. Figure 1, Site Location Map, depicts the site location relative to the surrounding area.

AP-1 was closed by-removal; the CCR material was removed from AP-1 to an onsite landfill. A permit application to comply with EPD Rules was submitted in November 2018 and is currently under review. Semiannual reporting is completed pursuant to 391-3-4-.10(6)(c).

### 1.2 Site Geology and Hydrogeologic Setting

Plant Yates is located in the Inner Piedmont Physiographic Province of western Georgia, immediately southeast of the regional zone of deformation referred to as the Brevard Zone. Rock units at Plant Yates are primarily interlayered gneiss and schists. The rocks in the area have been subjected to several episodes of metamorphism and intrusion by igneous bodies. Extensive jointing occurs in the area. Surface expressions of the joints are observed on topographic maps and aerial photos of the Plant Yates area.

A thin layer of soil from one to two feet thick overlies a thick layer of saprolite. The saprolite, which extends to typical depths of 20-40 feet below ground surface, was formed in-place by the physical and chemical weathering of the underlying metamorphic rocks. There is typically a zone of variable thickness (approximately 5-20 feet) of transitionally weathered rock between the saprolite and competent bedrock. Localized alluvial soils consisting of generally coarser material (silty-sand, clayey silt, and silty clay with well-rounded gravel and cobbles) than that observed in saprolite may be related to historical river channel migration.

At Plant Yates, groundwater is typically encountered slightly above the saprolite/weathered rock interface. Groundwater flow in the saprolite zone is through interconnected pores and relict textures and fractures. As the rock becomes increasing competent with depth groundwater flow occurs mainly through joints and fractures (i.e. secondary porosity). Recharge to the water-bearing zones in fractured bedrock takes place by seepage through the overlying mantle of soil/saprolite, or by direct entrance through openings in outcrops. The average depth of the water table at Plant Yates varies with topography, ranging from approximately 5 to 50 feet below ground surface. The water table occurs in the saprolite and in the transitionally weathered zone, at least several feet above the top of rock.

In-situ slug tests were performed in saprolite and weathered bedrock at multiple locations on the site. The hydraulic conductivity at these locations is typically in a range from  $10^{-3}$  to  $10^{-4}$  centimeters per second, based on multiple rising-head and falling-head slug tests. This indicates a fairly uniform medium across the saprolite and weathered rock horizon. The values from the field test fall within the standard range of hydraulic conductivity values associated with a silty sand.

### **1.3 Groundwater Monitoring Well Network and CCR Unit Description**

Pursuant to § 257.91, a groundwater monitoring system was installed within the uppermost aquifer at the CCR Unit AP-1. The monitoring system is designed to monitor groundwater passing the waste boundary of the CCR Units within the uppermost aquifer. Figure 2, Well Location Map, shows the monitoring well locations. Wells were located to serve as upgradient and downgradient monitoring points based on groundwater flow direction (Table 1A, Monitoring Network Well Summary, and Table 1B, Non-Network Well Summary).

Based on the site hydrogeology, the monitoring system is designed to monitor groundwater flow in the overburden, the transition-zone, and the upper bedrock as a single inter-connected aquifer system. Wells suffixed with an “S” are installed in overburden (saprolitic soil), an “I” indicates partially weathered rock (transition zone), and “D” indicates upper bedrock. The monitoring well network for the Site is provided on Figure 2, Well Location Map.

## **2.0 GROUNDWATER MONITORING ACTIVITIES**

Pursuant to 40 CFR § 257.90(e), the following describes monitoring-related activities performed in the second half of 2019. All groundwater sampling was performed in accordance with § 257.93. Samples were collected from each well in the certified monitoring system shown on Figure 2.

Based on results of the 2019 Annual Groundwater and Corrective Action Monitoring Report, assessment monitoring was initiated at the site. Table 2, Groundwater Sampling Event Summary, summarizes groundwater events conducted at AP-1 during the second half of 2019. During the initial assessment monitoring event completed in August 2019 groundwater samples were collected and analyzed for Appendix IV constituents to meet the requirement of § 257.95(b). During the October 2019 semiannual (assessment) sampling event, groundwater samples were collected for both Appendix III and the Appendix IV constituents detected during the August 2019 event.

## **2.1 Monitoring Well Installation/Maintenance**

Monitoring well-related activities were limited to visual inspection of well conditions prior to sampling, recording the site conditions, and performing exterior maintenance to provide safe access for sampling.

Downgradient monitoring network wells were installed along the downgradient waste boundary pursuant to § 257.91(a)(2). In November 2019 two additional wells (YAMW-6 and YAMW-7) were installed to further characterize groundwater conditions in the vicinity of well YGWC-46. Details regarding the well are included on Table 1B and locations presented on Figure 2. Installation details for these locations are provided in Appendix A, Well Installation Report.

## **2.2 Detection Monitoring Program**

In accordance with § 257.94(b), the detection groundwater monitoring program was implemented by collecting 8 background groundwater samples. In addition, a 9<sup>th</sup> round of groundwater samples was collected from the CCR monitoring wells as the initial detection monitoring event. Groundwater samples were collected from each monitoring well and analyzed for Appendix III constituents according to § 257.94(a). The background study and the initial detection monitoring event were documented in the 2019 Annual Groundwater Monitoring & Corrective Action Report, dated July 31, 2019.

## **2.3 Initial Assessment Monitoring**

Statistically Significant Increases (SSI) of Appendix III constituents were identified in the initial detection monitoring event (March 2019). Pursuant to § 257.94(e)(1), GPC implemented assessment monitoring in accordance with § 257.95. The initial assessment monitoring event was conducted from August 20 - 21, 2019. Pursuant to § 257.95(b), the CCR monitoring wells were sampled for the full suite of Appendix IV constituents during the initial assessment event. Following receipt of the initial Appendix IV sample results, the 2019 second semiannual monitoring event/assessment monitoring event was conducted October 8 - 9, 2019. Pursuant to § 257.95(d)(1), Groundwater samples collected from the CCR monitoring wells were analyzed for Appendix III constituents and those Appendix IV constituents detected during the initial assessment event in August.

## **3.0 SAMPLE METHODOLOGY AND ANALYSIS**

The following sections describe the methods used to conduct groundwater monitoring at the Site.

### **3.1 Groundwater Flow Direction, Gradient, and Velocity**

Prior to each sampling event, groundwater elevations were recorded from the certified well network and piezometers at the Site. Groundwater elevations recorded during the October 2019 monitoring event are summarized in Table 3, Summary of Groundwater Elevations – October 2019. The general direction of groundwater flow across the site is towards the west. The groundwater flow patterns observed during the October 2019 monitoring event are consistent with historical patterns.

The groundwater flow velocity at Plant Yates was calculated using a derivation of Darcy's Law. Specifically:

### Equation

$$v = \frac{K(dh/dl)}{P_e} \quad \text{where:} \quad \begin{array}{l} v = \text{ground water velocity} \\ K = \text{hydraulic conductivity} \\ dh/dl = \text{hydraulic gradient} \\ P_e = \text{effective porosity} \end{array}$$

Groundwater flow velocities were calculated for the site based on hydraulic gradients, average hydraulic conductivity based on previous slug test data, and an estimated effective porosity of 0.20 (based on a review of several sources, including Driscoll, 1986; US EPA, 1989; Freeze and Cherry, 1979). Groundwater flow velocities have been calculated and are tabulated on Table 4, Groundwater Flow Velocity Calculations – October 2019. The calculated flow velocity is 1.4 feet per day or 505 feet per year.

### **3.2 Groundwater Sampling**

Groundwater samples were collected using low-flow sampling procedures in accordance with 40 CFR § 257.93(a). Purging and sampling was performed using a dedicated bladder pump in each well.

Monitoring wells were purged and sampled using low-flow sampling procedures. A SmarTroll (In-Situ field instrument) was used to monitor and record field water quality parameters (pH, conductivity, and dissolved oxygen) during well purging to verify stabilization prior to sampling. Turbidity was measured using a Hach 2100Q portable turbidimeter. Groundwater samples were collected when the following stabilization criteria were met:

- $\pm 0.1$  standard units for pH
- $\pm 10\%$  for specific conductance
- $\pm 10\%$  for DO where DO > 0.5 mg/L. No criterion applies if DO < 0.5 mg/L.
- Turbidity measurements less than 10 nephelometric turbidity units (NTU)

Once stabilization was achieved, samples were collected directly into appropriately preserved laboratory-supplied sample containers. Sample bottles were placed in ice-packed coolers and submitted to Pace Analytical Services, LLC (Pace) of Peachtree Corners, Georgia following chain-of-custody protocol. Stabilization logs for each sample are included in Appendix B, Laboratory Analytical and Field Sampling Reports.

### **3.3 Laboratory Analyses**

Groundwater samples collected in October 2019 for the semiannual monitoring event were analyzed for Appendix III constituents, and those Appendix IV constituents detected in the initial assessment monitoring event (August 2019). Constituents not detected during the initial assessment event and were not analyzed during the subsequent semiannual event in accordance with 257.95(d)(1). Appendix IV parameters not detected above the laboratory MDL during the initial assessment event included: antimony, beryllium, chromium, fluoride lead, mercury, and selenium. Table 5, Summary of Groundwater Monitoring Parameters, presents a summary of the constituents monitored during the semiannual event.

Analytical data collected in monitoring events from the second half of 2019 (August 2019 and October 2019) are summarized in Table 6A, Summary of Groundwater Analytical Data – August 2019, and Table 6B, Summary of Groundwater Analytical Data – October 2019, respectively.

Laboratory analyses were performed by Pace. Pace is accredited by the National Environmental Laboratory Accreditation Program (NELAP) and maintains a NELAP certification for all parameters analyzed for this project. In addition, Pace is certified to perform analysis by the State of Georgia. Laboratory reports and chain-of-custody records for the monitoring events are presented in Appendix B.

### 3.4 Quality Assurance and Quality Control

During each sampling event, quality assurance/quality control samples (QA/QC) are collected at a rate of one QA/QC sample per every 10 groundwater samples. Equipment blanks (where non-dedicated sampling equipment is used) and duplicate samples were collected during each sampling event. QA/QC sample data was evaluated during data validation and is included in Appendix B.

Groundwater quality data in this report was validated in accordance with US EPA guidance (US EPA, 2011) and the analytical methods. Data validation generally consisted of reviewing sample integrity, holding times, laboratory method blanks, laboratory control samples, matrix spikes/matrix spike duplicate recoveries and relative percent differences, post digestions spikes, laboratory and field duplicate RPDs, field and equipment blanks, and reporting limits. Where appropriate, validation qualifiers and flags are applied to the data using US EPA procedures as guidance (US EPA, 2017).

Values followed by a "J" flag indicate that the value is an estimated analyte concentration detected between the method detection limit (MDL) and the laboratory reporting limit (PQL). The estimated value is positively identified but is below the lowest level that can be reliably achieved within specified limits of precision and accuracy under routine laboratory operating conditions. "J" flagged data are used to establish background statistical limits but are not used when performing statistical analyses.

## 4.0 STATISTICAL ANALYSIS

Statistical analysis of groundwater monitoring data was performed on samples collected from the certified groundwater monitoring network pursuant to § 257.93(f) and following the statistical analysis plan. The statistical method used at the site was developed by Groundwater Stats Consulting, LLC (GSC), in accordance with 40 CFR § 257.93(f) using methodology presented in *Statistical Analysis of Groundwater Data at RCRA Facilities, Unified Guidance*, March 2009, US EPA 530/R-09-007 (US EPA, 2009). To develop the statistical method, analytical data collected during the background period were evaluated and used to develop statistical limits for each Appendix III parameter. Subsequent detection monitoring results were compared to the statistical limits to determine if concentrations were statistically different from background.

Pursuant to § 257.95(d)(2) GPC will establish groundwater protection standards for the Appendix IV monitoring parameters and complete statistical analysis of the Appendix IV groundwater monitoring data obtained during the first semiannual assessment monitoring event within 90 days of obtaining the results. GPC will complete the assessment monitoring and statistical

analysis in accordance with § 257.95 and report the results in the Annual Groundwater Monitoring and Corrective Action Report, due August 1, 2020.

#### 4.1 Statistical Methods

Sanitas groundwater statistical software was used to perform the statistical analyses at the site. Sanitas is a decision support software package that incorporates the statistical tests required of Subtitle C and D facilities by US EPA regulations and guidance as recommended in the Unified Guidance (US EPA, 2009) document.

Groundwater analytical data will be evaluated through use of interwell prediction limits, combined with a 1-of-2 resampling strategy. Using this method, upgradient well data are pooled to establish a background statistical limit. Data from the October 2019 monitoring event were compared to the statistical limit to determine whether any concentrations exceed background levels. When an initial statistically significant increase (SSI) or questionable result occurs, a second sample may be collected to verify the initial result or determine if the result was an outlier.

If the initial finding is not verified by resampling, the resampled value will replace the initial finding. When the resample confirms the initial finding, the exceedance will be reported.

The following are also applicable to the site statistical analysis method:

- Statistical analyses are not performed on analytes containing 100% non-detects (US EPA Unified Guidance, 2009, Chapter 6).
- When data contain less than 15% non-detects in background, simple substitution of one-half the reporting limit is utilized in the statistical analysis. The reporting limit utilized for non-detects is the practical quantitation limit (PQL) as reported by the laboratory.
- When data contain between 15-50% non-detects the Kaplan-Meier non-detect adjustment is applied to the background data. This technique adjusts the mean and standard deviation of the historical concentrations to account for concentrations below the reporting limit.
- Nonparametric prediction limits are used on data containing greater than 50% non-detects.

The Sanitas Groundwater statistical software was used to perform the statistical analyses. Sanitas is a decision support software package that incorporates the statistical tests required of Subtitle C and D facilities by US EPA regulations and guidance as recommended in the Unified Guidance (US EPA, 2009) document. A summary of the statistical methodology used at the Site for routine groundwater monitoring is provided in Table 7, Summary of Statistical Methods.

#### 4.2 Statistical Analyses Results – Appendix III

Analytical data from the assessment monitoring event in October 2019 at AP-1 were statistically analyzed in accordance with the PE-certified statistical methods. Appendix III statistical analysis was performed to determine if constituents have returned to background levels. Appendix C, Statistical Analyses.

Based on the statistical results presented in Appendix C, the following summarizes parameters exhibiting SSIs as follows:

- Boron: YGWC-44, YGWC-45, YGWC-46

- Calcium: YGWC-44, YGWC-45, YGWC-46
- Chloride: YGWC-44, YGWC-46
- pH: YGWC-45, YGWC-46
- Sulfate: YGWC-45
- TDS: YGWC-45, YGWC-46

Appendix III constituents have not returned to background levels and assessment monitoring should continue pursuant to 40 CFR § 257.95(f). Statistical analysis of the Appendix IV assessment monitoring results for the October 2019 sampling event will be completed in 2020 following the requirements of 40 CFR 257.95(d).

#### **4.3 Appendix IV Background Data**

Pursuant to § 257.95, Appendix IV groundwater quality data will be parameters will be evaluated to determine if concentrations statistically analyzed exceeded the established groundwater protection standards if assessment monitoring is implemented. The Appendix III statistical analysis is included as Appendix C.

Based on review of the Appendix III statistical analyses presented in Appendix C, Appendix III constituents have not returned to background levels. Exceedances were noted and are presented on the prediction limit summary table included in Appendix C. Because the site is in Assessment Monitoring, no resamples will be collected at this time; however, concentrations will continue to be monitored and will be evaluated during the next subsequent sample event.

#### **4.3 Statistical Analyses – Appendix IV**

Pursuant to §257.95, Appendix IV groundwater quality data will be statistically analyzed and compared to groundwater protection standards within 90 days of receiving data from the first (October 2019) assessment monitoring event. GPC will complete the assessment monitoring and statistical analysis in accordance with § 257.95 and report the results in the Annual Groundwater Monitoring and Corrective Action Report, due August 1, 2020.

### **5.0 MONITORING PROGRAM STATUS**

In accordance with GA EPD rule 391-3-4-.10(6)(a) and 40 CFR §257.94(e), an assessment monitoring program was initiated in November 2019. The Site will remain in assessment monitoring due to SSIs for Appendix III parameters.

### **6.0 CONCLUSIONS AND FUTURE ACTIONS**

Statistical evaluations of the groundwater monitoring data for Ash Pond 1 identified SSIs of Appendix III groundwater monitoring constituents. GPC has initiated assessment monitoring pursuant to §257.95. During the first semiannual period of 2020 GPC will establish groundwater protection standards for Appendix IV constituents and complete statistical analysis of the first semiannual assessment monitoring results according to the regulations. Results of the statistical analysis will be presented in the 2020 first semiannual groundwater monitoring report.

The next monitoring event is planned for the first half of 2020 and will include sampling for Appendix III analytes and Appendix IV constituents detected during the August 2019 monitoring event.

## 7.0 REFERENCES

Driscoll, Fletcher G., 1986 *Groundwater and Wells*, Johnson Screens, Saint Paul, Minnesota, 1089 pp.

EPRI, 2015 Technical Report, Groundwater Monitoring Guidance for the Coal Combustion Residuals Rule.

Freeze, R.A. and Cherry, J.A. 1979, *Groundwater*, Prentice-Hall, Englewood Cliffs, New Jersey, 604 pp.

Groundwater Stats Consulting, LLC, *Statistical Analysis Plan – Plant Yates Ash Pond 1*, 2019.

State Waste Management Board. 2016. State Solid Waste Management Regulations – (9VAC20 81 et seq.). January.

US EPA, 1989 Risk Assessment Guidance for Superfund (RAGS), Vol. I: Human Health Evaluation Manual (Part A) (540-1-89-002).

US EPA. 2009. Statistical Analysis of Groundwater Monitoring Data at RCRA Facilities, Unified Guidance. Office of Resource Conservation and Recovery – Program Implementation and Information Division. March.

US EPA. 2011. *Data Validation Standard Operating Procedures*. Science and Ecosystem Support Division. Region IV. Athens, GA. September.

US EPA. 2017. National Functional Guidelines for Inorganic Superfund Methods Data Review. Office of Superfund Remediation and Technology Innovation. OLEM 9355.0-135 [EPA-540-R-2017-001]. Washington, DC. January.

## TABLES

**Table 1A**  
**Monitoring Network Well Summary**

| Well ID | Installation Date (mm/dd/yyyy) | Bottom Depth (ft BTOC) | Bottom Elevation (ft MSL) | Depth to Top of Screen (ft MSL) | Top of Screen Elevation (ft MSL) | Hydraulic Location |
|---------|--------------------------------|------------------------|---------------------------|---------------------------------|----------------------------------|--------------------|
| YGWA-47 | 7/11/2016                      | 59.40                  | 701.94                    | 49.40                           | 711.94                           | Upgradient         |
| YGWC-44 | 7/13/2016                      | 89.95                  | 672.77                    | 79.95                           | 682.77                           | Downgradient       |
| YGWC-45 | 7/10/2016                      | 73.80                  | 649.30                    | 63.80                           | 659.30                           | Downgradient       |
| YGWC-46 | 7/11/2016                      | 82.98                  | 667.23                    | 72.98                           | 677.23                           | Downgradient       |

Notes:

1. ft BTOC indicates feet below top of casing.
2. ft MSL indicates feet mean sea level.

**Table 1B**  
**Non-Network Well Summary**

| Well ID | Installation Date (mm/dd/yyyy) | Bottom Depth (ft BTOC) | Bottom Elevation (ft MSL) | Depth to Top of Screen (ft BTOC) | Top of Screen Elevation (ft MSL) | Purpose      |
|---------|--------------------------------|------------------------|---------------------------|----------------------------------|----------------------------------|--------------|
| PZ-09S  | 5/19/2014                      | 57.00                  | 653.10                    | 47.00                            | 663.10                           | Piezometer   |
| PZ-09I  | 5/19/2014                      | 77.00                  | 633.10                    | 67.00                            | 643.10                           | Piezometer   |
| PZ-10S  | 5/19/2014                      | 16.30                  | 682.00                    | 6.30                             | 692.00                           | Piezometer   |
| PZ-10I  | 5/19/2014                      | 46.50                  | 651.80                    | 36.50                            | 661.80                           | Piezometer   |
| YAMW-6  | 11/18/2019                     | 72.00                  | 660.80                    | 61.50                            | 661.10                           | Downgradient |
| YAMW-7  | 11/15/2019                     | 122.30                 | 611.16                    | 112.00                           | 621.50                           | Downgradient |

Notes:

1. ft BTOC indicates feet below top of casing.
2. ft MSL indicates feet mean sea level.

**Table 2**  
**Second 2019 Groundwater Sampling Event Summary**

| Well                      | Hydraulic Location | Aug. 20-21, 2019 | Oct. 8-9, 2019         |
|---------------------------|--------------------|------------------|------------------------|
| Purpose of Sampling Event |                    | Assessment       | Second 2019 Semiannual |
| YGWA-47                   | Upgradient         | Scan             | A-02                   |
| YGWC-44                   | Downgradient       | Scan             | A-02                   |
| YGWC-45                   | Downgradient       | Scan             | A-02                   |
| YGWC-46                   | Downgradient       | Scan             | A-02                   |

Notes:

1. Scan = All Appendix IV
2. A-XX = Assessment Event Number (Appendix III and Detected Appendix IV)

**Table 3A**  
**Summary of Groundwater Elevations**  
**August 2019**

| Well ID | TOC Elevation<br>(ft MSL) | Depth-to-<br>Water<br>(ft BTOC) | Groundwater<br>Elevation<br>(ft MSL) |
|---------|---------------------------|---------------------------------|--------------------------------------|
| YGWA-47 | 758.04                    | 33.80                           | 724.24                               |
| YGWC-44 | 758.27                    | 49.53                           | 708.74                               |
| YGWC-45 | 719.30                    | 22.78                           | 696.52                               |
| YGWC-46 | 747.23                    | 48.00                           | 699.23                               |
| PZ-9S   | 711.90                    | 19.74                           | 692.16                               |
| PZ-9I   | 712.04                    | 19.47                           | 692.57                               |
| PZ-10S  | 700.35                    | 8.35                            | 692.00                               |
| PZ-10I  | 700.27                    | 13.90                           | 686.37                               |
| YAMW-6  | 732.73                    | N/A                             | N/A                                  |
| YAMW-7  | 733.50                    | N/A                             | N/A                                  |

Notes:

1. ft BTOC indicates feet below top of casing.
2. ft MSL indicates feet mean sea level.
3. Depths to water measured August 19-20, 2019.
4. N/A = Not Applicable. Location installed November 2019.

**Table 3B  
Summary of Groundwater Elevations  
October 2019**

| Well ID | TOC Elevation<br>(ft MSL) | Depth-to-<br>Water<br>(ft BTOC) | Groundwater<br>Elevation<br>(ft MSL) |
|---------|---------------------------|---------------------------------|--------------------------------------|
| YGWA-47 | 758.04                    | 35.55                           | 722.49                               |
| YGWC-44 | 758.27                    | 50.61                           | 707.66                               |
| YGWC-45 | 719.30                    | 22.85                           | 696.45                               |
| YGWC-46 | 747.23                    | 48.18                           | 699.05                               |
| PZ-9S   | 711.90                    | 20.36                           | 691.54                               |
| PZ-9I   | 712.04                    | 20.62                           | 691.42                               |
| PZ-10S  | 700.35                    | 8.07                            | 692.28                               |
| PZ-10I  | 700.27                    | 14.11                           | 686.16                               |
| YAMW-6  | 732.73                    | N/A                             | N/A                                  |
| YAMW-7  | 733.50                    | N/A                             | N/A                                  |

Notes:

1. ft BTOC indicates feet below top of casing.
2. ft MSL indicates feet mean sea level.
3. Depths to water measured October 7-8, 2019.
4. N/A = Not Applicable. Location installed November 2019.

**Table 4**  
**CALCULATED GROUNDWATER FLOW RATE**  
**October 2019**

Equation

$$v = \frac{K (dh/dl)}{P_e}$$

where: v = ground water velocity  
K = hydraulic conductivity  
dh/dl = hydraulic gradient  
P<sub>e</sub> = effective porosity

Values Used in Calculation

|                  | Value               |                   | Source                                      |
|------------------|---------------------|-------------------|---|
| K =              | 3.7E-03<br>10.49    | cm/sec<br>ft/day  | See note 1.                                 |
| dh/dl =          | 30.95/1173<br>0.026 | ft/ft<br>unitless | Hydraulic gradient from<br>GWA-47 to PZ-09S |
| P <sub>e</sub> = | 0.20                | unitless          | See note 2.                                 |

Calculation

$$v = 1.4 \text{ ft/day}$$

$$v = 505 \text{ ft/yr}$$

Notes

- (1) Slug tests performed by Atlantic Coast Consulting, Inc. (2017).  
(2) Default value for silty sands from Interim Final RCRA Investigation (EPA, 1989).

0

**Table 5**  
**Summary of Groundwater Monitoring Parameters**

| <b>Appendix III<br/>(40 CFR 257)</b> | <b>Appendix IV<br/>(40 CFR 257)</b> |
|--------------------------------------|-------------------------------------|
| Boron                                | <i>Antimony</i>                     |
| Calcium                              | Arsenic                             |
| Chloride                             | Barium                              |
| Fluoride                             | <i>Beryllium</i>                    |
| pH                                   | Cadmium                             |
| Sulfate                              | <i>Chromium</i>                     |
| Total Dissolved Solids               | Cobalt                              |
|                                      | <i>Fluoride</i>                     |
|                                      | <i>Lead</i>                         |
|                                      | Lithium                             |
|                                      | <i>Mercury</i>                      |
|                                      | Molybdenum                          |
|                                      | Radium 226 and 228 combined         |
|                                      | <i>Selenium</i>                     |
|                                      | Thallium                            |

Notes:

1. Italicized groundwater monitoring parameters not detected during initial assessment monitoring event (August 2019) and therefore not included in semiannual parameter list (October 2019)..

**Table 6A**  
**Summary of Groundwater Analytical Data**  
**August 2019**

| Substance       |                   | YGWA-47        | YGWC-44        | YGWC-45        | YGWC-46        |
|-----------------|-------------------|----------------|----------------|----------------|----------------|
|                 |                   | 8/20/2019      | 8/20/2019      | 8/20/2019      | 8/21/2019      |
| Appendix IV     | <b>Antimony</b>   | ND             | ND             | ND             | ND             |
|                 | <b>Arsenic</b>    | ND             | ND (0.00097 J) | ND (0.00078 J) | ND (0.00074 J) |
|                 | <b>Barium</b>     | 0.024          | 0.10           | 0.057          | 0.023          |
|                 | <b>Beryllium</b>  | ND             | ND             | ND             | ND             |
|                 | <b>Cadmium</b>    | ND             | ND             | ND             | ND (0.00012 J) |
|                 | <b>Chromium</b>   | ND             | ND             | ND             | ND             |
|                 | <b>Cobalt</b>     | ND (0.00092 J) | ND (0.0020 J)  | ND (0.00071 J) | 0.027          |
|                 | <b>Fluoride</b>   | ND             | ND             | ND             | ND             |
|                 | <b>Lead</b>       | ND             | ND             | ND             | ND             |
|                 | <b>Lithium</b>    | ND (0.0036 J)  | ND (0.013 J)   | ND (0.012 J)   | ND (0.0076 J)  |
|                 | <b>Mercury</b>    | ND             | ND             | ND             | ND             |
|                 | <b>Molybdenum</b> | ND             | ND             | ND (0.0011 J)  | ND (0.0012 J)  |
|                 | <b>Radium</b>     | 2.44           | 1.71           | 2.23           | 1.31           |
|                 | <b>Selenium</b>   | ND             | ND             | ND             | ND             |
| <b>Thallium</b> | ND (0.000058 J)   | ND             | ND             | ND             |                |

Notes:

1. Results for substances are reported in milligrams per liter (mg/L). Radium results are reported in picocuries per liter (pCi/L).
2. ND (Not Detected) indicates the substance was not detected above the laboratory method detection limit (MDL).
3. ND (value J) indicates the substance was detected at such low levels that the precision of the laboratory instrument could not produce a reliable value. Therefore, the value displayed (value J) is qualified by the laboratory as an estimated value.
4. U indicates the substance was detected below the Minimum Detection Concentration (MDC) and the precision of the laboratory instruments could not produce a reliable value. Therefore, the value followed by U is qualified by the laboratory as estimated.
5. Appendix IV = parameters evaluated during Assessment Monitoring.

**Table 6B**  
**Summary of Groundwater Analytical Data**  
**October 2019**

| Substance           |                   | YGWA-47         | YGWC-44       | YGWC-45        | YGWC-46       |
|---------------------|-------------------|-----------------|---------------|----------------|---------------|
|                     |                   | 10/8/2019       | 10/8/2019     | 10/9/2019      | 10/9/2019     |
| <b>Appendix III</b> | <b>Boron</b>      | ND (0.012 J)    | 0.58          | 0.35           | 1.1           |
|                     | <b>Calcium</b>    | 9.7             | 28.1          | 47.9           | 64.2          |
|                     | <b>Chloride</b>   | 4.4             | 14.8          | 5.1            | 25.0          |
|                     | <b>Fluoride</b>   | ND (0.034 J)    | ND            | ND             | ND (0.12 J)   |
|                     | <b>Sulfate</b>    | 52.3            | 142           | 183            | ND            |
|                     | <b>TDS</b>        | 172             | 324           | 432            | 809           |
| <b>Appendix IV</b>  | <b>Arsenic</b>    | ND              | ND            | ND             | ND            |
|                     | <b>Barium</b>     | 0.025           | 0.098         | 0.058          | 0.024         |
|                     | <b>Cadmium</b>    | ND              | ND            | ND             | ND            |
|                     | <b>Cobalt</b>     | ND (0.0014 J)   | ND (0.0017 J) | ND (0.00070 J) | 0.024         |
|                     | <b>Lithium</b>    | ND (0.0036 J)   | ND (0.012 J)  | ND (0.012 J)   | ND (0.0078 J) |
|                     | <b>Molybdenum</b> | ND              | ND            | ND (0.0012 J)  | ND (0.0013 J) |
|                     | <b>Radium</b>     | 1.72            | 0.769 U       | 1.61           | 0.892 U       |
|                     | <b>Thallium</b>   | ND (0.000084 J) | ND            | ND             | ND            |

Notes:

1. Results for substances are reported in milligrams per liter (mg/L). Radium results are reported in picocuries per liter (pCi/L).
2. ND (Not Detected) indicates the substance was not detected above the laboratory method detection limit (MDL).
3. ND (value J) indicates the substance was detected at such low levels that the precision of the laboratory instrument could not produce a reliable value. Therefore, the value displayed (value J) is qualified by the laboratory as an estimated value.
4. TDS indicates total dissolved solids.
5. U indicates the substance was detected below the Minimum Detection Concentration (MDC) and the precision of the laboratory instruments could not produce a reliable value. Therefore, the value followed by U is qualified by the laboratory as estimated.
6. Appendix III = indicator parameters evaluated during Detection Monitoring; Appendix IV = parameters evaluated during Assessment Monitoring.


**Table 7**  
**Statistical Method Summary**

| Plant Yates AP-1 Statistical Method Summary |                                     |  |
|---|-------------------------------------|--|
| Monitoring Well Network                     | Upgradient Well                     | YGWA-47  |
|   | Downgradient Wells                  | YGWC-44, YGWC-45, and YGWC-46  |
| CCR Monitoring Parameters                   | Appendix III (Detection Monitoring) | Boron, Calcium, Chloride, Fluoride, pH, Sulfate, and TDS   |
|   | Appendix IV (Assessment Monitoring) | Antimony, Arsenic, Barium, Beryllium, Cadmium, Chromium, Cobalt, combined Radium 226 + 228, Fluoride, Lead, Lithium, Mercury, Molybdenum, Selenium, and Thallium |
| Statistical Methodology                     | Data Screening Proposed Background  | Evaluate outliers, trends, and seasonality when sufficient data are available  |
|   | Statistical Limits                  | Interwell statistical limits   |

## FIGURES



| LEGEND   |                               |
|----------|-------------------------------|
| EXISTING | DESCRIPTION                   |
|          | APPROXIMATE PROPERTY BOUNDARY |
|          | APPROXIMATE UNIT BOUNDARY     |



ATLANTIC COAST CONSULTING, INC.  
 1150 Northmeadow Pkwy.  
 Suite 100  
 Roswell, GA 30076  
 770.594.5998  
 www.atlcc.net

PROJECT:  
 PLANT YATES

708 DYER ROAD  
 NEWNAN, GEORGIA

| REVISIONS |
|-----------|
|           |
|           |
|           |
|           |
|           |
|           |
|           |
|           |
|           |
|           |

Drawn by: MM      Checked by: EP

PROJECT NUMBER:  
 IO54-110  
 July 2019

SITE LOCATION MAP

FIGURE 1




P:\Industrial\054 - Southern Company\110 - Groundwater Consulting Services 2018 - 2021\Plant Yates\2 - Semiannual AP-1 GWMRs\2nd 2019\DWG\Plant Yates October 2019 Pot. Map.dwg 2019-12-04 MATT MALONE

**Summary of Groundwater Elevations  
Plant Yates Landfill  
Ash Pond 1  
October 2019 Sampling Event**

| Monitoring Well ID | Total Depth (ft btoc ) | Top of Casing (MSL) | Depth to Water (feet) | Groundwater Elevation (MSL) |
|--------------------|------------------------|---------------------|-----------------------|-----------------------------|
| YGWA-47            | 59.50                  | 758.04              | 35.55                 | 722.49                      |
| YGWC-44            | 90.00                  | 758.27              | 50.61                 | 707.66                      |
| YGWC-45            | 74.00                  | 719.30              | 22.85                 | 696.45                      |
| YGWC-46            | 83.00                  | 747.23              | 48.18                 | 699.05                      |
| PZ-09S             | 59.20                  | 711.90              | 20.36                 | 691.54                      |
| PZ-09I             | 79.68                  | 712.04              | 20.62                 | 691.42                      |
| PZ-10S             | 18.90                  | 700.35              | 8.07                  | 692.28                      |
| PZ-10I             | 49.55                  | 700.27              | 14.11                 | 686.16                      |

**Notes:** Depths to water measured within a 24-hour period October 7-8, 2019.  
ft btoc - feet below top of casing.  
MSL = Mean Sea Level.



NOTE:  
1. WELLS WITH "I" SUFFIXES MONITOR DEEPER INTERVALS AND ARE NOT USED TO CONSTRUCT WATER TABLE CONTOURS.  
2. AERIAL IMAGE FROM 2018.

**ACC**  
ATLANTIC COAST CONSULTING, INC.  
1150 Northmeadow Pkwy.  
Suite 100  
Roswell, GA 30076  
770.594.5998  
www.atlcc.net

PROJECT:  
**PLANT YATES**

708 DYER ROAD  
NEWNAN, GEORGIA

REVISIONS

|  |  |
|--|--|
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |
|  |  |

Drawn by: **RW**      Checked by: **MM**

PROJECT NUMBER:  
**1054-110**  
November 2019

**OCTOBER 2019  
WATER TABLE  
CONTOUR MAP**

FIGURE **3**

**LEGEND**

|  |                          |  |
|--|--------------------------|--|
|  | <b>EXISTING</b>          | <b>DESCRIPTION</b>   |
|  | PERMITTED UNIT BOUNDARY  |  |
|  | <b>800</b>               | WATER TABLE CONTOUR  |
|  |                          | GROUNDWATER FLOW DIRECTION (INFERRED)                        |
|  | <b>YGWC-46</b><br>699.05 | GROUNDWATER MONITORING WELL<br>WATER TABLE CONTOUR ELEVATION |
|  | <b>PZ-10S</b><br>692.28  | PIEZOMETER<br>WATER TABLE CONTOUR ELEVATION                  |

SCALE: 1" = 300' (IN FEET)



## APPENDICES

**APPENDIX A**

**WELL INSTALLATION REPORT**

Georgia Power Company  
Plant Yates – Ash Pond 1  
Newnan, Georgia  
Coweta County

WELL INSTALLATION REPORT



ATLANTIC COAST  
CONSULTING, INC.

Georgia Power Company  
Plant Yates – Ash Pond 1  
Newnan, Georgia  
Coweta County

WELL INSTALLATION REPORT  
PROFESSIONAL CERTIFICATION

Evan B. Perry  
Georgia Registered Professional  
Geologist No. 1744



Richard T. Deason  
Georgia Registered Professional  
Engineer No. 27467



## TABLE OF CONTENTS

Cover Sheet

Table of Contents

| <u>Section</u>                           | <u>Page No.</u> |
|--|-----------------|
| 1.0 Introduction .....                   | 3               |
| 1.1 Justification for Well Network.....  | 4               |
| 2.0 Drilling and Well Installation ..... | 4               |
| 2.1 Drilling Method.....                 | 4               |
| 2.2 Screened Interval.....               | 5               |
| 2.3 Well Casing and Screens.....         | 5               |
| 2.4 Well Intake Design .....             | 5               |
| 2.5 Filter Pack.....                     | 5               |
| 2.6 Annular Seal .....                   | 5               |
| 2.7 Cap and Protective Casing .....      | 6               |
| 3.0 Well Development.....                | 6               |
| 4.0 Survey .....                         | 6               |
| 5.0 General References.....              | 6               |

Table

Table 1 – Summary of Well Installation Dates, Coordinates, Elevations, Screen Intervals, and Purposes

Table 2 – Summary of Piezometer and Assessment Well Installation Dates, Coordinates, Elevations, Screen Intervals, and Purposes

Figure

Figure 1 – Well Location Map

Attachments

Attachment A – Boring and Well Construction Logs

Attachment B – Well Development Data

Attachment C – Well Survey Documents

## 1.0 Introduction

In accordance with the United States Environmental Protection Agency (EPA) coal combustion residual (CCR) rule (40 Code of Federal Regulations [CFR] 257 Subpart D; published in 80 FR 21302-21501, April 17, 2015), a groundwater monitoring system was developed for Plant Yates Ash Pond 1 (AP-1) to monitor groundwater quality in the uppermost aquifer. This Monitoring Well Certification Report documents installation details for the detection groundwater monitoring system required by §257.91. The groundwater flow regime and geologic characteristics of the facility that the network design is based upon are described in the *Hydrogeologic Monitoring Plan* (ACC, 2018). This document presents details for the AP-1 monitoring network.

An Atlantic Coast Consulting, Inc. (ACC) professional engineer has reviewed the groundwater monitoring system and certified that the groundwater monitoring system has been designed and constructed to meet the requirements of §257.91. Those requirements include:

**40 CFR §257.91(a)**, the groundwater monitoring system must consist of a sufficient number of wells, installed at appropriate locations and depths, to yield groundwater samples from the uppermost aquifer that:

- (1) Accurately represent the quality of background groundwater that has not been affected by leakage from a CCR unit; and
- (2) Accurately represent the quality of groundwater passing the waste boundary of the CCR unit.

**40 CFR §257.91(b)**, the number, spacing, and depths of groundwater monitoring system must be determined based upon site-specific technical information that must include a characterization of:

- (1) Aquifer thickness, groundwater flow rate, groundwater flow direction, including seasonal and temporal fluctuations in groundwater flow; and
- (2) Saturated and unsaturated geologic units and fill materials overlying the uppermost aquifer, materials comprising the uppermost aquifer, and materials comprising the confining unit defining the lower boundary of the uppermost aquifer, including, but not limited to, thicknesses, stratigraphy, lithology, hydraulic conductivities, porosities and effective porosities.

This report documents well installation activities at the Georgia Power Company (GPC) Plant Yates Ash Pond 1. Plant Yates is located at 708 Dyer Road, on the east bank of the Chattahoochee River in Coweta County, Georgia near the Coweta and Carroll County line, approximately 8 miles northwest of the city of Newnan and 13 miles southeast of the city of Carrollton. Plant Yates has ceased coal combustion activities and is no longer generating new CCR.

The facility has installed one upgradient groundwater monitoring network well YGWA-47 and three downgradient groundwater monitoring network wells (YGWC-44, YGWC-45, and YGWC-46) along the perimeter of Ash Pond 1. Additionally, there are 6 non-network wells (PZ-9S, PZ-9I, PZ-10S, PZ-10I, YAMW-6, and YAMW-7) in the vicinity of AP-1. Piezometers are currently maintained for water level measurements. Piezometers suffixed with an “S” are installed in overburden (saprolitic soil), an “I” indicates partially weathered rock, and “D” indicates

bedrock. As typical of the Piedmont Physiographic Province, there is likely a high degree of connectivity between the overburden, partially weathered rock, fractured bedrock and the materials comprise a single uppermost aquifer. The four network monitoring wells are completed in the partially weathered bedrock. The monitoring well locations are presented on Figure 1.

### 1.1 Justification for Well Network

There is requirement provided in 40 CFR §257.91(f), that requires if the groundwater monitoring system includes the minimum number of monitoring wells specified (one upgradient and three downgradient), the certification must document the basis for that determination. The groundwater monitoring system for Ash Pond 1 includes the minimum number of monitoring wells, therefore this section is included to provide the basis for the determination.

The aerial extent of Ash Pond 1 is limited (totals 23.44 acres). Additionally, the facility has been closed by removal (i.e. the potential source of impact is no longer present). Beyond those considerations, there are documented geologic considerations that support the adequacy of the groundwater monitoring network. These considerations include:

- Simple site geology: strata are consistent across the site; geology is comprised of metamorphic silicate rock with no solution channels such as those present in limestone formations.
- Relatively low groundwater flow rates: The groundwater low rate at Plant Yates ranges from approximately 7.3 to 266 feet per year. The relatively low groundwater flow rates allow for a significant dispersive component to groundwater flow (i.e. as opposed to system with purely advective flow).

## 2.0 Drilling and Well Installation

Wells were properly designed and installed according to accepted industry standards and following guidelines presented in *Manual for Groundwater Monitoring* (EPD, 1991).

Groundwater monitoring network wells were installed along the boundaries of Ash Pond 1 in a mobilization completed July 2016. All well locations are shown on Figure 1, Well Location Map. The non-network piezometers were installed in 2014. Assessment groundwater monitoring wells were installed in November 2019. Prior to drilling, proposed well locations were surveyed to within  $\pm 0.5$ -foot horizontal accuracy, and staked in the field. A summary of well installation dates, locations, elevations, screen intervals, and purposes is provided in Table 1, Summary of Well Installation Dates, Coordinates, Elevations, Screen Intervals, and Purposes. Boring and well construction logs are included in Attachment B, Boring and Well Construction Logs.

### 2.1 Drilling Method

Cascade Drilling, LP (Cascade) performed drilling services during the mobilization in July 2016 as well as in 2014 for the piezometers and November 2019 for assessment wells. Monitoring wells were installed by Cascade using Rotosonic (Sonic) drilling technology. Sonic drilling utilizes high-frequency mechanical vibrations to advance drilling tools through various geologic media. The method is well-suited for collecting continuous samples in unconsolidated formations, reducing waste from cuttings, and running downhole geophysics.

Subsurface materials encountered during drilling generally consist of and clay, silt, and sand materials at shallow intervals (i.e. saprolitic material). A zone of partially weathered bedrock is typically present below the overburden. The weathered bedrock transitions to increasing competent bedrock with depth. The uppermost groundwater typically occurs in overburden.

## **2.2 Screened Interval**

Wells and piezometers are installed in overburden and partially weathered rock. The bottom 10 feet are screened.

## **2.3 Well Casing and Screens**

Wells and piezometers are constructed of two-inch inside diameter ASTM Schedule 40 polyvinyl chloride (PVC) casing affixed to a prepacked dual-wall slotted PVC screen. The casings and prepacked screens arrived pre-cleaned and packaged by the manufacturer. Well construction materials are sufficiently durable to resist chemical and physical degradation and not interfere with the quality of groundwater samples. Casing and screen sections are flush-threaded. Solvent or glue was not used to construct the wells.

## **2.4 Well Intake Design**

Wells and piezometers were designed and constructed to: (1) allow sufficient groundwater flow to the well for sampling; (2) minimize the passage of formation materials (turbidity) into the wells; and (3) ensure sufficient structural integrity to prevent collapse of the well. Wells and piezometers are screened using 0.010-inch slotted PVC prepacked dual-wall well screens. The prepacked dual-wall well screens combine a centralized inner well screen, a void for site-specific filter sand pack, and an outer conductor screen in one integrated unit. Based on the nature of deposits, the screen will retain at least 90 percent of the filter pack and 40 percent of the formation.

## **2.5 Filter Pack**

A filter pack sand size #1 was used for all filter packs at the site. This size sand is approximately 20-40 sieve range, medium fine well-rounded quartz (silica) sand.

Filter pack material was placed within the prepacked dual-wall well screens and in the annular space between the outside of the prepack screen and borehole wall to ensure an adequate thickness of filter pack material between the well and the formation. Filter pack material placed in the annular space outside of the well screen extended approximately 2 feet above the top of the screen, except in a few cases where up to 6 feet were used to ensure low turbidity samples. No bridging occurred during filter pack placement.

After placing the filter pack, the wells were pumped to ensure settlement of the filter pack, prior to installing the annular seal. The depth of top of filter pack was measured and recorded in well construction logs provided in Attachment A.

## **2.6 Annular Seal**

After installing the filter pack, 2 to 9 feet of bentonite pellets were placed in the annular space above the filter pack to seal the annulus and prevent vertical flow of water along the well casing. Bentonite pellets were allowed to hydrate and settle in accordance with manufacturers recommendations prior to grouting the well. A cement-bentonite grout was used as the annular sealant above the bentonite seal. The cement-bentonite grout was

tremied into place from the top of the bentonite seal to approximately 2 feet below land surface (BLS). The grout was injected at a low velocity to not disrupt the bentonite seal and the tremie pipe was raised as grout filled the annular space. A concrete seal extends from 2 feet BLS to land surface and was blended into a mounded cement apron extending outward from the edge of the borehole to direct rainwater run-off away from the well.

## 2.7 Cap and Protective Casing

The well was fitted with a cap and a protective cover was installed over the well to protect the casing from damage and secure the well from tampering. The annular space between the well pipe and protective casing was filled with pea stone and a small weep hole was drilled near the base of the protective cover to provide a path for water entering the protective casing to drain. Bollards were installed around the four corners of the concrete pad to protect the well. Wells are clearly marked with signs with the proper designation. Locations that are part of the groundwater monitoring network have been fitted with dedicated bladder pumps. The tops of the pumps are protected with caps to prevent particulate matter from entering the well. Construction details are documented in Well Construction Logs provided in Attachment A.

## 3.0 Well Development

Wells and piezometers were developed using a submersible pump to (1) restore the natural hydraulic conductivity of the formation and (2) to remove fine-grained sediment to ensure low-turbidity groundwater samples. Wells were alternatively surged and purged until visually clear of particulates. Turbidity, pH, dissolved oxygen (DO), oxidation-reduction potential (ORP), and specific conductivity measurements were made to ensure that each well was fully developed. A turbidity of less than 10 nephelometric turbidity units (NTU) was documented at each well prior to ceasing well development activities. The stabilization logs from development or from initial sampling to document low turbidity conditions are included in Attachment B, Well Development Forms.

All equipment and tubing placed in the well was decontaminated or disposed of between wells.

## 4.0 Survey

Wells and piezometers locations and top of casing (TOC) elevations were surveyed by Southern Company Services. Northings and eastings are in feet relative to the North America Datum of 1983 (NAD83) in the Georgia State Plane Coordinate System (West). TOC and ground surface elevations are in feet relative to NAVD88. Survey data are tabulated in Table 1. Well survey data are provided in Attachment C, Well Survey Documents.

## 5.0 General References

Atlantic Coast Consulting, Inc., November 2018. *Hydrogeologic Monitoring Plan – Plant Yates Ash Landfill R6*.

Atlantic Coast Consulting, Inc. November 2018. *Hydrogeologic Assessment Report – Plant Yates Ash Landfill R6*.

Georgia Department of Natural Resources, Environmental Protection Division. 1991. *Manual for Groundwater Monitoring*.



U.S. EPA Region IV SEDS, 2013, Design and Installation of Monitoring Wells – Operating Procedure: SESDGUID-101-R1.

## TABLE



**Table 1**  
**Summary of Well Installation Dates, Coordinates, Elevations, Screen Intervals, and Purposes**

| Well                     | Completion Date | Easting   | Northing  | Bottom Depth (ft BTOC) | Bottom Elevation (ft MSL) | Top of Screen Elevation (ft MSL) | Top of Casing Elevation (ft MSL) | Purpose      |
|--------------------------|-----------------|-----------|-----------|------------------------|---------------------------|----------------------------------|----------------------------------|--------------|
| <b>Network Locations</b> |                 |           |           |                        |                           |                                  |                                  |              |
| YGWA-47                  | 7/11/2016       | 2071818.0 | 1262410.8 | 59.4                   | 701.94                    | 711.94                           | 758.04                           | Upgradient   |
| YGWC-44                  | 7/13/2016       | 2071218.6 | 1261874.5 | 89.95                  | 672.77                    | 682.77                           | 758.27                           | Downgradient |
| YGWC-45                  | 7/10/2016       | 2070911.9 | 1261668.9 | 73.80                  | 649.30                    | 659.30                           | 719.30                           | Downgradient |
| YGWC-46                  | 7/11/2016       | 2071035.3 | 1261031.4 | 82.98                  | 667.23                    | 677.23                           | 747.23                           | Downgradient |

Notes:

1. ft BTOC indicates feet below top of casing.
2. ft MSL indicates feet mean sea level.

**Table 2**  
**Summary of Piezometer and Assessment Well Installation Dates, Coordinates, Elevations, Screen Intervals, and Purposes**

| Well                         | Completion Date | Easting   | Northing  | Bottom Depth (ft BTOC) | Bottom Elevation (ft MSL) | Top of Screen Elevation (ft MSL) | Top of Casing Elevation (ft MSL) | Purpose          |
|------------------------------|-----------------|-----------|-----------|------------------------|---------------------------|----------------------------------|----------------------------------|------------------|
| <b>Non-Network Locations</b> |                 |           |           |                        |                           |                                  |                                  |                  |
| PZ-09S                       | 5/19/2014       | 2070721.6 | 1262003.3 | 57.0                   | 653.1                     | 663.1                            | 711.90                           | Water Level Only |
| PZ-09I                       | 5/19/2014       | 2070721.1 | 1261995.6 | 77.0                   | 633.1                     | 643.1                            | 712.04                           | Water Level Only |
| PZ-10S                       | 5/19/2014       | 2070553.3 | 1260802.3 | 16.3                   | 682.0                     | 692.0                            | 700.35                           | Water Level Only |
| PZ-10I                       | 5/19/2014       | 2070552.8 | 1260809.7 | 46.5                   | 651.8                     | 661.8                            | 700.27                           | Water Level Only |
| YAMW-6                       | 11/18/2019      | 2070921.2 | 1260964.3 | 71.9                   | 661.1                     | 671.1                            | 732.73                           | Delineation      |
| YAMW-7                       | 11/15/2019      | 2071085.7 | 1261041.9 | 122.3                  | 611.4                     | 621.4                            | 733.50                           | Delineation      |

Notes:

1. ft BTOC indicates feet below top of casing.
2. ft MSL indicates feet mean sea level.

FIGURE

**LEGEND**

| EXISTING | DESCRIPTION                 |
|----------|-----------------------------|
|          | PERMITTED UNIT BOUNDARY     |
| YGWC-46  | GROUNDWATER MONITORING WELL |
| PZ-10S   | PIEZOMETER                  |
| YAMW-6   | ASSESSMENT MONITORING WELL  |

NOTE:  
1. AERIAL IMAGE FROM 2018.



**ATLANTIC COAST CONSULTING, INC.**  
1150 Northmeadow Pkwy.  
Suite 100  
Roswell, GA 30076  
770.594.5998  
www.atlcc.net

PROJECT:  
**PLANT YATES**

FORMER  
GYPSUM STACK  
LANDFILL

FORMER  
ASH  
POND 1

708 DYER ROAD  
NEWNAN, GEORGIA

REVISIONS

|  |
|--|
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |

Drawn by: MM      Checked by: EP

PROJECT NUMBER:

1054-110

January 2020

WELL LOCATION  
MAP

FIGURE 1

P:\Industrial\054-Southern Company\110-Groundwater Consulting Services\Plant Yates\1-Well Certification Reports\AP-1\DWG\Plant Yates AP-1 Well Location Map.dwg 2020-02-05 RYAN WALKER



SCALE: 1" = 300' (IN FEET)



## ATTACHMENTS

## ATTACHMENT A

### Boring and Well Construction Logs

# RECORD OF BOREHOLE YGWA-47 (PZ-47)

SHEET 1 of 2

PROJECT: SCS Plant Yates  
 PROJECT NUMBER: 1660300  
 DRILLED DEPTH: 56.50 ft  
 LOCATION: Newnan, GA

DRILL RIG: Sonic PS-150  
 DATE STARTED: 7/10/16  
 DATE COMPLETED: 7/11/16

NORTHING: 1,262,410.75  
 EASTING: 2,071,818.00  
 GS ELEVATION: 755.35  
 TOC ELEVATION: 758.04 ft

DEPTH W.L.: 21.6 ft (bgs)  
 ELEVATION W.L.: (amsl)  
 DATE W.L.: 7/11/2016  
 TIME W.L.: 07:30

| DEPTH (ft) | ELEVATION (ft) | SOIL PROFILE   |        |                    |                     | SAMPLES    |                |                             | MONITORING WELL/<br>PIEZOMETER<br>DIAGRAM and NOTES | WELL<br>CONSTRUCTION<br>DETAILS   |
|------------|----------------|--|--------|--------------------|---------------------|------------|----------------|-----------------------------|---|---|
|            |                | DESCRIPTION  | USCS   | GRAPHIC LOG        | ELEV.<br>DEPTH (ft) | SAMPLE NO. | TYPE           | REC                         |   |   |
| 0          | 755            | 0.00 - 10.00<br>no recovery, hydrovac  |        |                    |                     |            |                |                             | Portland Type 1                                     | <b>WELL CASING</b><br>Interval: 0.0'-46.1'<br>Material: Schedule 40 PVC<br>Diameter: 2"<br>Joint Type: Threaded<br><br><b>WELL SCREEN</b><br>Interval: 46.1'-56.1'<br>Material: U-Pack Schedule 40 PVC<br>Diameter: 2"<br>Slot Size: 0.010"<br>End Cap: Schedule 40 PVC<br><br><b>FILTER PACK</b><br>Interval: 43.4'-56.5'<br>Type: #1 Type Sand<br><br><b>FILTER PACK SEAL</b><br>Interval: 33.7'-43.4'<br>Type: Bentonite Pellets and Chips<br><br><b>ANNULUS SEAL</b><br>Interval: 0.0'-33.7'<br>Type: Portland Type 1<br><br><b>WELL COMPLETION</b><br>Pad: 4'x4'<br>Protective Casing: Aluminum<br><br><b>DRILLING METHODS</b><br>Soil Drill: 4" Sonic<br>Rock Drill: 4" Sonic |
| 10         | 745            | 10.00 - 13.00<br>silt SAND fining downward to low-plasticity CLAY, red, dry loose  | SM-CL  | [Hatched Pattern]  | 745.35<br>10.00     |            |                |                             |   |   |
| 15         | 740            | 13.00 - 20.00<br>sandy SILT, orange to white, loose, dry   | ML     | [Vertical Lines]   | 742.35<br>13.00     | 1          | 6.00<br>6.00   |                             |   |   |
| 20         | 735            | 20.00 - 21.00<br>highly weathered, mica schist, relict laminations (saprolite)   |        | [Vertical Lines]   | 735.35<br>20.00     | 2          | 10.00<br>10.00 |                             |   |   |
|            |                | 21.00 - 24.00<br>orange to white, loose, dry   |        | [Vertical Lines]   | 734.35<br>21.00     |            |                |                             |   |   |
| 25         | 730            | 24.00 - 26.00<br>orange to white, relict laminations, loose, dry (saprolite)   |        | [Vertical Lines]   | 731.35<br>24.00     | 3          | 3.00<br>4.00   |                             |   |   |
|            |                | 26.00 - 28.00<br>well sorted sand with some silt, relict laminations, saprolite - schistose  |        | [Vertical Lines]   | 729.35<br>26.00     |            |                |                             |   |   |
|            |                | 28.00 - 30.00<br>orange to white, relict laminations, loose, dry   |        | [Vertical Lines]   | 727.35<br>28.00     |            |                |                             |   |   |
| 30         | 725            | 30.00 - 36.00<br>transitionally weathered rock, highly weathered mica SCHIST, pulverized from drilling, dry                        | PWR    | [Triangle Pattern] | 725.35<br>30.00     | 4          | 6.00<br>6.00   |                             |   |   |
| 35         | 720            | 36.00 - 46.00<br>bedrock - AMPHIBOLITE/SCHIST, deep oxide staining, secondary mineralization                                       |        | [Triangle Pattern] | 719.35<br>36.00     | 5          | 3.00<br>10.00  | Bentonite Pellets and Chips |   |   |
| 40         | 715            |  | SCHIST | [Wavy Pattern]     |                     |            |                |                             |   |   |
| 45         | 710            | 46.00 - 56.00<br>AMPHIBOLITE/SCHIST grading to GNEISS, secondary mineralization, garnet, pyrite inclusions, some quartzite banding |        | [Wavy Pattern]     | 709.35<br>46.00     | 6          | 7.00<br>10.00  | 0.010" Slotted Screen       |   |   |

Log continued on next page

BOREHOLE RECORD: YATES BORING LOGS.GPJ PIEDMONT.GDT 9/26/17

LOG SCALE: 1 in = 6.5 ft  
 DRILLING COMPANY: Cascade Drilling  
 DRILLER: Dale

GA INSPECTOR: Ben Hodges  
 CHECKED BY: Rachel Kirkman, PG  
 DATE: 9/29/17



# RECORD OF BOREHOLE YWA-47 (PZ-47)

SHEET 2 of 2

PROJECT: SCS Plant Yates  
 PROJECT NUMBER: 1660300  
 DRILLED DEPTH: 56.50 ft  
 LOCATION: Newnan, GA

DRILL RIG: Sonic PS-150  
 DATE STARTED: 7/10/16  
 DATE COMPLETED: 7/11/16

NORTHING: 1,262,410.75  
 EASTING: 2,071,818.00  
 GS ELEVATION: 755.35  
 TOC ELEVATION: 758.04 ft

DEPTH W.L.: 21.6 ft (bgs)  
 ELEVATION W.L.: (amsl)  
 DATE W.L.: 7/11/2016  
 TIME W.L.: 07:30

| DEPTH (ft) | ELEVATION (ft) | SOIL PROFILE   |      |   | SAMPLES             |            |               | MONITORING WELL/<br>PIEZOMETER<br>DIAGRAM and NOTES | WELL<br>CONSTRUCTION<br>DETAILS  |
|------------|----------------|--|------|---|---------------------|------------|---------------|---|--|
|            |                | DESCRIPTION  | USCS | GRAPHIC LOG   | ELEV.<br>DEPTH (ft) | SAMPLE NO. | TYPE          |   |  |
| 50         | 705            | 46.00 - 56.00<br>AMPHIBOLITE/SCHIST grading to GNEISS, secondary mineralization, garnet, pyrite inclusions, some quartzite banding<br><i>(Continued)</i> |      |  | 699.35<br>56.00     | 6          | 7.00<br>10.00 | #1 Type Sand<br><br>Sump                            | <p><b>WELL CASING</b><br/>Interval: 0.0'-46.1'<br/>Material: Schedule 40 PVC<br/>Diameter: 2"<br/>Joint Type: Threaded</p> <p><b>WELL SCREEN</b><br/>Interval: 46.1'-56.1'<br/>Material: U-Pack Schedule 40 PVC<br/>Diameter: 2"<br/>Slot Size: 0.010"<br/>End Cap: Schedule 40 PVC</p> <p><b>FILTER PACK</b><br/>Interval: 43.4'-56.5'<br/>Type: #1 Type Sand</p> <p><b>FILTER PACK SEAL</b><br/>Interval: 33.7'-43.4'<br/>Type: Bentonite Pellets and Chips</p> <p><b>ANNULUS SEAL</b><br/>Interval: 0.0'-33.7'<br/>Type: Portland Type 1</p> <p><b>WELL COMPLETION</b><br/>Pad: 4'x4'x4"<br/>Protective Casing: Aluminum</p> <p><b>DRILLING METHODS</b><br/>Soil Drill: 4" Sonic<br/>Rock Drill: 4" Sonic</p> |
| 55         | 700            |  |      |   |                     |            |               |   |  |
| 60         | 695            |  |      |   |                     |            |               |   |  |
| 65         | 690            |  |      |   |                     |            |               |   |  |
| 70         | 685            |  |      |   |                     |            |               |   |  |
| 75         | 680            |  |      |   |                     |            |               |   |  |
| 80         | 675            |  |      |   |                     |            |               |   |  |
| 85         | 670            |  |      |   |                     |            |               |   |  |
| 90         | 665            |  |      |   |                     |            |               |   |  |
| 95         | 660            |  |      |   |                     |            |               |   |  |
| 100        |                |  |      |   |                     |            |               |   |  |

BOREHOLE RECORD - YATES BORING LOGS.GPJ - PIEDMONT.GDT 9/26/17

LOG SCALE: 1 in = 6.5 ft  
 DRILLING COMPANY: Cascade Drilling  
 DRILLER: Dale

GA INSPECTOR: Ben Hodges  
 CHECKED BY: Rachel Kirkman, PG  
 DATE: 9/29/17



# RECORD OF BOREHOLE YGWC-44/ PZ-44

SHEET 1 of 2

PROJECT: SCS Plant Yates  
 PROJECT NUMBER: 1660300  
 DRILLED DEPTH: 87.00 ft  
 LOCATION: Newnan, GA

DRILL RIG: Sonic PS-150  
 DATE STARTED: 7/11/16  
 DATE COMPLETED: 7/13/16

NORTHING: 1,261,874.46  
 EASTING: 2,071,218.56  
 GS ELEVATION: 755.39  
 TOC ELEVATION: 758.27 ft

DEPTH W.L.: 34.1 ft (bgs)  
 ELEVATION W.L.: (amsl)  
 DATE W.L.: 7/13/2016  
 TIME W.L.: N/A

| DEPTH (ft) | ELEVATION (ft) | SOIL PROFILE  |      |                                   |                           | SAMPLES    |                |     | MONITORING WELL/<br>PIEZOMETER<br>DIAGRAM and NOTES | WELL<br>CONSTRUCTION<br>DETAILS  |
|------------|----------------|---|------|-----------------------------------|---------------------------|------------|----------------|-----|---|--|
|            |                | DESCRIPTION   | USCS | GRAPHIC LOG                       | ELEV.<br>DEPTH (ft)       | SAMPLE NO. | TYPE           | REC |   |  |
| 0          | 755            | 0.00 - 10.00<br>No recovery; hydrovac   |      |                                   |                           |            |                |     |   | <p><b>WELL CASING</b><br/>Interval: 0.0'-75.5'<br/>Material: Schedule 40 PVC<br/>Diameter: 2"<br/>Joint Type: Threaded</p> <p><b>WELL SCREEN</b><br/>Interval: 75.5'-85.5'<br/>Material: U-Pack Schedule 40 PVC<br/>Diameter: 2"<br/>Slot Size: 0.010"<br/>End Cap: Schedule 40 PVC</p> <p><b>FILTER PACK</b><br/>Interval: 72.5'-87.0'<br/>Type: #1 Type Sand</p> <p><b>FILTER PACK SEAL</b><br/>Interval: 67.0'-72.5'<br/>Type: Bentonite Pellets and Chips</p> <p><b>ANNULUS SEAL</b><br/>Interval: 0.0'-67'<br/>Type: Portland Type 1</p> <p><b>WELL COMPLETION</b><br/>Pad: 4'x4'x4"<br/>Protective Casing: Aluminum</p> <p><b>DRILLING METHODS</b><br/>Soil Drill: 4" Sonic<br/>Rock Drill: 4" Sonic</p> |
| 5          | 750            |   |      |                                   |                           |            |                |     |   |  |
| 10         | 745            | 10.00 - 17.00<br>silty SAND, red to light brown, moist, micaceous, plagioclase            | SM   | [Graphic Log: Silty Sand]         | 745.39<br>10.00           | 1          | 7.00<br>7.00   |     |   |  |
| 15         | 740            |   |      |                                   |                           |            |                |     |   |  |
| 20         | 735            | 17.00 - 27.00<br>poorly sorted SAND, fine to medium sand, dark red to tan, dry to moist   | SP   | [Graphic Log: Poorly sorted sand] | 738.39<br>17.00           | 2          | 10.00<br>10.00 |     |   |  |
| 25         | 730            |   |      |                                   |                           |            |                |     |   |  |
| 30         | 725            | 27.00 - 28.00<br>silty SAND, some clay, red   | SM   | [Graphic Log: Silty sand]         | 728.39<br>27.00<br>727.39 | 3          | 10.00<br>10.00 |     |   |  |
| 35         | 720            | 28.00 - 34.00<br>some gravel, red, increasing mica with depth, moist                      |      |                                   | 721.39<br>34.00           |            |                |     |   |  |
| 40         | 715            | 34.00 - 37.00<br>tan to grey, plagioclase with biotite                                    |      |                                   | 718.39<br>37.00           |            |                |     |   |  |
| 45         | 710            | 37.00 - 47.00<br>tan to orange, occasional saprolite, biotite lenses                      |      |                                   |                           | 4          | 10.00<br>10.00 |     |   |  |
| 50         | 705            | 47.00 - 57.00<br>medium to fine sand, some gravel, grey to tan, plagioclase, dry to moist |      |                                   | 708.39<br>47.00           | 5          | 8.00<br>10.00  |     |   |  |

BOREHOLE RECORD: YATES BORING LOGS.GPJ PIEDMONT.GDT 9/26/17

Log continued on next page

LOG SCALE: 1 in = 6.5 ft  
 DRILLING COMPANY: Cascade Drilling  
 DRILLER: Tom Ardito

GA INSPECTOR: Kirk Fraley  
 CHECKED BY: Rachel Kirkman, PG  
 DATE: 9/29/17



# RECORD OF BOREHOLE YGWC-44/ PZ-44

SHEET 2 of 2

PROJECT: SCS Plant Yates  
 PROJECT NUMBER: 1660300  
 DRILLED DEPTH: 87.00 ft  
 LOCATION: Newnan, GA

DRILL RIG: Sonic PS-150  
 DATE STARTED: 7/11/16  
 DATE COMPLETED: 7/13/16

NORTHING: 1,261,874.46  
 EASTING: 2,071,218.56  
 GS ELEVATION: 755.39  
 TOC ELEVATION: 758.27 ft

DEPTH W.L.: 34.1 ft (bgs)  
 ELEVATION W.L.: (amsl)  
 DATE W.L.: 7/13/2016  
 TIME W.L.: N/A

| DEPTH (ft) | ELEVATION (ft) | SOIL PROFILE  |        |             | SAMPLES          |            |      | MONITORING WELL/PIEZOMETER DIAGRAM and NOTES | WELL CONSTRUCTION DETAILS   |
|------------|----------------|---|--------|-------------|------------------|------------|------|--|---|
|            |                | DESCRIPTION   | USCS   | GRAPHIC LOG | ELEV. DEPTH (ft) | SAMPLE NO. | TYPE |  |   |
| 50         | 705            | 47.00 - 57.00<br>medium to fine sand, some gravel, grey to tan, plagioclase, dry to moist (Continued)       |        |             |                  | 5          |      | 8.00<br>10.00                                | <p><b>WELL CASING</b><br/>Interval: 0.0'-75.5'<br/>Material: Schedule 40 PVC<br/>Diameter: 2"<br/>Joint Type: Threaded</p> <p><b>WELL SCREEN</b><br/>Interval: 75.5'-85.5'<br/>Material: U-Pack Schedule 40 PVC<br/>Diameter: 2"<br/>Slot Size: 0.010"<br/>End Cap: Schedule 40 PVC</p> <p><b>FILTER PACK</b><br/>Interval: 72.5'-87.0'<br/>Type: #1 Type Sand</p> <p><b>FILTER PACK SEAL</b><br/>Interval: 67.0'-72.5'<br/>Type: Bentonite Pellets and Chips</p> <p><b>ANNULUS SEAL</b><br/>Interval: 0.0'-67'<br/>Type: Portland Type 1</p> <p><b>WELL COMPLETION</b><br/>Pad: 4"x4"<br/>Protective Casing: Aluminum</p> <p><b>DRILLING METHODS</b><br/>Soil Drill: 4" Sonic<br/>Rock Drill: 4" Sonic</p> |
| 55         | 700            | 57.00 - 63.00<br>some gravel, grey-tan, weathered quartz lenses, dry-moist                                  |        |             | 698.39<br>57.00  |            |      |  |   |
| 60         | 695            | 63.00 - 66.00<br>transitionally weathered rock - with silty sand and gravel, grey, tan, quartz lenses       | PWR    |             | 692.39<br>63.00  | 6          |      | 8.00<br>10.00                                |   |
| 65         | 690            | 66.00 - 87.00<br>bedrock - AMPHIBOLITE, grading to feldspathic Gneiss, fresh to weathered, strong foliation |        |             | 689.39<br>66.00  |            |      |  |   |
| 70         | 685            |   |        |             |                  | 7          |      | 7.00<br>10.00                                |   |
| 75         | 680            |   | SCHIST |             |                  |            |      |  |   |
| 80         | 675            |   |        |             |                  | 8          |      | 5.00<br>10.00                                |   |
| 85         | 670            |   |        |             |                  |            |      |  |   |
|            |                | Boring completed at 87.00 ft  |        |             |                  |            |      |  |   |
| 90         | 665            |   |        |             |                  |            |      |  |   |
| 95         | 660            |   |        |             |                  |            |      |  |   |
| 100        |                |   |        |             |                  |            |      |  |   |

BOREHOLE RECORD - YATES BORING LOGS.GPJ - PIEDMONT.GDT 9/26/17

LOG SCALE: 1 in = 6.5 ft  
 DRILLING COMPANY: Cascade Drilling  
 DRILLER: Tom Ardito

GA INSPECTOR: Kirk Fraley  
 CHECKED BY: Rachel Kirkman, PG  
 DATE: 9/29/17



# RECORD OF BOREHOLE YGWC-45/ PZ-45

SHEET 1 of 2

PROJECT: SCS Plant Yates  
 PROJECT NUMBER: 1660300  
 DRILLED DEPTH: 71.30 ft  
 LOCATION: Newman, GA

DRILL RIG: Sonic PS-150  
 DATE STARTED: 7/9/16  
 DATE COMPLETED: 7/10/16

NORTHING: 1,261,668.89  
 EASTING: 2,070,911.89  
 GS ELEVATION: 716.34  
 TOC ELEVATION: 719.30 ft

DEPTH W.L.: 20.3 ft (bgs)  
 ELEVATION W.L.: (amsl)  
 DATE W.L.: 7/10/2016  
 TIME W.L.: 08:20

| DEPTH (ft) | ELEVATION (ft) | SOIL PROFILE  |      |             |                                    | SAMPLES    |      |                | MONITORING WELL/<br>PIEZOMETER<br>DIAGRAM and NOTES | WELL<br>CONSTRUCTION<br>DETAILS   |
|------------|----------------|---|------|-------------|------------------------------------|------------|------|----------------|---|---|
|            |                | DESCRIPTION   | USCS | GRAPHIC LOG | ELEV.<br>DEPTH (ft)                | SAMPLE NO. | TYPE | REC            |   |   |
| 0          | 715            | 0.00 - 10.00<br>no recovery; hydrovac   |      |             |                                    |            |      |                | Portland<br>Type 1                                  | <p><b>WELL CASING</b><br/>Interval: 0.0'-60.0'<br/>Material: Schedule 40 PVC<br/>Diameter: 2"<br/>Joint Type: Threaded</p> <p><b>WELL SCREEN</b><br/>Interval: 60.0'-70.0'<br/>Material: U-Pack Schedule 40 PVC<br/>Diameter: 2"<br/>Slot Size: 0.010" Slotted<br/>Screen<br/>End Cap: Schedule 40 PVC</p> <p><b>FILTER PACK</b><br/>Interval: 58.0'-71.3'<br/>Type: #1 Type Sand</p> <p><b>FILTER PACK SEAL</b><br/>Interval: 51.0'-58.0'<br/>Type: Bentonite Pellets and Chips</p> <p><b>ANNULUS SEAL</b><br/>Interval: 0.0'-51.0'<br/>Type: Portland Type 1</p> <p><b>WELL COMPLETION</b><br/>Pad: 4'x4'x4"<br/>Protective Casing: Aluminum</p> <p><b>DRILLING METHODS</b><br/>Soil Drill: 4" Sonic<br/>Rock Drill: 4" Sonic</p> |
| 5          | 710            |   |      |             |                                    |            |      |                |   |   |
| 10         | 705            | 10.00 - 16.00<br>sandy SILT, reddish brown to light yellowish brown, cohesive, low plastic, moist   | ML   |             | 706.34<br>10.00                    | 1          |      | 6.00<br>6.00   |   |   |
| 15         | 700            | 16.00 - 24.00<br>reddish brown to light yellowish brown, cohesive, low plastic, moist   |      |             | 700.34<br>16.00                    |            |      |                |   |   |
| 20         | 695            |   |      |             | 692.34<br>24.00                    | 2          |      | 10.00<br>10.00 |   |   |
| 25         | 690            | 24.00 - 26.00<br>silty SAND, dark brown and angular trace gravel, yellowish grey, fine to medium sand, cohesive, moist  | SM   |             | 690.34<br>26.00                    |            |      |                |   |   |
| 30         | 685            | 26.00 - 33.00<br>dark brown and angular trace gravel, yellowish grey, fine to medium sand, feldspar nodules, weathered amphibolite pieces, cohesive, moist                              |      |             | 683.34<br>33.00                    | 3          |      | 10.00<br>10.00 |   |   |
| 35         | 680            | 33.00 - 35.00<br>trace gravel, greenish black, fine to medium sand, coarse and angular gravel, dry  |      |             | 681.34<br>35.00                    |            |      |                |   |   |
| 40         | 675            | 35.00 - 36.00<br>yellowish grey, dry  |      |             | 680.34<br>36.00                    |            |      |                |   |   |
| 45         | 670            | 36.00 - 45.00<br>SAND, some gravel and silt, fine to coarse sand, subangular and highly weathered, dark reddish brown, increasing gravel, dry, loose                                    | SW   |             | 671.34<br>45.00<br>670.34<br>46.00 | 4          |      | 10.00<br>10.00 |   |   |
| 50         |                | 46.00 - 51.00<br>SAND, some gravel and silt, fine to coarse sand, subangular and highly weathered, dark reddish brown, gneissic fabric noted, increasing gravel, dry, loose (saprolite) |      |             | 670.34<br>46.00                    | 5          |      | 5.00<br>5.00   |   |   |

Log continued on next page

BOREHOLE RECORD\_YATES BORING LOGS.GPJ\_PIEDMONT.GDT 9/26/17

LOG SCALE: 1 in = 6.5 ft  
 DRILLING COMPANY: Cascade Drilling  
 DRILLER: Dale

GA INSPECTOR: Ben Hodges  
 CHECKED BY: Rachel Kirkman, PG  
 DATE: 9/29/17



# RECORD OF BOREHOLE YGWC-45/ PZ-45

SHEET 2 of 2

PROJECT: SCS Plant Yates  
 PROJECT NUMBER: 1660300  
 DRILLED DEPTH: 71.30 ft  
 LOCATION: Newnan, GA

DRILL RIG: Sonic PS-150  
 DATE STARTED: 7/9/16  
 DATE COMPLETED: 7/10/16

NORTHING: 1,261,668.89  
 EASTING: 2,070,911.89  
 GS ELEVATION: 716.34  
 TOC ELEVATION: 719.30 ft

DEPTH W.L.: 20.3 ft (bgs)  
 ELEVATION W.L.: (amsl)  
 DATE W.L.: 7/10/2016  
 TIME W.L.: 08:20

| DEPTH (ft) | ELEVATION (ft) | SOIL PROFILE   |        |                               |                     | SAMPLES    |               |     | MONITORING WELL/<br>PIEZOMETER<br>DIAGRAM and NOTES | WELL<br>CONSTRUCTION<br>DETAILS  |
|------------|----------------|--|--------|-------------------------------|---------------------|------------|---------------|-----|---|--|
|            |                | DESCRIPTION  | USCS   | GRAPHIC LOG                   | ELEV.<br>DEPTH (ft) | SAMPLE NO. | TYPE          | REC |   |  |
| 50         | 665            | 51.00 - 56.00<br>transitionally weathered rock - highly weathered garnet SCHIST, some amphibolite, coarse to fine sand | PWR    | [Graphic Log: Blue triangles] | 665.34              | 5          |               |     | Bentonite Pellets and Chips                         | <b>WELL CASING</b><br>Interval: 0.0'-60.0'<br>Material: Schedule 40 PVC<br>Diameter: 2"<br>Joint Type: Threaded<br><br><b>WELL SCREEN</b><br>Interval: 60.0'-70.0'<br>Material: U-Pack Schedule 40 PVC<br>Diameter: 2"<br>Slot Size: 0.010" Slotted Screen<br>End Cap: Schedule 40 PVC |
| 55         | 660            |  |        |                               | 51.00               | 6          | 5.00<br>5.00  |     |   |  |
| 60         | 660            | 56.00 - 66.00<br>bedrock - AMPHIBOLITE/SCHIST, competent, pyrite inclusions  | SCHIST | [Graphic Log: Wavy lines]     | 660.34              |            |               |     | 0.010" Slotted Screen                               | <b>FILTER PACK</b><br>Interval: 58.0'-71.3'<br>Type: #1 Type Sand<br><br><b>FILTER PACK SEAL</b><br>Interval: 51.0'-58.0'<br>Type: Bentonite Pellets and Chips<br><br><b>ANNULUS SEAL</b><br>Interval: 0.0'-51.0'<br>Type: Portland Type 1   |
| 65         | 655            |  |        |                               | 56.00               | 7          | 4.00<br>10.00 |     |   |  |
| 65         | 650            | 66.00 - 71.00<br>competent, pyrite inclusions  |        | [Graphic Log: Wavy lines]     | 650.34              |            |               |     | #1 Type Sand  | <b>WELL COMPLETION</b><br>Pad: 4'x4'x4"<br>Protective Casing: Aluminum<br><br><b>DRILLING METHODS</b><br>Soil Drill: 4" Sonic<br>Rock Drill: 4" Sonic  |
| 70         | 645            |  |        |                               | 66.00               | 8          | 4.00<br>5.00  |     |   |  |
| 75         | 645            | Boring completed at 71.30 ft   |        |                               |                     | 645.34     |               |     | Sump  |  |
| 80         | 640            |  |        |                               |                     |            |               |     |   |  |
| 85         | 635            |  |        |                               |                     |            |               |     |   |  |
| 90         | 630            |  |        |                               |                     |            |               |     |   |  |
| 95         | 625            |  |        |                               |                     |            |               |     |   |  |
| 100        | 620            |  |        |                               |                     |            |               |     |   |  |

BOREHOLE RECORD - YATES BORING LOGS.GPJ - PIEDMONT.GDT 9/26/17

LOG SCALE: 1 in = 6.5 ft  
 DRILLING COMPANY: Cascade Drilling  
 DRILLER: Dale

GA INSPECTOR: Ben Hodges  
 CHECKED BY: Rachel Kirkman, PG  
 DATE: 9/29/17



# RECORD OF BOREHOLE YGWC-46/ PZ-46

SHEET 1 of 2

PROJECT: SCS Plant Yates  
 PROJECT NUMBER: 1660300  
 DRILLED DEPTH: 80.00 ft  
 LOCATION: Newman, GA

DRILL RIG: Sonic PS-150  
 DATE STARTED: 7/10/16  
 DATE COMPLETED: 7/11/16

NORTHING: 1,261,031.44  
 EASTING: 2,071,035.31  
 GS ELEVATION: 744.32  
 TOC ELEVATION: 747.23 ft

DEPTH W.L.: 42.2 ft (bgs)  
 ELEVATION W.L.: (amsl)  
 DATE W.L.: 7/11/2016  
 TIME W.L.: 08:00

| DEPTH (ft) | ELEVATION (ft) | SOIL PROFILE  |       |                                    |                     | SAMPLES    |               |     | MONITORING WELL/<br>PIEZOMETER<br>DIAGRAM and NOTES | WELL<br>CONSTRUCTION<br>DETAILS   |
|------------|----------------|---|-------|------------------------------------|---------------------|------------|---------------|-----|---|---|
|            |                | DESCRIPTION   | USCS  | GRAPHIC LOG                        | ELEV.<br>DEPTH (ft) | SAMPLE NO. | TYPE          | REC |   |   |
| 0          |                | 0.00 - 10.00<br>no recovery, hydrovac   |       |                                    |                     |            |               |     | Portland<br>Type 1                                  | <p><b>WELL CASING</b><br/>Interval: 0.0'-70.0'<br/>Material: Schedule 40 PVC<br/>Diameter: 2"<br/>Joint Type: Threaded</p> <p><b>WELL SCREEN</b><br/>Interval: 70.0'-80.0'<br/>Material: U-Pack Schedule 40 PVC<br/>Diameter: 2"<br/>Slot Size: 0.010" Slotted<br/>Screen<br/>End Cap: Schedule 40 PVC</p> <p><b>FILTER PACK</b><br/>Interval: 68.0'-80.0'<br/>Type: #1 Type Sand</p> <p><b>FILTER PACK SEAL</b><br/>Interval: 62.5'-68.0'<br/>Type: Bentonite Pellets and Chips</p> <p><b>ANNULUS SEAL</b><br/>Interval: 0.0'-62.5'<br/>Type: Portland Type 1</p> <p><b>WELL COMPLETION</b><br/>Pad: 4'x4'x4"<br/>Protective Casing: Aluminum</p> <p><b>DRILLING METHODS</b><br/>Soil Drill: 4" Sonic<br/>Rock Drill: 4" Sonic</p> |
| 740        |                |   |       |                                    |                     |            |               |     |   |   |
| 735        |                | 10.00 - 20.00<br>silty SAND, fine to medium sand, non-plastic to low plastic fines, red to tan to orange tan to grey tan, micaceous, plagioclase zones, cohesive, moist | SM    | [Graphic Log: Silty Sand]          | 734.32<br>10.00     | 1          | 6.50<br>8.00  |     |   |   |
| 730        |                |   |       |                                    |                     |            |               |     |   |   |
| 725        |                | 20.00 - 23.00<br>fine to coarse SAND, tan   | SP-SM | [Graphic Log: Fine to coarse sand] | 724.32<br>20.00     |            |               |     |   |   |
| 720        |                | 23.00 - 28.00<br>silty SAND, fine to medium sand, non-plastic to low plastic fines, red to tan to orange tan to grey tan, micaceous, plagioclase zones, cohesive, moist | SM    | [Graphic Log: Silty Sand]          | 721.32<br>23.00     | 2          | 8.00<br>10.00 |     |   |   |
| 715        |                | 28.00 - 31.00<br>fine to coarse SAND, tan   | SP-SM | [Graphic Log: Fine to coarse sand] | 716.32<br>28.00     |            |               |     |   |   |
| 710        |                | 31.00 - 39.00<br>silty SAND, fine to medium sand, non-plastic to low plastic fines, red to tan to orange tan to grey tan, micaceous, plagioclase zones, cohesive, moist | SM    | [Graphic Log: Silty Sand]          | 713.32<br>31.00     | 3          | 8.50<br>10.00 |     |   |   |
| 705        |                | 39.00 - 44.00<br>transitionally weathered rock - highly weathered AMPHIBOLITE to SCHIST, fine-grained, grey and black, iron deposits                                    | PWR   | [Graphic Log: Weathered rock]      | 705.32<br>39.00     |            |               |     |   |   |
| 700        |                | 44.00 - 48.00<br>medium to highly weathered, medium strong to extremely strong, quartz, migmatite granite layers present  |       | [Graphic Log: Weathered rock]      | 700.32<br>44.00     | 4          | 7.80<br>10.00 |     |   |   |
| 695        |                | 48.00 - 59.00<br>highly weathered biotite GNEISS, green seams, quartz fragments   |       | [Graphic Log: Weathered rock]      | 696.32<br>48.00     | 5          | 5.00<br>10.00 |     |   |   |

Log continued on next page

BOREHOLE RECORD\_YATES BORING LOGS.GPJ\_PIEDMONT.GDT 9/26/17

LOG SCALE: 1 in = 6.5 ft  
 DRILLING COMPANY: Cascade Drilling  
 DRILLER: Tom Ardito

GA INSPECTOR: Courtney Vissman  
 CHECKED BY: Rachel Kirkman, PG  
 DATE: 9/29/17



# RECORD OF BOREHOLE YGWC-46/ PZ-46

SHEET 2 of 2

PROJECT: SCS Plant Yates  
 PROJECT NUMBER: 1660300  
 DRILLED DEPTH: 80.00 ft  
 LOCATION: Newman, GA

DRILL RIG: Sonic PS-150  
 DATE STARTED: 7/10/16  
 DATE COMPLETED: 7/11/16

NORTHING: 1,261,031.44  
 EASTING: 2,071,035.31  
 GS ELEVATION: 744.32  
 TOC ELEVATION: 747.23 ft

DEPTH W.L.: 42.2 ft (bgs)  
 ELEVATION W.L.: (amsl)  
 DATE W.L.: 7/11/2016  
 TIME W.L.: 08:00

| DEPTH (ft) | ELEVATION (ft) | SOIL PROFILE  |        |             |                  | SAMPLES    |      |     | MONITORING WELL/ PIEZOMETER DIAGRAM and NOTES | WELL CONSTRUCTION DETAILS   |   |
|------------|----------------|---|--------|-------------|------------------|------------|------|-----|---|---|---|
|            |                | DESCRIPTION   | USCS   | GRAPHIC LOG | ELEV. DEPTH (ft) | SAMPLE NO. | TYPE | REC |   |   |   |
| 50         |                | 48.00 - 59.00<br>highly weathered biotite GNEISS, green seams, quartz fragments<br><i>(Continued)</i>                           |        | ▲▲▲▲▲       |                  |            |      | 5   | 5.00<br>10.00                                 | <p style="font-size: small;">1/2" Bentonite Pelletes</p> <p style="font-size: small;">0.010" Slotted Screen</p> <p style="font-size: small;">#1 Type Sand</p> <p style="font-size: small;">Sump</p> | <p><b>WELL CASING</b><br/>Interval: 0.0'-70.0'<br/>Material: Schedule 40 PVC<br/>Diameter: 2"<br/>Joint Type: Threaded</p> <p><b>WELL SCREEN</b><br/>Interval: 70.0'-80.0'<br/>Material: U-Pack Schedule 40 PVC<br/>Diameter: 2"<br/>Slot Size: 0.010" Slotted Screen<br/>End Cap: Schedule 40 PVC</p> <p><b>FILTER PACK</b><br/>Interval: 68.0'-80.0'<br/>Type: #1 Type Sand</p> <p><b>FILTER PACK SEAL</b><br/>Interval: 62.5'-68.0'<br/>Type: Bentonite Pelletes and Chips</p> <p><b>ANNULUS SEAL</b><br/>Interval: 68.0'-80.0'<br/>Type: Portland Type 1</p> <p><b>WELL COMPLETION</b><br/>Pad: 4'x4'x4"<br/>Protective Casing: Aluminum</p> <p><b>DRILLING METHODS</b><br/>Soil Drill: 4" Sonic<br/>Rock Drill: 4" Sonic</p> |
| 55         | 690            |   |        |             | 685.32           |            |      |     |   |   |   |
| 60         | 685            | 59.00 - 60.00<br>highly weathered migmatitic GNEISS   |        | ▲▲▲▲▲       | 59.00<br>684.32  |            |      |     |   |   |   |
| 65         | 680            | 60.00 - 68.00<br>biotite GNEISS with AMPHIBOLITE, dark, highly weathered with quartz bands                                      |        | ▲▲▲▲▲       | 60.00            |            |      | 6   | 5.00<br>10.00                                 |   |   |
| 70         | 675            | 68.00 - 73.00<br>AMPHIBOLITE, medium to highly weathered, medium strong to extremely strong, quartz, migmatite granite layers   |        | ▲▲▲▲▲       | 676.32<br>68.00  |            |      |     |   |   |   |
| 75         | 670            | 73.00 - 75.00<br>medium to highly weathered, medium strong to extremely strong, quartz, migmatite granite layers, iron staining |        | ▲▲▲▲▲       | 671.32<br>73.00  |            |      | 7   | 5.00<br>9.00                                  |   |   |
| 80         | 665            | 75.00 - 78.00<br>highly weathered biotite GNEISS and SCHIST   |        | ▲▲▲▲▲       | 669.32<br>75.00  |            |      |     |   |   |   |
| 85         | 660            | 78.00 - 80.00<br>bedrock - AMPHIBOLITE, extremely strong, high quartz content, stains   | SCHIST | ▲▲▲▲▲       | 666.32<br>78.00  |            |      | 8   | 3.00<br>3.00                                  |   |   |
|            |                | Boring completed at 80.00 ft  |        |             |                  |            |      |     |   |   |   |
| 90         | 655            |   |        |             | 664.32           |            |      |     |   |   |   |
| 95         | 650            |   |        |             |                  |            |      |     |   |   |   |
| 100        | 645            |   |        |             |                  |            |      |     |   |   |   |

BOREHOLE RECORD - YATES BORING LOGS.GPJ - PIEDMONT.GDT 9/26/17

LOG SCALE: 1 in = 6.5 ft  
 DRILLING COMPANY: Cascade Drilling  
 DRILLER: Tom Ardito

GA INSPECTOR: Courtney Vissman  
 CHECKED BY: Rachel Kirkman, PG  
 DATE: 9/29/17





# LOG OF TEST BORING AND WELL INSTALLATION

**BORING PZ-9I**  
PAGE 1 OF 2  
ECS37976

SOUTHERN COMPANY SERVICES, INC.  
EARTH SCIENCE AND ENVIRONMENTAL ENGINEERING

PROJECT Plant Yates Hydro-Geological Study  
LOCATION Newnan, GA

DATE STARTED 5/2/2014 COMPLETED 5/19/2014 SURF. ELEV. 709.8 COORDINATES: N:1,261,995.57 E:2,070,721.12

CONTRACTOR Cascade Drilling EQUIPMENT PS-150 METHOD Rotosonic

DRILLED BY D. Wilcox LOGGED BY B. Smelser CHECKED BY \_\_\_\_\_ ANGLE \_\_\_\_\_ BEARING \_\_\_\_\_

BORING DEPTH 77 ft. GROUND WATER DEPTH: DURING \_\_\_\_\_ COMP. 13.6 ft. DELAYED \_\_\_\_\_

NOTES Surface Elevation noted above is the elevation of the survey pin located in the top of the concrete pad; Top of Casing Elevation = 712.044

2012 GEOTECH LOG WITH WELL - ESEE2012DATABASE.GDT - 7/9/14 14:47 - \\ALTRCF502X2DBSMEL\$\GINT\PLANT YATES HYDRO-GEOLOGICAL STUDY.GPJ

| DEPTH (ft) | GRAPHIC LOG | STRATA DESCRIPTION   | WELL DATA   |
|------------|-------------|--|---|
|            |             |  | Surface:<br>protective aluminum cover with bollards; 4-foot square concrete pad |
|            |             |  | ELEV. (DEPTH)   |
| 5          |             | <b>Fill (FILL)</b><br>- reddish brown grading to dark reddish brown with black mottling @ 2' grading to rusty red @ 4', damp, medium stiff to stiff, low plasticity, very fine to lower fine grain, cohesive; micaceous; trace organics near surface   | 707.8<br>(2.0)  |
| 10         |             | <b>Silt (ML)</b><br>- orangish brown with light brown/tan to rusty red mottling, damp, very stiff to stiff decreasing to medium stiff to soft, low plasticity, very fine to upper fine grain, cohesive; decreasing clay content with depth to a more silty sand with clay; increasing grain size with depth; micaceous               | 702.8   |
| 15         |             | <b>Silty Sand (SM)</b><br>- rusty red with black mottling, damp, medium dense, no plasticity, lower fine to upper fine grain, cohesive; micaceous; thin layer of interbedded/mottled, fine to medium sized with trace upper coarse to fine gravel sized bottom ash   | 695.8   |
| 20         |             | <b>Poorly-graded Sand (SP)</b><br>- orangish brown, moist, medium dense to loose, no plasticity, lower medium to lower coarse grain, <i>alluvium</i> , noncohesive; rounded to subrounded grains; rounded gravel to cobble sized inclusions; possible alluvial sediments   | 692.8   |
| 25         |             | <b>Silty Sand (SM)</b><br>- dark brown to orangish brown with rusty red to light gray to greenish gray mottling, moist, medium dense to loose, no plasticity, lower fine to lower medium grain, <i>saprolite</i> , cohesive; completely weathered to residual soil; subangular to subrounded grains; micaceous                       | 687.3   |
| 30         |             | - SM: medium gray to light gray with white mottling, trace greenish gray to dark brown mottling, moist, medium dense, no plasticity, lower fine to lower medium grain, <i>saprolite</i> , noncohesive; completely weathered to residual soil; subangular to angular grains; micaceous  |   |
| 35         |             | - SM: light brown to orangish brown with light gray mottling, moist, medium dense to loose interbedded with zones of dense, no plasticity, upper fine to upper medium grain, <i>saprolite</i> , noncohesive; completely weathered to residual soil; quartz, muscovite, biotite identifiable; micaceous; angular to subangular grains |   |
| 40         |             |  |   |

Annular Fill: 90/10 Portland Cement/Bentonite Powder

(Continued Next Page)



# LOG OF TEST BORING AND WELL INSTALLATION


**BORING PZ-9I**  
PAGE 2 OF 2  
ECS37976

SOUTHERN COMPANY SERVICES, INC.  
EARTH SCIENCE AND ENVIRONMENTAL ENGINEERING

PROJECT Plant Yates Hydro-Geological Study

LOCATION Newnan, GA

2012 GEOTECH LOG WITH WELL - ESEE2012DATABASE.GDT - 7/9/14 14:47 - \\ALTRCF502X2DBSMEL\$\GINT\PLANT YATES HYDRO-GEOLOGICAL STUDY.GPJ





# LOG OF TEST BORING AND WELL INSTALLATION

**BORING PZ-9S**  
PAGE 1 OF 2  
ECS37976

SOUTHERN COMPANY SERVICES, INC.  
EARTH SCIENCE AND ENVIRONMENTAL ENGINEERING

PROJECT Plant Yates Hydro-Geological Study  
LOCATION Newnan, GA

DATE STARTED 5/2/2014 COMPLETED 5/19/2014 SURF. ELEV. 709.8 COORDINATES: N:1,262,003.29 E:2,070,721.60

CONTRACTOR Cascade Drilling EQUIPMENT PS-150 METHOD Rotosonic

DRILLED BY D. Wilcox LOGGED BY B. Smelser CHECKED BY \_\_\_\_\_ ANGLE \_\_\_\_\_ BEARING \_\_\_\_\_

BORING DEPTH 57 ft. GROUND WATER DEPTH: DURING \_\_\_\_\_ COMP. 13.51 ft. DELAYED \_\_\_\_\_

NOTES Surface Elevation noted above is the elevation of the survey pin located in the top of the concrete pad; Top of Casing Elevation = 711.896

2012 GEOTECH LOG WITH WELL - ESEE2012.DATABASE.GDT - 7/9/14 14:49 - \\ALTRCF502\X2\BDSMEL\GINT\PLANT YATES HYDRO-GEOLOGICAL STUDY.GPJ

| DEPTH (ft) | GRAPHIC LOG | STRATA DESCRIPTION   | ELEV. | WELL DATA   |
|------------|-------------|--|-------|---|
|            |             |  |       | Surface:<br>protective aluminum cover with bollards; 4-foot square concrete pad |
|            |             |  |       | ELEV. (DEPTH)   |
| 5          |             | <b>Fill (FILL)</b><br>- reddish brown grading to dark reddish brown with black mottling @ 2' grading to rusty red @ 4', damp, medium stiff to stiff, low plasticity, very fine to lower fine grain, cohesive; micaceous; trace organics near surface   | 707.8 | ← Surface Seal: concrete  |
| 10         |             | <b>Silt (ML)</b><br>- orangish brown with light brown/tan to rusty red mottling, damp, very stiff to stiff decreasing to medium stiff to soft, low plasticity, very fine to upper fine grain, cohesive; decreasing clay content with depth to a more silty sand with clay; increasing grain size with depth; micaceous               | 702.8 |   |
| 15         |             | <b>Silty Sand (SM)</b><br>- rusty red with black mottling, damp, medium dense, no plasticity, lower fine to upper fine grain, cohesive; micaceous; thin layer of interbedded/mottled, fine to medium-sized with trace upper coarse to fine gravel sized bottom ash   | 695.8 |   |
| 20         |             | <b>Poorly-graded Sand (SP)</b><br>- orangish brown, moist, medium dense to loose, no plasticity, lower medium to lower coarse grain, <i>alluvium</i> , noncohesive; rounded to subrounded grains; rounded gravel to cobble sized inclusions; possible alluvial sediments   | 692.8 |   |
| 25         |             | <b>Silty Sand (SM)</b><br>- dark brown to orangish brown with rusty red to light gray to greenish gray mottling, moist, medium dense to loose, no plasticity, lower fine to lower medium grain, <i>saprolite</i> , cohesive; completely weathered to residual soil; subangular to subrounded grains; micaceous                       | 687.3 | ← Annular Fill: 90/10 Portland Cement/Bentonite Powder                          |
| 30         |             | - SM: medium gray to light gray with white mottling, trace greenish gray to dark brown mottling, moist, medium dense, no plasticity, lower fine to lower medium grain, <i>saprolite</i> , noncohesive; completely weathered to residual soil; subangular to angular grains; micaceous  |       |   |
| 35         |             |  |       |   |
| 40         |             | - SM: light brown to orangish brown with light gray mottling, moist, medium dense to loose interbedded with zones of dense, no plasticity, upper fine to upper medium grain, <i>saprolite</i> , noncohesive; completely weathered to residual soil; quartz, muscovite, biotite identifiable; micaceous; angular to subangular grains |       |   |
|            |             |  |       | 667.8   |

(Continued Next Page)



# LOG OF TEST BORING AND WELL INSTALLATION

**BORING PZ-9S**  
PAGE 2 OF 2  
ECS37976

SOUTHERN COMPANY SERVICES, INC.  
EARTH SCIENCE AND ENVIRONMENTAL ENGINEERING

PROJECT Plant Yates Hydro-Geological Study

LOCATION Newnan, GA

|  | DEPTH (ft) | GRAPHIC LOG | STRATA DESCRIPTION   | WELL DATA   | ELEV. (DEPTH)   |
|--|------------|-------------|--|---|-----------------|
|  |            |             |  | Surface:<br>protective aluminum cover with bollards; 4-foot square concrete pad |                 |
|  |            |             |  | ELEV. (CONTINUED)   |                 |
|  | 45         |             | <p><b>Silty Sand (SM) (Con't)</b></p> <p>- SM: light brown to orangish brown with interbedded zones of light gray, moist, medium dense to loose interbedded with zones of dense, no plasticity, upper fine to upper medium grain, <i>saprolite</i>, noncohesive; completely weathered to residual soil; remnant rock fabric visible in the light gray interbedded zones, @ approx. 45-47'; grain size in this zone increases to lower coarse to upper coarse; quartz, muscovite, biotite identifiable; micaceous</p> | <p>Annular Seal: 3/8 Hole Plug (medium bentonite chips)</p>                     | (42.0)<br>664.6 |
|  | 50         |             |  | <p>Filter: 20/30 Silica Sand</p>  | (45.2)<br>663.1 |
|  | 55         |             | <p>- SM: light gray, dry, loose, no plasticity, lower fine to upper medium grain, <i>saprolite</i>, noncohesive; completely weathered to residual soil; brittle/friable gravel sized rock fragments with thin (1-2") zones of rubble/broken rock; angular to subangular rock fragments; rock fragment becomes harder/more competent with depth</p>   | <p>Well: 2" OD PVC (SCH 40)</p> <p>Screen: 10 ft; pre-pack</p>                  | (46.7)<br>653.1 |
|  |            |             | Bottom of borehole at 57.0 feet.   | Sump: 0.30 ft.  | 652.8<br>652.8  |

2012 GEOTECH LOG WITH WELL - ESEE2012DATABASE.GDT - 7/9/14 14:49 - \\ALTRCF02X2DBSMEL\$\GINT\PLANT YATES HYDRO-GEOLOGICAL STUDY.GPJ



# LOG OF TEST BORING AND WELL INSTALLATION

**BORING PZ-101**  
PAGE 1 OF 2  
ECS37976

SOUTHERN COMPANY SERVICES, INC.  
EARTH SCIENCE AND ENVIRONMENTAL ENGINEERING

PROJECT Plant Yates Hydro-Geological Study  
LOCATION Newnan, GA


DATE STARTED 4/17/2014 COMPLETED 5/19/2014 SURF. ELEV. 698.0 COORDINATES: N:1,260,809.74 E:2,070,552.83

CONTRACTOR Cascade Drilling EQUIPMENT PS-150 METHOD Rotosonic

DRILLED BY D. Wilcox LOGGED BY B. Smelser CHECKED BY \_\_\_\_\_ ANGLE \_\_\_\_\_ BEARING \_\_\_\_\_

BORING DEPTH 46.5 ft. GROUND WATER DEPTH: DURING \_\_\_\_\_ COMP. 10.26 ft. DELAYED \_\_\_\_\_

NOTES Surface Elevation noted above is the elevation of the survey pin located in the top of the concrete pad; Top of Casing Elevation = 700.266



2012 GEOTECH LOG WITH WELL - ESEE2012DATABASE.GDT - 6/23/14 13:43 - \\VALTRCF02\X2\DBSMEL\GINT\PLANT YATES HYDRO-GEOLOGICAL STUDY.GPJ

(Continued Next Page)




# LOG OF TEST BORING AND WELL INSTALLATION

**BORING PZ-101**  
PAGE 2 OF 2  
ECS37976

SOUTHERN COMPANY SERVICES, INC.  
EARTH SCIENCE AND ENVIRONMENTAL ENGINEERING

PROJECT Plant Yates Hydro-Geological Study  
LOCATION Newnan, GA

2012 GEOTECH LOG WITH WELL - ESEE2012DATABASE.GDT - 6/23/14 13:43 - \\VALTRCF02\X2DBSME\GINT\PLANT YATES HYDRO-GEOLOGICAL STUDY.GPJ





# LOG OF TEST BORING AND WELL INSTALLATION

**BORING PZ-10S**  
PAGE 1 OF 1  
ECS37976

SOUTHERN COMPANY SERVICES, INC.  
EARTH SCIENCE AND ENVIRONMENTAL ENGINEERING

PROJECT Plant Yates Hydro-Geological Study  
LOCATION Newnan, GA

DATE STARTED 4/17/2014 COMPLETED 5/19/2014 SURF. ELEV. 698.0 COORDINATES: N:1,260,802.29 E:2,070,553.32

CONTRACTOR Cascade Drilling EQUIPMENT PS-150 METHOD Rotosonic

DRILLED BY D. Wilcox LOGGED BY B. Smelser CHECKED BY \_\_\_\_\_ ANGLE \_\_\_\_\_ BEARING \_\_\_\_\_

BORING DEPTH 16.3 ft. GROUND WATER DEPTH: DURING \_\_\_\_\_ COMP. 4.1 ft. DELAYED \_\_\_\_\_

NOTES Surface Elevation noted above is the elevation of the survey pin located in the top of the concrete pad; Top of Casing Elevation = 700.348

2012 GEOTECH LOG WITH WELL - ESEE2012DATABASE.GDT - 6/23/14 13:45 - \VALTRCF502X2DBSME\GINT\PLANT YATES HYDRO-GEOLOGICAL STUDY.GPJ

| DEPTH (ft) | GRAPHIC LOG | STRATA DESCRIPTION | WELL DATA   | ELEV. (DEPTH) |
|------------|-------------|--------------------|---|---------------|
|            |             |                    | Surface:<br>protective aluminum cover with bollards; 4-foot square concrete pad |               |
|            |             |                    |   | 696.0         |
|            |             |                    | ← Surface Seal: concrete  | (2.0)         |
|            |             |                    | ← Annular Seal: 3/8 Hole Plug (medium bentonite chips)                          | 693.5         |
|            |             |                    | ← Filter: 20/30 Silica Sand   | (4.5)         |
|            |             |                    |   | 692.0         |
|            |             |                    |   | (6.0)         |
|            |             |                    | <b>Well: 2" OD PVC (SCH 40)</b>   |               |
|            |             |                    | ← Screen: 10 ft; pre-pack   |               |
|            |             |                    |   | 682.0         |
|            |             |                    | ← Sump: 0.30 ft.  | 681.7         |

**Clayey Sand (SC)**  
- reddish brown, damp, medium dense, low to no plasticity, lower fine to upper fine grain, cohesive; micaceous; trace organics near surface

**Silty Sand (SM)**  
- reddish brown, dry, medium dense to loose, no plasticity, lower fine to upper fine grain, cohesive; micaceous; subangular to subrounded grains

- SM: dark brown, damp, medium dense, no plasticity, lower fine to upper fine grain, cohesive; micaceous; subangular grains

- SM: dark brown, damp, medium dense, no plasticity, lower fine to upper fine grain, cohesive; micaceous; subangular grains

Bottom of borehole at 16.3 feet.




ATLANTIC COAST CONSULTING, INC.

**YAMW-6**

**BORING ID**

**PROJECT:** Plant Yates  
**TOTAL DEPTH:** 71.89 ft. BTOC  
**DATE BEGIN:** 13-Nov-2019  
**DATE COMPLETE:** 18-Nov-2019  
**INSTALLED BY:** Cascade  
**SUPERVISED BY:** Taylor Goble  
**WATER 1ST ENCOUNTERED:** 40' BGS  
**WATER AFTER 48 HOURS:** 35.74' BGS

**PROJECT NO.:** 1054-110  
**SITE LOCATION:** Newnan, Georgia  
**DRILLER:** Jamie Everson  
**RIG TYPE:** T-300 Rotasonic  
**METHOD:** Rotasonic



Northing: 1260964.384  
 Easting: 2070921.276

**SURFACE COMPLETION:**  
 4"x4" Aluminum Protective Casing  
 4"x4"x4" Concrete Pad  
 Weather Resistant Lock  
 Survey Pin

**SOIL DESCRIPTION**  
 0-10' Hydrovac. No observable cuttings

Core Photos

10-15' White silty sand, dry, soft, well sorted, micaceous, and fine grained

15-20' As above except more silt content around 18' and rare brown mottling

20-25' Brittle white micaceous, strong cleavage, friable, dry

25-30' Color change to light brown. Continuation of friable and micaceous. Rock pieces present, quartz rich and brittle with larger rock pieces present at 28'. Dry



**MATERIALS:**

|                   |  |                        |
|-------------------|--|------------------------|
| GROUT:            |  | Bentonite Grout        |
| MANUFACTURER:     |  | AquaGuard              |
| BENTONITE SEAL:   |  | 3/8" Bentonite Pellets |
| MANUFACTURER:     |  | Pel-Plug               |
| FILTER PACK SAND: |  | 20/30 Mesh             |
| MANUFACTURER:     |  | Filter Media           |
| WELL SCREEN:      |  | Sch. 40 - 2" PVC       |
| MANUFACTURER:     |  | Campbell Monoflex      |
| SLOT SIZE:        |  | 0.010-Inch Slot        |
| WELL CASING:      |  | Sch. 40 - 2" PVC       |
| MANUFACTURER:     |  | Campbell Monoflex      |

Soil Descriptions from Unified Soil Classification System


BTOC - Below Top of Casing  
 ID - Inside Diameter; OD - Outside Diameter  
 MSL - Mean Sea Level  
 BGS - Below Ground Surface



ATLANTIC COAST CONSULTING, INC.

**YAMW-6**  
BORING ID

|   |                                       |
|---|---------------------------------------|
| <b>PROJECT:</b> Plant Yates             | <b>PROJECT NO.:</b> 1054-110          |
| <b>TOTAL DEPTH:</b> 71.89 ft. BTOC      | <b>SITE LOCATION:</b> Newnan, Georgia |
| <b>DATE BEGIN:</b> 13-Nov-2019          | <b>DRILLER:</b> Jamie Everson         |
| <b>DATE COMPLETE:</b> 18-Nov-2019       | <b>RIG TYPE:</b> T-300 Rotosonic      |
| <b>INSTALLED BY:</b> Cascade            | <b>METHOD:</b> Rotosonic              |
| <b>SUPERVISED BY:</b> Taylor Goble      |                                       |
| <b>WATER 1ST ENCOUNTERED:</b> 40' BGS   |                                       |
| <b>WATER AFTER 48 HOURS:</b> 35.74' BGS |                                       |



**MATERIALS:**

- |                   |  |                        |
|-------------------|--|------------------------|
| GROUT:            |  | Bentonite Grout        |
| MANUFACTURER:     |  | AquaGuard              |
| BENTONITE SEAL:   |  | 3/8" Bentonite Pellets |
| MANUFACTURER:     |  | Pel-Plug               |
| FILTER PACK SAND: |  | 20/30 Mesh             |
| MANUFACTURER:     |  | Filter Media           |
| WELL SCREEN:      |  | Sch. 40 - 2" PVC       |
| MANUFACTURER:     |  | Silver-Line            |
| SLOT SIZE:        |  | 0.010-Inch Slot        |
| WELL CASING:      |  | Sch. 40 - 2" PVC       |
| MANUFACTURER:     |  | Silver-Line            |


TOC - Top of Casing  
 ID - Inside Diameter; OD - Outside Diameter  
 MSL - Mean Sea Level  
 BGS - Below Ground Surface



ATLANTIC COAST CONSULTING, INC.

**YAMW-6**  
BORING ID

|   |                                       |
|---|---------------------------------------|
| <b>PROJECT:</b> Plant Yates             | <b>PROJECT NO.:</b> I054-110          |
| <b>TOTAL DEPTH:</b> 71.89 ft. BTOC      | <b>SITE LOCATION:</b> Newnan, Georgia |
| <b>DATE BEGIN:</b> 13-Nov-2019          | <b>DRILLER:</b> Jamie Everson         |
| <b>DATE COMPLETE:</b> 18-Nov-2019       | <b>RIG TYPE:</b> T-300 Rotosonic      |
| <b>INSTALLED BY:</b> Cascade            | <b>METHOD:</b> Rotosonic              |
| <b>SUPERVISED BY:</b> Taylor Goble      |                                       |
| <b>WATER 1ST ENCOUNTERED:</b> 40' BGS   |                                       |
| <b>WATER AFTER 48 HOURS:</b> 35.74' BGS |                                       |



**MATERIALS:**

|   |  |  |
|---|--|--|
| GROUT:<br>MANUFACTURER:                     |  | Bentonite Grout<br>AquaGuard                       |
| BENTONITE SEAL:<br>MANUFACTURER:            |  | 3/8" Bentonite Pellets<br>Pel-Plug                 |
| FILTER PACK SAND:<br>MANUFACTURER:          |  | 20/30 Mesh<br>Filter Media                         |
| WELL SCREEN:<br>MANUFACTURER:<br>SLOT SIZE: |  | Sch. 40 - 2" PVC<br>Silver-Line<br>0.010-Inch Slot |
| WELL CASING:<br>MANUFACTURER:               |  | Sch. 40 - 2" PVC<br>Silver-Line                    |

TOC - Top of Casing  
 ID - Inside Diameter; OD - Outside Diameter  
 MSL - Mean Sea Level  
 BGS - Below Ground Surface




ATLANTIC COAST CONSULTING, INC.

**YAMW-7**

**BORING ID**

|  |                                       |
|--|---------------------------------------|
| <b>PROJECT:</b> Plant Yates              | <b>PROJECT NO.:</b> I054-110          |
| <b>TOTAL DEPTH:</b> 122.34 ft. BTOC      | <b>SITE LOCATION:</b> Newnan, Georgia |
| <b>DATE BEGIN:</b> 14-Nov-2019           | <b>DRILLER:</b> Isaac Young           |
| <b>DATE COMPLETE:</b> 15-Nov-2019        | <b>RIG TYPE:</b> T-300 Rotosonic      |
| <b>INSTALLED BY:</b> Cascade             | <b>METHOD:</b> Rotosonic              |
| <b>SUPERVISED BY:</b> Ryan Walker        |                                       |
| <b>WATER 1ST ENCOUNTERED:</b> 33' BGS    |                                       |
| <b>WATER AFTER 48 HOURS:</b> 39.77' BTOC |                                       |

Weather Resistant Lock  
Protective Cover  
733.50 TOC Elevation  
stick-up  
Well Cap  
Vent Hole  
Pea Gravel  
3.40  
Weep Hole  
Survey Pin  
730.10 Ground Elev. (MSL)  
GROUND SURFACE  
SOIL DESCRIPTION  
0-10' No recovery



Core Photos



**MATERIALS:**

|                   |  |                        |
|-------------------|--|------------------------|
| GROUT:            |  | Bentonite Grout        |
| MANUFACTURER:     |  | AquaGuard              |
| BENTONITE SEAL:   |  | 3/8" Bentonite Pellets |
| MANUFACTURER:     |  | Pel-Plug               |
| FILTER PACK SAND: |  | 20/30 Mesh             |
| MANUFACTURER:     |  | Filter Media           |
| WELL SCREEN:      |  | Sch. 40 - 2" PVC       |
| MANUFACTURER:     |  | Campbell Monoflex      |
| SLOT SIZE:        |  | 0.010-Inch Slot        |
| WELL CASING:      |  | Sch. 40 - 2" PVC       |
| MANUFACTURER:     |  | Campbell Monoflex      |

Soil Descriptions from Unified Soil Classification System

BTOC - Below Top of Casing  
 ID - Inside Diameter; OD - Outside Diameter  
 MSL - Mean Sea Level  
 BGS - Below Ground Surface






ATLANTIC COAST CONSULTING, INC.

**YAMW-7**  
BORING ID

PROJECT: Plant Yates  
 TOTAL DEPTH: 122.34 ft. BTOC  
 DATE BEGIN: 14-Nov-2019  
 DATE COMPLETE: 15-Nov-2019  
 INSTALLED BY: Cascade  
 SUPERVISED BY: Ryan Walker  
 WATER 1ST ENCOUNTERED: 33' BGS  
 WATER AFTER 48 HOURS: 39.77' BTOC

PROJECT NO.: I054-110  
 SITE LOCATION: Newnan, Georgia  
 DRILLER: Isaac Young  
 RIG TYPE: T-300 Rotosonic  
 METHOD: Rotosonic

Core Photos



59-69' As above. Very little iron staining present (7/10)

69-79' As above. No iron staining. Extremely hard and quartz-rich rock  
More schist than above (8/10)



**MATERIALS:**

|   |   |  |
|---|---|--|
| GROUT:<br>MANUFACTURER:                     |  | Bentonite Grout<br>AquaGuard                       |
| BENTONITE SEAL:<br>MANUFACTURER:            |  | 3/8" Bentonite Pellets<br>Pel-Plug                 |
| FILTER PACK SAND:<br>MANUFACTURER:          |  | 20/30 Mesh<br>Filter Media                         |
| WELL SCREEN:<br>MANUFACTURER:<br>SLOT SIZE: |  | Sch. 40 - 2" PVC<br>Silver-Line<br>0.010-Inch Slot |
| WELL CASING:<br>MANUFACTURER:               |  | Sch. 40 - 2" PVC<br>Silver-Line                    |

TOC - Top of Casing  
 ID - Inside Diameter; OD - Outside Diameter  
 MSL - Mean Sea Level  
 BGS - Below Ground Surface




ATLANTIC COAST CONSULTING, INC.

**YAMW-7**  
BORING ID

|  |                                       |
|--|---------------------------------------|
| <b>PROJECT:</b> Plant Yates              | <b>PROJECT NO.:</b> I054-110          |
| <b>TOTAL DEPTH:</b> 122.34 ft. BTOC      | <b>SITE LOCATION:</b> Newnan, Georgia |
| <b>DATE BEGIN:</b> 14-Nov-2019           | <b>DRILLER:</b> Isaac Young           |
| <b>DATE COMPLETE:</b> 15-Nov-2019        | <b>RIG TYPE:</b> T-300 Rotosonic      |
| <b>INSTALLED BY:</b> Cascade             | <b>METHOD:</b> Rotosonic              |
| <b>SUPERVISED BY:</b> Ryan Walker        |                                       |
| <b>WATER 1ST ENCOUNTERED:</b> 33' BGS    |                                       |
| <b>WATER AFTER 48 HOURS:</b> 39.77' BTOC |                                       |

Core Photos



79-89' As above. No iron staining. No visible fracturing (8/10)

89-99' As above. More fracturing. No iron staining present (8/10)

99-109' As above. No iron staining present (8/10)



**MATERIALS:**

- |                   |  |                        |
|-------------------|--|------------------------|
| GROUT:            |  | Bentonite Grout        |
| MANUFACTURER:     |  | AquaGuard              |
| BENTONITE SEAL:   |  | 3/8" Bentonite Pellets |
| MANUFACTURER:     |  | Pel-Plug               |
| FILTER PACK SAND: |  | 20/30 Mesh             |
| MANUFACTURER:     |  | Filter Media           |
| WELL SCREEN:      |  | Sch. 40 - 2" PVC       |
| MANUFACTURER:     |  | Silver-Line            |
| SLOT SIZE:        |  | 0.010-Inch Slot        |
| WELL CASING:      |  | Sch. 40 - 2" PVC       |
| MANUFACTURER:     |  | Silver-Line            |

TOC - Top of Casing  
 ID - Inside Diameter; OD - Outside Diameter  
 MSL - Mean Sea Level  
 BGS - Below Ground Surface




ATLANTIC COAST CONSULTING, INC.

**YAMW-7**  
BORING ID

|                       |                 |                       |                 |
|-----------------------|-----------------|-----------------------|-----------------|
| <b>PROJECT:</b>       | Plant Yates     | <b>PROJECT NO.:</b>   | I054-110        |
| <b>TOTAL DEPTH:</b>   | 122.34 ft. BTOC | <b>SITE LOCATION:</b> | Newnan, Georgia |
| <b>DATE BEGIN:</b>    | 14-Nov-2019     | <b>DRILLER:</b>       | Isaac Young     |
| <b>DATE COMPLETE:</b> | 15-Nov-2019     | <b>RIG TYPE:</b>      | T-300 Rotosonic |
| <b>INSTALLED BY:</b>  | Cascade         | <b>METHOD:</b>        | Rotosonic       |
| <b>SUPERVISED BY:</b> | Ryan Walker     |                       |                 |

**WATER 1ST ENCOUNTERED:** 33' BGS  
**WATER AFTER 48 HOURS:** 39.77' BTOC

Core Photos



109-119' As above. Some iron staining and slight fracturing present. (8/10)

Total well depth 118.94' BGS



**MATERIALS:**

|                   |  |                        |
|-------------------|--|------------------------|
| GROUT:            |  | Bentonite Grout        |
| MANUFACTURER:     |  | AquaGuard              |
| BENTONITE SEAL:   |  | 3/8" Bentonite Pellets |
| MANUFACTURER:     |  | Pel-Plug               |
| FILTER PACK SAND: |  | 20/30 Mesh             |
| MANUFACTURER:     |  | Filter Media           |
| WELL SCREEN:      |  | Sch. 40 - 2" PVC       |
| MANUFACTURER:     |  | Silver-Line            |
| SLOT SIZE:        |  | 0.010-Inch Slot        |
| WELL CASING:      |  | Sch. 40 - 2" PVC       |
| MANUFACTURER:     |  | Silver-Line            |

TOC - Top of Casing  
 ID - Inside Diameter; OD - Outside Diameter  
 MSL - Mean Sea Level  
 BGS - Below Ground Surface

**ATTACHMENT B**

**Well Development Forms**

# AECOM GROUNDWATER DEVELOPMENT LOG

|  |   |
|--|---|
| SITE NAME: Georgia Power Company Plant Yates | SITE LOCATION: 708 Dyer Road Newnan, GA |
| WELL NO: PZ-44                               |   |
| FIELD TECHNICIAN: Charles Watson             | DATE: 7/19/16                           |

## PURGING DATA

|  |  |                                     |                                      |
|--|--|-------------------------------------|--------------------------------------|
| WELL DIAMETER (Inches): 2  | WELL SCREEN INTERVAL DEPTH: 78.9 feet to 88.8 feet | STATIC DEPTH TO WATER (feet): 45.25 | PURGE PUMP TYPE OR BAILER: Perchlor  |
| WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY                                    |  |                                     |                                      |
| 1 WELL VOLUME = (88.16 feet - 45.25 feet) X 0.65 liters/foot = 28.54 liters <span style="float: right;">3x = 85.62 L</span>      |  |                                     |                                      |
| EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOLUME = PUMP VOLUME + (TOTAL LENGTH OF TUBING X TUBING CAPACITY) + FLOW THROUGH CELL VOLUME |  |                                     |                                      |
| 1 EQUIPMENT VOLUME = 1.0 liters + (100 feet X 0.04 liters/foot) + 0.5 liters = 5.5 liters  |  |                                     |                                      |
| INITIAL PUMP OR TUBING DEPTH IN WELL (feet): 89  | FINAL PUMP OR TUBING DEPTH IN WELL (feet): 89      | PURGING INITIATED AT: 811           | PURGING ENDED AT: 1210 <sup>CV</sup> |
| WATER QUALITY INSTRUMENT(S): In-Situ SmarTroll   |  | SERIAL NO(S):                       | TOTAL VOLUME PURGED (liters): 50.6   |
| LaMotte 2020we   |  |                                     | 463068<br>7009-1416                  |

## FIELD DATA TABLE

| PUMP SETTING / PSI | TIME | VOLUME PURGED (liters) | TOTAL VOLUME PURGED (liters) | PURGE RATE (L/min) | DEPTH TO WATER (feet) | TURBIDITY (NTUs) | pH (standard units) | SPECIFIC COND. (µS/cm) | OXYGEN REDUCTION POTENTIAL (mV) | DISSOLVED OXYGEN (mg/L) | TEMP. (°C) |
|--------------------|------|------------------------|------------------------------|--------------------|-----------------------|------------------|---------------------|------------------------|---------------------------------|-------------------------|------------|
| 103/40             | 817  | 6.0                    | 6.0                          | 0.50               | 50.5                  | 11.5             | 6.22                | 319.9                  | 116.8                           | 6.57                    | 22.81      |
| *103/35            | 827  | 4.0                    | 10.0                         | 0.46               | 55.2                  | 9.68             | 6.04                | 436.7                  | 39.8                            | 3.61                    | 20.12      |
| 103/35             | 837  | 4.0                    | 14.0                         | 0.40               | 58.25                 | 11.2             | 6.05                | 433.8                  | 26.6                            | 3.64                    | 21.28      |
| *103/35            | 847  | 3.0                    | 17.0                         | 0.30               | 61.25                 | 17.3             | 6.07                | 435.7                  | 19.8                            | 4.13                    | 21.28      |
| 103/35             | 857  | 3.0                    | 20.0                         | 0.30               | 64.6                  | 36.3             | 6.13                | 390.5                  | 25.7                            | 4.59                    | 21.50      |
| 105/35             | 907  | 3.0                    | 23.0                         | 0.30               | 65.95                 | 24.3             | 6.13                | 387                    | 27.0                            | 4.64                    | 21.73      |
| *105/35            | 917  | 3.0                    | 26.0                         | 0.30               | 68.65                 | 38.7             | 6.16                | 371.3                  | 29.1                            | 4.90                    | 21.61      |
| 105/35             | 927  | 3.0                    | 29.0                         | 0.3                | 70.7                  | 34.7             | 6.16                | 404.2                  | 28.2                            | 4.82                    | 21.15      |
| 105/40             | 937  | 2.0                    | 31.0                         | 0.2                | 72.22                 | 23.6             | 6.15                | 418.1                  | 24.8                            | 4.75                    | 22.12      |
| 105/40             | 947  | 2.0                    | 33.0                         | 0.2                | 74.8                  | 46.7             | 6.19                | 405.7                  | 27.7                            | 5.26                    | 21.37      |
| 105/40             | 957  | 1.4                    | 34.4                         | 0.14               | 77.4                  | 36.0             | 6.19                | 400.6                  | 27.9                            | 5.16                    | 21.28      |
| 105/40             | 1007 | 1.4                    | 35.8                         | 0.14               | 79.7                  | 25.1             | 6.15                | 413.4                  | 16.2                            | 4.71                    | 20.76      |
| 105/40             | 1017 | 1.4                    | 37.2                         | 0.14               | 81.35                 | 13.5             | 6.15                | 415.2                  | 12.7                            | 4.66                    | 21.28      |
| 105/40             | 1027 | 1.4                    | 38.6                         | 0.14               | 82.60                 | 8.98             | 6.11                | 431.2                  | 10.5                            | 4.43                    | 21.62      |
| 105/40             | 1037 | 1.4                    | 40.0                         | 0.14               | 83.71                 | 5.11             | 6.16                | 407.4                  | 15.0                            | 4.42                    | 22.18      |
| 105/40             | 1047 | 1.4                    | 41.4                         | 0.14               | 84.1                  | 3.65             | 6.24                | 383.0                  | 20.9                            | 4.44                    | 22.86      |
| 105/40             | 1057 | 1.4                    | 42.8                         | 0.14               | 83.9                  | 3.29             | 6.28                | 368.7                  | 26.1                            | 4.82                    | 21.82      |
| 105/40             | 1107 | 1.4                    | 44.2                         | 0.14               | 83.85                 | 4.20             | 6.29                | 342.1                  | 30.0                            | 4.47                    | 25.24      |

CONTINUED ON REVERSE SIDE

WELL CAPACITY (L Per Ft): 0.75" = 0.10; 1" = 0.20; 1.25" = 0.30; 2" = 0.65; 3" = 1.45; 4" = 2.50; 5" = 3.90; 6" = 5.60; 8" = 9.75; 10" = 15.40; 12" = 21.80  
 TUBING CAPACITY (L Per Ft): 1/16" = 0.001; 0.17" = 0.005; ¼" = 0.01; ⅜" = 0.022; ½" = 0.04; ⅝" = 0.06; ¾" = 0.09; 1" = 0.16

**NOTES:**

Surge: 827, 947, 917

**CHEMICAL PARAMETER STABILIZATION CRITERIA (THREE CONSECUTIVE READINGS AFTER DEPTH TO WATER HAS STABILIZED)**

|  |  |
|--|--|
| <p><b>Required:</b><br/>                 Turbidity: &lt;5 NTU, or stable (±10%)<br/>                 pH: ±0.1 SU<br/>                 Specific Conductance: ± 5% (µS/cm)</p> | <p><b>Record Only:</b><br/>                 Dissolved Oxygen: ± 10%<br/>                 Oxygen Reduction Potential (mV)<br/>                 Temperature (°C)</p> |
|--|--|



# AECOM WELL DEVELOPMENT LOG

|   |  |
|---|--|
| SITE NAME: Georgia Power Company<br>Plant Yates | SITE LOCATION: 708 Dyer Road<br>Newnan, GA |
| WELL NO: P2-45                                  |  |
| FIELD TECHNICIAN: B. Hilliard                   | DATE: 7/15/16                              |

### PURGING DATA

|  |  |                                     |  |
|--|--|-------------------------------------|--|
| WELL DIAMETER (inches): 2  | WELL SCREEN INTERVAL DEPTH: 63.6 feet to 73.6 feet | STATIC DEPTH TO WATER (feet): 22.32 | PURGE PUMP TYPE OR BAILER: GEOTECH RECLAIMER |
| WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY<br>10x - 336   |  |                                     |  |
| L<br>1 WELL VOLUME = (73.92 feet - 22.32 feet) X 0.65 liters/foot = 33.6 liters  |  |                                     |  |
| EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOLUME = PUMP VOLUME + (TOTAL LENGTH OF TUBING X TUBING CAPACITY) + FLOW THROUGH CELL VOLUME<br>1 EQUIPMENT VOLUME = 0.3 liters + (90 feet X 0.04 liters/foot) + 0.5 liters = 4.5 liters |  |                                     |  |
| INITIAL PUMP OR TUBING DEPTH IN WELL (feet): 73.5  | FINAL PUMP OR TUBING DEPTH IN WELL (feet):         | DEVELOPMENT INITIATED AT: 0741      | DEVELOPMENT ENDED AT:                        |
| WATER QUALITY INSTRUMENT(S): In-Situ SmartTroll<br>LaMotte 2020we  |  | SERIAL NO(S): 465016<br>2279-2612   |  |

### FIELD DATA TABLE

| PUMP SETTING / PSI | TIME | VOLUME PURGED (liters) | TOTAL VOLUME PURGED (liters) | PURGE RATE (L/min) | DEPTH TO WATER (feet) | TURBIDITY (NTUs) | pH (standard units) | SPECIFIC COND. (µS/cm) | OXYGEN REDUCTION POTENTIAL (mV) | DISSOLVED OXYGEN (mg/L) | TEMP. (°C) |
|--------------------|------|------------------------|------------------------------|--------------------|-----------------------|------------------|---------------------|------------------------|---------------------------------|-------------------------|------------|
| 103/50             | 0757 | 18                     | 18                           | 1.8                | 48.8                  | 216              | 8.02                | 164.4                  | -360.5                          | 0.59                    | 18.3       |
| 103/50             | 0801 | 18                     | 36                           | 1.8                | 61.81                 | 667              | 7.42                | 310.0                  | -325.9                          | 0.81                    | 18.2       |
| 103/50             | 0811 | 13.8                   | 49.8                         | 1.1                | 61.83                 | 164              | 7.30                | 417.7                  | -307.2                          | 1.16                    | 18.3       |
| 103/50             | 0821 | 11                     | 60.8                         | 1.1                | 60.13                 | 281              | 7.25                | 485.0                  | -341.9                          | 0.50                    | 18.3       |
| 103/45             | 0831 | 11                     | 71.8                         | 1.1                | 57.37                 | 101.3            | 7.23                | 501.6                  | -320.0                          | 0.57                    | 18.4       |
| 103/45             | 0841 | 11                     | 82.8                         | 1.1                | 54.44                 | 633              | 7.22                | 481.0                  | -348.2                          | 0.42                    | 18.7       |
| 103/47             | 0857 | 14                     | 96.8                         | 1.4                | 54.38                 | 1648             | 7.22                | 456.6                  | -307.7                          | 0.88                    | 18.8       |
| 103/47             | 0907 | 14                     | 110.8                        | 1.4                | 54.85                 | 148              | 7.20                | 510.5                  | -292.9                          | 0.52                    | 18.6       |
| 103/47             | 0911 | 14                     | 124.8                        | 1.4                | 55.15                 | 94.0             | 7.18                | 518.1                  | -305.0                          | 0.43                    | 18.5       |
| 103/47             | 0921 | 14                     | 138.8                        | 1.4                | 55.13                 | 39.9             | 7.18                | 521.0                  | -270.1                          | 0.67                    | 18.4       |
| 103/47             | 0931 | 14                     | 152.8                        | 1.4                | 54.88                 | 37.4             | 7.15                | 523.8                  | -272.5                          | 0.57                    | 18.4       |
| 103/47             | 0941 | 14                     | 166.8                        | 1.4                | 56.28                 | 112              | 7.05                | 498.4                  | -298.9                          | 0.59                    | 18.6       |
| 103/47             | 0957 | 7                      | 173.8                        | 1.4                | 45.7                  | 47.3             | 7.11                | 522.6                  | -258.1                          | 0.54                    | 19.3       |
| 103/49             | 1001 | 15                     | 188.8                        | 1.5                | 53.38                 | 21.3             | 7.06                | 545.4                  | -260.7                          | 0.65                    | 18.5       |
| 103/49             | 1011 | 15                     | 203.8                        | 1.5                | 56.8                  | 135              | 7.05                | 536.7                  | -258.1                          | 0.64                    | 18.5       |
| 103/49             | 1021 | 15                     | 218.8                        | 1.5                | 57.13                 | 35.7             | 7.08                | 549.3                  | -241.1                          | 0.98                    | 18.4       |
| 103/49             | 1031 | 15                     | 233.8                        | 1.5                | 57.25                 | 54.5             | 7.08                | 560.0                  | -247.3                          | 0.58                    | 18.5       |

CONTINUED ON REVERSE SIDE

WELL CAPACITY (L Per Ft): 0.75" = 0.10; 1" = 0.20; 1.25" = 0.30; 2" = 0.65; 3" = 1.45; 4" = 2.50; 5" = 3.90; 6" = 5.60; 8" = 9.75; 10" = 15.40; 12" = 21.80  
 TUBING CAPACITY (L Per Ft): 1/16" = 0.001; 0.17" = 0.005; 1/4" = 0.01; 3/8" = 0.022; 1/2" = 0.04; 5/8" = 0.06; 3/4" = 0.09; 7/8" = 0.12; 1" = 0.16

NOTES: 0738 - Surge screened interval before starting. 0813 - Surge.  
 0833 - Surge.  
 0841 - Inc. flow  
 0843 - to 14 LPM  
 0903 - Surge.  
 0927 - Surge.  
 0937 - Surge.  
 0953 - Surge.  
 1005 - Surge.  
 1008 - Accidental hit finish, Regrab at 1011. Took line readings

#### CHEMICAL PARAMETER STABILIZATION CRITERIA (THREE CONSECUTIVE READINGS AFTER DEPTH TO WATER HAS STABILIZED)

**Required:**  
 Turbidity: <10 NTU, or stable (±10%)  
 pH: ± 0.1 SU  
 Specific Conductance: ± 5% (µS/cm)

**Record Only:**  
 Oxygen Reduction Potential (mV)  
 Temperature (°C)  
 Dissolved Oxygen (mg/L)



# AECOM WELL DEVELOPMENT LOG

|   |  |
|---|--|
| SITE NAME: Georgia Power Company<br>Plant Yates | SITE LOCATION: 708 Dyer Road<br>Newnan, GA |
| WELL NO: PZ-46                                  |  |
| FIELD TECHNICIAN: R. Hilliard                   | DATE: 7/14/16                              |

## PURGING DATA

|   |  |                                     |  |
|---|--|-------------------------------------|--|
| WELL DIAMETER (inches): 2   | WELL SCREEN INTERVAL DEPTH: 74.7 feet to 84.7 feet | STATIC DEPTH TO WATER (feet): 47.11 | PURGE PUMP TYPE OR BAILER: GEOTECH RECLAIMER |
| WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY<br>10x - 246  |  |                                     |  |
| L<br>1 WELL VOLUME = (85.02 feet - 47.11 feet) X 0.65 liters/foot = 24.6 liters   |  |                                     |  |
| EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOLUME = PUMP VOLUME + (TOTAL LENGTH OF TUBING X TUBING CAPACITY) + FLOW THROUGH CELL VOLUME<br>1 EQUIPMENT VOLUME = 0.3 liters + (100 feet X 0.04 liters/foot) + 0.5 liters = 4.8 liters |  |                                     |  |
| INITIAL PUMP OR TUBING DEPTH IN WELL (feet): 84.7   | FINAL PUMP OR TUBING DEPTH IN WELL (feet): 84.7    | DEVELOPMENT INITIATED AT: 0900      | DEVELOPMENT ENDED AT: 1340                   |
| WATER QUALITY INSTRUMENT(S): In-Situ SmartTroll<br>LaMotte 2020we   |  | SERIAL NO(S): 465014<br>2279-2612   |  |
| TOTAL VOLUME REMOVED (liters): 404  |  |                                     |  |

## FIELD DATA TABLE

| PUMP SETTING / PSI | TIME | VOLUME PURGED (liters) | TOTAL VOLUME PURGED (liters) | PURGE RATE (L/min) | DEPTH TO WATER (feet) | TURBIDITY (NTUs) | pH (standard units) | SPECIFIC COND. (µS/cm) | OXYGEN REDUCTION POTENTIAL (mV) | DISSOLVED OXYGEN (mg/L) | TEMP. (°C) |
|--------------------|------|------------------------|------------------------------|--------------------|-----------------------|------------------|---------------------|------------------------|---------------------------------|-------------------------|------------|
| 105/45             | 0910 | 7                      | 7                            | 1.4                | 52.25                 | 172              | 7.15                | 348.6                  | -281.5                          | 2.82                    | 21.9       |
| 105/45             | 0920 | 15                     | 22                           | 1.5                | 51.90                 | 604              | 6.64                | 532.2                  | -209.9                          | 3.10                    | 20.2       |
| 105/45             | 0930 | 15                     | 37                           | 1.5                | 54.30                 | 115              | 6.48                | 747.5                  | -216.2                          | 6.93                    | 20.3       |
| 105/45             | 0940 | 15                     | 52                           | 1.5                | 59.50                 | 117              | 6.62                | 278.5                  | -141.0                          | 8.85                    | 20.5       |
| 105/45             | 0950 | 15                     | 67                           | 1.5                | 55.20                 | 120              | 6.46                | 859.1                  | -103.1                          | 10.31                   | 20.1       |
| 105/45             | 1000 | 15                     | 82                           | 1.5                | 61.10                 | 104              | 6.47                | 895.0                  | -107.8                          | 9.93                    | 20.2       |
| 105/45             | 1010 | 15                     | 97                           | 1.5                | 61.60                 | 54.3             | 6.38                | 980.1                  | -116.6                          | 8.80                    | 20.4       |
| 105/45             | 1020 | 15                     | 112                          | 1.5                | 60.50                 | 79               | 6.35                | 955.4                  | -120.6                          | 7.73                    | 21.1       |
| 105/45             | 1030 | 15                     | 127                          | 1.5                | 61.30                 | 59.8             | 6.43                | 986.9                  | -93.2                           | 9.86                    | 20.5       |
| 105/45             | 1040 | 15                     | 142                          | 1.5                | 61.75                 | 88.4             | 6.33                | 1060.8                 | -129.1                          | 8.88                    | 21.0       |
| 105/45             | 1050 | 15                     | 157                          | 1.5                | 63.80                 | 63.8             | 6.25                | 1131.3                 | -147.0                          | 8.12                    | 20.1       |
| 105/45             | 1100 | 15                     | 172                          | 1.5                | 66.50                 | 84.5             | 6.30                | 1135.5                 | -107.8                          | 6.86                    | 20.2       |
| 105/45             | 1110 | 15                     | 187                          | 1.5                | 67.64                 | 11.8             | 6.04                | 1223.0                 | -240.7                          | 1.87                    | 20.0       |
| 105/45             | 1120 | 15                     | 202                          | 1.5                | 69.00                 | 34.0             | 6.04                | 1226.6                 | -234.3                          | 1.98                    | 20.0       |
| 105/45             | 1130 | 15                     | 217                          | 1.5                | 69.33                 | 13.5             | 6.01                | 1263.8                 | -250.7                          | 1.13                    | 20.1       |
| 105/45             | 1140 | 15                     | 232                          | 1.5                | 69.85                 | 9.66             | 6.01                | 1273.2                 | -239.1                          | 1.16                    | 20.0       |
| 105/45             | 1150 | 15                     | 247                          | 1.5                | 67.90                 | 49.6             | 6.63                | 1192.1                 | 6.70                            | 8.89                    | 20.3       |

CONTINUED ON REVERSE SIDE

WELL CAPACITY (L Per Ft): 0.75" = 0.10; 1" = 0.20; 1.25" = 0.30; 2" = 0.65; 3" = 1.45; 4" = 2.50; 5" = 3.90; 6" = 5.60; 8" = 9.75; 10" = 15.40; 12" = 21.80  
 TUBING CAPACITY (L Per Ft): 1/16" = 0.001; 0.17" = 0.005; ¼" = 0.01; ⅜" = 0.022; ½" = 0.04; ⅝" = 0.06; ¾" = 0.09; 1" = 0.16

**NOTES:**

0858 - surge before starting.  
 0914 - surge.  
 0933 - surge.  
 0945 - surge.  
 0952 - surge.  
 1012 - surge.  
 1032 - surge.  
 1057 - surge.  
 1112 - surge.  
 1102 - surge air from RDO sensor overlapping cups.  
 1137 - check well sticking backflow surge tooling blowing sand air.

**CHEMICAL PARAMETER STABILIZATION CRITERIA (THREE CONSECUTIVE READINGS AFTER DEPTH TO WATER HAS STABILIZED)**

**Required:**  
 Turbidity: <10 NTU, or stable (±10%)  
 pH: ±0.1 SU  
 Specific Conductance: ±5% (µS/cm)

**Record Only:**  
 Oxygen Reduction Potential (mV)  
 Temperature (°C)  
 Dissolved Oxygen (mg/L)



# AECOM GROUNDWATER DEVELOPMENT LOG

|   |  |
|---|--|
| SITE NAME: Georgia Power Company<br>Plant Yates | SITE LOCATION: 708 Dyer Road<br>Newnan, GA |
| WELL NO: PZ-47                                  |  |
| FIELD TECHNICIAN: Charles Watson                | DATE: 7/15/16                              |

## PURGING DATA

|  |  |                                     |   |
|--|--|-------------------------------------|---|
| WELL DIAMETER (inches): 2  | WELL SCREEN INTERVAL DEPTH: 48.6 feet to 58.6 feet | STATIC DEPTH TO WATER (feet): 24.81 | PURGE PUMP TYPE OR BAILER: Recirculator |
| WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY<br>1 WELL VOLUME = (58.95 feet - 24.81 feet) X 0.65 liters/foot = 22.19 liters      3x = 66.57 L                               |  |                                     |   |
| EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOLUME = PUMP VOLUME + (TOTAL LENGTH OF TUBING X TUBING CAPACITY) + FLOW THROUGH CELL VOLUME<br>1 EQUIPMENT VOLUME = 0.4 liters + (70 feet X 0.04 liters/foot) + 0.6 liters = 4.0 liters |  |                                     |   |
| INITIAL PUMP OR TUBING DEPTH IN WELL (feet): 58.9  | FINAL PUMP OR TUBING DEPTH IN WELL (feet): 55      | PURGING INITIATED AT: 800           | PURGING ENDED AT: 1152                  |
| WATER QUALITY INSTRUMENT(S): In-Situ SmarTroll<br>LaMotte 2020we   |  | SERIAL NO(S): 463068<br>7009-1416   |   |
| TOTAL VOLUME PURGED (liters): 310  |  |                                     |   |

## FIELD DATA TABLE

| PUMP SETTING / PSI | TIME | VOLUME PURGED (liters) | TOTAL VOLUME PURGED (liters) | PURGE RATE (L/min) | DEPTH TO WATER (feet) | TURBIDITY (NTUs) | pH (standard units) | SPECIFIC COND. (µS/cm) | OXYGEN REDUCTION POTENTIAL (mV) | DISSOLVED OXYGEN (mg/L) | TEMP. (°C) |
|--------------------|------|------------------------|------------------------------|--------------------|-----------------------|------------------|---------------------|------------------------|---------------------------------|-------------------------|------------|
| 160/35             | 830  | 4.0                    | 4.0                          | 1.2                | 28.55                 | 1085             | 6.13                | 453.8                  | -178.5                          | 5.11                    | 18.48      |
| 158/35             | 840  | 12.0                   | 16.0                         | 1.2                | 37.8                  | 1325             | 5.92                | 431.5                  | -197.5                          | 2.29                    | 18.30      |
| 156/35             | 850  | 12.0                   | 28.0                         | 1.2                | 36.4                  | 50.9             | 5.68                | 432.0                  | -156.6                          | 1.82                    | 18.35      |
| * 156/35           | 900  | 12.0                   | 40.0                         | 1.2                | 36.85                 | 16.7             | 5.72                | 434.1                  | -170.2                          | 1.75                    | 18.40      |
|                    | 910  | 12.0                   | 52.0                         | 1.2                | 39.5                  | 166              | 5.74                | 427.3                  | -152                            | 1.57                    | 18.35      |
|                    | 920  | 12.0                   | 64.0                         | 1.2                | 39.75                 | 51               | 5.68                | 426.6                  | -128.6                          | 1.76                    | 18.26      |
| *                  | 930  | 12                     | 76                           | 1.2                | 39.40                 | 16.1             | 5.66                | 427.8                  | -112.6                          | 1.89                    | 18.21      |
|                    | 940  | 12                     | 88                           | 1.2                | 39.89                 | 173              | 5.68                | 413.5                  | -116.2                          | 1.83                    | 18.38      |
|                    | 950  | 12                     | 100                          | 1.2                | 39.89                 | 48.6             | 5.63                | 462.6                  | -82.1                           | 2.01                    | 18.35      |
| * 156/35           | 1000 | 12                     | 112                          | 1.2                | 39.60                 | 20.4             | 5.61                | 463.0                  | -68.7                           | 2.12                    | 18.42      |
| 157/40             | 1010 | 15                     | 127                          | 1.5                | 39.00                 | 89               | 5.61                | 455.6                  | -74.2                           | 2.15                    | 18.46      |
| 159/40             | 1020 | 21                     | 148                          | 2.1                | 40.25                 | 46.4             | 5.60                | 458                    | -42.8                           | 2.41                    | 18.23      |
| * 159/35           | 1030 | 18                     | 166                          | 1.8                | 42.1                  | 19.6             | 5.62                | 459.6                  | -46.2                           | 2.24                    | 18.26      |
|                    | 1040 | 18                     | 184                          | 1.8                | 41.88                 | 54.2             | 5.58                | 450.9                  | -40.4                           | 2.28                    | 18.26      |
| *                  | 1050 | 18                     | 202                          | 1.8                | 41.60                 | 16               | 5.59                | 454.8                  | -27.1                           | 2.26                    | 18.34      |
|                    | 1100 | 18                     | 220                          | 1.8                | 43.10                 | 132              | 5.59                | 448.4                  | -46.6                           | 2.35                    | 18.6       |
|                    | 1110 | 18                     | 238                          | 1.8                | 42.94                 | 33.2             | 5.59                | 453.5                  | -16.1                           | 2.31                    | 18.51      |
| 159/35             | 1120 | 18                     | 256                          | 1.8                | 42.65                 | 11.45            | 5.59                | 451.9                  | -10.2                           | 2.28                    | 18.61      |

CONTINUED ON REVERSE SIDE

WELL CAPACITY (L Per Ft): 0.75" = 0.10; 1" = 0.20; 1.25" = 0.30; 2" = 0.65; 3" = 1.45; 4" = 2.50; 5" = 3.90; 6" = 5.60; 8" = 9.75; 10" = 15.40; 12" = 21.80  
 TUBING CAPACITY (L Per Ft): 1/16" = 0.001; 0.17" = 0.005; ¼" = 0.01; ⅜" = 0.022; ½" = 0.04; ⅝" = 0.06; ¾" = 0.09; 1" = 0.16

NOTES: pump clogged @ 810 pulled & cleaned restart @ 828

Surge 808, 900, 930, 1000, 1030, 1050

### CHEMICAL PARAMETER STABILIZATION CRITERIA (THREE CONSECUTIVE READINGS AFTER DEPTH TO WATER HAS STABILIZED)

|   |  |
|---|--|
| <b>Required:</b><br>Turbidity: <5 NTU, or stable (±10%)<br>pH: ±0.1 SU<br>Specific Conductance: ±5% (µS/cm) | <b>Record Only:</b><br>Dissolved Oxygen: ±10%<br>Oxygen Reduction Potential (mV)<br>Temperature (°C) |
|---|--|





## Atlantic Coast Consulting, Inc. Well Development Field Record

|  |  |
|--|--|
| Job Name: <u>Plant Yates Drilling</u>                      | Job No. <u>I054-110</u> Well No. <u>YAMW-7</u>                     |
| Developed By: <u>Ryan Walker</u>                           | Date of Installation: <u>11/13/2019</u> Sheet <u>1</u> of <u>1</u> |
| Started Dev. <u>12-3-19 / 0900</u>                         | Completed Dev. <u>12-3-19 / 1633</u>                               |
| Date / Time  | Date / Time  |
| W.L. Before Dev. <u>39.77 / 12-3-19 / 0820</u>             | W.L. After Dev. <u>112.6 / 12-3-19 / 1633</u>                      |
| TOC / Date / Time  | TOC / Date / Time  |
| Well Depth Before Dev.: <u>122.34</u> TOC                  | Well Depth After Dev.: <u>122.34</u> TOC                           |
| Water Column (H): <u>82.57</u> Ft. Well Dia.: <u>2</u> In. | Well Volume: <u>13.2</u> Gal.                                      |
| Screen Length: <u>10</u> Ft.                               |  |

| Date / Time    | Volume Removed (Gal.) | Field Parameters                |                  |           |                 | Remarks           |
|----------------|-----------------------|---------------------------------|------------------|-----------|-----------------|-------------------|
|                |                       | Specific Cond. (umhos/cm)       | Temperature (°C) | pH (S.U.) | Turbidity (NTU) |                   |
| 12-3-2019/0900 | 0                     |                                 |                  |           |                 | Begin development |
| 12-3-2019/1513 | 100                   | 1,387                           | 20.52            | 7.28      | 19.9            |                   |
| 12-3-2019/1518 | 101.25                | 1,372                           | 20.38            | 7.30      | 9.86            |                   |
| 12/3/2019/1523 | 102.5                 | 1,379                           | 20.51            | 7.29      | 9.10            |                   |
| 12-3-2019/1528 | 103.75                | 1,381                           | 20.34            | 7.27      | 10.6            |                   |
| 12-3-2019/1533 | 105                   | 1,384                           | 20.29            | 7.27      | 9.76            |                   |
| 12-3-2019/1538 | 106.25                | 1,382                           | 20.38            | 7.27      | 8.30            |                   |
| 12-3-2019/1543 | 107.5                 | 1,387                           | 18.65            | 7.26      | 11.8            |                   |
| 12-3-2019/1548 | 108.75                | 1,379                           | 19.40            | 7.27      | 13.3            |                   |
| 12-3-2019/1553 | 110                   | 1,384                           | 19.9             | 7.27      | 10.1            |                   |
| 12-3-2019/1558 | 111.25                | 1,384                           | 19.91            | 7.28      | 8.42            |                   |
| 12-3-2019/1603 | 112.5                 | 1,385                           | 20.08            | 7.27      | 10.6            |                   |
| 12-3-2019/1608 | 113.75                | 1,384                           | 20.22            | 7.27      | 9.15            |                   |
| 12-3-2019/1613 | 115                   | 1,380                           | 20.21            | 7.28      | 8.97            |                   |
| 12-3-2019/1618 | 116.25                | 1,387                           | 20.36            | 7.27      | 7.41            |                   |
| 12-3-2019/1623 | 117.5                 | 1,368                           | 20.06            | 7.30      | 6.37            |                   |
| 12-3-2019/1628 | 118.75                | 1,384                           | 19.94            | 7.28      | 6.11            |                   |
| 12-3-2019/1633 | 120                   | 1,381                           | 20.17            | 7.27      | 4.69            |                   |
|                |                       | Total Volume Removed (gal): 120 |                  |           |                 |                   |

Development Method: Surged Pump Q= 0.5 gpm

Pre-development on 12/3/2019, surged pump periodically during pre-development

WL/TD on electronic log all listed as TOC

Notes: H = well depth (BTOC) - W.L. (BTOC)

Well volume in pipe:

2" diameter well: 0.16 X H = volume in gallons

4" diameter well: 0.66 X H = voume in gallons

**ATTACHMENT C**

**Well Survey Documents**

**PLANT YATES PIEZOMETER LOCATIONS**

LOCATION EQUIPMENT - LEICA GS14 ANTENNA AND CS15 SENSOR &amp; TCRP 1201 TOTAL STATION

**JULY 26, 2016**

POSITIONAL TOLLERANCE 0.10'H:V

FIELD WORK BY FRANK KENNEY &amp; RUSTY BULLARD, E&amp;CS CIVIL FIELD SERVICES

| PIEZOMETER WELL ID | LATITUDE DD | LONGITUDE DD | NAD 83 NORTHING | NAD 83 EASTING | ELEVATION TOP OF PK NAIL | NAVD 88 ELEVATION TOP OF PVC | ELEVATION OF HIGH SIDE GROUND | SURVEYOR'S POINT# |
|--------------------|-------------|--------------|-----------------|----------------|--------------------------|------------------------------|-------------------------------|-------------------|
| PZ 35              | 33.4579020  | -84.8971231  | 1258593.89      | 2073806.07     | 741.02                   | 743.74                       | 740.92                        | 5                 |
| PZ 36              | 33.4576812  | -84.8972361  | 1258513.81      | 2073771.04     | 736.97                   | 739.53                       | 736.72                        | 6                 |
| PZ 37              | 33.4520878  | -84.8941431  | 1256471.98      | 2074700.15     | 757.85                   | 760.53                       | 757.83                        | 13                |
| PZ 38              | 33.4510840  | -84.8949677  | 1256108.50      | 2074446.06     | 796.98                   | 799.45                       | 796.88                        | 14                |
| PZ 39              | 33.4499999  | -84.8968623  | 1255718.09      | 2073865.43     | 815.33                   | 817.99                       | 815.23                        | 15                |
| PZ 40              | 33.4501972  | -84.8982860  | 1255792.92      | 2073431.66     | 813.32                   | 815.63                       | 813.22                        | 16                |
| PZ 41              | 33.4521642  | -84.8988180  | 1256509.78      | 2073274.44     | 801.14                   | 803.83                       | 800.81                        | 17                |
| PZ 42              | 33.4531871  | -84.8986554  | 1256881.62      | 2073326.65     | 795.23                   | 797.75                       | 795.13                        | 18                |
| PZ 43              | 33.4550127  | -84.8990856  | 1257546.80      | 2073200.13     | 742.53                   | 744.99                       | 745.33                        | 3                 |
| PZ 44              | 33.4668672  | -84.9056831  | 1261874.46      | 2071218.56     | 755.59                   | 758.27                       | 755.39                        | 10                |
| PZ 45              | 33.4662963  | -84.9066839  | 1261668.89      | 2070911.89     | 716.64                   | 719.30                       | 716.34                        | 11                |
| PZ 46              | 33.4645469  | -84.9062643  | 1261031.44      | 2071035.31     | 744.62                   | 747.23                       | 744.32                        | 9                 |
| PZ 47              | 33.4683527  | -84.9037300  | 1262410.75      | 2071818.00     | 755.55                   | 758.04                       | 755.35                        | 12                |
| PZ 48              | 33.4614195  | -84.8947879  | 1259868.78      | 2074527.26     | 777.32                   | 779.88                       | 777.12                        | 7                 |
| PZ 49              | 33.4600615  | -84.8953998  | 1259375.98      | 2074337.19     | 780.09                   | 782.72                       | 779.89                        | 8                 |

Yates Plant

Piezometers

Georgia West Zone - NAD83

6/4/2014

| Piez #             | North       | East        | Elev.   |
|--------------------|-------------|-------------|---------|
| PZ-1D TOP PIPE     | 1256868.183 | 2070105.870 | 837.134 |
| PZ-1S TOP PIPE     | 1256872.753 | 2070102.305 | 836.739 |
| PZ-1I TOP PIPE     | 1256876.951 | 2070099.142 | 836.477 |
| PZ-2I TOP PIPE     | 1256144.518 | 2070791.420 | 866.150 |
| PZ-3S TOP OF PIPE  | 1256411.555 | 2072022.649 | 796.205 |
| PZ-3I TOP OF PIPE  | 1256405.795 | 2072025.183 | 796.333 |
| PZ-3D TOP OF PIPE  | 1256400.444 | 2072027.212 | 796.700 |
| PZ-4I TOP PIPE     | 1254436.485 | 2075456.340 | 784.180 |
| PZ-4S TOP PIPE     | 1254442.757 | 2075454.763 | 784.535 |
| PZ-5D TOP PIPE     | 1254397.344 | 2076224.102 | 784.526 |
| PZ-5I TOP PIPE     | 1254400.691 | 2076219.160 | 784.535 |
| PZ-5S TOP PIPE     | 1254404.501 | 2076214.291 | 784.642 |
| PZ-6I TOP OF PIPE  | 1260490.852 | 2074789.826 | 782.576 |
| PZ-6S TOP OF PIPE  | 1260485.631 | 2074785.699 | 782.280 |
| PZ-6D TOP OF PIPE  | 1260481.001 | 2074782.008 | 781.933 |
| PZ-7S TOP OF PIPE  | 1262715.668 | 2072535.447 | 747.876 |
| PZ-7I TOP PIPE     | 1262713.795 | 2072529.536 | 747.997 |
| PZ-8I TOP PIPE     | 1262284.593 | 2072745.740 | 747.814 |
| PZ-8S TOP PIPE     | 1262287.369 | 2072739.491 | 747.579 |
| PZ-9S TOP OF PIPE  | 1262003.292 | 2070721.595 | 711.896 |
| PZ-9I TOP OF PIPE  | 1261995.566 | 2070721.123 | 712.044 |
| PZ-10S TOP PIPE    | 1260802.289 | 2070553.323 | 700.348 |
| PZ-10I TOP PIPE    | 1260809.739 | 2070552.828 | 700.266 |
| PZ-13S TOP PIPE    | 1257849.008 | 2069810.458 | 807.892 |
| PZ-13I TOP PIPE    | 1257849.186 | 2069817.291 | 807.721 |
| PZ-14I TOP OF PIPE | 1257827.415 | 2072543.169 | 749.112 |
| PZ-14S TOP OF PIPE | 1257829.835 | 2072537.686 | 748.766 |
| PZ-16S TOP OF PIPE | 1261575.593 | 2073874.323 | 809.362 |
| PZ-16I TOP OF PIPE | 1261572.170 | 2073879.691 | 809.355 |

PLANT YATES WELL LOCATION

DECEMBER 4, 2019

NAD 83 GEORGIA WEST ZONE

FIELD WORK BY STEVE CULBERSON, T&PS-CIVIL FIELD SERVICES

| WELL ID | LATITUDE DD | LONGITUDE DD | NAD 83<br>NORTHING | NAD 83 EASTING | ELEVATION TOP<br>OF PK NAIL | ELEVATION TOP<br>OF CASING | ELEVATION OF<br>GROUND |
|---------|-------------|--------------|--------------------|----------------|-----------------------------|----------------------------|------------------------|
| PZ-51   | 33.4551466  | -84.8991476  | 1257595.67         | 2073181.55     | 741.07                      | 744.14                     | 741.00                 |
| YAMW-2  | 33.4529055  | -84.8999724  | 1256781.99         | 2072924.24     | 777.78                      | 781.00                     | 777.70                 |
| YAMW-3  | 33.4532792  | -84.8985983  | 1256915.01         | 2073344.31     | 792.97                      | 796.04                     | 792.90                 |
| YAMW-4  | 33.4522276  | -84.8987944  | 1256532.78         | 2073281.79     | 802.57                      | 805.57                     | 802.50                 |
| YAMW-5  | 33.4511702  | -84.8948326  | 1256139.57         | 2074487.49     | 785.77                      | 788.79                     | 785.70                 |
| YAMW-6  | 33.4643604  | -84.9066366  | 1260964.38         | 2070921.28     | 729.85                      | 732.73                     | 729.80                 |
| YAMW-7  | 33.4645766  | -84.9060992  | 1261041.91         | 2071085.73     | 730.10                      | 733.50                     | 730.00                 |

## APPENDIX C

# LABORATORY ANALYTICAL AND FIELD SAMPLING REPORTS

December 11, 2019

Joju Abraham  
Georgia Power - Coal Combustion Residuals  
2480 Maner Road  
Atlanta, GA 30339

RE: Project: Plant Yates-Pond 1  
Pace Project No.: 2622246

Dear Joju Abraham:

Enclosed are the analytical results for sample(s) received by the laboratory on August 21, 2019. The results relate only to the samples included in this report. Results reported herein conform to the most current, applicable TNI/NELAC standards and the laboratory's Quality Assurance Manual, where applicable, unless otherwise noted in the body of the report.

This revised report replaces the report issued on 8/29/2019. The report has been revised to correct the project-required RLs per consultant request. No other changes have been made to this report.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,



Kevin Herring for  
Betsy McDaniel  
betsy.mcdaniel@pacelabs.com  
(770)734-4200  
Project Manager

Enclosures

cc: Betsy McDaniel, Atlantic Coast Consulting  
Chris Parker, Atlantic Coast Consulting  
Evan Perry, Atlantic Coast Consulting  
Lauren Petty, Southern Company Services, Inc.  
Rebecca Thornton, Pace Analytical Atlanta



## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## CERTIFICATIONS

Project: Plant Yates-Pond 1  
Pace Project No.: 2622246

---

**Pace Analytical Services Atlanta**

110 Technology Parkway Peachtree Corners, GA 30092  
Florida DOH Certification #: E87315  
Georgia DW Inorganics Certification #: 812  
Georgia DW Microbiology Certification #: 812

North Carolina Certification #: 381  
South Carolina Certification #: 98011001  
Virginia Certification #: 460204

---

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### SAMPLE SUMMARY

Project: Plant Yates-Pond 1

Pace Project No.: 2622246

| Lab ID     | Sample ID    | Matrix | Date Collected | Date Received  |
|------------|--------------|--------|----------------|----------------|
| 2622246001 | YGWA-47      | Water  | 08/20/19 10:30 | 08/21/19 16:50 |
| 2622246002 | YGWC-45      | Water  | 08/20/19 11:35 | 08/21/19 16:50 |
| 2622246003 | YGWC-44      | Water  | 08/20/19 13:45 | 08/21/19 16:50 |
| 2622246004 | FB-1-8-20-19 | Water  | 08/20/19 13:30 | 08/21/19 16:50 |
| 2622246005 | YGWC-46      | Water  | 08/21/19 09:45 | 08/21/19 16:50 |
| 2622246006 | EB-1-8-21-19 | Water  | 08/21/19 10:00 | 08/21/19 16:50 |
| 2622246007 | Dup-1        | Water  | 08/21/19 00:00 | 08/21/19 16:50 |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### SAMPLE ANALYTE COUNT

Project: Plant Yates-Pond 1

Pace Project No.: 2622246

| Lab ID     | Sample ID    | Method    | Analysts | Analytes Reported |
|------------|--------------|-----------|----------|-------------------|
| 2622246001 | YGWA-47      | EPA 6020B | CSW      | 12                |
|            |              | EPA 7470A | DRB      | 1                 |
|            |              | EPA 300.0 | MWB      | 1                 |
| 2622246002 | YGWC-45      | EPA 6020B | CSW      | 12                |
|            |              | EPA 7470A | DRB      | 1                 |
|            |              | EPA 300.0 | MWB      | 1                 |
| 2622246003 | YGWC-44      | EPA 6020B | CSW      | 12                |
|            |              | EPA 7470A | DRB      | 1                 |
|            |              | EPA 300.0 | MWB      | 1                 |
| 2622246004 | FB-1-8-20-19 | EPA 6020B | CSW      | 12                |
|            |              | EPA 7470A | DRB      | 1                 |
|            |              | EPA 300.0 | MWB      | 1                 |
| 2622246005 | YGWC-46      | EPA 6020B | CSW      | 12                |
|            |              | EPA 7470A | DRB      | 1                 |
|            |              | EPA 300.0 | MWB      | 1                 |
| 2622246006 | EB-1-8-21-19 | EPA 6020B | CSW      | 12                |
|            |              | EPA 7470A | DRB      | 1                 |
|            |              | EPA 300.0 | MWB      | 1                 |
| 2622246007 | Dup-1        | EPA 6020B | CSW      | 12                |
|            |              | EPA 7470A | DRB      | 1                 |
|            |              | EPA 300.0 | MWB      | 1                 |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS

Project: Plant Yates-Pond 1

Pace Project No.: 2622246

| Sample: YGWA-47                |                  | Lab ID: 2622246001   |              | Collected: 08/20/19 10:30 |    | Received: 08/21/19 16:50 |                | Matrix: Water |      |
|--------------------------------|------------------|--|--------------|---------------------------|----|--------------------------|----------------|---------------|------|
| Parameters                     | Results          | Units  | Report Limit | MDL                       | DF | Prepared                 | Analyzed       | CAS No.       | Qual |
| <b>6020B MET ICPMS</b>         |                  | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |              |                           |    |                          |                |               |      |
| Antimony                       | ND               | mg/L   | 0.0030       | 0.00027                   | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7440-36-0     |      |
| Arsenic                        | ND               | mg/L   | 0.0050       | 0.00035                   | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7440-38-2     |      |
| Barium                         | <b>0.024</b>     | mg/L   | 0.010        | 0.00049                   | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7440-39-3     |      |
| Beryllium                      | ND               | mg/L   | 0.0030       | 0.000074                  | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7440-41-7     |      |
| Cadmium                        | ND               | mg/L   | 0.0025       | 0.00011                   | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7440-43-9     |      |
| Chromium                       | ND               | mg/L   | 0.010        | 0.00039                   | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7440-47-3     |      |
| Cobalt                         | <b>0.00092J</b>  | mg/L   | 0.0050       | 0.00030                   | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7440-48-4     |      |
| Lead                           | ND               | mg/L   | 0.0050       | 0.000046                  | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7439-92-1     |      |
| Lithium                        | <b>0.0036J</b>   | mg/L   | 0.030        | 0.00078                   | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7439-93-2     |      |
| Molybdenum                     | ND               | mg/L   | 0.010        | 0.00095                   | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7439-98-7     |      |
| Selenium                       | ND               | mg/L   | 0.010        | 0.0013                    | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7782-49-2     |      |
| Thallium                       | <b>0.000058J</b> | mg/L   | 0.0010       | 0.000052                  | 1  | 08/23/19 14:17           | 08/26/19 17:07 | 7440-28-0     |      |
| <b>7470 Mercury</b>            |                  | Analytical Method: EPA 7470A Preparation Method: EPA 7470A |              |                           |    |                          |                |               |      |
| Mercury                        | ND               | mg/L   | 0.00050      | 0.00014                   | 1  | 08/26/19 14:21           | 08/27/19 10:54 | 7439-97-6     |      |
| <b>300.0 IC Anions 28 Days</b> |                  | Analytical Method: EPA 300.0                               |              |                           |    |                          |                |               |      |
| Fluoride                       | ND               | mg/L   | 0.30         | 0.029                     | 1  |                          | 08/28/19 21:18 | 16984-48-8    |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## ANALYTICAL RESULTS

Project: Plant Yates-Pond 1  
Pace Project No.: 2622246

| Sample: YGWC-45                |                 | Lab ID: 2622246002   |         | Collected: 08/20/19 11:35 |    | Received: 08/21/19 16:50 |                | Matrix: Water |      |  |
|--------------------------------|-----------------|--|---------|---------------------------|----|--------------------------|----------------|---------------|------|--|
| Parameters                     | Results         | Units  | Report  |                           |    | Prepared                 | Analyzed       | CAS No.       | Qual |  |
|                                |                 |  | Limit   | MDL                       | DF |                          |                |               |      |  |
| <b>6020B MET ICPMS</b>         |                 | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |         |                           |    |                          |                |               |      |  |
| Antimony                       | ND              | mg/L   | 0.0030  | 0.00027                   | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7440-36-0     |      |  |
| Arsenic                        | <b>0.00078J</b> | mg/L   | 0.0050  | 0.00035                   | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7440-38-2     |      |  |
| Barium                         | <b>0.057</b>    | mg/L   | 0.010   | 0.00049                   | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7440-39-3     |      |  |
| Beryllium                      | ND              | mg/L   | 0.0030  | 0.000074                  | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7440-41-7     |      |  |
| Cadmium                        | ND              | mg/L   | 0.0025  | 0.00011                   | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7440-43-9     |      |  |
| Chromium                       | ND              | mg/L   | 0.010   | 0.00039                   | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7440-47-3     |      |  |
| Cobalt                         | <b>0.00071J</b> | mg/L   | 0.0050  | 0.00030                   | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7440-48-4     |      |  |
| Lead                           | ND              | mg/L   | 0.0050  | 0.000046                  | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7439-92-1     |      |  |
| Lithium                        | <b>0.012J</b>   | mg/L   | 0.030   | 0.00078                   | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7439-93-2     |      |  |
| Molybdenum                     | <b>0.0011J</b>  | mg/L   | 0.010   | 0.00095                   | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7439-98-7     |      |  |
| Selenium                       | ND              | mg/L   | 0.010   | 0.0013                    | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7782-49-2     |      |  |
| Thallium                       | ND              | mg/L   | 0.0010  | 0.000052                  | 1  | 08/23/19 14:17           | 08/26/19 17:12 | 7440-28-0     |      |  |
| <b>7470 Mercury</b>            |                 | Analytical Method: EPA 7470A Preparation Method: EPA 7470A |         |                           |    |                          |                |               |      |  |
| Mercury                        | ND              | mg/L   | 0.00050 | 0.00014                   | 1  | 08/26/19 14:21           | 08/27/19 11:04 | 7439-97-6     |      |  |
| <b>300.0 IC Anions 28 Days</b> |                 | Analytical Method: EPA 300.0                               |         |                           |    |                          |                |               |      |  |
| Fluoride                       | ND              | mg/L   | 0.30    | 0.029                     | 1  |                          | 08/28/19 22:26 | 16984-48-8    |      |  |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## ANALYTICAL RESULTS

Project: Plant Yates-Pond 1  
Pace Project No.: 2622246

| <b>Sample: YGWC-44</b>         |                 | <b>Lab ID: 2622246003</b>                                  |              | Collected: 08/20/19 13:45 |    | Received: 08/21/19 16:50 |                | Matrix: Water |      |
|--------------------------------|-----------------|--|--------------|---------------------------|----|--------------------------|----------------|---------------|------|
| Parameters                     | Results         | Units  | Report Limit | MDL                       | DF | Prepared                 | Analyzed       | CAS No.       | Qual |
| <b>6020B MET ICPMS</b>         |                 | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |              |                           |    |                          |                |               |      |
| Antimony                       | ND              | mg/L   | 0.0030       | 0.00027                   | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7440-36-0     |      |
| Arsenic                        | <b>0.00097J</b> | mg/L   | 0.0050       | 0.00035                   | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7440-38-2     |      |
| Barium                         | <b>0.10</b>     | mg/L   | 0.010        | 0.00049                   | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7440-39-3     |      |
| Beryllium                      | ND              | mg/L   | 0.0030       | 0.000074                  | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7440-41-7     |      |
| Cadmium                        | ND              | mg/L   | 0.0025       | 0.00011                   | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7440-43-9     |      |
| Chromium                       | ND              | mg/L   | 0.010        | 0.00039                   | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7440-47-3     |      |
| Cobalt                         | <b>0.0020J</b>  | mg/L   | 0.0050       | 0.00030                   | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7440-48-4     |      |
| Lead                           | ND              | mg/L   | 0.0050       | 0.000046                  | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7439-92-1     |      |
| Lithium                        | <b>0.013J</b>   | mg/L   | 0.030        | 0.00078                   | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7439-93-2     |      |
| Molybdenum                     | ND              | mg/L   | 0.010        | 0.00095                   | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7439-98-7     |      |
| Selenium                       | ND              | mg/L   | 0.010        | 0.0013                    | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7782-49-2     |      |
| Thallium                       | ND              | mg/L   | 0.0010       | 0.000052                  | 1  | 08/23/19 14:17           | 08/26/19 17:18 | 7440-28-0     |      |
| <b>7470 Mercury</b>            |                 | Analytical Method: EPA 7470A Preparation Method: EPA 7470A |              |                           |    |                          |                |               |      |
| Mercury                        | ND              | mg/L   | 0.00050      | 0.00014                   | 1  | 08/26/19 14:21           | 08/27/19 11:06 | 7439-97-6     |      |
| <b>300.0 IC Anions 28 Days</b> |                 | Analytical Method: EPA 300.0                               |              |                           |    |                          |                |               |      |
| Fluoride                       | ND              | mg/L   | 0.30         | 0.029                     | 1  |                          | 08/28/19 22:48 | 16984-48-8    |      |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## ANALYTICAL RESULTS

Project: Plant Yates-Pond 1  
Pace Project No.: 2622246

| Sample: <b>FB-1-8-20-19</b>    |                 | Lab ID: <b>2622246004</b>                                  |         | Collected: 08/20/19 13:30 |    | Received: 08/21/19 16:50 |                | Matrix: Water |      |  |
|--------------------------------|-----------------|--|---------|---------------------------|----|--------------------------|----------------|---------------|------|--|
| Parameters                     | Results         | Units  | Report  |                           |    | Prepared                 | Analyzed       | CAS No.       | Qual |  |
|                                |                 |  | Limit   | MDL                       | DF |                          |                |               |      |  |
| <b>6020B MET ICPMS</b>         |                 | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |         |                           |    |                          |                |               |      |  |
| Antimony                       | ND              | mg/L   | 0.0030  | 0.00027                   | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7440-36-0     |      |  |
| Arsenic                        | <b>0.00063J</b> | mg/L   | 0.0050  | 0.00035                   | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7440-38-2     |      |  |
| Barium                         | ND              | mg/L   | 0.010   | 0.00049                   | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7440-39-3     |      |  |
| Beryllium                      | ND              | mg/L   | 0.0030  | 0.000074                  | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7440-41-7     |      |  |
| Cadmium                        | ND              | mg/L   | 0.0025  | 0.00011                   | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7440-43-9     |      |  |
| Chromium                       | ND              | mg/L   | 0.010   | 0.00039                   | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7440-47-3     |      |  |
| Cobalt                         | ND              | mg/L   | 0.0050  | 0.00030                   | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7440-48-4     |      |  |
| Lead                           | ND              | mg/L   | 0.0050  | 0.000046                  | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7439-92-1     |      |  |
| Lithium                        | ND              | mg/L   | 0.030   | 0.00078                   | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7439-93-2     |      |  |
| Molybdenum                     | ND              | mg/L   | 0.010   | 0.00095                   | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7439-98-7     |      |  |
| Selenium                       | ND              | mg/L   | 0.010   | 0.0013                    | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7782-49-2     |      |  |
| Thallium                       | ND              | mg/L   | 0.0010  | 0.000052                  | 1  | 08/23/19 14:17           | 08/26/19 17:24 | 7440-28-0     |      |  |
| <b>7470 Mercury</b>            |                 | Analytical Method: EPA 7470A Preparation Method: EPA 7470A |         |                           |    |                          |                |               |      |  |
| Mercury                        | ND              | mg/L   | 0.00050 | 0.00014                   | 1  | 08/26/19 14:21           | 08/27/19 11:08 | 7439-97-6     |      |  |
| <b>300.0 IC Anions 28 Days</b> |                 | Analytical Method: EPA 300.0                               |         |                           |    |                          |                |               |      |  |
| Fluoride                       | ND              | mg/L   | 0.30    | 0.029                     | 1  |                          | 08/28/19 23:11 | 16984-48-8    |      |  |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## ANALYTICAL RESULTS

Project: Plant Yates-Pond 1  
Pace Project No.: 2622246

| Sample: YGWC-46                |                 | Lab ID: 2622246005   |         | Collected: 08/21/19 09:45 |    | Received: 08/21/19 16:50 |                | Matrix: Water |      |  |
|--------------------------------|-----------------|--|---------|---------------------------|----|--------------------------|----------------|---------------|------|--|
| Parameters                     | Results         | Units  | Report  |                           |    | Prepared                 | Analyzed       | CAS No.       | Qual |  |
|                                |                 |  | Limit   | MDL                       | DF |                          |                |               |      |  |
| <b>6020B MET ICPMS</b>         |                 | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |         |                           |    |                          |                |               |      |  |
| Antimony                       | ND              | mg/L   | 0.0030  | 0.00027                   | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7440-36-0     |      |  |
| Arsenic                        | <b>0.00074J</b> | mg/L   | 0.0050  | 0.00035                   | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7440-38-2     |      |  |
| Barium                         | <b>0.023</b>    | mg/L   | 0.010   | 0.00049                   | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7440-39-3     |      |  |
| Beryllium                      | ND              | mg/L   | 0.0030  | 0.000074                  | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7440-41-7     |      |  |
| Cadmium                        | <b>0.00012J</b> | mg/L   | 0.0025  | 0.00011                   | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7440-43-9     |      |  |
| Chromium                       | ND              | mg/L   | 0.010   | 0.00039                   | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7440-47-3     |      |  |
| Cobalt                         | <b>0.027</b>    | mg/L   | 0.0050  | 0.00030                   | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7440-48-4     |      |  |
| Lead                           | ND              | mg/L   | 0.0050  | 0.000046                  | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7439-92-1     |      |  |
| Lithium                        | <b>0.0076J</b>  | mg/L   | 0.030   | 0.00078                   | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7439-93-2     |      |  |
| Molybdenum                     | <b>0.0012J</b>  | mg/L   | 0.010   | 0.00095                   | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7439-98-7     |      |  |
| Selenium                       | ND              | mg/L   | 0.010   | 0.0013                    | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7782-49-2     |      |  |
| Thallium                       | ND              | mg/L   | 0.0010  | 0.000052                  | 1  | 08/23/19 14:17           | 08/26/19 17:30 | 7440-28-0     |      |  |
| <b>7470 Mercury</b>            |                 | Analytical Method: EPA 7470A Preparation Method: EPA 7470A |         |                           |    |                          |                |               |      |  |
| Mercury                        | ND              | mg/L   | 0.00050 | 0.00014                   | 1  | 08/26/19 14:21           | 08/27/19 11:15 | 7439-97-6     |      |  |
| <b>300.0 IC Anions 28 Days</b> |                 | Analytical Method: EPA 300.0                               |         |                           |    |                          |                |               |      |  |
| Fluoride                       | ND              | mg/L   | 0.30    | 0.029                     | 1  |                          | 08/28/19 23:34 | 16984-48-8    |      |  |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## ANALYTICAL RESULTS

Project: Plant Yates-Pond 1  
Pace Project No.: 2622246

| Sample: EB-1-8-21-19           |                 | Lab ID: 2622246006   |         | Collected: 08/21/19 10:00 |    | Received: 08/21/19 16:50 |                | Matrix: Water |      |  |
|--------------------------------|-----------------|--|---------|---------------------------|----|--------------------------|----------------|---------------|------|--|
| Parameters                     | Results         | Units  | Report  |                           |    | Prepared                 | Analyzed       | CAS No.       | Qual |  |
|                                |                 |  | Limit   | MDL                       | DF |                          |                |               |      |  |
| <b>6020B MET ICPMS</b>         |                 | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |         |                           |    |                          |                |               |      |  |
| Antimony                       | ND              | mg/L   | 0.0030  | 0.00027                   | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7440-36-0     |      |  |
| Arsenic                        | <b>0.00063J</b> | mg/L   | 0.0050  | 0.00035                   | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7440-38-2     |      |  |
| Barium                         | ND              | mg/L   | 0.010   | 0.00049                   | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7440-39-3     |      |  |
| Beryllium                      | ND              | mg/L   | 0.0030  | 0.000074                  | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7440-41-7     |      |  |
| Cadmium                        | ND              | mg/L   | 0.0025  | 0.00011                   | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7440-43-9     |      |  |
| Chromium                       | ND              | mg/L   | 0.010   | 0.00039                   | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7440-47-3     |      |  |
| Cobalt                         | ND              | mg/L   | 0.0050  | 0.00030                   | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7440-48-4     |      |  |
| Lead                           | ND              | mg/L   | 0.0050  | 0.000046                  | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7439-92-1     |      |  |
| Lithium                        | ND              | mg/L   | 0.030   | 0.00078                   | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7439-93-2     |      |  |
| Molybdenum                     | ND              | mg/L   | 0.010   | 0.00095                   | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7439-98-7     |      |  |
| Selenium                       | ND              | mg/L   | 0.010   | 0.0013                    | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7782-49-2     |      |  |
| Thallium                       | ND              | mg/L   | 0.0010  | 0.000052                  | 1  | 08/23/19 14:17           | 08/26/19 17:35 | 7440-28-0     |      |  |
| <b>7470 Mercury</b>            |                 | Analytical Method: EPA 7470A Preparation Method: EPA 7470A |         |                           |    |                          |                |               |      |  |
| Mercury                        | ND              | mg/L   | 0.00050 | 0.00014                   | 1  | 08/26/19 14:21           | 08/27/19 11:18 | 7439-97-6     |      |  |
| <b>300.0 IC Anions 28 Days</b> |                 | Analytical Method: EPA 300.0                               |         |                           |    |                          |                |               |      |  |
| Fluoride                       | ND              | mg/L   | 0.30    | 0.029                     | 1  |                          | 08/28/19 23:56 | 16984-48-8    |      |  |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS

Project: Plant Yates-Pond 1  
Pace Project No.: 2622246

| Sample: Dup-1                  |                 | Lab ID: 2622246007   |         | Collected: 08/21/19 00:00 |    | Received: 08/21/19 16:50 |                | Matrix: Water |      |  |
|--------------------------------|-----------------|--|---------|---------------------------|----|--------------------------|----------------|---------------|------|--|
| Parameters                     | Results         | Units  | Report  |                           |    | Prepared                 | Analyzed       | CAS No.       | Qual |  |
|                                |                 |  | Limit   | MDL                       | DF |                          |                |               |      |  |
| <b>6020B MET ICPMS</b>         |                 | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |         |                           |    |                          |                |               |      |  |
| Antimony                       | ND              | mg/L   | 0.0030  | 0.00027                   | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7440-36-0     |      |  |
| Arsenic                        | <b>0.00061J</b> | mg/L   | 0.0050  | 0.00035                   | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7440-38-2     |      |  |
| Barium                         | <b>0.025</b>    | mg/L   | 0.010   | 0.00049                   | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7440-39-3     |      |  |
| Beryllium                      | ND              | mg/L   | 0.0030  | 0.000074                  | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7440-41-7     |      |  |
| Cadmium                        | <b>0.00011J</b> | mg/L   | 0.0025  | 0.00011                   | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7440-43-9     |      |  |
| Chromium                       | ND              | mg/L   | 0.010   | 0.00039                   | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7440-47-3     |      |  |
| Cobalt                         | <b>0.028</b>    | mg/L   | 0.0050  | 0.00030                   | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7440-48-4     |      |  |
| Lead                           | ND              | mg/L   | 0.0050  | 0.000046                  | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7439-92-1     |      |  |
| Lithium                        | <b>0.0080J</b>  | mg/L   | 0.030   | 0.00078                   | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7439-93-2     |      |  |
| Molybdenum                     | <b>0.0013J</b>  | mg/L   | 0.010   | 0.00095                   | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7439-98-7     |      |  |
| Selenium                       | ND              | mg/L   | 0.010   | 0.0013                    | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7782-49-2     |      |  |
| Thallium                       | ND              | mg/L   | 0.0010  | 0.000052                  | 1  | 08/23/19 14:17           | 08/26/19 17:41 | 7440-28-0     |      |  |
| <b>7470 Mercury</b>            |                 | Analytical Method: EPA 7470A Preparation Method: EPA 7470A |         |                           |    |                          |                |               |      |  |
| Mercury                        | ND              | mg/L   | 0.00050 | 0.00014                   | 1  | 08/26/19 14:21           | 08/27/19 11:20 | 7439-97-6     |      |  |
| <b>300.0 IC Anions 28 Days</b> |                 | Analytical Method: EPA 300.0                               |         |                           |    |                          |                |               |      |  |
| Fluoride                       | ND              | mg/L   | 0.30    | 0.029                     | 1  |                          | 08/29/19 00:19 | 16984-48-8    |      |  |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL DATA

Project: Plant Yates-Pond 1

Pace Project No.: 2622246

QC Batch: 34231 Analysis Method: EPA 7470A  
 QC Batch Method: EPA 7470A Analysis Description: 7470 Mercury  
 Associated Lab Samples: 2622246001, 2622246002, 2622246003, 2622246004, 2622246005, 2622246006, 2622246007

METHOD BLANK: 154028 Matrix: Water  
 Associated Lab Samples: 2622246001, 2622246002, 2622246003, 2622246004, 2622246005, 2622246006, 2622246007

| Parameter | Units | Blank Result | Reporting Limit | MDL     | Analyzed       | Qualifiers |
|-----------|-------|--------------|-----------------|---------|----------------|------------|
| Mercury   | mg/L  | ND           | 0.00050         | 0.00014 | 08/27/19 10:49 |            |

LABORATORY CONTROL SAMPLE: 154029

| Parameter | Units | Spike Conc. | LCS Result | LCS % Rec | % Rec Limits | Qualifiers |
|-----------|-------|-------------|------------|-----------|--------------|------------|
| Mercury   | mg/L  | 0.0025      | 0.0025     | 102       | 80-120       |            |

MATRIX SPIKE & MATRIX SPIKE DUPLICATE: 154030 154031

| Parameter | Units | 2622246001 Result | MS Spike Conc. | MSD Spike Conc. | MS Result | MSD Result | MS % Rec | MSD % Rec | % Rec Limits | RPD | Max RPD | Qual |
|-----------|-------|-------------------|----------------|-----------------|-----------|------------|----------|-----------|--------------|-----|---------|------|
| Mercury   | mg/L  | ND                | 0.0025         | 0.0025          | 0.0026    | 0.0025     | 103      | 99        | 75-125       | 3   | 20      |      |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL DATA

Project: Plant Yates-Pond 1  
Pace Project No.: 2622246

QC Batch: 34176 Analysis Method: EPA 6020B  
QC Batch Method: EPA 3005A Analysis Description: 6020B MET  
Associated Lab Samples: 2622246001, 2622246002, 2622246003, 2622246004, 2622246005, 2622246006, 2622246007

METHOD BLANK: 153777 Matrix: Water  
Associated Lab Samples: 2622246001, 2622246002, 2622246003, 2622246004, 2622246005, 2622246006, 2622246007

| Parameter  | Units | Blank Result | Reporting Limit | MDL      | Analyzed       | Qualifiers |
|------------|-------|--------------|-----------------|----------|----------------|------------|
| Antimony   | mg/L  | ND           | 0.0030          | 0.00027  | 08/26/19 16:54 |            |
| Arsenic    | mg/L  | ND           | 0.0050          | 0.00035  | 08/26/19 16:54 |            |
| Barium     | mg/L  | ND           | 0.010           | 0.00049  | 08/26/19 16:54 |            |
| Beryllium  | mg/L  | ND           | 0.0030          | 0.000074 | 08/26/19 16:54 |            |
| Cadmium    | mg/L  | ND           | 0.0025          | 0.00011  | 08/26/19 16:54 |            |
| Chromium   | mg/L  | ND           | 0.010           | 0.00039  | 08/26/19 16:54 |            |
| Cobalt     | mg/L  | ND           | 0.0050          | 0.00030  | 08/26/19 16:54 |            |
| Lead       | mg/L  | ND           | 0.0050          | 0.000046 | 08/26/19 16:54 |            |
| Lithium    | mg/L  | ND           | 0.030           | 0.00078  | 08/26/19 16:54 |            |
| Molybdenum | mg/L  | ND           | 0.010           | 0.00095  | 08/26/19 16:54 |            |
| Selenium   | mg/L  | ND           | 0.010           | 0.0013   | 08/26/19 16:54 |            |
| Thallium   | mg/L  | ND           | 0.0010          | 0.000052 | 08/26/19 16:54 |            |

LABORATORY CONTROL SAMPLE: 153778

| Parameter  | Units | Spike Conc. | LCS Result | LCS % Rec | % Rec Limits | Qualifiers |
|------------|-------|-------------|------------|-----------|--------------|------------|
| Antimony   | mg/L  | 0.1         | 0.11       | 105       | 80-120       |            |
| Arsenic    | mg/L  | 0.1         | 0.10       | 102       | 80-120       |            |
| Barium     | mg/L  | 0.1         | 0.10       | 103       | 80-120       |            |
| Beryllium  | mg/L  | 0.1         | 0.10       | 103       | 80-120       |            |
| Cadmium    | mg/L  | 0.1         | 0.10       | 103       | 80-120       |            |
| Chromium   | mg/L  | 0.1         | 0.10       | 103       | 80-120       |            |
| Cobalt     | mg/L  | 0.1         | 0.10       | 103       | 80-120       |            |
| Lead       | mg/L  | 0.1         | 0.10       | 103       | 80-120       |            |
| Lithium    | mg/L  | 0.1         | 0.10       | 104       | 80-120       |            |
| Molybdenum | mg/L  | 0.1         | 0.11       | 106       | 80-120       |            |
| Selenium   | mg/L  | 0.1         | 0.099      | 99        | 80-120       |            |
| Thallium   | mg/L  | 0.1         | 0.10       | 102       | 80-120       |            |

MATRIX SPIKE & MATRIX SPIKE DUPLICATE: 153779 153780

| Parameter | Units | MS                |             | MSD         |           | MS % Rec | MSD % Rec | % Rec Limits | RPD    | Max RPD | Qual |            |
|-----------|-------|-------------------|-------------|-------------|-----------|----------|-----------|--------------|--------|---------|------|------------|
|           |       | 2622250005 Result | Spike Conc. | Spike Conc. | MS Result |          |           |              |        |         |      | MSD Result |
| Antimony  | mg/L  | ND                | 0.1         | 0.1         | 0.10      | 0.10     | 100       | 101          | 75-125 | 1       | 20   |            |
| Arsenic   | mg/L  | 0.00059J          | 0.1         | 0.1         | 0.098     | 0.098    | 97        | 98           | 75-125 | 1       | 20   |            |
| Barium    | mg/L  | 0.020             | 0.1         | 0.1         | 0.12      | 0.12     | 95        | 96           | 75-125 | 1       | 20   |            |
| Beryllium | mg/L  | ND                | 0.1         | 0.1         | 0.096     | 0.096    | 96        | 96           | 75-125 | 0       | 20   |            |
| Cadmium   | mg/L  | ND                | 0.1         | 0.1         | 0.098     | 0.10     | 98        | 100          | 75-125 | 2       | 20   |            |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL DATA

Project: Plant Yates-Pond 1

Pace Project No.: 2622246

| MATRIX SPIKE & MATRIX SPIKE DUPLICATE: 153779 |       |            |             |             |        |        |       |       |        |     |     | 153780 |  |
|---|-------|------------|-------------|-------------|--------|--------|-------|-------|--------|-----|-----|--------|--|
| Parameter                                     | Units | 2622250005 | MS          | MSD         | MS     | MSD    | MS    | MSD   | % Rec  | Max | RPD | Qual   |  |
|   |       | Result     | Spike Conc. | Spike Conc. | Result | Result | % Rec | % Rec | Limits |     |     |        |  |
| Chromium                                      | mg/L  | 0.00051J   | 0.1         | 0.1         | 0.10   | 0.10   | 101   | 100   | 75-125 | 1   | 20  |        |  |
| Cobalt  | mg/L  | 0.0010J    | 0.1         | 0.1         | 0.10   | 0.10   | 100   | 99    | 75-125 | 0   | 20  |        |  |
| Lead  | mg/L  | ND         | 0.1         | 0.1         | 0.096  | 0.097  | 96    | 97    | 75-125 | 0   | 20  |        |  |
| Lithium                                       | mg/L  | 0.00094J   | 0.1         | 0.1         | 0.096  | 0.096  | 95    | 95    | 75-125 | 0   | 20  |        |  |
| Molybdenum                                    | mg/L  | ND         | 0.1         | 0.1         | 0.10   | 0.10   | 101   | 102   | 75-125 | 1   | 20  |        |  |
| Selenium                                      | mg/L  | 0.0030J    | 0.1         | 0.1         | 0.098  | 0.10   | 95    | 97    | 75-125 | 2   | 20  |        |  |
| Thallium                                      | mg/L  | ND         | 0.1         | 0.1         | 0.096  | 0.097  | 96    | 97    | 75-125 | 1   | 20  |        |  |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL DATA

Project: Plant Yates-Pond 1  
Pace Project No.: 2622246

QC Batch: 34413 Analysis Method: EPA 300.0  
QC Batch Method: EPA 300.0 Analysis Description: 300.0 IC Anions  
Associated Lab Samples: 2622246001, 2622246002, 2622246003, 2622246004, 2622246005, 2622246006, 2622246007

METHOD BLANK: 154817 Matrix: Water  
Associated Lab Samples: 2622246001, 2622246002, 2622246003, 2622246004, 2622246005, 2622246006, 2622246007

| Parameter | Units | Blank Result | Reporting Limit | MDL   | Analyzed       | Qualifiers |
|-----------|-------|--------------|-----------------|-------|----------------|------------|
| Fluoride  | mg/L  | ND           | 0.30            | 0.029 | 08/28/19 20:32 |            |

LABORATORY CONTROL SAMPLE: 154818

| Parameter | Units | Spike Conc. | LCS Result | LCS % Rec | % Rec Limits | Qualifiers |
|-----------|-------|-------------|------------|-----------|--------------|------------|
| Fluoride  | mg/L  | 10          | 9.5        | 95        | 90-110       |            |

MATRIX SPIKE & MATRIX SPIKE DUPLICATE: 154819 154820

| Parameter | Units | 2622246001 |            | 2622246002     |                 | 2622246003 |            | % Rec Limits | RPD | Max RPD | Qual |          |
|-----------|-------|------------|------------|----------------|-----------------|------------|------------|--------------|-----|---------|------|----------|
|           |       | MS Result  | MSD Result | MS Spike Conc. | MSD Spike Conc. | MS Result  | MSD Result |              |     |         |      | MS % Rec |
| Fluoride  | mg/L  | ND         | ND         | 10             | 10              | 9.9        | 9.8        | 99           | 98  | 90-110  | 1    | 15       |

MATRIX SPIKE SAMPLE: 154821

| Parameter | Units | 2622246002 Result | Spike Conc. | MS Result | MS % Rec | % Rec Limits | Qualifiers |
|-----------|-------|-------------------|-------------|-----------|----------|--------------|------------|
| Fluoride  | mg/L  | ND                | 10          | 9.7       | 97       | 90-110       |            |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## QUALIFIERS

Project: Plant Yates-Pond 1

Pace Project No.: 2622246

---

### DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to dilution of the sample aliquot.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

PQL - Practical Quantitation Limit.

RL - Reporting Limit - The lowest concentration value that meets project requirements for quantitative data with known precision and bias for a specific analyte in a specific matrix.

S - Surrogate

1,2-Diphenylhydrazine decomposes to and cannot be separated from Azobenzene using Method 8270. The result for each analyte is a combined concentration.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

SG - Silica Gel - Clean-Up

U - Indicates the compound was analyzed for, but not detected.

N-Nitrosodiphenylamine decomposes and cannot be separated from Diphenylamine using Method 8270. The result reported for each analyte is a combined concentration.

Pace Analytical is TNI accredited. Contact your Pace PM for the current list of accredited analytes.

TNI - The NELAC Institute.

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL DATA CROSS REFERENCE TABLE

Project: Plant Yates-Pond 1  
Pace Project No.: 2622246

| Lab ID     | Sample ID    | QC Batch Method | QC Batch | Analytical Method | Analytical Batch |
|------------|--------------|-----------------|----------|-------------------|------------------|
| 2622246001 | YGWA-47      | EPA 3005A       | 34176    | EPA 6020B         | 34193            |
| 2622246002 | YGWC-45      | EPA 3005A       | 34176    | EPA 6020B         | 34193            |
| 2622246003 | YGWC-44      | EPA 3005A       | 34176    | EPA 6020B         | 34193            |
| 2622246004 | FB-1-8-20-19 | EPA 3005A       | 34176    | EPA 6020B         | 34193            |
| 2622246005 | YGWC-46      | EPA 3005A       | 34176    | EPA 6020B         | 34193            |
| 2622246006 | EB-1-8-21-19 | EPA 3005A       | 34176    | EPA 6020B         | 34193            |
| 2622246007 | Dup-1        | EPA 3005A       | 34176    | EPA 6020B         | 34193            |
| 2622246001 | YGWA-47      | EPA 7470A       | 34231    | EPA 7470A         | 34309            |
| 2622246002 | YGWC-45      | EPA 7470A       | 34231    | EPA 7470A         | 34309            |
| 2622246003 | YGWC-44      | EPA 7470A       | 34231    | EPA 7470A         | 34309            |
| 2622246004 | FB-1-8-20-19 | EPA 7470A       | 34231    | EPA 7470A         | 34309            |
| 2622246005 | YGWC-46      | EPA 7470A       | 34231    | EPA 7470A         | 34309            |
| 2622246006 | EB-1-8-21-19 | EPA 7470A       | 34231    | EPA 7470A         | 34309            |
| 2622246007 | Dup-1        | EPA 7470A       | 34231    | EPA 7470A         | 34309            |
| 2622246001 | YGWA-47      | EPA 300.0       | 34413    |                   |                  |
| 2622246002 | YGWC-45      | EPA 300.0       | 34413    |                   |                  |
| 2622246003 | YGWC-44      | EPA 300.0       | 34413    |                   |                  |
| 2622246004 | FB-1-8-20-19 | EPA 300.0       | 34413    |                   |                  |
| 2622246005 | YGWC-46      | EPA 300.0       | 34413    |                   |                  |
| 2622246006 | EB-1-8-21-19 | EPA 300.0       | 34413    |                   |                  |
| 2622246007 | Dup-1        | EPA 300.0       | 34413    |                   |                  |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.



Pace Analytical Services, Inc.  
 110 TECHNOLOGY PARKWAY, PEACHTREE CORNERS, GA 30092  
 (770) 734-4200 : FAX (770) 734-4201

**CHAIN OF CUSTODY RECORD**

PAGE: / OF ]

|   |                            |   |                                 |                            |                       |  |          |  |  |
|---|----------------------------|---|---------------------------------|----------------------------|-----------------------|--|----------|--|--|
| CLIENT NAME:<br>Georgia Power   |                            | CONTAINER TYPE:<br>PRESERVATION:            |                                 | ANALYSIS REQUESTED         |                       | CONTAINER TYPE   |          | PRESERVATION   |  |
| CLIENT ADDRESS/PHONE NUMBER/FAX NUMBER:<br>241 Ralph McGill Blvd SE B10185<br>Atlanta, GA 30308<br>404-506-7239 |                            | # of  |                                 |                            |                       | P - PLASTIC<br>A - AMBER GLASS<br>G - CLEAR GLASS<br>V - VOA VIAL<br>S - STERILE<br>O - OTHER  |          | 1 - HCl, ≤6°C<br>2 - H <sub>2</sub> SO <sub>4</sub> , ≤6°C<br>3 - HNO <sub>3</sub><br>4 - NaOH, ≤6°C<br>5 - NaOH/ZnAc, ≤6°C<br>6 - Na <sub>2</sub> S <sub>2</sub> O <sub>3</sub> , ≤6°C<br>7 - ≤6°C not frozen |  |
| REPORT TO:<br>Joju Abraham  | CC:                        | CONTAINERS →                                |                                 | L A B I D N U M B E R      |                       | MATRIX CODES:  |          | REMARKS/ADDITIONAL INFORMATION   |  |
| REQUESTED COMPLETION DATE:  | PO #:                      | PROJECT NAME/STATE:<br>Plant Yates - Pond 1 |                                 |                            |                       | DW - DRINKING WATER S - SOIL<br>MW - WASTEWATER SL - SLUDGE<br>GW - GROUNDWATER SD - SOLID<br>SW - SURFACE WATER A - AIR<br>ST - STORM WATER L - LIQUID<br>W - WATER P - PRODUCT |          |  |  |
| PROJECT #:  |                            | PROJECT #:                                  |                                 |                            |                       | *MATRIX CODES:   |          |  |  |
| Collection DATE   | Collection TIME            | MATRIX CODE                                 | C O M P                         | G R A B                    | SAMPLE IDENTIFICATION | Metals App. IV (EPA 6020/7470)   | Flouride | Radium 226 & 228 (SW-846 9315/9320)  |  |
| 8-20-19   | 1030                       | GW  | X                               | X                          | YGWA-47               | ✓  | ✓        | ✓  |  |
| 8-20-19   | 1135                       | GW  | X                               | X                          | YGWC-45               | ✓  | ✓        | ✓  |  |
| 8-20-19   | 1345                       | GW  | X                               | X                          | YGWC-44               | ✓  | ✓        | ✓  |  |
| 8-20-19   | 1330                       | W   | X                               | X                          | FB-1-8-20-19          | ✓  | ✓        | ✓  |  |
| 8-21-19   | 0945                       | GW  | X                               | X                          | YGWC-46               | ✓  | ✓        | ✓  |  |
| 8-21-19   | 1000                       | W   | X                               | X                          | FB-1-8-21-19          | ✓  | ✓        | ✓  |  |
| ---   | ---                        | GW  | X                               | X                          | Dup-1                 | ✓  | ✓        | ✓  |  |
| SAMPLED BY AND TITLE:<br>JAC  |                            | DATE/TIME:<br>8-21-19 1650                  | RELINQUISHED BY:<br>[Signature] | DATE/TIME:<br>8-21-19 1650 | RELINQUISHED BY:      | DATE/TIME:<br>8-21-19 1650   |          | DATE/TIME:   |  |
| RECEIVED BY:<br>[Signature]   | DATE/TIME:<br>8-21-19 1650 | SAMPLE SHIPPED VIA:<br>UPS                  | FED-EX                          | USPS                       | COURIER               | OTHER  | FS       | FOR LAB USE ONLY   |  |
| RECEIVED BY/LAB:<br>[Signature]   | DATE/TIME:<br>8-21-19 1650 | Temperature:<br>Mon: 2.0 Max:               | Intact                          | Broken                     | Not Present           | CLIENT   |          | Entered Into LIMS:<br>Tracking #:  |  |

WO#: 2622246

Yates Phase- Pond 1 - Blank COCs



Sample Condition Upon Receipt

Client Name: GIA Power Project # \_\_\_\_\_

Courier:  Fed Ex  UPS  USPS  Client  Commercial  Pace Other \_\_\_\_\_  
Tracking #: \_\_\_\_\_

**WO#: 2622246**

Custody Seal on Cooler/Box Present:  yes  no Seals intact:  yes  no

PM: BM Due Date: 08/28/19  
CLIENT: GAPower-CCR

Packing Material:  Bubble Wrap  Bubble Bags  None  Other \_\_\_\_\_

Thermometer Used 83 Type of Ice:  Wet  Blue  None  Samples on ice, cooling process has begun

Cooler Temperature 2'0 Biological Tissue is Frozen: Yes No  
Temp should be above freezing to 6°C

Date and Initials of person examining contents: 8/21/19 MR

|  |  |                        |                             |
|--|--|------------------------|-----------------------------|
| Chain of Custody Present:  | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 1.                     |                             |
| Chain of Custody Filled Out:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 2.                     |                             |
| Chain of Custody Relinquished:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 3.                     |                             |
| Sampler Name & Signature on COC:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 4.                     |                             |
| Samples Arrived within Hold Time:  | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 5.                     |                             |
| Short Hold Time Analysis (<72hr):  | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> N/A | 6.                     |                             |
| Rush Turn Around Time Requested:   | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> N/A | 7.                     |                             |
| Sufficient Volume:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 8.                     |                             |
| Correct Containers Used:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 9.                     |                             |
| -Pace Containers Used:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A |                        |                             |
| Containers Intact:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 10.                    |                             |
| Filtered volume received for Dissolved tests   | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 11.                    |                             |
| Sample Labels match COC:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 12.                    |                             |
| -Includes date/time/ID/Analysis Matrix:  | <u>W</u>   |                        |                             |
| All containers needing preservation have been checked.                                     | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 13.                    |                             |
| All containers needing preservation are found to be in compliance with EPA recommendation. | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A |                        |                             |
| exceptions: VOA, coliform, TOC, O&G, WI-DRO (water)  | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No                              | Initial when completed | Lot # of added preservative |
| Samples checked for dechlorination:  | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 14.                    |                             |
| Headspace in VOA Vials (>6mm):   | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 15.                    |                             |
| Trip Blank Present:  | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 16.                    |                             |
| Trip Blank Custody Seals Present   | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A |                        |                             |
| Pace Trip Blank Lot # (if purchased):  | _____  |                        |                             |

Client Notification/ Resolution: \_\_\_\_\_ Field Data Required? Y / N

Person Contacted: \_\_\_\_\_ Date/Time: \_\_\_\_\_

Comments/ Resolution: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Project Manager Review: \_\_\_\_\_ Date: \_\_\_\_\_

Note: Whenever there is a discrepancy affecting North Carolina compliance samples, a copy of this form will be sent to the North Carolina DEHNR Certification Office ( i.e out of hold, incorrect preservative, out of temp, incorrect containers)

September 16, 2019

Joju Abraham  
Georgia Power - Coal Combustion Residuals  
2480 Maner Road  
Atlanta, GA 30339

RE: Project: Plant Yates-Pond 1  
Pace Project No.: 2622248

Dear Joju Abraham:

Enclosed are the analytical results for sample(s) received by the laboratory on August 21, 2019. The results relate only to the samples included in this report. Results reported herein conform to the most current, applicable TNI/NELAC standards and the laboratory's Quality Assurance Manual, where applicable, unless otherwise noted in the body of the report.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,



Betsy McDaniel  
betsy.mcdaniel@pacelabs.com  
(770)734-4200  
Project Manager

Enclosures

cc: Chris Parker, Atlantic Coast Consulting  
Evan Perry, Atlantic Coast Consulting  
Lauren Petty, Southern Company Services, Inc.  
Rebecca Thornton, Pace Analytical Atlanta



## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## CERTIFICATIONS

Project: Plant Yates-Pond 1  
Pace Project No.: 2622248

---

### Pennsylvania Certification IDs

1638 Roseytown Rd Suites 2,3&4, Greensburg, PA 15601  
ANAB DOD-ELAP Rad Accreditation #: L2417  
Alabama Certification #: 41590  
Arizona Certification #: AZ0734  
Arkansas Certification  
California Certification #: 04222CA  
Colorado Certification #: PA01547  
Connecticut Certification #: PH-0694  
Delaware Certification  
EPA Region 4 DW Rad  
Florida/TNI Certification #: E87683  
Georgia Certification #: C040  
Florida: Cert E871149 SEKS WET  
Guam Certification  
Hawaii Certification  
Idaho Certification  
Illinois Certification  
Indiana Certification  
Iowa Certification #: 391  
Kansas/TNI Certification #: E-10358  
Kentucky Certification #: KY90133  
KY WW Permit #: KY0098221  
KY WW Permit #: KY0000221  
Louisiana DHH/TNI Certification #: LA180012  
Louisiana DEQ/TNI Certification #: 4086  
Maine Certification #: 2017020  
Maryland Certification #: 308  
Massachusetts Certification #: M-PA1457  
Michigan/PADEP Certification #: 9991

Missouri Certification #: 235  
Montana Certification #: Cert0082  
Nebraska Certification #: NE-OS-29-14  
Nevada Certification #: PA014572018-1  
New Hampshire/TNI Certification #: 297617  
New Jersey/TNI Certification #: PA051  
New Mexico Certification #: PA01457  
New York/TNI Certification #: 10888  
North Carolina Certification #: 42706  
North Dakota Certification #: R-190  
Ohio EPA Rad Approval: #41249  
Oregon/TNI Certification #: PA200002-010  
Pennsylvania/TNI Certification #: 65-00282  
Puerto Rico Certification #: PA01457  
Rhode Island Certification #: 65-00282  
South Dakota Certification  
Tennessee Certification #: 02867  
Texas/TNI Certification #: T104704188-17-3  
Utah/TNI Certification #: PA014572017-9  
USDA Soil Permit #: P330-17-00091  
Vermont Dept. of Health: ID# VT-0282  
Virgin Island/PADEP Certification  
Virginia/VELAP Certification #: 9526  
Washington Certification #: C868  
West Virginia DEP Certification #: 143  
West Virginia DHHR Certification #: 9964C  
Wisconsin Approve List for Rad  
Wyoming Certification #: 8TMS-L

---

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## SAMPLE SUMMARY

Project: Plant Yates-Pond 1

Pace Project No.: 2622248

| Lab ID     | Sample ID    | Matrix | Date Collected | Date Received  |
|------------|--------------|--------|----------------|----------------|
| 2622248001 | YGWA-47      | Water  | 08/20/19 10:30 | 08/21/19 16:50 |
| 2622248002 | YGWC-45      | Water  | 08/20/19 11:35 | 08/21/19 16:50 |
| 2622248003 | YGWC-44      | Water  | 08/20/19 13:45 | 08/21/19 16:50 |
| 2622248004 | FB-1-8-20-19 | Water  | 08/20/19 13:30 | 08/21/19 16:50 |
| 2622248005 | YGWC-46      | Water  | 08/21/19 09:45 | 08/21/19 16:50 |
| 2622248006 | EB-1-8-21-19 | Water  | 08/21/19 10:00 | 08/21/19 16:50 |
| 2622248007 | Dup-1        | Water  | 08/21/19 00:00 | 08/21/19 16:50 |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### SAMPLE ANALYTE COUNT

Project: Plant Yates-Pond 1

Pace Project No.: 2622248

| Lab ID     | Sample ID    | Method                   | Analysts | Analytes Reported | Laboratory |
|------------|--------------|--------------------------|----------|-------------------|------------|
| 2622248001 | YGWA-47      | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2622248002 | YGWC-45      | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2622248003 | YGWC-44      | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2622248004 | FB-1-8-20-19 | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2622248005 | YGWC-46      | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2622248006 | EB-1-8-21-19 | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2622248007 | Dup-1        | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates-Pond 1

Pace Project No.: 2622248

**Sample: YGWA-47**      **Lab ID: 2622248001**      Collected: 08/20/19 10:30      Received: 08/21/19 16:50      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                  | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|--|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.884 ± 0.360 (0.298)</b><br>C:91% T:NA | pCi/L | 09/05/19 11:25 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>1.56 ± 0.588 (0.902)</b><br>C:79% T:73% | pCi/L | 09/12/19 10:29 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>2.44 ± 0.948 (1.20)</b>                 | pCi/L | 09/16/19 11:22 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates-Pond 1

Pace Project No.: 2622248

**Sample: YGWC-45**      **Lab ID: 2622248002**      Collected: 08/20/19 11:35      Received: 08/21/19 16:50      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                  | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|--|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.869 ± 0.372 (0.404)</b><br>C:93% T:NA | pCi/L | 09/05/19 08:30 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>1.36 ± 0.515 (0.785)</b><br>C:78% T:81% | pCi/L | 09/12/19 10:29 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>2.23 ± 0.887 (1.19)</b>                 | pCi/L | 09/16/19 11:22 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates-Pond 1

Pace Project No.: 2622248

**Sample: YGWC-44**      **Lab ID: 2622248003**      Collected: 08/20/19 13:45      Received: 08/21/19 16:50      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                   | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|---|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.727 ± 0.353 (0.413)</b><br>C:84% T:NA  | pCi/L | 09/05/19 08:30 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>0.984 ± 0.482 (0.852)</b><br>C:77% T:82% | pCi/L | 09/12/19 10:29 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>1.71 ± 0.835 (1.27)</b>                  | pCi/L | 09/16/19 11:22 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates-Pond 1

Pace Project No.: 2622248

**Sample: FB-1-8-20-19**      **Lab ID: 2622248004**      Collected: 08/20/19 13:30      Received: 08/21/19 16:50      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                          | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|--|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.436 ± 0.271 (0.382)</b><br><b>C:90% T:NA</b>  | pCi/L | 09/05/19 08:30 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>0.611 ± 0.435 (0.853)</b><br><b>C:77% T:81%</b> | pCi/L | 09/12/19 10:29 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>1.05 ± 0.706 (1.24)</b>                         | pCi/L | 09/16/19 11:22 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates-Pond 1

Pace Project No.: 2622248

**Sample: YGWC-46**      **Lab ID: 2622248005**      Collected: 08/21/19 09:45      Received: 08/21/19 16:50      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                   | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|---|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.719 ± 0.340 (0.388)</b><br>C:89% T:NA  | pCi/L | 09/05/19 08:30 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>0.590 ± 0.412 (0.801)</b><br>C:77% T:86% | pCi/L | 09/12/19 10:29 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>1.31 ± 0.752 (1.19)</b>                  | pCi/L | 09/16/19 11:22 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates-Pond 1

Pace Project No.: 2622248

**Sample: EB-1-8-21-19**      **Lab ID: 2622248006**      Collected: 08/21/19 10:00      Received: 08/21/19 16:50      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                   | Act ± Unc (MDC) Carr Trac                   | Units | Analyzed       | CAS No.    | Qual |
|--------------|--------------------------|---|-------|----------------|------------|------|
| Radium-226   | EPA 9315                 | <b>0.405 ± 0.280 (0.468)</b><br>C:98% T:NA  | pCi/L | 09/05/19 08:30 | 13982-63-3 |      |
| Radium-228   | EPA 9320                 | <b>0.339 ± 0.436 (0.932)</b><br>C:80% T:90% | pCi/L | 09/12/19 10:38 | 15262-20-1 |      |
| Total Radium | Total Radium Calculation | <b>0.744 ± 0.716 (1.40)</b>                 | pCi/L | 09/16/19 11:22 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates-Pond 1

Pace Project No.: 2622248

**Sample: Dup-1**      **Lab ID: 2622248007**      Collected: 08/21/19 00:00      Received: 08/21/19 16:50      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                         | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|---|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.567 ± 0.325 (0.473)</b><br><b>C:91% T:NA</b> | pCi/L | 09/05/19 08:30 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>1.01 ± 0.528 (0.974)</b><br><b>C:79% T:85%</b> | pCi/L | 09/12/19 10:38 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>1.58 ± 0.853 (1.45)</b>                        | pCi/L | 09/16/19 11:22 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL - RADIOCHEMISTRY

Project: Plant Yates-Pond 1

Pace Project No.: 2622248

QC Batch: 359489

Analysis Method: EPA 9315

QC Batch Method: EPA 9315

Analysis Description: 9315 Total Radium

Associated Lab Samples: 2622248001, 2622248002, 2622248003, 2622248004, 2622248005, 2622248006, 2622248007

METHOD BLANK: 1745578

Matrix: Water

Associated Lab Samples: 2622248001, 2622248002, 2622248003, 2622248004, 2622248005, 2622248006, 2622248007

| Parameter  | Act ± Unc (MDC) Carr Trac         | Units | Analyzed       | Qualifiers |
|------------|-----------------------------------|-------|----------------|------------|
| Radium-226 | 0.402 ± 0.246 (0.327) C:100% T:NA | pCi/L | 09/05/19 08:30 |            |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL - RADIOCHEMISTRY

Project: Plant Yates-Pond 1

Pace Project No.: 2622248

QC Batch: 358698

Analysis Method: EPA 9320

QC Batch Method: EPA 9320

Analysis Description: 9320 Radium 228

Associated Lab Samples: 2622248001, 2622248002, 2622248003, 2622248004, 2622248005, 2622248006, 2622248007

METHOD BLANK: 1741705

Matrix: Water

Associated Lab Samples: 2622248001, 2622248002, 2622248003, 2622248004, 2622248005, 2622248006, 2622248007

| Parameter  | Act ± Unc (MDC) Carr Trac         | Units | Analyzed       | Qualifiers |
|------------|-----------------------------------|-------|----------------|------------|
| Radium-228 | 0.944 ± 0.396 (0.631) C:81% T:90% | pCi/L | 09/12/19 10:29 |            |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## QUALIFIERS

Project: Plant Yates-Pond 1  
Pace Project No.: 2622248

---

### DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to dilution of the sample aliquot.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

PQL - Practical Quantitation Limit.

RL - Reporting Limit - The lowest concentration value that meets project requirements for quantitative data with known precision and bias for a specific analyte in a specific matrix.

S - Surrogate

1,2-Diphenylhydrazine decomposes to and cannot be separated from Azobenzene using Method 8270. The result for each analyte is a combined concentration.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

SG - Silica Gel - Clean-Up

U - Indicates the compound was analyzed for, but not detected.

N-Nitrosodiphenylamine decomposes and cannot be separated from Diphenylamine using Method 8270. The result reported for each analyte is a combined concentration.

Act - Activity

Unc - Uncertainty: SDWA = 1.96 sigma count uncertainty, all other matrices = Expanded Uncertainty (95% confidence interval).

Gamma Spec = Expanded Uncertainty (95.4% Confidence Interval)

(MDC) - Minimum Detectable Concentration

Trac - Tracer Recovery (%)

Carr - Carrier Recovery (%)

Pace Analytical is TNI accredited. Contact your Pace PM for the current list of accredited analytes.

TNI - The NELAC Institute.

### LABORATORIES

PASI-PA Pace Analytical Services - Greensburg

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

**QUALITY CONTROL DATA CROSS REFERENCE TABLE**

Project: Plant Yates-Pond 1  
Pace Project No.: 2622248

| Lab ID     | Sample ID    | QC Batch Method          | QC Batch | Analytical Method | Analytical Batch |
|------------|--------------|--------------------------|----------|-------------------|------------------|
| 2622248001 | YGWA-47      | EPA 9315                 | 359489   |                   |                  |
| 2622248002 | YGWC-45      | EPA 9315                 | 359489   |                   |                  |
| 2622248003 | YGWC-44      | EPA 9315                 | 359489   |                   |                  |
| 2622248004 | FB-1-8-20-19 | EPA 9315                 | 359489   |                   |                  |
| 2622248005 | YGWC-46      | EPA 9315                 | 359489   |                   |                  |
| 2622248006 | EB-1-8-21-19 | EPA 9315                 | 359489   |                   |                  |
| 2622248007 | Dup-1        | EPA 9315                 | 359489   |                   |                  |
| 2622248001 | YGWA-47      | EPA 9320                 | 358698   |                   |                  |
| 2622248002 | YGWC-45      | EPA 9320                 | 358698   |                   |                  |
| 2622248003 | YGWC-44      | EPA 9320                 | 358698   |                   |                  |
| 2622248004 | FB-1-8-20-19 | EPA 9320                 | 358698   |                   |                  |
| 2622248005 | YGWC-46      | EPA 9320                 | 358698   |                   |                  |
| 2622248006 | EB-1-8-21-19 | EPA 9320                 | 358698   |                   |                  |
| 2622248007 | Dup-1        | EPA 9320                 | 358698   |                   |                  |
| 2622248001 | YGWA-47      | Total Radium Calculation | 361426   |                   |                  |
| 2622248002 | YGWC-45      | Total Radium Calculation | 361426   |                   |                  |
| 2622248003 | YGWC-44      | Total Radium Calculation | 361426   |                   |                  |
| 2622248004 | FB-1-8-20-19 | Total Radium Calculation | 361426   |                   |                  |
| 2622248005 | YGWC-46      | Total Radium Calculation | 361426   |                   |                  |
| 2622248006 | EB-1-8-21-19 | Total Radium Calculation | 361426   |                   |                  |
| 2622248007 | Dup-1        | Total Radium Calculation | 361426   |                   |                  |

**REPORT OF LABORATORY ANALYSIS**

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.



**Sample Condition Upon Receipt**



Client Name: GIA Power

Project # \_\_\_\_\_

**WO# : 2622248**

Courier:  Fed Ex  UPS  USPS  Client  Commercial  Pace Other  
Tracking #: \_\_\_\_\_

PH: **BM** Due Date: **09/19/19**  
CLIENT: **GAPower-CCR**

Custody Seal on Cooler/Box Present:  yes  no Seals intact:  yes

Packing Material:  Bubble Wrap  Bubble Bags  None  Other

Thermometer Used 83 Type of Ice: Wet Blue None  Samples on ice, cooling process has begun

Cooler Temperature 2'0

Biological Tissue is Frozen: Yes No

Date and initials of person examining contents: 9/21/19 MR

Temp should be above freezing to 6°C

Comments:

|  |  |                             |
|--|--|-----------------------------|
| Chain of Custody Present:  | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 1.                          |
| Chain of Custody Filled Out:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 2.                          |
| Chain of Custody Relinquished:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 3.                          |
| Sampler Name & Signature on COC:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 4.                          |
| Samples Arrived within Hold Time:  | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 5.                          |
| Short Hold Time Analysis (<72hr):  | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> N/A | 6.                          |
| Rush Turn Around Time Requested:   | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> N/A | 7.                          |
| Sufficient Volume:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 8.                          |
| Correct Containers Used:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 9.                          |
| -Pace Containers Used:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A |                             |
| Containers Intact:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 10.                         |
| Filtered volume received for Dissolved tests   | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 11.                         |
| Sample Labels match COC:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 12.                         |
| -Includes date/time/ID/Analysis Matrix:  | <u>W</u>   |                             |
| All containers needing preservation have been checked.                                     | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 13.                         |
| All containers needing preservation are found to be in compliance with EPA recommendation. | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A |                             |
| exceptions: VOA, coliform, TOC, O&G, WI-DRO (water)  | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No                              | Initial when completed      |
|  |  | Lot # of added preservative |
| Samples checked for dechlorination:  | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 14.                         |
| Headspace in VOA Vials (>6mm):   | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 15.                         |
| Trip Blank Present:  | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 16.                         |
| Trip Blank Custody Seals Present   | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A |                             |
| Pace Trip Blank Lot # (if purchased):  |  |                             |

Client Notification/ Resolution:

Field Data Required? Y / N

Person Contacted: \_\_\_\_\_ Date/Time: \_\_\_\_\_

Comments/ Resolution: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Project Manager Review: \_\_\_\_\_

Date: \_\_\_\_\_

Note: Whenever there is a discrepancy affecting North Carolina compliance samples, a copy of this form will be sent to the North Carolina DEHNR Certification Office ( i.e out of hold, incorrect preservative, out of temp, incorrect containers)

**LEVEL 2A LABORATORY DATA VALIDATIONS**

**Plant Yates Ash Pond-1**

**Scan Event**

**August 2019**

## **Georgia Power Company – Plant Yates Ash Pond-1**

### **Quality Control Review of Analytical Data – August 2019**

This narrative presents results of the Quality Control (QC) data review performed on analytical data submitted by Pace Analytical Services, Atlanta and Pittsburgh for groundwater samples collected at Plant Yates AP-1 between August 20, 2019 and August 21, 2019. The chemical data were reviewed to identify quality issues which could affect the use of the data for decision-making purposes.

Information regarding the primary sample locations, analytical parameters, QC samples, sampling dates, and laboratory sample delivery group (SDG) designations is summarized in Table 1 of this Appendix. SDG 2622246 was revised by the laboratory to correct the reporting limits (RLs) to meet project requirements.

In accordance with groundwater monitoring and corrective action procedures discussed in Title 40 CFR, Subpart D – Standards for the Disposal of Coal Combustion Residuals in Landfills and Surface Impoundments, the samples were analyzed for detected monitoring constituents listed in 40 CFR, Part 257, Appendix III and assessment monitoring constituents listed in 40 CFR, Part 257, Appendix IV. Test methods included Inductively Coupled Plasma – Mass Spectrometry (USEPA Method 6020B), Mercury in Liquid Wastes (USEPA Method 7470A), Determination of Inorganic Anions (USEPA Method 300.0), Solids in Water (Standard Methods 2540C), Radium-226 (USEPA 9315), and Radium-228 (USEPA Method 9320).

Data were reviewed in accordance with the US EPA Region IV Data Validation Standard Operating Procedures for Contract Laboratory Program Inorganic Data by Inductively Coupled Plasma – Atomic Emission Spectroscopy and Inductively Coupled Plasma – Mass Spectroscopy (September 2011, Rev. 2.0)<sup>1</sup> and the National Functional Guidelines for Inorganic Superfund Methods Data Review (January 2017)<sup>2</sup>. The review included an assessment of the results for completeness, precision (laboratory duplicate recoveries and matrix spike/matrix spike duplicate recoveries), accuracy (laboratory control samples and matrix spike samples), and blank contamination (field, equipment, and laboratory blanks). Sample receipt conditions, holding times, and chains of custody (COCs) were reviewed. Where there was a discrepancy between the QC criteria in the guidelines and the QC criterion established in the analytical methodology, method-specific criteria or professional judgment were used.

## DATA QUALITY OBJECTIVES

**Laboratory Precision:** Laboratory goals for precision were met, with the exception of Radum-226 on YGWC-44 (2622248003) as described in the qualifications section below.

**Field Precision:** Field goals for precision were met.

**Accuracy:** Laboratory goals for accuracy were met.

**Detection Limits:** Project goals for detection limits were met.

**Completeness:** There were no rejected analytical results for this event, resulting in a completion of 100%.

**Holding Times:** Holding time requirements were met.

## QUALIFICATIONS

In general, chemical results for the samples collected at the site were qualified on the basis of low precision or low accuracy or on the basis of professional judgment. The following definitions provide brief explanations of the qualifiers which may have been assigned to data by the laboratory during the validation process:

**J:** The analyte was positively identified above the method detection limit; however, the associated numerical value is the approximate concentration of the analyte in the sample

**ND:** The analyte was not detected above the method detection limit

The data generated as part of this sampling event met the QC criteria established in the respective analytical methods and data validation guidelines except as specified below. The applied qualifications may not have been required for all samples collected at the site. A summary of sample qualifications can be found in Table 2 of this Appendix.

- Sample YGWC-44 (2622248003) was qualified as estimated (J) for Radium-226 as the laboratory relative percent difference (RPD) exceeded QC criteria (78.31% above limit of 25).
- Radium-226 data for YGWA-47 (2622248001) was qualified as non-detect (ND) due to the analyte being detected at a similar concentration in an associated blank sample. As shown in Table 2, the minimum detectable concentration (MDC) was raised to the sample result as part of the qualification process.

Atlantic Coast Consulting, Inc. reviewed the laboratory data from the Plant Yates Ash Pond-1 sampled between August 20, 2019 and August 21, 2019 in accordance with the analytical methods, the laboratory-specified QC criteria, and the guidelines. As described above, the results were acceptable for project use.

## **REFERENCES**

<sup>1</sup>USEPA, September 2011, Region 4, Science and Ecosystem Support Division, Quality Assurance Section, MTSB, Data Validation Standard Operating Procedures for Contract Laboratory Program Inorganic Data by Inductively Coupled Plasma – Atomic Emission Spectroscopy and Inductively Coupled Plasma – Mass Spectroscopy, Revision 2.0

<sup>2</sup>USEPA, January 2017, National Office of Superfund Remediation and Technology Innovation, National Functional Guidelines for Inorganic Superfund Methods Data Review, Revision 0.0

TABLE 1

Georgia Power Company – Plant Yates Ash Pond-1

Sample Summary Table – August 2019

| SDG   | Field Identification | Collection Date | Lab Identification | Matrix | QC Samples   | Analyses              |                |                |                              |
|-------|----------------------|-----------------|--------------------|--------|--------------|-----------------------|----------------|----------------|------------------------------|
|       |                      |                 |                    |        |              | Metals (6020B, 7470A) | Anions (300.0) | TDS (SM 2540C) | Radium-226/-228 (9315, 9320) |
| 22246 | YGWA-47              | 8/20/2019       | 2622246001         | GW     |              | X                     | X              | X              |                              |
| 22248 | YGWA-47              | 8/20/2019       | 2622248001         | GW     |              |                       |                |                | X                            |
| 22246 | YGWC-45              | 8/20/2019       | 2622246002         | GW     |              | X                     | X              | X              |                              |
| 22248 | YGWC-45              | 8/20/2019       | 2622248002         | GW     |              |                       |                |                | X                            |
| 22246 | YGWC-44              | 8/20/2019       | 2622246003         | GW     |              | X                     | X              | X              |                              |
| 22248 | YGWC-44              | 8/20/2019       | 2622248003         | GW     |              |                       |                |                | X                            |
| 22246 | FB-1-8-20-19         | 8/20/2019       | 2622246004         | WQ     | FB           | X                     | X              | X              |                              |
| 22248 | FB-1-8-20-19         | 8/20/2019       | 2622248004         | WQ     | FB           |                       |                |                | X                            |
| 22246 | YGWC-46              | 8/21/2019       | 2622246005         | GW     |              | X                     | X              | X              |                              |
| 22248 | YGWC-46              | 8/21/2019       | 2622248005         | GW     |              |                       |                |                | X                            |
| 22246 | EB-1-8-21-19         | 8/21/2019       | 2622246006         | WQ     | EB           | X                     | X              | X              |                              |
| 22248 | EB-1-8-21-19         | 8/21/2019       | 2622248006         | WQ     | EB           |                       |                |                | X                            |
| 22246 | DUP-1                | 8/21/2019       | 2622246007         | GW     | FD (YGWC-46) | X                     | X              | X              |                              |
| 22248 | DUP-1                | 8/21/2019       | 2622248007         | GW     | FD (YGWC-46) |                       |                |                | X                            |

Abbreviations:

- EB – Equipment Blank
- FB – Field Blank
- FD – Field Duplicate
- GW – Groundwater
- QC – Quality Control
- TDS – Total Dissolved Solids
- WQ – Water Quality Control

TABLE 2

Georgia Power Company – Plant Yates Ash Pond-1

Qualifier Summary Table – August 2019

| SDG   | Field Identification | Constituent | New RL | New MDL or MDC | Qualifier | Reason                      |
|-------|----------------------|-------------|--------|----------------|-----------|-----------------------------|
| 22248 | YGWA-47              | Radium-226  |        | 0.298          | ND        | Blank detection             |
| 22248 | YGWC-44              | Radium-226  |        |                | J         | RPD exceeds laboratory goal |

Abbreviations:

MDC – Minimum Detectable Concentration  
 MS/MSD – Matrix Spike / Matrix Spike Duplicate  
 MDL – Method Detection Limit  
 RL – Reporting Limit  
 RPD – Relative Percent Difference  
 SDG – Sample Delivery Group

Qualifiers:

J – Estimated Result  
 ND – Non-Detect Result

Product Name: Low-Flow System

Date: 2019-08-20 10:31:08

Project Information:

Operator Name J Berisford  
 Company Name Atlantic Coast Consulting  
 Project Name Phase II-Pond 1  
 Site Name Plant Yates  
 Latitude 0° 0' 0"  
 Longitude 0° 0' 0"  
 Sonde SN 501336  
 Turbidity Make/Model HACH 2100Q

Pump Information:

Pump Model/Type QED Bladder  
 Tubing Type poly  
 Tubing Diameter .375 in  
 Tubing Length 59 ft  
 Pump placement from TOC 54 ft

Well Information:

Well ID YGWA-47  
 Well diameter 2 in  
 Well Total Depth 59.50 ft  
 Screen Length 10 ft  
 Depth to Water 33.85 ft

Pumping Information:

Final Pumping Rate 150 mL/min  
 Total System Volume 1.7664 L  
 Calculated Sample Rate 300 sec  
 Stabilization Drawdown 4.2 in  
 Total Volume Pumped 5.25 L

Low-Flow Sampling Stabilization Summary

| Stabilization Time | Elapsed | Temp C  | pH      | SpCond $\mu$ S/cm | Turb NTU | DTW ft | RDO mg/L | ORP mV  |
|--------------------|---------|---------|---------|-------------------|----------|--------|----------|---------|
|                    |         | +/- 100 | +/- 0.1 | +/- 5%            | +/- 100  |        | +/- 10%  | +/- 100 |
| Last 5 10:10:07    | 900.02  | 20.72   | 5.61    | 227.58            | 2.01     | 34.20  | 3.94     | 53.98   |
| Last 5 10:15:07    | 1200.03 | 20.67   | 5.60    | 224.71            | 1.77     | 34.20  | 3.81     | 52.73   |
| Last 5 10:20:07    | 1500.02 | 20.74   | 5.60    | 223.04            | 1.66     | 34.20  | 3.72     | 52.25   |
| Last 5 10:25:07    | 1800.02 | 20.92   | 5.59    | 222.43            | 1.81     | 34.20  | 3.67     | 52.16   |
| Last 5 10:30:07    | 2100.02 | 21.35   | 5.58    | 223.74            | 1.55     | 34.20  | 3.66     | 51.94   |
| Variance 0         |         | 0.07    | -0.00   | -1.68             |          |        | -0.09    | -0.48   |
| Variance 1         |         | 0.18    | -0.01   | -0.61             |          |        | -0.05    | -0.09   |
| Variance 2         |         | 0.44    | -0.01   | 1.31              |          |        | -0.01    | -0.22   |

Notes

Sunny, Sample time-1030

Grab Samples

Product Name: Low-Flow System

Date: 2019-08-20 13:46:25

Project Information:

Operator Name J Berisford  
Company Name Atlantic Coast Consulting  
Project Name Phase II-Pond 1  
Site Name Plant Yates  
Latitude 0° 0' 0"  
Longitude 0° 0' 0"  
Sonde SN 501336  
Turbidity Make/Model HACH 2100Q

Pump Information:

Pump Model/Type QED Bladder  
Tubing Type poly  
Tubing Diameter .375 in  
Tubing Length 90 ft  
Pump placement from TOC 85 ft

Well Information:

Well ID YGWC-44  
Well diameter 2 in  
Well Total Depth 90 ft  
Screen Length 10 ft  
Depth to Water 49.6 ft

Pumping Information:

Final Pumping Rate 100 mL/min  
Total System Volume 2.439678 L  
Calculated Sample Rate 300 sec  
Stabilization Drawdown 14.4 in  
Total Volume Pumped 5 L

Low-Flow Sampling Stabilization Summary

| Stabilization Time | Elapsed  | Temp C  | pH      | SpCond $\mu$ S/cm | Turb NTU | DTW ft | RDO mg/L | ORP mV  |
|--------------------|----------|---------|---------|-------------------|----------|--------|----------|---------|
|                    |          | +/- 100 | +/- 0.1 | +/- 5%            | +/- 100  |        | +/- 10%  | +/- 100 |
| Last 5             | 13:25:15 | 1800.02 | 5.79    | 470.54            | 1.74     | 50.80  | 0.32     | -37.78  |
| Last 5             | 13:30:15 | 2100.02 | 5.79    | 474.37            | 2.39     | 50.80  | 0.28     | -36.04  |
| Last 5             | 13:35:15 | 2400.02 | 5.78    | 471.96            | 1.11     | 50.80  | 0.25     | -34.26  |
| Last 5             | 13:40:15 | 2700.02 | 5.78    | 470.71            | 1.28     | 50.80  | 0.24     | -32.12  |
| Last 5             | 13:45:15 | 3000.02 | 5.78    | 466.92            | 1.52     | 50.80  | 0.23     | -29.82  |
| Variance 0         |          | 0.87    | -0.00   | -2.40             |          |        | -0.03    | 1.78    |
| Variance 1         |          | 0.17    | -0.00   | -1.25             |          |        | -0.01    | 2.14    |
| Variance 2         |          | -0.50   | 0.00    | -3.79             |          |        | -0.01    | 2.30    |

Notes

Sunny, Sample time-1345, FB-1-8-20-19 here at 1330

Grab Samples

Product Name: Low-Flow System

Date: 2019-08-20 11:38:52

Project Information:

Operator Name J Berisford  
 Company Name Atlantic Coast Consulting  
 Project Name Phase II-Pond 1  
 Site Name Plant Yates  
 Latitude 0° 0' 0"  
 Longitude 0° 0' 0"  
 Sonde SN 501336  
 Turbidity Make/Model HACH 2100Q

Pump Information:

Pump Model/Type QED Bladder  
 Tubing Type poly  
 Tubing Diameter .375 in  
 Tubing Length 74 ft  
 Pump placement from TOC 69 ft

Well Information:

Well ID YGWC-45  
 Well diameter 2 in  
 Well Total Depth 74 ft  
 Screen Length 10 ft  
 Depth to Water 22.79 ft

Pumping Information:

Final Pumping Rate 150 mL/min  
 Total System Volume 2.09218 L  
 Calculated Sample Rate 300 sec  
 Stabilization Drawdown 8.5 in  
 Total Volume Pumped 5.25 L

Low-Flow Sampling Stabilization Summary

| Stabilization Time | Elapsed | Temp C  | pH      | SpCond $\mu$ S/cm | Turb NTU | DTW ft | RDO mg/L | ORP mV  |
|--------------------|---------|---------|---------|-------------------|----------|--------|----------|---------|
|                    |         | +/- 100 | +/- 0.1 | +/- 5%            | +/- 100  |        | +/- 10%  | +/- 100 |
| Last 5 11:15:04    | 900.02  | 25.14   | 6.40    | 582.64            | 2.22     | 23.50  | 0.68     | 2.55    |
| Last 5 11:20:04    | 1200.02 | 24.91   | 6.35    | 583.02            | 1.90     | 23.50  | 0.43     | 6.52    |
| Last 5 11:25:04    | 1500.02 | 25.45   | 6.39    | 584.25            | 2.00     | 23.50  | 0.34     | 8.36    |
| Last 5 11:30:04    | 1800.02 | 25.65   | 6.44    | 585.27            | 1.77     | 23.50  | 0.32     | 8.82    |
| Last 5 11:35:04    | 2100.02 | 25.70   | 6.48    | 585.12            | 1.57     | 23.50  | 0.28     | 7.74    |
| Variance 0         |         | 0.54    | 0.04    | 1.23              |          |        | -0.08    | 1.84    |
| Variance 1         |         | 0.20    | 0.05    | 1.02              |          |        | -0.02    | 0.47    |
| Variance 2         |         | 0.05    | 0.04    | -0.15             |          |        | -0.04    | -1.08   |

Notes

Sunny, Sample time- 1135

Grab Samples

Product Name: Low-Flow System

Date: 2019-08-21 09:45:54

**Project Information:**

Operator Name J Berisford  
Company Name Atlantic Coast Consulting  
Project Name Phase II-Pond 1  
Site Name Plant Yates  
Latitude 0° 0' 0"  
Longitude 0° 0' 0"  
Sonde SN 501336  
Turbidity Make/Model HACH 2100Q

**Pump Information:**

Pump Model/Type QED Bladder  
Tubing Type poly  
Tubing Diameter .375 in  
Tubing Length 83 ft  
Pump placement from TOC 78 ft

**Well Information:**

Well ID YGWC-46  
Well diameter 2 in  
Well Total Depth 83. ft  
Screen Length 10 ft  
Depth to Water 48.03 ft

**Pumping Information:**

Final Pumping Rate 180 mL/min  
Total System Volume 2.287648 L  
Calculated Sample Rate 300 sec  
Stabilization Drawdown 7.8 in  
Total Volume Pumped 6.3 L

**Low-Flow Sampling Stabilization Summary**

| Stabilization Time | Elapsed  | Temp C  | pH      | SpCond $\mu$ S/cm | Turb NTU | DTW ft | RDO mg/L | ORP mV  |
|--------------------|----------|---------|---------|-------------------|----------|--------|----------|---------|
|                    |          | +/- 100 | +/- 0.1 | +/- 5%            | +/- 100  |        | +/- 10%  | +/- 100 |
| Last 5             | 09:20:01 | 21.67   | 5.86    | 996.88            | 0.57     | 48.80  | 0.72     | 55.68   |
| Last 5             | 09:25:01 | 21.58   | 5.83    | 1002.81           | 0.77     | 48.90  | 0.59     | 58.49   |
| Last 5             | 09:30:01 | 21.85   | 5.82    | 1010.20           | 0.92     | 48.90  | 0.49     | 59.04   |
| Last 5             | 09:35:01 | 21.88   | 5.82    | 1018.80           | 0.57     | 48.90  | 0.33     | 59.61   |
| Last 5             | 09:45:03 | 22.30   | 5.82    | 1018.89           | 0.44     | 48.90  | 0.25     | 59.60   |
| Variance 0         |          | 0.27    | -0.00   | 7.39              |          |        | -0.10    | 0.55    |
| Variance 1         |          | 0.03    | -0.01   | 8.60              |          |        | -0.16    | 0.57    |
| Variance 2         |          | 0.42    | -0.00   | 0.09              |          |        | -0.07    | -0.01   |

**Notes**

Sunny, Sample time 0945, DUP-1 here

**Grab Samples**

December 11, 2019

Joju Abraham  
Georgia Power - Coal Combustion Residuals  
2480 Maner Road  
Atlanta, GA 30339

RE: Project: Plant Yates Pond 1  
Pace Project No.: 2624140

Dear Joju Abraham:

Enclosed are the analytical results for sample(s) received by the laboratory on October 09, 2019. The results relate only to the samples included in this report. Results reported herein conform to the most current, applicable TNI/NELAC standards and the laboratory's Quality Assurance Manual, where applicable, unless otherwise noted in the body of the report.

This revised report replaces the report issued on 10/16/2019. The report has been revised to include Appendix IV Metals data which were omitted in the original report. No other changes have been made to this report.

This revised report replaces the revised report issued on 10/25/2019. The report has been revised to correct sample IDs per consultant request. No other changes have been made to this report.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,



Kevin Herring for  
Betsy McDaniel  
betsy.mcdaniel@pacelabs.com  
(770)734-4200  
Project Manager

Enclosures



## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

December 11, 2019

Page 2

cc: Betsy McDaniel, Atlantic Coast Consulting  
Chris Parker, Atlantic Coast Consulting  
Evan Perry, Atlantic Coast Consulting  
Lauren Petty, Southern Company Services, Inc.  
Rebecca Thornton, Pace Analytical Atlanta



## **REPORT OF LABORATORY ANALYSIS**

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## CERTIFICATIONS

Project: Plant Yates Pond 1

Pace Project No.: 2624140

---

### **Pace Analytical Services Atlanta**

110 Technology Parkway Peachtree Corners, GA 30092

Florida DOH Certification #: E87315

Georgia DW Inorganics Certification #: 812

Georgia DW Microbiology Certification #: 812

North Carolina Certification #: 381

South Carolina Certification #: 98011001

Virginia Certification #: 460204

---

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## SAMPLE SUMMARY

Project: Plant Yates Pond 1  
Pace Project No.: 2624140

| Lab ID     | Sample ID    | Matrix | Date Collected | Date Received  |
|------------|--------------|--------|----------------|----------------|
| 2624140001 | YGWA-47      | Water  | 10/08/19 12:34 | 10/09/19 17:00 |
| 2624140002 | YGWC-44      | Water  | 10/08/19 14:07 | 10/09/19 17:00 |
| 2624140003 | YGWC-45      | Water  | 10/09/19 10:23 | 10/09/19 17:00 |
| 2624140004 | EB-1 10-9-19 | Water  | 10/09/19 10:40 | 10/09/19 17:00 |
| 2624140005 | FB-1 10-9-19 | Water  | 10/08/19 13:40 | 10/09/19 17:00 |
| 2624140006 | YGWC-46      | Water  | 10/09/19 12:22 | 10/09/19 17:00 |
| 2624140007 | DUP-1        | Water  | 10/09/19 00:00 | 10/09/19 17:00 |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### SAMPLE ANALYTE COUNT

Project: Plant Yates Pond 1

Pace Project No.: 2624140

| Lab ID     | Sample ID    | Method    | Analysts | Analytes Reported |
|------------|--------------|-----------|----------|-------------------|
| 2624140001 | YGWA-47      | EPA 6020B | CSW      | 9                 |
|            |              | SM 2540C  | ALW      | 1                 |
|            |              | EPA 300.0 | MWB      | 3                 |
| 2624140002 | YGWC-44      | EPA 6020B | CSW      | 9                 |
|            |              | SM 2540C  | ALW      | 1                 |
|            |              | EPA 300.0 | MWB      | 3                 |
| 2624140003 | YGWC-45      | EPA 6020B | CSW      | 9                 |
|            |              | SM 2540C  | ALW      | 1                 |
|            |              | EPA 300.0 | MWB      | 3                 |
| 2624140004 | EB-1 10-9-19 | EPA 6020B | CSW      | 9                 |
|            |              | SM 2540C  | ALW      | 1                 |
|            |              | EPA 300.0 | MWB      | 3                 |
| 2624140005 | FB-1 10-9-19 | EPA 6020B | CSW      | 9                 |
|            |              | SM 2540C  | ALW      | 1                 |
|            |              | EPA 300.0 | MWB      | 3                 |
| 2624140006 | YGWC-46      | EPA 6020B | CSW      | 9                 |
|            |              | SM 2540C  | ALW      | 1                 |
|            |              | EPA 300.0 | MWB      | 3                 |
| 2624140007 | DUP-1        | EPA 6020B | CSW      | 9                 |
|            |              | SM 2540C  | ALW      | 1                 |
|            |              | EPA 300.0 | MWB      | 3                 |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS

Project: Plant Yates Pond 1  
Pace Project No.: 2624140

| Sample: YGWA-47                     |                  | Lab ID: 2624140001   |        | Collected: 10/08/19 12:34 |    | Received: 10/09/19 17:00 |                | Matrix: Water |      |  |
|-------------------------------------|------------------|--|--------|---------------------------|----|--------------------------|----------------|---------------|------|--|
| Parameters                          | Results          | Units  | Report |                           |    | Prepared                 | Analyzed       | CAS No.       | Qual |  |
|                                     |                  |  | Limit  | MDL                       | DF |                          |                |               |      |  |
| <b>6020B MET ICPMS</b>              |                  | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |        |                           |    |                          |                |               |      |  |
| Arsenic                             | ND               | mg/L   | 0.0050 | 0.00035                   | 1  | 10/10/19 17:50           | 10/14/19 18:20 | 7440-38-2     |      |  |
| Barium                              | <b>0.025</b>     | mg/L   | 0.010  | 0.00049                   | 1  | 10/10/19 17:50           | 10/14/19 18:20 | 7440-39-3     |      |  |
| Boron                               | <b>0.012J</b>    | mg/L   | 0.040  | 0.0049                    | 1  | 10/10/19 17:50           | 10/14/19 18:20 | 7440-42-8     |      |  |
| Cadmium                             | ND               | mg/L   | 0.0025 | 0.00011                   | 1  | 10/10/19 17:50           | 10/14/19 18:20 | 7440-43-9     |      |  |
| Calcium                             | <b>9.7</b>       | mg/L   | 0.10   | 0.011                     | 1  | 10/10/19 17:50           | 10/14/19 18:20 | 7440-70-2     | M6   |  |
| Cobalt                              | <b>0.0014J</b>   | mg/L   | 0.0050 | 0.00030                   | 1  | 10/10/19 17:50           | 10/14/19 18:20 | 7440-48-4     |      |  |
| Lithium                             | <b>0.0036J</b>   | mg/L   | 0.030  | 0.00078                   | 1  | 10/10/19 17:50           | 10/14/19 18:20 | 7439-93-2     |      |  |
| Molybdenum                          | ND               | mg/L   | 0.010  | 0.00095                   | 1  | 10/10/19 17:50           | 10/14/19 18:20 | 7439-98-7     |      |  |
| Thallium                            | <b>0.000084J</b> | mg/L   | 0.0010 | 0.000052                  | 1  | 10/10/19 17:50           | 10/14/19 18:20 | 7440-28-0     |      |  |
| <b>2540C Total Dissolved Solids</b> |                  | Analytical Method: SM 2540C                                |        |                           |    |                          |                |               |      |  |
| Total Dissolved Solids              | <b>172</b>       | mg/L   | 10.0   | 10.0                      | 1  |                          | 10/11/19 11:28 |               |      |  |
| <b>300.0 IC Anions 28 Days</b>      |                  | Analytical Method: EPA 300.0                               |        |                           |    |                          |                |               |      |  |
| Chloride                            | <b>4.4</b>       | mg/L   | 1.0    | 0.024                     | 1  |                          | 10/12/19 08:27 | 16887-00-6    | B    |  |
| Fluoride                            | <b>0.034J</b>    | mg/L   | 0.30   | 0.029                     | 1  |                          | 10/12/19 08:27 | 16984-48-8    |      |  |
| Sulfate                             | <b>52.3</b>      | mg/L   | 10.0   | 0.17                      | 10 |                          | 10/14/19 19:00 | 14808-79-8    |      |  |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## ANALYTICAL RESULTS

Project: Plant Yates Pond 1

Pace Project No.: 2624140

| Sample: YGWC-44                     |                | Lab ID: 2624140002   |        | Collected: 10/08/19 14:07 |    | Received: 10/09/19 17:00 |                | Matrix: Water |      |  |
|-------------------------------------|----------------|--|--------|---------------------------|----|--------------------------|----------------|---------------|------|--|
| Parameters                          | Results        | Units  | Report |                           |    | Prepared                 | Analyzed       | CAS No.       | Qual |  |
|                                     |                |  | Limit  | MDL                       | DF |                          |                |               |      |  |
| <b>6020B MET ICPMS</b>              |                | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |        |                           |    |                          |                |               |      |  |
| Arsenic                             | ND             | mg/L   | 0.0050 | 0.00035                   | 1  | 10/10/19 17:50           | 10/14/19 19:12 | 7440-38-2     |      |  |
| Barium                              | <b>0.098</b>   | mg/L   | 0.010  | 0.00049                   | 1  | 10/10/19 17:50           | 10/14/19 19:12 | 7440-39-3     |      |  |
| Boron                               | <b>0.58</b>    | mg/L   | 0.040  | 0.0049                    | 1  | 10/10/19 17:50           | 10/14/19 19:12 | 7440-42-8     |      |  |
| Cadmium                             | ND             | mg/L   | 0.0025 | 0.00011                   | 1  | 10/10/19 17:50           | 10/14/19 19:12 | 7440-43-9     |      |  |
| Calcium                             | <b>28.1</b>    | mg/L   | 5.0    | 0.55                      | 50 | 10/10/19 17:50           | 10/14/19 19:17 | 7440-70-2     |      |  |
| Cobalt                              | <b>0.0017J</b> | mg/L   | 0.0050 | 0.00030                   | 1  | 10/10/19 17:50           | 10/14/19 19:12 | 7440-48-4     |      |  |
| Lithium                             | <b>0.012J</b>  | mg/L   | 0.030  | 0.00078                   | 1  | 10/10/19 17:50           | 10/14/19 19:12 | 7439-93-2     |      |  |
| Molybdenum                          | ND             | mg/L   | 0.010  | 0.00095                   | 1  | 10/10/19 17:50           | 10/14/19 19:12 | 7439-98-7     |      |  |
| Thallium                            | ND             | mg/L   | 0.0010 | 0.000052                  | 1  | 10/10/19 17:50           | 10/14/19 19:12 | 7440-28-0     |      |  |
| <b>2540C Total Dissolved Solids</b> |                | Analytical Method: SM 2540C                                |        |                           |    |                          |                |               |      |  |
| Total Dissolved Solids              | <b>324</b>     | mg/L   | 10.0   | 10.0                      | 1  |                          | 10/11/19 11:28 |               |      |  |
| <b>300.0 IC Anions 28 Days</b>      |                | Analytical Method: EPA 300.0                               |        |                           |    |                          |                |               |      |  |
| Chloride                            | <b>14.8</b>    | mg/L   | 1.0    | 0.024                     | 1  |                          | 10/12/19 08:49 | 16887-00-6    |      |  |
| Fluoride                            | ND             | mg/L   | 0.30   | 0.029                     | 1  |                          | 10/12/19 08:49 | 16984-48-8    |      |  |
| Sulfate                             | <b>142</b>     | mg/L   | 10.0   | 0.17                      | 10 |                          | 10/15/19 02:39 | 14808-79-8    |      |  |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## ANALYTICAL RESULTS

Project: Plant Yates Pond 1  
Pace Project No.: 2624140

| <b>Sample: YGWC-45</b>              |                 | <b>Lab ID: 2624140003</b>                                  |        | Collected: 10/09/19 10:23 | Received: 10/09/19 17:00 | Matrix: Water  |                |            |      |
|-------------------------------------|-----------------|--|--------|---------------------------|--------------------------|----------------|----------------|------------|------|
| Parameters                          | Results         | Units  | Report |                           |                          | Prepared       | Analyzed       | CAS No.    | Qual |
|                                     |                 |  | Limit  | MDL                       | DF                       |                |                |            |      |
| <b>6020B MET ICPMS</b>              |                 | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |        |                           |                          |                |                |            |      |
| Arsenic                             | ND              | mg/L   | 0.0050 | 0.00035                   | 1                        | 10/10/19 17:50 | 10/14/19 19:23 | 7440-38-2  |      |
| Barium                              | <b>0.058</b>    | mg/L   | 0.010  | 0.00049                   | 1                        | 10/10/19 17:50 | 10/14/19 19:23 | 7440-39-3  |      |
| Boron                               | <b>0.35</b>     | mg/L   | 0.040  | 0.0049                    | 1                        | 10/10/19 17:50 | 10/14/19 19:23 | 7440-42-8  |      |
| Cadmium                             | ND              | mg/L   | 0.0025 | 0.00011                   | 1                        | 10/10/19 17:50 | 10/14/19 19:23 | 7440-43-9  |      |
| Calcium                             | <b>47.9</b>     | mg/L   | 5.0    | 0.55                      | 50                       | 10/10/19 17:50 | 10/14/19 19:29 | 7440-70-2  |      |
| Cobalt                              | <b>0.00070J</b> | mg/L   | 0.0050 | 0.00030                   | 1                        | 10/10/19 17:50 | 10/14/19 19:23 | 7440-48-4  |      |
| Lithium                             | <b>0.012J</b>   | mg/L   | 0.030  | 0.00078                   | 1                        | 10/10/19 17:50 | 10/14/19 19:23 | 7439-93-2  |      |
| Molybdenum                          | <b>0.0012J</b>  | mg/L   | 0.010  | 0.00095                   | 1                        | 10/10/19 17:50 | 10/14/19 19:23 | 7439-98-7  |      |
| Thallium                            | ND              | mg/L   | 0.0010 | 0.000052                  | 1                        | 10/10/19 17:50 | 10/14/19 19:23 | 7440-28-0  |      |
| <b>2540C Total Dissolved Solids</b> |                 | Analytical Method: SM 2540C                                |        |                           |                          |                |                |            |      |
| Total Dissolved Solids              | <b>432</b>      | mg/L   | 10.0   | 10.0                      | 1                        |                | 10/14/19 11:51 |            |      |
| <b>300.0 IC Anions 28 Days</b>      |                 | Analytical Method: EPA 300.0                               |        |                           |                          |                |                |            |      |
| Chloride                            | <b>5.1</b>      | mg/L   | 1.0    | 0.024                     | 1                        |                | 10/12/19 10:18 | 16887-00-6 |      |
| Fluoride                            | ND              | mg/L   | 0.30   | 0.029                     | 1                        |                | 10/12/19 10:18 | 16984-48-8 |      |
| Sulfate                             | <b>183</b>      | mg/L   | 10.0   | 0.17                      | 10                       |                | 10/15/19 02:59 | 14808-79-8 |      |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## ANALYTICAL RESULTS

Project: Plant Yates Pond 1  
Pace Project No.: 2624140

| Sample: <b>EB-1 10-9-19</b>         |               | Lab ID: <b>2624140004</b>                                  |        | Collected: 10/09/19 10:40 |    | Received: 10/09/19 17:00 |                | Matrix: Water |      |  |
|-------------------------------------|---------------|--|--------|---------------------------|----|--------------------------|----------------|---------------|------|--|
| Parameters                          | Results       | Units  | Report |                           |    | Prepared                 | Analyzed       | CAS No.       | Qual |  |
|                                     |               |  | Limit  | MDL                       | DF |                          |                |               |      |  |
| <b>6020B MET ICPMS</b>              |               | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |        |                           |    |                          |                |               |      |  |
| Arsenic                             | ND            | mg/L   | 0.0050 | 0.00035                   | 1  | 10/10/19 17:50           | 10/14/19 19:35 | 7440-38-2     |      |  |
| Barium                              | ND            | mg/L   | 0.010  | 0.00049                   | 1  | 10/10/19 17:50           | 10/14/19 19:35 | 7440-39-3     |      |  |
| Boron                               | ND            | mg/L   | 0.040  | 0.0049                    | 1  | 10/10/19 17:50           | 10/14/19 19:35 | 7440-42-8     |      |  |
| Cadmium                             | ND            | mg/L   | 0.0025 | 0.00011                   | 1  | 10/10/19 17:50           | 10/14/19 19:35 | 7440-43-9     |      |  |
| Calcium                             | <b>0.13</b>   | mg/L   | 0.10   | 0.011                     | 1  | 10/10/19 17:50           | 10/14/19 19:35 | 7440-70-2     |      |  |
| Cobalt                              | ND            | mg/L   | 0.0050 | 0.00030                   | 1  | 10/10/19 17:50           | 10/14/19 19:35 | 7440-48-4     |      |  |
| Lithium                             | ND            | mg/L   | 0.030  | 0.00078                   | 1  | 10/10/19 17:50           | 10/14/19 19:35 | 7439-93-2     |      |  |
| Molybdenum                          | ND            | mg/L   | 0.010  | 0.00095                   | 1  | 10/10/19 17:50           | 10/14/19 19:35 | 7439-98-7     |      |  |
| Thallium                            | ND            | mg/L   | 0.0010 | 0.000052                  | 1  | 10/10/19 17:50           | 10/14/19 19:35 | 7440-28-0     |      |  |
| <b>2540C Total Dissolved Solids</b> |               | Analytical Method: SM 2540C                                |        |                           |    |                          |                |               |      |  |
| Total Dissolved Solids              | <b>18.0</b>   | mg/L   | 10.0   | 10.0                      | 1  |                          | 10/14/19 11:52 |               | D6   |  |
| <b>300.0 IC Anions 28 Days</b>      |               | Analytical Method: EPA 300.0                               |        |                           |    |                          |                |               |      |  |
| Chloride                            | <b>0.030J</b> | mg/L   | 1.0    | 0.024                     | 1  |                          | 10/12/19 10:40 | 16887-00-6    | B    |  |
| Fluoride                            | ND            | mg/L   | 0.30   | 0.029                     | 1  |                          | 10/12/19 10:40 | 16984-48-8    |      |  |
| Sulfate                             | <b>0.10J</b>  | mg/L   | 1.0    | 0.017                     | 1  |                          | 10/12/19 10:40 | 14808-79-8    |      |  |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## ANALYTICAL RESULTS

Project: Plant Yates Pond 1  
Pace Project No.: 2624140

| Sample: <b>FB-1 10-9-19</b>         |               | Lab ID: <b>2624140005</b>                                  |        | Collected: 10/08/19 13:40 | Received: 10/09/19 17:00 | Matrix: Water  |                |            |      |  |
|-------------------------------------|---------------|--|--------|---------------------------|--------------------------|----------------|----------------|------------|------|--|
| Parameters                          | Results       | Units  | Report |                           |                          | Prepared       | Analyzed       | CAS No.    | Qual |  |
|                                     |               |  | Limit  | MDL                       | DF                       |                |                |            |      |  |
| <b>6020B MET ICPMS</b>              |               | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |        |                           |                          |                |                |            |      |  |
| Arsenic                             | ND            | mg/L   | 0.0050 | 0.00035                   | 1                        | 10/10/19 17:50 | 10/14/19 19:40 | 7440-38-2  |      |  |
| Barium                              | ND            | mg/L   | 0.010  | 0.00049                   | 1                        | 10/10/19 17:50 | 10/14/19 19:40 | 7440-39-3  |      |  |
| Boron                               | ND            | mg/L   | 0.040  | 0.0049                    | 1                        | 10/10/19 17:50 | 10/14/19 19:40 | 7440-42-8  |      |  |
| Cadmium                             | ND            | mg/L   | 0.0025 | 0.00011                   | 1                        | 10/10/19 17:50 | 10/14/19 19:40 | 7440-43-9  |      |  |
| Calcium                             | ND            | mg/L   | 0.10   | 0.011                     | 1                        | 10/10/19 17:50 | 10/14/19 19:40 | 7440-70-2  |      |  |
| Cobalt                              | ND            | mg/L   | 0.0050 | 0.00030                   | 1                        | 10/10/19 17:50 | 10/14/19 19:40 | 7440-48-4  |      |  |
| Lithium                             | ND            | mg/L   | 0.030  | 0.00078                   | 1                        | 10/10/19 17:50 | 10/14/19 19:40 | 7439-93-2  |      |  |
| Molybdenum                          | ND            | mg/L   | 0.010  | 0.00095                   | 1                        | 10/10/19 17:50 | 10/14/19 19:40 | 7439-98-7  |      |  |
| Thallium                            | ND            | mg/L   | 0.0010 | 0.000052                  | 1                        | 10/10/19 17:50 | 10/14/19 19:40 | 7440-28-0  |      |  |
| <b>2540C Total Dissolved Solids</b> |               | Analytical Method: SM 2540C                                |        |                           |                          |                |                |            |      |  |
| Total Dissolved Solids              | ND            | mg/L   | 10.0   | 10.0                      | 1                        |                | 10/11/19 11:28 |            |      |  |
| <b>300.0 IC Anions 28 Days</b>      |               | Analytical Method: EPA 300.0                               |        |                           |                          |                |                |            |      |  |
| Chloride                            | ND            | mg/L   | 1.0    | 0.024                     | 1                        |                | 10/12/19 11:25 | 16887-00-6 |      |  |
| Fluoride                            | ND            | mg/L   | 0.30   | 0.029                     | 1                        |                | 10/12/19 11:25 | 16984-48-8 |      |  |
| Sulfate                             | <b>0.020J</b> | mg/L   | 1.0    | 0.017                     | 1                        |                | 10/12/19 11:25 | 14808-79-8 |      |  |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## ANALYTICAL RESULTS

Project: Plant Yates Pond 1  
Pace Project No.: 2624140

| Sample: YGWC-46                     |                | Lab ID: 2624140006   |        | Collected: 10/09/19 12:22 |    | Received: 10/09/19 17:00 |                | Matrix: Water |      |  |
|-------------------------------------|----------------|--|--------|---------------------------|----|--------------------------|----------------|---------------|------|--|
| Parameters                          | Results        | Units  | Report |                           |    | Prepared                 | Analyzed       | CAS No.       | Qual |  |
|                                     |                |  | Limit  | MDL                       | DF |                          |                |               |      |  |
| <b>6020B MET ICPMS</b>              |                | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |        |                           |    |                          |                |               |      |  |
| Arsenic                             | ND             | mg/L   | 0.0050 | 0.00035                   | 1  | 10/10/19 17:50           | 10/14/19 19:46 | 7440-38-2     |      |  |
| Barium                              | <b>0.024</b>   | mg/L   | 0.010  | 0.00049                   | 1  | 10/10/19 17:50           | 10/14/19 19:46 | 7440-39-3     |      |  |
| Boron                               | <b>1.1</b>     | mg/L   | 0.040  | 0.0049                    | 1  | 10/10/19 17:50           | 10/14/19 19:46 | 7440-42-8     |      |  |
| Cadmium                             | ND             | mg/L   | 0.0025 | 0.00011                   | 1  | 10/10/19 17:50           | 10/14/19 19:46 | 7440-43-9     |      |  |
| Calcium                             | <b>64.2</b>    | mg/L   | 5.0    | 0.55                      | 50 | 10/10/19 17:50           | 10/14/19 19:52 | 7440-70-2     |      |  |
| Cobalt                              | <b>0.024</b>   | mg/L   | 0.0050 | 0.00030                   | 1  | 10/10/19 17:50           | 10/14/19 19:46 | 7440-48-4     |      |  |
| Lithium                             | <b>0.0078J</b> | mg/L   | 0.030  | 0.00078                   | 1  | 10/10/19 17:50           | 10/14/19 19:46 | 7439-93-2     |      |  |
| Molybdenum                          | <b>0.0013J</b> | mg/L   | 0.010  | 0.00095                   | 1  | 10/10/19 17:50           | 10/14/19 19:46 | 7439-98-7     |      |  |
| Thallium                            | ND             | mg/L   | 0.0010 | 0.000052                  | 1  | 10/10/19 17:50           | 10/14/19 19:46 | 7440-28-0     |      |  |
| <b>2540C Total Dissolved Solids</b> |                | Analytical Method: SM 2540C                                |        |                           |    |                          |                |               |      |  |
| Total Dissolved Solids              | <b>809</b>     | mg/L   | 10.0   | 10.0                      | 1  |                          | 10/14/19 11:52 |               |      |  |
| <b>300.0 IC Anions 28 Days</b>      |                | Analytical Method: EPA 300.0                               |        |                           |    |                          |                |               |      |  |
| Chloride                            | <b>25.0</b>    | mg/L   | 1.0    | 0.024                     | 1  |                          | 10/15/19 04:02 | 16887-00-6    |      |  |
| Fluoride                            | <b>0.12J</b>   | mg/L   | 0.30   | 0.029                     | 1  |                          | 10/15/19 04:02 | 16984-48-8    |      |  |
| Sulfate                             | ND             | mg/L   | 1.0    | 0.017                     | 1  |                          | 10/15/19 04:02 | 14808-79-8    |      |  |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## ANALYTICAL RESULTS

Project: Plant Yates Pond 1  
Pace Project No.: 2624140

| Sample: DUP-1                       |                 | Lab ID: 2624140007   |        | Collected: 10/09/19 00:00 |    | Received: 10/09/19 17:00 |                | Matrix: Water |      |  |
|-------------------------------------|-----------------|--|--------|---------------------------|----|--------------------------|----------------|---------------|------|--|
| Parameters                          | Results         | Units  | Report |                           |    | Prepared                 | Analyzed       | CAS No.       | Qual |  |
|                                     |                 |  | Limit  | MDL                       | DF |                          |                |               |      |  |
| <b>6020B MET ICPMS</b>              |                 | Analytical Method: EPA 6020B Preparation Method: EPA 3005A |        |                           |    |                          |                |               |      |  |
| Arsenic                             | <b>0.00041J</b> | mg/L   | 0.0050 | 0.00035                   | 1  | 10/10/19 17:50           | 10/14/19 19:58 | 7440-38-2     |      |  |
| Barium                              | <b>0.024</b>    | mg/L   | 0.010  | 0.00049                   | 1  | 10/10/19 17:50           | 10/14/19 19:58 | 7440-39-3     |      |  |
| Boron                               | <b>1.1</b>      | mg/L   | 0.040  | 0.0049                    | 1  | 10/10/19 17:50           | 10/14/19 19:58 | 7440-42-8     |      |  |
| Cadmium                             | ND              | mg/L   | 0.0025 | 0.00011                   | 1  | 10/10/19 17:50           | 10/14/19 19:58 | 7440-43-9     |      |  |
| Calcium                             | <b>62.2</b>     | mg/L   | 5.0    | 0.55                      | 50 | 10/10/19 17:50           | 10/14/19 20:03 | 7440-70-2     |      |  |
| Cobalt                              | <b>0.024</b>    | mg/L   | 0.0050 | 0.00030                   | 1  | 10/10/19 17:50           | 10/14/19 19:58 | 7440-48-4     |      |  |
| Lithium                             | <b>0.0076J</b>  | mg/L   | 0.030  | 0.00078                   | 1  | 10/10/19 17:50           | 10/14/19 19:58 | 7439-93-2     |      |  |
| Molybdenum                          | <b>0.0013J</b>  | mg/L   | 0.010  | 0.00095                   | 1  | 10/10/19 17:50           | 10/14/19 19:58 | 7439-98-7     |      |  |
| Thallium                            | ND              | mg/L   | 0.0010 | 0.000052                  | 1  | 10/10/19 17:50           | 10/14/19 19:58 | 7440-28-0     |      |  |
| <b>2540C Total Dissolved Solids</b> |                 | Analytical Method: SM 2540C                                |        |                           |    |                          |                |               |      |  |
| Total Dissolved Solids              | <b>798</b>      | mg/L   | 10.0   | 10.0                      | 1  |                          | 10/14/19 11:52 |               |      |  |
| <b>300.0 IC Anions 28 Days</b>      |                 | Analytical Method: EPA 300.0                               |        |                           |    |                          |                |               |      |  |
| Chloride                            | <b>24.9</b>     | mg/L   | 1.0    | 0.024                     | 1  |                          | 10/15/19 04:22 | 16887-00-6    |      |  |
| Fluoride                            | <b>0.11J</b>    | mg/L   | 0.30   | 0.029                     | 1  |                          | 10/15/19 04:22 | 16984-48-8    |      |  |
| Sulfate                             | ND              | mg/L   | 1.0    | 0.017                     | 1  |                          | 10/15/19 04:22 | 14808-79-8    |      |  |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL DATA

Project: Plant Yates Pond 1  
Pace Project No.: 2624140

QC Batch: 36815 Analysis Method: EPA 6020B  
QC Batch Method: EPA 3005A Analysis Description: 6020B MET  
Associated Lab Samples: 2624140001, 2624140002, 2624140003, 2624140004, 2624140005, 2624140006, 2624140007

METHOD BLANK: 166313 Matrix: Water  
Associated Lab Samples: 2624140001, 2624140002, 2624140003, 2624140004, 2624140005, 2624140006, 2624140007

| Parameter  | Units | Blank Result | Reporting Limit | MDL      | Analyzed       | Qualifiers |
|------------|-------|--------------|-----------------|----------|----------------|------------|
| Arsenic    | mg/L  | ND           | 0.0050          | 0.00035  | 10/14/19 18:02 |            |
| Barium     | mg/L  | ND           | 0.010           | 0.00049  | 10/14/19 18:02 |            |
| Boron      | mg/L  | ND           | 0.040           | 0.0049   | 10/14/19 18:02 |            |
| Cadmium    | mg/L  | ND           | 0.0025          | 0.00011  | 10/14/19 18:02 |            |
| Calcium    | mg/L  | ND           | 0.10            | 0.011    | 10/14/19 18:02 |            |
| Cobalt     | mg/L  | ND           | 0.0050          | 0.00030  | 10/14/19 18:02 |            |
| Molybdenum | mg/L  | ND           | 0.010           | 0.00095  | 10/14/19 18:02 |            |
| Thallium   | mg/L  | ND           | 0.0010          | 0.000052 | 10/14/19 18:02 |            |

LABORATORY CONTROL SAMPLE: 166314

| Parameter  | Units | Spike Conc. | LCS Result | LCS % Rec | % Rec Limits | Qualifiers |
|------------|-------|-------------|------------|-----------|--------------|------------|
| Arsenic    | mg/L  | 0.1         | 0.097      | 97        | 80-120       |            |
| Barium     | mg/L  | 0.1         | 0.098      | 98        | 80-120       |            |
| Boron      | mg/L  | 1           | 0.95       | 95        | 80-120       |            |
| Cadmium    | mg/L  | 0.1         | 0.10       | 100       | 80-120       |            |
| Calcium    | mg/L  | 1           | 0.97       | 97        | 80-120       |            |
| Cobalt     | mg/L  | 0.1         | 0.098      | 98        | 80-120       |            |
| Molybdenum | mg/L  | 0.1         | 0.10       | 101       | 80-120       |            |
| Thallium   | mg/L  | 0.1         | 0.10       | 100       | 80-120       |            |

MATRIX SPIKE & MATRIX SPIKE DUPLICATE: 166315 166316

| Parameter | Units | MS                |             | MSD         |           | MS % Rec | MSD % Rec | % Rec Limits | RPD    | Max RPD | Qual  |
|-----------|-------|-------------------|-------------|-------------|-----------|----------|-----------|--------------|--------|---------|-------|
|           |       | 2624140001 Result | Spike Conc. | Spike Conc. | MS Result |          |           |              |        |         |       |
| Boron     | mg/L  | 0.012J            | 1           | 1           | 0.92      | 0.93     | 91        | 92           | 75-125 | 1       | 20    |
| Calcium   | mg/L  | 9.7               | 1           | 1           | 9.8       | 9.3      | 11        | -46          | 75-125 | 6       | 20 M6 |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.





### QUALITY CONTROL DATA

Project: Plant Yates Pond 1  
Pace Project No.: 2624140

QC Batch: 36855 Analysis Method: EPA 300.0  
QC Batch Method: EPA 300.0 Analysis Description: 300.0 IC Anions  
Associated Lab Samples: 2624140001, 2624140002, 2624140003, 2624140004, 2624140005, 2624140006, 2624140007

METHOD BLANK: 166564 Matrix: Water  
Associated Lab Samples: 2624140001, 2624140002, 2624140003, 2624140004, 2624140005, 2624140006, 2624140007

| Parameter | Units | Blank Result | Reporting Limit | MDL   | Analyzed       | Qualifiers |
|-----------|-------|--------------|-----------------|-------|----------------|------------|
| Chloride  | mg/L  | 0.44J        | 1.0             | 0.024 | 10/12/19 04:46 |            |
| Fluoride  | mg/L  | ND           | 0.30            | 0.029 | 10/12/19 04:46 |            |
| Sulfate   | mg/L  | ND           | 1.0             | 0.017 | 10/12/19 04:46 |            |

LABORATORY CONTROL SAMPLE: 166565

| Parameter | Units | Spike Conc. | LCS Result | LCS % Rec | % Rec Limits | Qualifiers |
|-----------|-------|-------------|------------|-----------|--------------|------------|
| Chloride  | mg/L  | 10          | 10.1       | 101       | 90-110       |            |
| Fluoride  | mg/L  | 10          | 10.2       | 102       | 90-110       |            |
| Sulfate   | mg/L  | 10          | 10.2       | 102       | 90-110       |            |

MATRIX SPIKE & MATRIX SPIKE DUPLICATE: 166566 166567

| Parameter | Units | 2624117001 Result | MS Spike Conc. | MSD Spike Conc. | MS Result | MSD Result | MS % Rec | MSD % Rec | % Rec Limits | RPD | Max RPD | Qual |
|-----------|-------|-------------------|----------------|-----------------|-----------|------------|----------|-----------|--------------|-----|---------|------|
| Fluoride  | mg/L  | 35.5              | 10             | 10              | 39.4      | 39.9       | 38       | 44        | 90-110       | 1   | 15      | M1   |

MATRIX SPIKE SAMPLE: 166568

| Parameter | Units | 2624140004 Result | Spike Conc. | MS Result | MS % Rec | % Rec Limits | Qualifiers |
|-----------|-------|-------------------|-------------|-----------|----------|--------------|------------|
| Chloride  | mg/L  | 0.030J            | 10          | 10.0      | 100      | 90-110       |            |
| Fluoride  | mg/L  | ND                | 10          | 10.2      | 102      | 90-110       |            |
| Sulfate   | mg/L  | 0.10J             | 10          | 10.1      | 100      | 90-110       |            |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## QUALIFIERS

Project: Plant Yates Pond 1

Pace Project No.: 2624140

---

### DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to dilution of the sample aliquot.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

PQL - Practical Quantitation Limit.

RL - Reporting Limit - The lowest concentration value that meets project requirements for quantitative data with known precision and bias for a specific analyte in a specific matrix.

S - Surrogate

1,2-Diphenylhydrazine decomposes to and cannot be separated from Azobenzene using Method 8270. The result for each analyte is a combined concentration.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

SG - Silica Gel - Clean-Up

U - Indicates the compound was analyzed for, but not detected.

N-Nitrosodiphenylamine decomposes and cannot be separated from Diphenylamine using Method 8270. The result reported for each analyte is a combined concentration.

Pace Analytical is TNI accredited. Contact your Pace PM for the current list of accredited analytes.

TNI - The NELAC Institute.

### ANALYTE QUALIFIERS

B Analyte was detected in the associated method blank.

D6 The precision between the sample and sample duplicate exceeded laboratory control limits.

M1 Matrix spike recovery exceeded QC limits. Batch accepted based on laboratory control sample (LCS) recovery.

M6 Matrix spike and Matrix spike duplicate recovery not evaluated against control limits due to sample dilution.

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL DATA CROSS REFERENCE TABLE

Project: Plant Yates Pond 1  
Pace Project No.: 2624140

| Lab ID     | Sample ID    | QC Batch Method | QC Batch | Analytical Method | Analytical Batch |
|------------|--------------|-----------------|----------|-------------------|------------------|
| 2624140001 | YGWA-47      | EPA 3005A       | 36815    | EPA 6020B         | 36833            |
| 2624140002 | YGWC-44      | EPA 3005A       | 36815    | EPA 6020B         | 36833            |
| 2624140003 | YGWC-45      | EPA 3005A       | 36815    | EPA 6020B         | 36833            |
| 2624140004 | EB-1 10-9-19 | EPA 3005A       | 36815    | EPA 6020B         | 36833            |
| 2624140005 | FB-1 10-9-19 | EPA 3005A       | 36815    | EPA 6020B         | 36833            |
| 2624140006 | YGWC-46      | EPA 3005A       | 36815    | EPA 6020B         | 36833            |
| 2624140007 | DUP-1        | EPA 3005A       | 36815    | EPA 6020B         | 36833            |
| 2624140001 | YGWA-47      | SM 2540C        | 36858    |                   |                  |
| 2624140002 | YGWC-44      | SM 2540C        | 36858    |                   |                  |
| 2624140003 | YGWC-45      | SM 2540C        | 36914    |                   |                  |
| 2624140004 | EB-1 10-9-19 | SM 2540C        | 36914    |                   |                  |
| 2624140005 | FB-1 10-9-19 | SM 2540C        | 36858    |                   |                  |
| 2624140006 | YGWC-46      | SM 2540C        | 36914    |                   |                  |
| 2624140007 | DUP-1        | SM 2540C        | 36914    |                   |                  |
| 2624140001 | YGWA-47      | EPA 300.0       | 36855    |                   |                  |
| 2624140002 | YGWC-44      | EPA 300.0       | 36855    |                   |                  |
| 2624140003 | YGWC-45      | EPA 300.0       | 36855    |                   |                  |
| 2624140004 | EB-1 10-9-19 | EPA 300.0       | 36855    |                   |                  |
| 2624140005 | FB-1 10-9-19 | EPA 300.0       | 36855    |                   |                  |
| 2624140006 | YGWC-46      | EPA 300.0       | 36855    |                   |                  |
| 2624140007 | DUP-1        | EPA 300.0       | 36855    |                   |                  |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.





Sample Condition Upon Receipt

WO#: 2624140

Client Name: Georgia Power

PM: BM Due Date: 10/16/19

CLIENT: GAPower-CCR

Courier: [ ] Fed Ex [ ] UPS [ ] USPS [x] Client [ ] Commercial [ ] Pace Other

Tracking #: \_\_\_\_\_

Custody Seal on Cooler/Box Present: [x] yes [ ] no Seals intact: [x] yes [ ] no

Proj. Due Date: \_\_\_\_\_
Proj. Name: \_\_\_\_\_

Packing Material: [ ] Bubble Wrap [ ] Bubble Bags [x] None [ ] Other

Thermometer Used 214 Type of Ice: Wet Blue None [ ] Samples on ice, cooling process has begun

Cooler Temperature 1.8°C Biological Tissue is Frozen: Yes No

Temp should be above freezing to 6°C

Date and Initials of person examining contents: 10/19/19 CCF

Table with 16 rows of checklist items including Chain of Custody Present, Chain of Custody Filled Out, Chain of Custody Relinquished, Sampler Name & Signature on COC, Samples Arrived within Hold Time, Short Hold Time Analysis (<72hr), Rush Turn Around Time Requested, Sufficient Volume, Correct Containers Used, Containers Intact, Filtered volume received for Dissolved tests, Sample Labels match COC, All containers needing preservation have been checked, All containers needing preservation are found to be in compliance with EPA recommendation, exceptions: VOA, coliform, TOC, O&G, WI-DRO (water), Samples checked for dechlorination, Headspace in VOA Vials (>6mm), Trip Blank Present, Trip Blank Custody Seals Present, Pace Trip Blank Lot # (if purchased).

Client Notification/ Resolution: Field Data Required? Y / N

Person Contacted: \_\_\_\_\_ Date/Time: \_\_\_\_\_

Comments/ Resolution: \_\_\_\_\_

Project Manager Review: \_\_\_\_\_ Date: \_\_\_\_\_

Note: Whenever there is a discrepancy affecting North Carolina compliance samples, a copy of this form will be sent to the North Carolina DEHNR Certification Office ( i.e out of hold, incorrect preservative, out of temp, incorrect containers)

November 12, 2019

Joju Abraham  
Georgia Power - Coal Combustion Residuals  
2480 Maner Road  
Atlanta, GA 30339

RE: Project: Plant Yates Pond 1  
Pace Project No.: 2624141

Dear Joju Abraham:

Enclosed are the analytical results for sample(s) received by the laboratory on October 09, 2019. The results relate only to the samples included in this report. Results reported herein conform to the most current, applicable TNI/NELAC standards and the laboratory's Quality Assurance Manual, where applicable, unless otherwise noted in the body of the report.

This report was revised 11/12/19 to correct a sample ID error made by the lab.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,



Betsy McDaniel  
betsy.mcdaniel@pacelabs.com  
(770)734-4200  
Project Manager

Enclosures

cc: Chris Parker, Atlantic Coast Consulting  
Evan Perry, Atlantic Coast Consulting  
Lauren Petty, Southern Company Services, Inc.  
Rebecca Thornton, Pace Analytical Atlanta



## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## CERTIFICATIONS

Project: Plant Yates Pond 1  
Pace Project No.: 2624141

---

### Pennsylvania Certification IDs

1638 Roseytown Rd Suites 2,3&4, Greensburg, PA 15601  
ANAB DOD-ELAP Rad Accreditation #: L2417  
Alabama Certification #: 41590  
Arizona Certification #: AZ0734  
Arkansas Certification  
California Certification #: 04222CA  
Colorado Certification #: PA01547  
Connecticut Certification #: PH-0694  
Delaware Certification  
EPA Region 4 DW Rad  
Florida/TNI Certification #: E87683  
Georgia Certification #: C040  
Florida: Cert E871149 SEKS WET  
Guam Certification  
Hawaii Certification  
Idaho Certification  
Illinois Certification  
Indiana Certification  
Iowa Certification #: 391  
Kansas/TNI Certification #: E-10358  
Kentucky Certification #: KY90133  
KY WW Permit #: KY0098221  
KY WW Permit #: KY0000221  
Louisiana DHH/TNI Certification #: LA180012  
Louisiana DEQ/TNI Certification #: 4086  
Maine Certification #: 2017020  
Maryland Certification #: 308  
Massachusetts Certification #: M-PA1457  
Michigan/PADEP Certification #: 9991

Missouri Certification #: 235  
Montana Certification #: Cert0082  
Nebraska Certification #: NE-OS-29-14  
Nevada Certification #: PA014572018-1  
New Hampshire/TNI Certification #: 297617  
New Jersey/TNI Certification #: PA051  
New Mexico Certification #: PA01457  
New York/TNI Certification #: 10888  
North Carolina Certification #: 42706  
North Dakota Certification #: R-190  
Ohio EPA Rad Approval: #41249  
Oregon/TNI Certification #: PA200002-010  
Pennsylvania/TNI Certification #: 65-00282  
Puerto Rico Certification #: PA01457  
Rhode Island Certification #: 65-00282  
South Dakota Certification  
Tennessee Certification #: 02867  
Texas/TNI Certification #: T104704188-17-3  
Utah/TNI Certification #: PA014572017-9  
USDA Soil Permit #: P330-17-00091  
Vermont Dept. of Health: ID# VT-0282  
Virgin Island/PADEP Certification  
Virginia/VELAP Certification #: 9526  
Washington Certification #: C868  
West Virginia DEP Certification #: 143  
West Virginia DHHR Certification #: 9964C  
Wisconsin Approve List for Rad  
Wyoming Certification #: 8TMS-L

---

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## SAMPLE SUMMARY

Project: Plant Yates Pond 1  
Pace Project No.: 2624141

| Lab ID     | Sample ID    | Matrix | Date Collected | Date Received  |
|------------|--------------|--------|----------------|----------------|
| 2624141001 | YGWA-47      | Water  | 10/08/19 12:34 | 10/09/19 17:00 |
| 2624141002 | YGWC-44      | Water  | 10/08/19 14:07 | 10/09/19 17:00 |
| 2624141003 | YGWC-45      | Water  | 10/09/19 10:23 | 10/09/19 17:00 |
| 2624141004 | EB-1 10-9-19 | Water  | 10/09/19 10:40 | 10/09/19 17:00 |
| 2624141005 | FB-1 10-9-19 | Water  | 10/08/19 13:40 | 10/09/19 17:00 |
| 2624141006 | YGWC-46      | Water  | 10/09/19 12:22 | 10/09/19 17:00 |
| 2624141007 | DUP-1        | Water  | 10/09/19 00:00 | 10/09/19 17:00 |

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### SAMPLE ANALYTE COUNT

Project: Plant Yates Pond 1  
Pace Project No.: 2624141

| Lab ID     | Sample ID    | Method                   | Analysts | Analytes Reported | Laboratory |
|------------|--------------|--------------------------|----------|-------------------|------------|
| 2624141001 | YGWA-47      | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2624141002 | YGWC-44      | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2624141003 | YGWC-45      | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2624141004 | EB-1 10-9-19 | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2624141005 | FB-1 10-9-19 | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2624141006 | YGWC-46      | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |
| 2624141007 | DUP-1        | EPA 9315                 | LAL      | 1                 | PASI-PA    |
|            |              | EPA 9320                 | VAL      | 1                 | PASI-PA    |
|            |              | Total Radium Calculation | CMC      | 1                 | PASI-PA    |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates Pond 1

Pace Project No.: 2624141

**Sample: YGWA-47**      **Lab ID: 2624141001**      Collected: 10/08/19 12:34      Received: 10/09/19 17:00      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                  | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|--|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.710 ± 0.267 (0.231)</b><br>C:91% T:NA | pCi/L | 11/04/19 08:50 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>1.01 ± 0.471 (0.786)</b><br>C:69% T:82% | pCi/L | 11/04/19 12:59 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>1.72 ± 0.738 (1.02)</b>                 | pCi/L | 11/07/19 09:47 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates Pond 1

Pace Project No.: 2624141

**Sample: YGWC-44**      **Lab ID: 2624141002**      Collected: 10/08/19 14:07      Received: 10/09/19 17:00      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                           | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|---|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.731 ± 0.276 (0.193)</b><br><b>C:88% T:NA</b>   | pCi/L | 11/04/19 08:51 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>0.0381 ± 0.406 (0.934)</b><br><b>C:70% T:78%</b> | pCi/L | 11/04/19 13:02 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>0.769 ± 0.682 (1.13)</b>                         | pCi/L | 11/07/19 09:47 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates Pond 1

Pace Project No.: 2624141

**Sample: YGWC-45**      **Lab ID: 2624141003**      Collected: 10/09/19 10:23      Received: 10/09/19 17:00      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                  | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|--|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>1.43 ± 0.403 (0.253)</b><br>C:96% T:NA  | pCi/L | 11/04/19 08:52 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>0.178 ± 0.584 (1.31)</b><br>C:70% T:76% | pCi/L | 11/04/19 13:08 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>1.61 ± 0.987 (1.56)</b>                 | pCi/L | 11/07/19 09:47 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates Pond 1

Pace Project No.: 2624141

**Sample: EB-1 10-9-19**      **Lab ID: 2624141004**      Collected: 10/09/19 10:40      Received: 10/09/19 17:00      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                   | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|---|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.398 ± 0.203 (0.228)</b><br>C:86% T:NA  | pCi/L | 11/04/19 08:54 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>0.336 ± 0.460 (0.987)</b><br>C:66% T:91% | pCi/L | 11/04/19 13:08 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>0.734 ± 0.663 (1.22)</b>                 | pCi/L | 11/07/19 09:47 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates Pond 1

Pace Project No.: 2624141

**Sample: FB-1 10-9-19**      **Lab ID: 2624141005**      Collected: 10/08/19 13:40      Received: 10/09/19 17:00      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                  | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|--|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.440 ± 0.203 (0.197)</b><br>C:96% T:NA | pCi/L | 11/04/19 08:54 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>0.401 ± 0.477 (1.01)</b><br>C:69% T:87% | pCi/L | 11/04/19 13:08 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>0.841 ± 0.680 (1.21)</b>                | pCi/L | 11/07/19 09:47 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates Pond 1

Pace Project No.: 2624141

**Sample: YGWC-46**      **Lab ID: 2624141006**      Collected: 10/09/19 12:22      Received: 10/09/19 17:00      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                  | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|--|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.480 ± 0.214 (0.226)</b><br>C:97% T:NA | pCi/L | 11/04/19 08:55 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>0.412 ± 0.534 (1.14)</b><br>C:72% T:87% | pCi/L | 11/04/19 13:08 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>0.892 ± 0.748 (1.37)</b>                | pCi/L | 11/07/19 09:47 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### ANALYTICAL RESULTS - RADIOCHEMISTRY

Project: Plant Yates Pond 1

Pace Project No.: 2624141

**Sample: DUP-1**      **Lab ID: 2624141007**      Collected: 10/09/19 00:00      Received: 10/09/19 17:00      Matrix: Water  
PWS:      Site ID:      Sample Type:

| Parameters   | Method                      | Act ± Unc (MDC) Carr Trac                          | Units | Analyzed       | CAS No.    | Qual |
|--------------|-----------------------------|--|-------|----------------|------------|------|
| Radium-226   | EPA 9315                    | <b>0.610 ± 0.327 (0.436)</b><br><b>C:86% T:NA</b>  | pCi/L | 11/06/19 08:02 | 13982-63-3 |      |
| Radium-228   | EPA 9320                    | <b>0.219 ± 0.367 (0.798)</b><br><b>C:79% T:85%</b> | pCi/L | 11/06/19 17:17 | 15262-20-1 |      |
| Total Radium | Total Radium<br>Calculation | <b>0.829 ± 0.694 (1.23)</b>                        | pCi/L | 11/08/19 13:51 | 7440-14-4  |      |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL - RADIOCHEMISTRY

Project: Plant Yates Pond 1

Pace Project No.: 2624141

QC Batch: 366971

Analysis Method: EPA 9320

QC Batch Method: EPA 9320

Analysis Description: 9320 Radium 228

Associated Lab Samples: 2624141001, 2624141002, 2624141003, 2624141004, 2624141005, 2624141006

METHOD BLANK: 1780043

Matrix: Water

Associated Lab Samples: 2624141001, 2624141002, 2624141003, 2624141004, 2624141005, 2624141006

| Parameter  | Act ± Unc (MDC) Carr Trac         | Units | Analyzed       | Qualifiers |
|------------|-----------------------------------|-------|----------------|------------|
| Radium-228 | 0.325 ± 0.327 (0.672) C:75% T:91% | pCi/L | 11/04/19 13:01 |            |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL - RADIOCHEMISTRY

Project: Plant Yates Pond 1

Pace Project No.: 2624141

QC Batch: 366969 Analysis Method: EPA 9315

QC Batch Method: EPA 9315 Analysis Description: 9315 Total Radium

Associated Lab Samples: 2624141001, 2624141002, 2624141003, 2624141004, 2624141005, 2624141006

METHOD BLANK: 1780037 Matrix: Water

Associated Lab Samples: 2624141001, 2624141002, 2624141003, 2624141004, 2624141005, 2624141006

| Parameter  | Act ± Unc (MDC) Carr Trac        | Units | Analyzed       | Qualifiers |
|------------|----------------------------------|-------|----------------|------------|
| Radium-226 | 0.340 ± 0.211 (0.351) C:96% T:NA | pCi/L | 11/04/19 08:33 |            |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL - RADIOCHEMISTRY

Project: Plant Yates Pond 1

Pace Project No.: 2624141

QC Batch: 368259

Analysis Method: EPA 9315

QC Batch Method: EPA 9315

Analysis Description: 9315 Total Radium

Associated Lab Samples: 2624141007

METHOD BLANK: 1786863

Matrix: Water

Associated Lab Samples: 2624141007

| Parameter  | Act ± Unc (MDC) Carr Trac        | Units | Analyzed       | Qualifiers |
|------------|----------------------------------|-------|----------------|------------|
| Radium-226 | 0.306 ± 0.244 (0.419) C:96% T:NA | pCi/L | 11/06/19 08:02 |            |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL - RADIOCHEMISTRY

Project: Plant Yates Pond 1

Pace Project No.: 2624141

QC Batch: 368258

Analysis Method: EPA 9320

QC Batch Method: EPA 9320

Analysis Description: 9320 Radium 228

Associated Lab Samples: 2624141007

METHOD BLANK: 1786861

Matrix: Water

Associated Lab Samples: 2624141007

| Parameter  | Act ± Unc (MDC) Carr Trac          | Units | Analyzed       | Qualifiers |
|------------|------------------------------------|-------|----------------|------------|
| Radium-228 | 0.0170 ± 0.384 (0.894) C:77% T:79% | pCi/L | 11/06/19 17:17 |            |

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

## QUALIFIERS

Project: Plant Yates Pond 1  
Pace Project No.: 2624141

---

### DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to dilution of the sample aliquot.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

PQL - Practical Quantitation Limit.

RL - Reporting Limit - The lowest concentration value that meets project requirements for quantitative data with known precision and bias for a specific analyte in a specific matrix.

S - Surrogate

1,2-Diphenylhydrazine decomposes to and cannot be separated from Azobenzene using Method 8270. The result for each analyte is a combined concentration.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

SG - Silica Gel - Clean-Up

U - Indicates the compound was analyzed for, but not detected.

N-Nitrosodiphenylamine decomposes and cannot be separated from Diphenylamine using Method 8270. The result reported for each analyte is a combined concentration.

Act - Activity

Unc - Uncertainty: SDWA = 1.96 sigma count uncertainty, all other matrices = Expanded Uncertainty (95% confidence interval).

Gamma Spec = Expanded Uncertainty (95.4% Confidence Interval)

(MDC) - Minimum Detectable Concentration

Trac - Tracer Recovery (%)

Carr - Carrier Recovery (%)

Pace Analytical is TNI accredited. Contact your Pace PM for the current list of accredited analytes.

TNI - The NELAC Institute.

### LABORATORIES

PASI-PA Pace Analytical Services - Greensburg

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.

### QUALITY CONTROL DATA CROSS REFERENCE TABLE

Project: Plant Yates Pond 1  
Pace Project No.: 2624141

| Lab ID     | Sample ID    | QC Batch Method          | QC Batch | Analytical Method | Analytical Batch |
|------------|--------------|--------------------------|----------|-------------------|------------------|
| 2624141001 | YGWA-47      | EPA 9315                 | 366969   |                   |                  |
| 2624141002 | YGWC-44      | EPA 9315                 | 366969   |                   |                  |
| 2624141003 | YGWC-45      | EPA 9315                 | 366969   |                   |                  |
| 2624141004 | EB-1 10-9-19 | EPA 9315                 | 366969   |                   |                  |
| 2624141005 | FB-1 10-9-19 | EPA 9315                 | 366969   |                   |                  |
| 2624141006 | YGWC-46      | EPA 9315                 | 366969   |                   |                  |
| 2624141007 | DUP-1        | EPA 9315                 | 368259   |                   |                  |
| 2624141001 | YGWA-47      | EPA 9320                 | 366971   |                   |                  |
| 2624141002 | YGWC-44      | EPA 9320                 | 366971   |                   |                  |
| 2624141003 | YGWC-45      | EPA 9320                 | 366971   |                   |                  |
| 2624141004 | EB-1 10-9-19 | EPA 9320                 | 366971   |                   |                  |
| 2624141005 | FB-1 10-9-19 | EPA 9320                 | 366971   |                   |                  |
| 2624141006 | YGWC-46      | EPA 9320                 | 366971   |                   |                  |
| 2624141007 | DUP-1        | EPA 9320                 | 368258   |                   |                  |
| 2624141001 | YGWA-47      | Total Radium Calculation | 369812   |                   |                  |
| 2624141002 | YGWC-44      | Total Radium Calculation | 369812   |                   |                  |
| 2624141003 | YGWC-45      | Total Radium Calculation | 369812   |                   |                  |
| 2624141004 | EB-1 10-9-19 | Total Radium Calculation | 369812   |                   |                  |
| 2624141005 | FB-1 10-9-19 | Total Radium Calculation | 369812   |                   |                  |
| 2624141006 | YGWC-46      | Total Radium Calculation | 369812   |                   |                  |
| 2624141007 | DUP-1        | Total Radium Calculation | 370118   |                   |                  |

### REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, LLC.





Sample Condition Upon Receipt

Client Name: Georgia Power

WO#: **2624141**

PM: BM Due Date: 11/06/19  
CLIENT: GAPower-CCR

Courier:  Fed Ex  UPS  USPS  Client  Commercial  Pace Other  
Tracking #: \_\_\_\_\_

Custody Seal on Cooler/Box Present:  yes  no Seals intact:  yes  no

Proj. Name: \_\_\_\_\_

Packing Material:  Bubble Wrap  Bubble Bags  None  Other \_\_\_\_\_

Thermometer Used 214 Type of Ice: Wet Blue None  Samples on ice, cooling process has begun

Cooler Temperature 1.8°C Biological Tissue is Frozen: Yes No  
Temp should be above freezing to 6°C

Date and Initials of person examining contents: 10/19/19 CDF

|  |  |                        |                             |
|--|--|------------------------|-----------------------------|
| Chain of Custody Present:  | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 1.                     |                             |
| Chain of Custody Filled Out:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 2.                     |                             |
| Chain of Custody Relinquished:   | <input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A            | 3.                     |                             |
| Sampler Name & Signature on COC:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 4.                     |                             |
| Samples Arrived within Hold Time:  | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 5.                     |                             |
| Short Hold Time Analysis (<72hr):  | <input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A            | 6.                     |                             |
| Rush Turn Around Time Requested:   | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> N/A | 7.                     |                             |
| Sufficient Volume:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 8.                     |                             |
| Correct Containers Used:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 9.                     |                             |
| -Pace Containers Used:   | <input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A            |                        |                             |
| Containers Intact:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 10.                    |                             |
| Filtered volume received for Dissolved tests   | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 11.                    |                             |
| Sample Labels match COC:   | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 12.                    |                             |
| -Includes date/time/ID/Analysis Matrix: <u>W</u>   |  |                        |                             |
| All containers needing preservation have been checked.                                     | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A | 13.                    |                             |
| All containers needing preservation are found to be in compliance with EPA recommendation. | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A |                        |                             |
| exceptions: VOA, coliform, TOC, O&G, WI-DRO (water)  | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No                              | Initial when completed | Lot # of added preservative |
| Samples checked for dechlorination:  | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 14.                    |                             |
| Headspace in VOA Vials (>6mm):   | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 15.                    |                             |
| Trip Blank Present:  | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A | 16.                    |                             |
| Trip Blank Custody Seals Present   | <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A |                        |                             |
| Pace Trip Blank Lot # (if purchased):  |  |                        |                             |

Client Notification/ Resolution: \_\_\_\_\_ Field Data Required? Y / N

Person Contacted: \_\_\_\_\_ Date/Time: \_\_\_\_\_

Comments/ Resolution: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Project Manager Review: \_\_\_\_\_ Date: \_\_\_\_\_

Note: Whenever there is a discrepancy affecting North Carolina compliance samples, a copy of this form will be sent to the North Carolina DEHNR Certification Office ( i.e out of hold, incorrect preservative, out of temp, incorrect containers)

**LEVEL 2A LABORATORY DATA VALIDATIONS**

**Plant Yates Ash Pond-1**

**2<sup>nd</sup> Semi-Annual Event**

**October 2019**

## **Georgia Power Company – Plant Yates Ash Pond-1**

### **Quality Control Review of Analytical Data – October 2019**

This narrative presents results of the Quality Control (QC) data review performed on analytical data submitted by Pace Analytical Services, Atlanta and Pittsburgh for groundwater samples collected at Plant Yates AP-1 between October 8, 2019 and October 9, 2019. The chemical data were reviewed to identify quality issues which could affect the use of the data for decision-making purposes.

Information regarding the primary sample locations, analytical parameters, QC samples, sampling dates, and laboratory sample delivery group (SDG) designations is summarized in Table 1 of this Appendix. SDG 2624140 was revised by the laboratory to add target analytes that were missing from the original report. SDGs 2624140 and 2624141 were revised by the laboratory to correct sample identifications.

In accordance with groundwater monitoring and corrective action procedures discussed in Title 40 CFR, Subpart D – Standards for the Disposal of Coal Combustion Residuals in Landfills and Surface Impoundments, the samples were analyzed for detected monitoring constituents listed in 40 CFR, Part 257, Appendix III and assessment monitoring constituents listed in 40 CFR, Part 257, Appendix IV. Test methods included Inductively Coupled Plasma – Mass Spectrometry (USEPA Method 6020B), Mercury in Liquid Wastes (USEPA Method 7470A), Determination of Inorganic Anions (USEPA Method 300.0), Solids in Water (Standard Methods 2540C), Radium-226 (USEPA 9315), and Radium-228 (USEPA Method 9320).

Data were reviewed in accordance with the US EPA Region IV Data Validation Standard Operating Procedures for Contract Laboratory Program Inorganic Data by Inductively Coupled Plasma – Atomic Emission Spectroscopy and Inductively Coupled Plasma – Mass Spectroscopy (September 2011, Rev. 2.0)<sup>1</sup> and the National Functional Guidelines for Inorganic Superfund Methods Data Review (January 2017)<sup>2</sup>. The review included an assessment of the results for completeness, precision (laboratory duplicate recoveries and matrix spike/matrix spike duplicate recoveries), accuracy (laboratory control samples and matrix spike samples), and blank contamination (field, equipment, and laboratory blanks). Sample receipt conditions, holding times, and chains of custody (COCs) were reviewed. Where there was a discrepancy between the QC criteria in the guidelines and the QC criterion established in the analytical methodology, method-specific criteria or professional judgment were used.

## DATA QUALITY OBJECTIVES

**Laboratory Precision:** Laboratory goals for precision were met, with the exception of Radium-226 on DUP-1 (2624142007) as described in the qualifications section below. Additionally, Radium-226 in SDG 2624141 yielded a relative percent difference (RPD) for the laboratory control sample/laboratory control sample duplicate that exceeded the QC criteria (54.43% above limit of 36). This batch was passed on the individual recoveries, and no batch qualification was necessary for Radium-226.

**Field Precision:** Field goals for precision were met.

**Accuracy:** Laboratory goals for accuracy were met, with the exception of Calcium in SDG 2624140 as described in the qualifications section below.

**Detection Limits:** Project goals for detection limits were met.

**Completeness:** There were no rejected analytical results for this event, resulting in a completion of 100%.

**Holding Times:** Holding time requirements were met.

## QUALIFICATIONS

In general, chemical results for the samples collected at the site were qualified on the basis of low precision or low accuracy or on the basis of professional judgment. The following definitions provide brief explanations of the qualifiers which may have been assigned to data by the laboratory during the validation process:

**J:** The analyte was positively identified above the method detection limit; however, the associated numerical value is the approximate concentration of the analyte in the sample

**ND:** The analyte was not detected above the method detection limit

The data generated as part of this sampling event met the QC criteria established in the respective analytical methods and data validation guidelines except as specified below. The applied qualifications may not have been required for all samples collected at the site. A summary of sample qualifications can be found in Table 2 of this Appendix.

- Sample YGWA-47 (2624140001) was qualified as estimated (J) for Calcium as the associated matrix spike and matrix spike duplicate recoveries were outside the QC criteria. The sample received 50-times dilution, which yielded spike recoveries that could not be evaluated.
- Sample DUP-1 (2624141007) was qualified as estimated (J) for Radium-226 as the laboratory RPD exceeded QC criteria (41.19% above limit of 25).
- The Chloride result for sample YGWA-47 (2624140001) was qualified as estimated (J) due to the analyte being detected at a concentration between the method detection limit (MDL) and reporting limit (RL) in an associated blank sample and an order of magnitude above the RL in the sample. As shown in Table 2, the MDL was raised as part of the qualification process.
- Certain radium results in SDGs 2624140 and 2624141 were qualified as non-detect (ND) due to the analyte being detected at a similar concentration in an associated blank sample. As shown in Table 2, the minimum detectable concentration (MDC) was raised to the sample result as part of the qualification process.

Atlantic Coast Consulting, Inc. reviewed the laboratory data from the Plant Yates Ash Pond-1 sampled between October 8, 2019 and October 9, 2019 in accordance with the analytical methods, the laboratory-specified QC criteria, and the guidelines. As described above, the results were acceptable for project use.

## REFERENCES

<sup>1</sup>USEPA, September 2011, Region 4, Science and Ecosystem Support Division, Quality Assurance Section, MTSB, Data Validation Standard Operating Procedures for Contract Laboratory Program Inorganic Data by Inductively Coupled Plasma – Atomic Emission Spectroscopy and Inductively Coupled Plasma – Mass Spectroscopy, Revision 2.0

<sup>2</sup>USEPA, January 2017, National Office of Superfund Remediation and Technology Innovation, National Functional Guidelines for Inorganic Superfund Methods Data Review, Revision 0.0

TABLE 1

## Georgia Power Company – Plant Yates Ash Pond-1

## Sample Summary Table – October 2019

| SDG   | Field Identification | Collection Date | Lab Identification | Matrix | QC Samples   | Analyses              |                |                |                              |
|-------|----------------------|-----------------|--------------------|--------|--------------|-----------------------|----------------|----------------|------------------------------|
|       |                      |                 |                    |        |              | Metals (6020B, 7470A) | Anions (300.0) | TDS (SM 2540C) | Radium-226/-228 (9315, 9320) |
| 24140 | YGWA-47              | 10/8/2019       | 2624140001         | GW     |              | X                     | X              | X              |                              |
| 24141 | YGWA-47              | 10/8/2019       | 2624141001         | GW     |              |                       |                |                | X                            |
| 24140 | YGWC-44              | 10/8/2019       | 2624140002         | GW     |              | X                     | X              | X              |                              |
| 24141 | YGWC-44              | 10/8/2019       | 2624141002         | GW     |              |                       |                |                | X                            |
| 24140 | YGWC-45              | 10/9/2019       | 2624140003         | GW     |              | X                     | X              | X              |                              |
| 24141 | YGWC-45              | 10/9/2019       | 2624141003         | GW     |              |                       |                |                | X                            |
| 24140 | EB-1 10-9-19         | 10/9/2019       | 2624140004         | WQ     | EB           | X                     | X              | X              |                              |
| 24141 | EB-1 10-9-19         | 10/9/2019       | 2624141004         | WQ     | EB           |                       |                |                | X                            |
| 24140 | FB-1 10-9-19         | 10/8/2019       | 2624140005         | WQ     | FB           | X                     | X              | X              |                              |
| 24141 | FB-1 10-9-19         | 10/8/2019       | 2624141005         | WQ     | FB           |                       |                |                | X                            |
| 24140 | YGWC-46              | 10/9/2019       | 2624140006         | GW     |              | X                     | X              | X              |                              |
| 24141 | YGWC-46              | 10/9/2019       | 2624141006         | GW     |              |                       |                |                | X                            |
| 24140 | DUP-1                | 10/9/2019       | 2624140007         | GW     | FD (YGWC-46) | X                     | X              | X              |                              |
| 24141 | DUP-1                | 10/9/2019       | 2624141007         | GW     | FD (YGWC-46) |                       |                |                | X                            |

## Abbreviations:

EB – Equipment Blank

FB – Field Blank

FD – Field Duplicate

GW – Groundwater

QC – Quality Control

TDS – Total Dissolved Solids

WQ – Water Quality Control

TABLE 2

## Georgia Power Company – Plant Yates Ash Pond-1

## Qualifier Summary Table – October 2019

| SDG   | Field Identification | Constituent | New RL | New MDL or MDC | Qualifier | Reason  |
|-------|----------------------|-------------|--------|----------------|-----------|---|
| 24140 | YGWA-47              | Calcium     |        |                | J         | MS/MSD outside QC criteria                              |
| 24140 | YGWA-47              | Chloride    |        | 0.445          | J         | Blank detection above MDL and sample detection above RL |
| 24141 | YGWA-47              | Radium-226  |        | 0.231          | ND        | Blank detection   |
| 24141 | YGWC-44              | Radium-226  |        | 0.193          | ND        | Blank detection   |
| 24141 | YGWC-45              | Radium-226  |        | 0.253          | ND        | Blank detection   |
| 24141 | YGWC-46              | Radium-226  |        | 0.226          | ND        | Blank detection   |
| 24241 | DUP-1                | Radium-226  |        |                | J         | RPD exceeds laboratory goal                             |

## Abbreviations:

MDC – Minimum Detectable Concentration  
MS/MSD – Matrix Spike / Matrix Spike Duplicate  
MDL – Method Detection Limit  
RL – Reporting Limit  
RPD – Relative Percent Difference  
SDG – Sample Delivery Group

## Qualifiers:

J – Estimated Result  
ND – Non-Detect Result

Product Name: Low-Flow System

Date: 2019-10-08 12:35:36

Project Information:

Operator Name Taylor Goble  
 Company Name ACC  
 Project Name Pond 1  
 Site Name Plant Yates  
 Latitude 0° 0' 0"  
 Longitude 0° 0' 0"  
 Sonde SN 613229  
 Turbidity Make/Model HACH

Pump Information:

Pump Model/Type Bladder Pump  
 Tubing Type Poly  
 Tubing Diameter .25 in  
 Tubing Length 60 ft

Pump placement from TOC 55 ft

Well Information:

Well ID YGWA-47  
 Well diameter 2 in  
 Well Total Depth 59.50 ft  
 Screen Length 10 ft  
 Depth to Water 35.63 ft

Pumping Information:

Final Pumping Rate 150 mL/min  
 Total System Volume 0.6691639 L  
 Calculated Sample Rate 300 sec  
 Stabilization Drawdown 10 in  
 Total Volume Pumped 4.8 L

Low-Flow Sampling Stabilization Summary

| Stabilization Time | Elapsed | Temp C | pH      | SpCond $\mu$ S/cm | Turb NTU | DTW ft | RDO mg/L | ORP mV |
|--------------------|---------|--------|---------|-------------------|----------|--------|----------|--------|
|                    |         | +/- 1  | +/- 0.1 | +/- 5%            | +/- 10   |        | +/- 10%  | +/- 25 |
| Last 5 12:14:21    | 600.02  | 19.86  | 6.05    | 219.40            | 1.55     | 36.18  | 4.23     | 116.51 |
| Last 5 12:19:21    | 899.93  | 19.32  | 5.77    | 219.40            | 1.39     | 36.24  | 3.86     | 100.65 |
| Last 5 12:24:21    | 1199.93 | 19.11  | 5.68    | 219.16            | 1.22     | 36.29  | 3.70     | 92.73  |
| Last 5 12:29:21    | 1499.93 | 19.04  | 5.65    | 220.37            | 1.28     | 36.34  | 3.68     | 88.31  |
| Last 5 12:34:21    | 1799.93 | 18.99  | 5.59    | 221.35            | 1.22     | 36.40  | 3.66     | 86.92  |
| Variance 0         |         | -0.22  | -0.09   | -0.24             |          |        | -0.16    | -7.92  |
| Variance 1         |         | -0.06  | -0.03   | 1.21              |          |        | -0.02    | -4.42  |
| Variance 2         |         | -0.06  | -0.06   | 0.98              |          |        | -0.02    | -1.39  |

Notes

Sampled at 1234. Rainy 78 degrees

Grab Samples

Product Name: Low-Flow System

Date: 2019-10-08 14:08:37

Project Information:

Operator Name Taylor Goble  
 Company Name ACC  
 Project Name Pond 1  
 Site Name Plant Yates  
 Latitude 0° 0' 0"  
 Longitude 0° 0' 0"  
 Sonde SN 613229  
 Turbidity Make/Model HACH

Pump Information:

Pump Model/Type Bladder Pump  
 Tubing Type Poly  
 Tubing Diameter .25 in  
 Tubing Length 90 ft

Pump placement from TOC 85 ft

Well Information:

Well ID YGWC-44  
 Well diameter 2 in  
 Well Total Depth 90.00 ft  
 Screen Length 10 ft  
 Depth to Water 50.68 ft

Pumping Information:

Final Pumping Rate 100 mL/min  
 Total System Volume 0.9587458 L  
 Calculated Sample Rate 300 sec  
 Stabilization Drawdown 14 in  
 Total Volume Pumped 3 L

Low-Flow Sampling Stabilization Summary

| Stabilization Time | Elapsed | Temp C | pH      | SpCond $\mu$ S/cm | Turb NTU | DTW ft | RDO mg/L | ORP mV |
|--------------------|---------|--------|---------|-------------------|----------|--------|----------|--------|
|                    |         | +/- 1  | +/- 0.1 | +/- 5%            | +/- 10   |        | +/- 10%  | +/- 25 |
| Last 5 13:47:06    | 1200.02 | 25.19  | 5.90    | 471.27            | 0.77     | 51.61  | 1.42     | -48.16 |
| Last 5 13:52:08    | 1502.02 | 25.55  | 5.86    | 471.93            | 1.23     | 51.75  | 0.96     | -34.23 |
| Last 5 13:57:09    | 1803.02 | 25.87  | 5.84    | 473.11            | 0.98     | 51.82  | 0.79     | -19.63 |
| Last 5 14:02:09    | 2103.02 | 26.33  | 5.83    | 472.37            | 1.54     | 51.90  | 0.73     | -7.60  |
| Last 5 14:07:09    | 2403.05 | 25.78  | 5.84    | 470.04            | 2.01     | 52.01  | 0.69     | 0.99   |
| Variance 0         |         | 0.32   | -0.02   | 1.18              |          |        | -0.17    | 14.60  |
| Variance 1         |         | 0.46   | -0.01   | -0.74             |          |        | -0.05    | 12.03  |
| Variance 2         |         | -0.55  | 0.00    | -2.33             |          |        | -0.04    | 8.59   |

Notes

Sampled at 1407. Sunny 79 degrees

Grab Samples

Product Name: Low-Flow System

Date: 2019-10-09 10:24:28

**Project Information:**

Operator Name Taylor Goble  
Company Name ACC  
Project Name Pond 1  
Site Name Plant Yates  
Latitude 0° 0' 0"  
Longitude 0° 0' 0"  
Sonde SN 613229  
Turbidity Make/Model HACH

**Pump Information:**

Pump Model/Type Bladder Pump  
Tubing Type Poly  
Tubing Diameter .25 in  
Tubing Length 70 ft  
Pump placement from TOC 65 ft

**Well Information:**

Well ID YGWC-45  
Well diameter 2 in  
Well Total Depth 74.00 ft  
Screen Length 10 ft  
Depth to Water 22.94 ft

**Pumping Information:**

Final Pumping Rate 150 mL/min  
Total System Volume 0.7656912 L  
Calculated Sample Rate 300 sec  
Stabilization Drawdown 13 in  
Total Volume Pumped 5 L

**Low-Flow Sampling Stabilization Summary**

| Stabilization Time | Elapsed  | Temp C | pH   | SpCond $\mu$ S/cm | Turb NTU | DTW ft | RDO mg/L | ORP mV |
|--------------------|----------|--------|------|-------------------|----------|--------|----------|--------|
| Last 5             | 10:03:30 | 19.35  | 6.57 | 566.71            | 3.15     | 23.78  | 1.40     | +/- 25 |
| Last 5             | 10:08:30 | 19.32  | 6.48 | 569.07            | 2.26     | 23.84  | 1.24     | 22.12  |
| Last 5             | 10:13:31 | 19.29  | 6.49 | 570.56            | 2.17     | 23.92  | 1.22     | 26.34  |
| Last 5             | 10:18:31 | 19.32  | 6.52 | 572.40            | 1.88     | 24.00  | 1.08     | 24.53  |
| Last 5             | 10:23:31 | 19.29  | 6.55 | 573.15            | 1.72     | 24.10  | 1.10     | 21.00  |
| Variance 0         |          | -0.03  | 0.01 | 1.48              |          |        | -0.03    | 17.15  |
| Variance 1         |          | 0.03   | 0.03 | 1.85              |          |        | -0.14    | -1.81  |
| Variance 2         |          | -0.03  | 0.03 | 0.75              |          |        | 0.02     | -3.53  |

**Notes**

Sampled at 1023. Cloudy 70 degrees

**Grab Samples**

Product Name: Low-Flow System

Date: 2019-10-09 12:23:44

**Project Information:**

Operator Name Taylor Goble  
Company Name ACC  
Project Name Pond 1  
Site Name Plant Yates  
Latitude 0° 0' 0"  
Longitude 0° 0' 0"  
Sonde SN 613229  
Turbidity Make/Model HACH

**Pump Information:**

Pump Model/Type Bladder Pump  
Tubing Type Poly  
Tubing Diameter .25 in  
Tubing Length 84 ft  
Pump placement from TOC 79 ft

**Well Information:**

Well ID YGWC-46  
Well diameter 2 in  
Well Total Depth 83.60 ft  
Screen Length 10 ft  
Depth to Water 48.29 ft

**Pumping Information:**

Final Pumping Rate 180 mL/min  
Total System Volume 0.9008295 L  
Calculated Sample Rate 300 sec  
Stabilization Drawdown 14 in  
Total Volume Pumped 5 L

**Low-Flow Sampling Stabilization Summary**

| Stabilization Time | Elapsed  | Temp C | pH    | SpCond $\mu$ S/cm | Turb NTU | DTW ft | RDO mg/L | ORP mV |
|--------------------|----------|--------|-------|-------------------|----------|--------|----------|--------|
| Last 5             | 12:02:26 | 20.84  | 6.13  | 1006.14           | 1.07     | 48.98  | 0.96     | +/- 25 |
| Last 5             | 12:07:26 | 20.76  | 6.02  | 1006.34           | 1.55     | 49.11  | 0.69     | -11.05 |
| Last 5             | 12:12:26 | 20.79  | 5.98  | 1005.72           | 1.28     | 49.20  | 0.61     | 2.93   |
| Last 5             | 12:17:27 | 20.80  | 5.97  | 1006.92           | 1.11     | 49.31  | 0.58     | 8.50   |
| Last 5             | 12:22:27 | 20.79  | 5.96  | 1006.30           | 1.23     | 49.44  | 0.49     | 10.97  |
| Variance 0         |          | 0.03   | -0.04 | -0.62             |          |        | -0.08    | 11.96  |
| Variance 1         |          | 0.00   | -0.02 | 1.19              |          |        | -0.03    | 5.57   |
| Variance 2         |          | -0.00  | -0.01 | -0.62             |          |        | -0.09    | 2.47   |

**Notes**

Sampled at 1222. Cloudy 75 degrees. Duplicate 1 here

**Grab Samples**

# APPENDIX B

## STATISTICAL ANALYSES

# AP-1 100% ND

Date: 12/3/2019 2:27 PM

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

Cadmium (mg/L)

YGWC-44, YGWC-45

Molybdenum (mg/L)

YGWA-47

Thallium (mg/L)

YGWC-44, YGWC-45, YGWC-46

# Interwell Prediction Limit Significant Results

Plant Yates    Client: Southern Company    Data: Yates Ash Pond 1    Printed 12/3/2019, 2:31 PM

| <u>Constituent</u>            | <u>Well</u> | <u>Upper Lim.</u> | <u>Lower Lim.</u> | <u>Date</u> | <u>Observ.</u> | <u>Sig.</u> | <u>Bq.N</u> | <u>%NDs</u> | <u>Transform</u> | <u>Alpha</u> | <u>Method</u>               |
|-------------------------------|-------------|-------------------|-------------------|-------------|----------------|-------------|-------------|-------------|------------------|--------------|-----------------------------|
| Boron (mg/L)                  | YGWC-44     | 0.01752           | n/a               | 10/8/2019   | 0.58           | Yes         | 10          | 0           | No               | 0.002505     | Param Inter 1 of 2          |
| Boron (mg/L)                  | YGWC-45     | 0.01752           | n/a               | 10/9/2019   | 0.35           | Yes         | 10          | 0           | No               | 0.002505     | Param Inter 1 of 2          |
| Boron (mg/L)                  | YGWC-46     | 0.01752           | n/a               | 10/9/2019   | 1.1            | Yes         | 10          | 0           | No               | 0.002505     | Param Inter 1 of 2          |
| Calcium (mg/L)                | YGWC-44     | 22.04             | n/a               | 10/8/2019   | 28.1           | Yes         | 10          | 10          | No               | 0.002505     | Param Inter 1 of 2          |
| Calcium (mg/L)                | YGWC-45     | 22.04             | n/a               | 10/9/2019   | 47.9           | Yes         | 10          | 10          | No               | 0.002505     | Param Inter 1 of 2          |
| Calcium (mg/L)                | YGWC-46     | 22.04             | n/a               | 10/9/2019   | 64.2           | Yes         | 10          | 10          | No               | 0.002505     | Param Inter 1 of 2          |
| Chloride (mg/L)               | YGWC-44     | 6.986             | n/a               | 10/8/2019   | 14.8           | Yes         | 10          | 0           | No               | 0.002505     | Param Inter 1 of 2          |
| Chloride (mg/L)               | YGWC-46     | 6.986             | n/a               | 10/9/2019   | 25             | Yes         | 10          | 0           | No               | 0.002505     | Param Inter 1 of 2          |
| pH (S.U.)                     | YGWC-45     | 5.847             | 5.345             | 10/9/2019   | 6.55           | Yes         | 10          | 0           | No               | 0.001253     | Param Inter 1 of 2          |
| pH (S.U.)                     | YGWC-46     | 5.847             | 5.345             | 10/9/2019   | 5.96           | Yes         | 10          | 0           | No               | 0.001253     | Param Inter 1 of 2          |
| Sulfate (mg/L)                | YGWC-44     | 181.3             | n/a               | 10/9/2019   | 183            | Yes         | 10          | 0           | No               | 0.002505     | Param Inter 1 of 2          |
| Total Dissolved Solids (mg/L) | YGWC-45     | 319               | n/a               | 10/8/2019   | 324            | Yes         | 10          | 0           | n/a              | 0.01337      | NP Inter (normality) 1 of 2 |
| Total Dissolved Solids (mg/L) | YGWC-45     | 319               | n/a               | 10/9/2019   | 432            | Yes         | 10          | 0           | n/a              | 0.01337      | NP Inter (normality) 1 of 2 |
| Total Dissolved Solids (mg/L) | YGWC-46     | 319               | n/a               | 10/9/2019   | 809            | Yes         | 10          | 0           | n/a              | 0.01337      | NP Inter (normality) 1 of 2 |


# Interwell Prediction Limit All Results

Plant Yates Client: Southern Company Data: Yates Ash Pond 1 Printed 12/3/2019, 2:31 PM

| Constituent                   | Well    | Upper Lim. | Lower Lim. | Date      | Observ. | Sig. | Bq.N | %NDs  | Transform | Alpha    | Method                      |
|-------------------------------|---------|------------|------------|-----------|---------|------|------|-------|-----------|----------|-----------------------------|
| Boron (mg/L)                  | YGWC-44 | 0.01752    | n/a        | 10/8/2019 | 0.58    | Yes  | 10   | 0     | No        | 0.002505 | Param Inter 1 of 2          |
| Boron (mg/L)                  | YGWC-45 | 0.01752    | n/a        | 10/9/2019 | 0.35    | Yes  | 10   | 0     | No        | 0.002505 | Param Inter 1 of 2          |
| Boron (mg/L)                  | YGWC-46 | 0.01752    | n/a        | 10/9/2019 | 1.1     | Yes  | 10   | 0     | No        | 0.002505 | Param Inter 1 of 2          |
| Calcium (mg/L)                | YGWC-44 | 22.04      | n/a        | 10/8/2019 | 28.1    | Yes  | 10   | 10    | No        | 0.002505 | Param Inter 1 of 2          |
| Calcium (mg/L)                | YGWC-45 | 22.04      | n/a        | 10/9/2019 | 47.9    | Yes  | 10   | 10    | No        | 0.002505 | Param Inter 1 of 2          |
| Calcium (mg/L)                | YGWC-46 | 22.04      | n/a        | 10/9/2019 | 64.2    | Yes  | 10   | 10    | No        | 0.002505 | Param Inter 1 of 2          |
| Chloride (mg/L)               | YGWC-44 | 6.986      | n/a        | 10/8/2019 | 14.8    | Yes  | 10   | 0     | No        | 0.002505 | Param Inter 1 of 2          |
| Chloride (mg/L)               | YGWC-45 | 6.986      | n/a        | 10/9/2019 | 5.1     | No   | 10   | 0     | No        | 0.002505 | Param Inter 1 of 2          |
| Chloride (mg/L)               | YGWC-46 | 6.986      | n/a        | 10/9/2019 | 25      | Yes  | 10   | 0     | No        | 0.002505 | Param Inter 1 of 2          |
| Fluoride (mg/L)               | YGWC-44 | 0.1893     | n/a        | 10/8/2019 | 0.3ND   | No   | 11   | 36.36 | sqrt(x)   | 0.002505 | Param Inter 1 of 2          |
| Fluoride (mg/L)               | YGWC-45 | 0.1893     | n/a        | 10/9/2019 | 0.3ND   | No   | 11   | 36.36 | sqrt(x)   | 0.002505 | Param Inter 1 of 2          |
| Fluoride (mg/L)               | YGWC-46 | 0.1893     | n/a        | 10/9/2019 | 0.12    | No   | 11   | 36.36 | sqrt(x)   | 0.002505 | Param Inter 1 of 2          |
| pH (S.U.)                     | YGWC-44 | 5.847      | 5.345      | 10/8/2019 | 5.84    | No   | 10   | 0     | No        | 0.001253 | Param Inter 1 of 2          |
| pH (S.U.)                     | YGWC-45 | 5.847      | 5.345      | 10/9/2019 | 6.55    | Yes  | 10   | 0     | No        | 0.001253 | Param Inter 1 of 2          |
| pH (S.U.)                     | YGWC-46 | 5.847      | 5.345      | 10/9/2019 | 5.96    | Yes  | 10   | 0     | No        | 0.001253 | Param Inter 1 of 2          |
| Sulfate (mg/L)                | YGWC-44 | 181.3      | n/a        | 10/8/2019 | 142     | No   | 10   | 0     | No        | 0.002505 | Param Inter 1 of 2          |
| Sulfate (mg/L)                | YGWC-45 | 181.3      | n/a        | 10/9/2019 | 183     | Yes  | 10   | 0     | No        | 0.002505 | Param Inter 1 of 2          |
| Sulfate (mg/L)                | YGWC-46 | 181.3      | n/a        | 10/9/2019 | 0.5ND   | No   | 10   | 0     | No        | 0.002505 | Param Inter 1 of 2          |
| Total Dissolved Solids (mg/L) | YGWC-44 | 319        | n/a        | 10/8/2019 | 324     | Yes  | 10   | 0     | n/a       | 0.01337  | NP Inter (normality) 1 of 2 |
| Total Dissolved Solids (mg/L) | YGWC-45 | 319        | n/a        | 10/9/2019 | 432     | Yes  | 10   | 0     | n/a       | 0.01337  | NP Inter (normality) 1 of 2 |
| Total Dissolved Solids (mg/L) | YGWC-46 | 319        | n/a        | 10/9/2019 | 809     | Yes  | 10   | 0     | n/a       | 0.01337  | NP Inter (normality) 1 of 2 |

Exceeds Limit: YGWC-44, YGWC-45, YGWC-46

Prediction Limit  
Interwell Parametric




Background Data Summary: Mean=0.01373, Std. Dev.=0.001713, n=10. Insufficient data to test for seasonality; not deseasonalized. Normality test: Shapiro Wilk @alpha = 0.01, calculated = 0.8511, critical = 0.781. Kappa = 2.214 (c=7, w=3, 1 of 2, event alpha = 0.05132). Report alpha = 0.007498. Individual comparison alpha = 0.002505. Comparing 3 points to limit.

Constituent: Boron Analysis Run 12/3/2019 2:28 PM View: AP-1 Interwell PL  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Exceeds Limit: YGWC-44, YGWC-45, YGWC-46

Prediction Limit  
Interwell Parametric




Background Data Summary: Mean=14.07, Std. Dev.=3.599, n=10. 10% NDs. Insufficient data to test for seasonality; not deseasonalized. Normality test: Shapiro Wilk @alpha = 0.01, calculated = 0.9355, critical = 0.781. Kappa = 2.214 (c=7, w=3, 1 of 2, event alpha = 0.05132). Report alpha = 0.007498. Individual comparison alpha = 0.002505. Comparing 3 points to limit.

Constituent: Calcium Analysis Run 12/3/2019 2:28 PM View: AP-1 Interwell PL  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Exceeds Limit: YGWC-44, YGWC-45, YGWC-46

Prediction Limit  
Interwell Parametric




Background Data Summary: Mean=0.01373, Std. Dev.=0.001713, n=10. Insufficient data to test for seasonality; not deseasonalized. Normality test: Shapiro Wilk @alpha = 0.01, calculated = 0.8511, critical = 0.781. Kappa = 2.214 (c=7, w=3, 1 of 2, event alpha = 0.05132). Report alpha = 0.007498. Individual comparison alpha = 0.002505. Comparing 3 points to limit.

Constituent: Boron Analysis Run 12/3/2019 2:28 PM View: AP-1 Interwell PL  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Exceeds Limit: YGWC-44, YGWC-45, YGWC-46

Prediction Limit  
Interwell Parametric




Background Data Summary: Mean=0.01373, Std. Dev.=0.001713, n=10. Insufficient data to test for seasonality; not deseasonalized. Normality test: Shapiro Wilk @alpha = 0.01, calculated = 0.8511, critical = 0.781. Kappa = 2.214 (c=7, w=3, 1 of 2, event alpha = 0.05132). Report alpha = 0.007498. Individual comparison alpha = 0.002505. Comparing 3 points to limit.

Constituent: Calcium Analysis Run 12/3/2019 2:28 PM View: AP-1 Interwell PL  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Exceeds Limit: YGWC-44, YGWC-45, YGWC-46

Prediction Limit  
Interwell Parametric




Background Data Summary: Mean=5.21, Std. Dev.=0.802, n=10. Insufficient data to test for seasonality; not deseasonalized. Normality test: Shapiro Wilk @alpha = 0.01, calculated = 0.9443, critical = 0.781. Kappa = 2.214 (c=7, w=3, 1 of 2, event alpha = 0.05132). Report alpha = 0.007498. Individual comparison alpha = 0.002505. Comparing 3 points to limit.

Constituent: Chloride Analysis Run 12/3/2019 2:28 PM View: AP-1 Interwell PL  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Exceeds Limit: YGWC-44, YGWC-45, YGWC-46

Prediction Limit  
Interwell Parametric




Background Data Summary: Mean=0.01373, Std. Dev.=0.001713, n=10. Insufficient data to test for seasonality; not deseasonalized. Normality test: Shapiro Wilk @alpha = 0.01, calculated = 0.8511, critical = 0.781. Kappa = 2.214 (c=7, w=3, 1 of 2, event alpha = 0.05132). Report alpha = 0.007498. Individual comparison alpha = 0.002505. Comparing 3 points to limit.

Constituent: Calcium Analysis Run 12/3/2019 2:28 PM View: AP-1 Interwell PL  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Exceeds Limit: YGWC-44, YGWC-45, YGWC-46

Prediction Limit  
Interwell Parametric




Background Data Summary: Mean=5.21, Std. Dev.=0.802, n=10. Insufficient data to test for seasonality; not deseasonalized. Normality test: Shapiro Wilk @alpha = 0.01, calculated = 0.9443, critical = 0.781. Kappa = 2.214 (c=7, w=3, 1 of 2, event alpha = 0.05132). Report alpha = 0.007498. Individual comparison alpha = 0.002505. Comparing 3 points to limit.

Constituent: Chloride Analysis Run 12/3/2019 2:28 PM View: AP-1 Interwell PL  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Exceeds Limits: YGWC-45, YGWC-46

Prediction Limit  
Interwell Parametric




Background Data Summary: Mean=5.596, Std. Dev.=0.1132, n=10. Insufficient data to test for seasonality; not deseasonalized. Normality test: Shapiro Wilk @alpha = 0.01, calculated = 0.8289, critical = 0.781. Kappa = 2.214 (C=7, w=3, T of 2, event alpha = 0.05132). Report alpha = 0.007498. Individual comparison alpha = 0.007253. Comparing 3 points to limit.

Constituent: pH Analysis Run 12/3/2019 2:28 PM View: AP-1 Interwell PL  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Exceeds Limit: YGWC-44, YGWC-45, YGWC-46

Prediction Limit  
Interwell Non-parametric




Non-parametric test used in lieu of parametric prediction limit because the Shapiro Wilk normality test showed the data to be non-normal at the 0.01 alpha level. Limit is highest of 10 background values. Annual per-constituent alpha = 0.07757. Individual comparison alpha = 0.01337 (1 of 2). Comparing 3 points to limit. Insufficient data to test for seasonality; data will not be deseasonalized.

Constituent: Total Dissolved Solids Analysis Run 12/3/2019 2:28 PM View: AP-1 Interwell PL  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Hollow symbols indicate censored values.

Exceeds Limit: YGWC-45

Prediction Limit  
Interwell Parametric



Background Data Summary: Mean=103.5, Std. Dev.=35.14, n=10. Insufficient data to test for seasonality; not deseasonalized. Normality test: Shapiro Wilk @alpha = 0.01, calculated = 0.966, critical = 0.781. Kappa = 2.214 (C=7, w=3, T of 2, event alpha = 0.05132). Report alpha = 0.007498. Individual comparison alpha = 0.002505. Comparing 3 points to limit.

Constituent: Sulfate Analysis Run 12/3/2019 2:28 PM View: AP-1 Interwell PL  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

# Prediction Limit

Constituent: Boron (mg/L) Analysis Run 12/3/2019 2:31 PM View: AP-1 Interwell PL

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

|            | YGWA-47 (bg) | YGWC-44 | YGWC-45 | YGWC-46 |
|------------|--------------|---------|---------|---------|
| 8/30/2016  | 0.0166 (J)   |         |         |         |
| 8/31/2016  |              | 0.541   | 0.308   |         |
| 9/1/2016   |              |         |         | 2.12    |
| 11/14/2016 | 0.0166 (J)   |         | 0.368   |         |
| 11/15/2016 |              | 0.706   |         |         |
| 11/16/2016 |              |         |         | 2.03    |
| 2/24/2017  | 0.0145 (J)   |         |         |         |
| 2/27/2017  |              |         | 0.321   | 1.29    |
| 2/28/2017  |              | 0.623   |         |         |
| 5/8/2017   | 0.0141 (J)   | 0.69    |         | 1.71    |
| 5/9/2017   |              |         | 0.338   |         |
| 7/11/2017  | 0.0131 (J)   |         |         |         |
| 7/13/2017  |              | 0.649   | 0.34    | 1.62    |
| 10/10/2017 | 0.0124 (J)   | 0.603   | 0.319   |         |
| 10/11/2017 |              |         |         | 1.17    |
| 4/2/2018   | 0.013 (J)    |         |         |         |
| 4/3/2018   |              |         | 0.35    |         |
| 4/4/2018   |              | 0.66    |         | 1.2     |
| 9/19/2018  | 0.012 (J)    | 0.66    | 0.35    | 1.2     |
| 3/27/2019  | 0.013 (J)    | 0.57    | 0.33    | 0.89    |
| 10/8/2019  | 0.012 (J)    | 0.58    |         |         |
| 10/9/2019  |              |         | 0.35    | 1.1     |

# Prediction Limit

Constituent: Calcium (mg/L) Analysis Run 12/3/2019 2:31 PM View: AP-1 Interwell PL

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

|            | YGWA-47 (bg) | YGWC-44 | YGWC-45 | YGWC-46 |
|------------|--------------|---------|---------|---------|
| 8/30/2016  | 20.9         |         |         |         |
| 8/31/2016  |              | 27.3    | 46.7    |         |
| 9/1/2016   |              |         |         | 96.8    |
| 11/14/2016 | 18.6         |         | 50.6    |         |
| 11/15/2016 |              | 27.8    |         |         |
| 11/16/2016 |              |         |         | 107     |
| 2/24/2017  | 16.1         |         |         |         |
| 2/27/2017  |              |         | 49.4    | 104     |
| 2/28/2017  |              | 26.4    |         |         |
| 5/8/2017   | 14.6         | 29.9    |         | 103     |
| 5/9/2017   |              |         | 56      |         |
| 7/11/2017  | 14.3         |         |         |         |
| 7/13/2017  |              | 30.2    | 54.8    | 83.7    |
| 10/10/2017 | 12.1         | 27.2    | 52.8    |         |
| 10/11/2017 |              |         |         | 69      |
| 4/2/2018   | <25          |         |         |         |
| 4/3/2018   |              |         | 50.6    |         |
| 4/4/2018   |              | 30.1    |         | 51.9    |
| 9/19/2018  | 11.1 (J)     | 29.2    | 50.5    | 51.9    |
| 3/27/2019  | 10.8 (J)     | 27.9    | 48.8    | 54.2    |
| 10/8/2019  | 9.7          | 28.1    |         |         |
| 10/9/2019  |              |         | 47.9    | 64.2    |

# Prediction Limit

Constituent: Chloride (mg/L) Analysis Run 12/3/2019 2:31 PM View: AP-1 Interwell PL

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

|            | YGWA-47 (bg) | YGWC-44 | YGWC-45 | YGWC-46 |
|------------|--------------|---------|---------|---------|
| 8/30/2016  | 5.2          |         |         |         |
| 8/31/2016  |              | 13      | 5.8     |         |
| 9/1/2016   |              |         |         | 37      |
| 11/14/2016 | 6.4          |         | 5.8     |         |
| 11/15/2016 |              | 14      |         |         |
| 11/16/2016 |              |         |         | 37      |
| 2/24/2017  | 5.5          |         |         |         |
| 2/27/2017  |              |         | 5       | 33      |
| 2/28/2017  |              | 12      |         |         |
| 5/8/2017   | 5.8          | 13      |         | 33      |
| 5/9/2017   |              |         | 4.6     |         |
| 7/11/2017  | 5.8          |         |         |         |
| 7/13/2017  |              | 13      | 4.7     | 32      |
| 10/10/2017 | 5.9          | 14      | 4.5     |         |
| 10/11/2017 |              |         |         | 29      |
| 4/2/2018   | 4.8          |         |         |         |
| 4/3/2018   |              |         | 4.6     |         |
| 4/4/2018   |              | 13.4    |         | 26.6    |
| 9/19/2018  | 4            | 14.2    | 4.7     | 26.5    |
| 3/27/2019  | 4.3          | 14      | 4.6     | 20.9    |
| 10/8/2019  | 4.4          | 14.8    |         |         |
| 10/9/2019  |              |         | 5.1     | 25      |

# Prediction Limit

Constituent: Fluoride (mg/L) Analysis Run 12/3/2019 2:31 PM View: AP-1 Interwell PL  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

|            | YGWA-47 (bg) | YGWC-44  | YGWC-45  | YGWC-46   |
|------------|--------------|----------|----------|-----------|
| 8/30/2016  | 0.09 (J)     |          |          |           |
| 8/31/2016  |              | <0.3     | 0.11 (J) |           |
| 9/1/2016   |              |          |          | 0.08 (J)  |
| 11/14/2016 | 0.18 (J)     |          | 0.71     |           |
| 11/15/2016 |              | 0.12 (J) |          |           |
| 11/16/2016 |              |          |          | 0.04 (J)  |
| 2/24/2017  | 0.05 (J)     |          |          |           |
| 2/27/2017  |              |          | 0.22 (J) | 0.05 (J)  |
| 2/28/2017  |              | 0.07 (J) |          |           |
| 5/8/2017   | 0.03 (J)     | 0.04 (J) |          | 0.004 (J) |
| 5/9/2017   |              |          | 0.2 (J)  |           |
| 7/11/2017  | 0.07 (J)     |          |          |           |
| 7/13/2017  |              | <0.3     | 0.11 (J) | 0.35      |
| 10/10/2017 | <0.3         | <0.3     | 0.39     |           |
| 10/11/2017 |              |          |          | <0.3      |
| 4/2/2018   | <0.3         |          |          |           |
| 4/3/2018   |              |          | <0.3     |           |
| 4/4/2018   |              | <0.3     |          | <0.3      |
| 9/19/2018  | <0.3         | <0.3     | <0.3     | <0.3      |
| 3/27/2019  | 0.081 (J)    | <0.3     | 0.18 (J) | 0.12 (J)  |
| 8/20/2019  | <0.3         | <0.3     | <0.3     |           |
| 8/21/2019  |              |          |          | <0.3      |
| 10/8/2019  | 0.034 (J)    | <0.3     |          |           |
| 10/9/2019  |              |          | <0.3     | 0.12 (J)  |

# Prediction Limit

Constituent: pH (S.U.) Analysis Run 12/3/2019 2:31 PM View: AP-1 Interwell PL

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

|            | YGWA-47 (bg) | YGWC-44 | YGWC-45 | YGWC-46 |
|------------|--------------|---------|---------|---------|
| 8/30/2016  | 5.75         |         |         |         |
| 8/31/2016  |              | 6.01    | 7.15    |         |
| 9/1/2016   |              |         |         | 6.19    |
| 11/14/2016 | 5.59         |         | 6.96    |         |
| 11/15/2016 |              | 5.91    |         |         |
| 11/16/2016 |              |         |         | 6.05    |
| 2/24/2017  | 5.49         |         |         |         |
| 2/27/2017  |              |         | 6.79    | 6.01    |
| 2/28/2017  |              | 5.85    |         |         |
| 5/8/2017   | 5.58         | 5.91    |         | 6.1     |
| 5/9/2017   |              |         | 6.9     |         |
| 7/11/2017  | 5.58         |         |         |         |
| 7/13/2017  |              | 5.8     | 6.77    | 6.07    |
| 10/10/2017 | 5.49         | 5.76    | 6.9     |         |
| 10/11/2017 |              |         |         | 5.93    |
| 4/2/2018   | 6.3 (o)      |         |         |         |
| 4/3/2018   |              |         | 6.44    |         |
| 4/4/2018   |              | 5.77    |         | 6.01    |
| 9/19/2018  | 5.48         | 5.77    | 6.47    | 6.09    |
| 3/27/2019  | 5.83         | 6.1     | 7.18    | 6.2     |
| 8/20/2019  | 5.58         | 5.78    | 6.48    |         |
| 8/21/2019  |              |         |         | 5.82    |
| 10/8/2019  | 5.59         | 5.84    |         |         |
| 10/9/2019  |              |         | 6.55    | 5.96    |

# Prediction Limit

Constituent: Sulfate (mg/L) Analysis Run 12/3/2019 2:31 PM View: AP-1 Interwell PL

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

|            | YGWA-47 (bg) | YGWC-44 | YGWC-45 | YGWC-46 |
|------------|--------------|---------|---------|---------|
| 8/30/2016  | 160          |         |         |         |
| 8/31/2016  |              | 150     | 190     |         |
| 9/1/2016   |              |         |         | 770     |
| 11/14/2016 | 150          |         | 200     |         |
| 11/15/2016 |              | 150     |         |         |
| 11/16/2016 |              |         |         | 780     |
| 2/24/2017  | 120          |         |         |         |
| 2/27/2017  |              |         | 190     | 650     |
| 2/28/2017  |              | 130     |         |         |
| 5/8/2017   | 120          | 150     |         | 770     |
| 5/9/2017   |              |         | 190     |         |
| 7/11/2017  | 110          |         |         |         |
| 7/13/2017  |              | 150     | 180     | 630     |
| 10/10/2017 | 93           | 140     | 180     |         |
| 10/11/2017 |              |         |         | 540     |
| 4/2/2018   | 88.8         |         |         |         |
| 4/3/2018   |              |         | 183     |         |
| 4/4/2018   |              | 137     |         | 430     |
| 9/19/2018  | 75           | 137     | 192     | 395     |
| 3/27/2019  | 65.9         | 146     | 188     | 437     |
| 10/8/2019  | 52.3         | 142     |         |         |
| 10/9/2019  |              |         | 183     | <1      |

# Prediction Limit

Constituent: Total Dissolved Solids (mg/L) Analysis Run 12/3/2019 2:31 PM View: AP-1 Interwell PL


Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

|            | YGWA-47 (bg) | YGWC-45 | YGWC-44 | YGWC-46 |
|------------|--------------|---------|---------|---------|
| 8/30/2016  | 319          |         |         |         |
| 8/31/2016  |              | 402     | 332     |         |
| 9/1/2016   |              |         |         | 1240    |
| 11/14/2016 | 280          | 445     |         |         |
| 11/15/2016 |              |         | 356     |         |
| 11/16/2016 |              |         |         | 1220    |
| 2/24/2017  | 162          |         |         |         |
| 2/27/2017  |              | 346     |         | 1060    |
| 2/28/2017  |              |         | 483     |         |
| 5/8/2017   | 194          |         | 296     | 1160    |
| 5/9/2017   |              | 388     |         |         |
| 7/11/2017  | 193          |         |         |         |
| 7/13/2017  |              | 433     | 345     | 996     |
| 10/10/2017 | 175          | 396     | 311     |         |
| 10/11/2017 |              |         |         | 835     |
| 4/2/2018   | 192          |         |         |         |
| 4/3/2018   |              | 418     |         |         |
| 4/4/2018   |              |         | 313     | 1470    |
| 9/19/2018  | 186          | 413     | 326     | 702     |
| 3/27/2019  | 170          | 383     | 302     | 641     |
| 10/8/2019  | 172          |         | 324     |         |
| 10/9/2019  |              | 432     |         | 809     |

Sanitas™ v.9.6.24 Sanitas software licensed to ACC, UG  
Hollow symbols indicate censored values.


Time Series



Constituent: Antimony Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Sanitas™ v.9.6.24 Sanitas software licensed to ACC, UG  
Hollow symbols indicate censored values.


Time Series



Constituent: Barium Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Sanitas™ v.9.6.24 Sanitas software licensed to ACC, UG  
Hollow symbols indicate censored values.


Time Series



Constituent: Arsenic Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1


Sanitas™ v.9.6.24 Sanitas software licensed to ACC, UG  
Hollow symbols indicate censored values.

Time Series




Constituent: Benlyium Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Time Series




Constituent: Boron Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Time Series




Constituent: Cadmium Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Time Series



Constituent: Calcium Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1


Time Series



Constituent: Chloride Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Sanitas™ v.9.6.24 Sanitas software licensed to ACC, UG  
Hollow symbols indicate censored values.


Time Series



Constituent: Chromium Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Sanitas™ v.9.6.24 Sanitas software licensed to ACC, UG  
Hollow symbols indicate censored values.


Time Series



Constituent: Cobalt Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Sanitas™ v.9.6.24 Sanitas software licensed to ACC, UG  
Hollow symbols indicate censored values.


Time Series



Constituent: Combined Radium 226 + 228 Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1


Sanitas™ v.9.6.24 Sanitas software licensed to ACC, UG  
Hollow symbols indicate censored values.

Time Series




Constituent: Fluoride Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Time Series




Constituent: Lead Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Time Series




Constituent: Mercury Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Time Series




Constituent: Lithium Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Time Series




Constituent: Molybdenum Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Time Series




Constituent: pH Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Time Series




Constituent: Selenium Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Time Series




Constituent: Sulfate Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

Time Series



Constituent: Thallium Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1



Constituent: Total Dissolved Solids Analysis Run 12/18/2019 3:13 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

# Trend Test

Plant Yates Client: Southern Company Data: Yates Ash Pond 1 Printed 2/11/2020, 5:44 PM


| <u>Constituent</u> | <u>Well</u>  | <u>Slope</u> | <u>Calc.</u> | <u>Critical</u> | <u>Sig.</u> | <u>N</u> | <u>%NDS</u> | <u>Normality</u> | <u>Xform</u> | <u>Alpha</u> | <u>Method</u> |
|--------------------|--------------|--------------|--------------|-----------------|-------------|----------|-------------|------------------|--------------|--------------|---------------|
| Boron (mg/L)       | YGWA-47 (bg) | -0.00...     | -36          | -30             | Yes         | 10       | 0           | n/a              | n/a          | 0.01         | NP            |
| Boron (mg/L)       | YGWC-46      | -0.4284      | -34          | -30             | Yes         | 10       | 0           | n/a              | n/a          | 0.01         | NP            |
| Calcium (mg/L)     | YGWA-47 (bg) | -3.191       | -43          | -30             | Yes         | 10       | 10          | n/a              | n/a          | 0.01         | NP            |
| Chloride (mg/L)    | YGWC-46      | -5.794       | -41          | -30             | Yes         | 10       | 0           | n/a              | n/a          | 0.01         | NP            |
| Sulfate (mg/L)     | YGWA-47 (bg) | -32.92       | -44          | -30             | Yes         | 10       | 0           | n/a              | n/a          | 0.01         | NP            |

# Trend Test

Plant Yates    Client: Southern Company    Data: Yates Ash Pond 1    Printed 2/11/2020, 5:44 PM


| Constituent                   | Well                | Slope           | Calc.      | Critical   | Sig.       | N         | %NDS      | Normality  | Xform      | Alpha       | Method    |
|-------------------------------|---------------------|-----------------|------------|------------|------------|-----------|-----------|------------|------------|-------------|-----------|
| <b>Boron (mg/L)</b>           | <b>YGWA-47 (bg)</b> | <b>-0.00...</b> | <b>-36</b> | <b>-30</b> | <b>Yes</b> | <b>10</b> | <b>0</b>  | <b>n/a</b> | <b>n/a</b> | <b>0.01</b> | <b>NP</b> |
| Boron (mg/L)                  | YGWC-44             | -0.0226         | -8         | -30        | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| Boron (mg/L)                  | YGWC-45             | 0.00843         | 12         | 30         | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| <b>Boron (mg/L)</b>           | <b>YGWC-46</b>      | <b>-0.4284</b>  | <b>-34</b> | <b>-30</b> | <b>Yes</b> | <b>10</b> | <b>0</b>  | <b>n/a</b> | <b>n/a</b> | <b>0.01</b> | <b>NP</b> |
| <b>Calcium (mg/L)</b>         | <b>YGWA-47 (bg)</b> | <b>-3.191</b>   | <b>-43</b> | <b>-30</b> | <b>Yes</b> | <b>10</b> | <b>10</b> | <b>n/a</b> | <b>n/a</b> | <b>0.01</b> | <b>NP</b> |
| Calcium (mg/L)                | YGWC-44             | 0.2577          | 9          | 30         | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| Calcium (mg/L)                | YGWC-45             | -0.7613         | -10        | -30        | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| Calcium (mg/L)                | YGWC-46             | -18.2           | -28        | -30        | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| Chloride (mg/L)               | YGWA-47 (bg)        | -0.5787         | -18        | -30        | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| Chloride (mg/L)               | YGWC-44             | 0.5703          | 25         | 30         | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| <b>Chloride (mg/L)</b>        | <b>YGWC-46</b>      | <b>-5.794</b>   | <b>-41</b> | <b>-30</b> | <b>Yes</b> | <b>10</b> | <b>0</b>  | <b>n/a</b> | <b>n/a</b> | <b>0.01</b> | <b>NP</b> |
| pH (S.U.)                     | YGWA-47 (bg)        | 0               | -4         | -30        | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| pH (S.U.)                     | YGWC-45             | -0.1736         | -20        | -34        | No         | 11        | 0         | n/a        | n/a        | 0.01        | NP        |
| pH (S.U.)                     | YGWC-46             | -0.04908        | -14        | -34        | No         | 11        | 0         | n/a        | n/a        | 0.01        | NP        |
| <b>Sulfate (mg/L)</b>         | <b>YGWA-47 (bg)</b> | <b>-32.92</b>   | <b>-44</b> | <b>-30</b> | <b>Yes</b> | <b>10</b> | <b>0</b>  | <b>n/a</b> | <b>n/a</b> | <b>0.01</b> | <b>NP</b> |
| Sulfate (mg/L)                | YGWC-45             | -2.253          | -12        | -30        | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| Total Dissolved Solids (mg/L) | YGWA-47 (bg)        | -13.31          | -25        | -30        | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| Total Dissolved Solids (mg/L) | YGWC-44             | -11.25          | -13        | -30        | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| Total Dissolved Solids (mg/L) | YGWC-45             | 5.36            | 1          | 30         | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |
| Total Dissolved Solids (mg/L) | YGWC-46             | -201.8          | -27        | -30        | No         | 10        | 0         | n/a        | n/a        | 0.01        | NP        |

### Sen's Slope Estimator




Constituent: Boron Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: Boron Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: Boron Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: Boron Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: Chloride Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: Chloride Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: Chloride Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator



Constituent: pH Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1


### Sen's Slope Estimator



n = 10  
Slope = -3.191  
units per year.  
Mann-Kendall  
statistic = -43  
critical = -30  
Decreasing trend  
significant at 99%  
confidence level  
( $\alpha = 0.005$  per  
tail).

Constituent: Calcium Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1


### Sen's Slope Estimator



n = 10  
Slope = 0.2577  
units per year.  
Mann-Kendall  
statistic = 9  
critical = 30  
Trend not sig-  
nificant at 99%  
confidence level  
( $\alpha = 0.005$  per  
tail).

Constituent: Calcium Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1


### Sen's Slope Estimator



n = 10  
Slope = -0.7613  
units per year.  
Mann-Kendall  
statistic = -10  
critical = -30  
Trend not sig-  
nificant at 99%  
confidence level  
( $\alpha = 0.005$  per  
tail).

Constituent: Calcium Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1


### Sen's Slope Estimator



n = 10  
Slope = -16.2  
units per year.  
Mann-Kendall  
statistic = -28  
critical = -30  
Trend not sig-  
nificant at 99%  
confidence level  
( $\alpha = 0.005$  per  
tail).


Constituent: Calcium Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: pH Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
 Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: pH Analysis Run 2/11/2020 5:40 PM View: AP-1 Time Series  
 Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: Sulfate Analysis Run 2/11/2020 5:41 PM View: AP-1 Time Series  
 Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: Sulfate Analysis Run 2/11/2020 5:41 PM View: AP-1 Time Series  
 Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: Total Dissolved Solids Analysis Run 2/11/2020 5:41 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator




Constituent: Total Dissolved Solids Analysis Run 2/11/2020 5:41 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator



Constituent: Total Dissolved Solids Analysis Run 2/11/2020 5:41 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

### Sen's Slope Estimator



Constituent: Total Dissolved Solids Analysis Run 2/11/2020 5:41 PM View: AP-1 Time Series  
Plant Yates Client: Southern Company Data: Yates Ash Pond 1

# Sen's Slope Estimator

Constituent: Boron (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWA-47 (bg)

|            |            |
|------------|------------|
| 8/30/2016  | 0.0166 (J) |
| 11/14/2016 | 0.0166 (J) |
| 2/24/2017  | 0.0145 (J) |
| 5/8/2017   | 0.0141 (J) |
| 7/11/2017  | 0.0131 (J) |
| 10/10/2017 | 0.0124 (J) |
| 4/2/2018   | 0.013 (J)  |
| 9/19/2018  | 0.012 (J)  |
| 3/27/2019  | 0.013 (J)  |
| 10/8/2019  | 0.012 (J)  |

# Sen's Slope Estimator

Constituent: Boron (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-44

|            |       |
|------------|-------|
| 8/31/2016  | 0.541 |
| 11/15/2016 | 0.706 |
| 2/28/2017  | 0.623 |
| 5/8/2017   | 0.69  |
| 7/13/2017  | 0.649 |
| 10/10/2017 | 0.603 |
| 4/4/2018   | 0.66  |
| 9/19/2018  | 0.66  |
| 3/27/2019  | 0.57  |
| 10/8/2019  | 0.58  |

# Sen's Slope Estimator

Constituent: Boron (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-45

|            |       |
|------------|-------|
| 8/31/2016  | 0.308 |
| 11/14/2016 | 0.368 |
| 2/27/2017  | 0.321 |
| 5/9/2017   | 0.338 |
| 7/13/2017  | 0.34  |
| 10/10/2017 | 0.319 |
| 4/3/2018   | 0.35  |
| 9/19/2018  | 0.35  |
| 3/27/2019  | 0.33  |
| 10/9/2019  | 0.35  |

# Sen's Slope Estimator

Constituent: Boron (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-46

|            |      |
|------------|------|
| 9/1/2016   | 2.12 |
| 11/16/2016 | 2.03 |
| 2/27/2017  | 1.29 |
| 5/8/2017   | 1.71 |
| 7/13/2017  | 1.62 |
| 10/11/2017 | 1.17 |
| 4/4/2018   | 1.2  |
| 9/19/2018  | 1.2  |
| 3/27/2019  | 0.89 |
| 10/9/2019  | 1.1  |

# Sen's Slope Estimator

Constituent: Calcium (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWA-47 (bg)

|            |          |
|------------|----------|
| 8/30/2016  | 20.9     |
| 11/14/2016 | 18.6     |
| 2/24/2017  | 16.1     |
| 5/8/2017   | 14.6     |
| 7/11/2017  | 14.3     |
| 10/10/2017 | 12.1     |
| 4/2/2018   | <25      |
| 9/19/2018  | 11.1 (J) |
| 3/27/2019  | 10.8 (J) |
| 10/8/2019  | 9.7      |

# Sen's Slope Estimator

Constituent: Calcium (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-44

|            |      |
|------------|------|
| 8/31/2016  | 27.3 |
| 11/15/2016 | 27.8 |
| 2/28/2017  | 26.4 |
| 5/8/2017   | 29.9 |
| 7/13/2017  | 30.2 |
| 10/10/2017 | 27.2 |
| 4/4/2018   | 30.1 |
| 9/19/2018  | 29.2 |
| 3/27/2019  | 27.9 |
| 10/8/2019  | 28.1 |

# Sen's Slope Estimator

Constituent: Calcium (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-45

|            |      |
|------------|------|
| 8/31/2016  | 46.7 |
| 11/14/2016 | 50.6 |
| 2/27/2017  | 49.4 |
| 5/9/2017   | 56   |
| 7/13/2017  | 54.8 |
| 10/10/2017 | 52.8 |
| 4/3/2018   | 50.6 |
| 9/19/2018  | 50.5 |
| 3/27/2019  | 48.8 |
| 10/9/2019  | 47.9 |

# Sen's Slope Estimator

Constituent: Calcium (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-46

|            |      |
|------------|------|
| 9/1/2016   | 96.8 |
| 11/16/2016 | 107  |
| 2/27/2017  | 104  |
| 5/8/2017   | 103  |
| 7/13/2017  | 83.7 |
| 10/11/2017 | 69   |
| 4/4/2018   | 51.9 |
| 9/19/2018  | 51.9 |
| 3/27/2019  | 54.2 |
| 10/9/2019  | 64.2 |

# Sen's Slope Estimator

Constituent: Chloride (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWA-47 (bg)

|            |     |
|------------|-----|
| 8/30/2016  | 5.2 |
| 11/14/2016 | 6.4 |
| 2/24/2017  | 5.5 |
| 5/8/2017   | 5.8 |
| 7/11/2017  | 5.8 |
| 10/10/2017 | 5.9 |
| 4/2/2018   | 4.8 |
| 9/19/2018  | 4   |
| 3/27/2019  | 4.3 |
| 10/8/2019  | 4.4 |

# Sen's Slope Estimator

Constituent: Chloride (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-44

|            |      |
|------------|------|
| 8/31/2016  | 13   |
| 11/15/2016 | 14   |
| 2/28/2017  | 12   |
| 5/8/2017   | 13   |
| 7/13/2017  | 13   |
| 10/10/2017 | 14   |
| 4/4/2018   | 13.4 |
| 9/19/2018  | 14.2 |
| 3/27/2019  | 14   |
| 10/8/2019  | 14.8 |

# Sen's Slope Estimator

Constituent: Chloride (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-46

|            |      |
|------------|------|
| 9/1/2016   | 37   |
| 11/16/2016 | 37   |
| 2/27/2017  | 33   |
| 5/8/2017   | 33   |
| 7/13/2017  | 32   |
| 10/11/2017 | 29   |
| 4/4/2018   | 26.6 |
| 9/19/2018  | 26.5 |
| 3/27/2019  | 20.9 |
| 10/9/2019  | 25   |

# Sen's Slope Estimator

Constituent: pH (S.U.) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWA-47 (bg)

|            |         |
|------------|---------|
| 8/30/2016  | 5.75    |
| 11/14/2016 | 5.59    |
| 2/24/2017  | 5.49    |
| 5/8/2017   | 5.58    |
| 7/11/2017  | 5.58    |
| 10/10/2017 | 5.49    |
| 4/2/2018   | 6.3 (o) |
| 9/19/2018  | 5.48    |
| 3/27/2019  | 5.83    |
| 8/20/2019  | 5.58    |
| 10/8/2019  | 5.59    |

# Sen's Slope Estimator

Constituent: pH (S.U.) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-45

|            |      |
|------------|------|
| 8/31/2016  | 7.15 |
| 11/14/2016 | 6.96 |
| 2/27/2017  | 6.79 |
| 5/9/2017   | 6.9  |
| 7/13/2017  | 6.77 |
| 10/10/2017 | 6.9  |
| 4/3/2018   | 6.44 |
| 9/19/2018  | 6.47 |
| 3/27/2019  | 7.18 |
| 8/20/2019  | 6.48 |
| 10/9/2019  | 6.55 |

# Sen's Slope Estimator

Constituent: pH (S.U.) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-46

|            |      |
|------------|------|
| 9/1/2016   | 6.19 |
| 11/16/2016 | 6.05 |
| 2/27/2017  | 6.01 |
| 5/8/2017   | 6.1  |
| 7/13/2017  | 6.07 |
| 10/11/2017 | 5.93 |
| 4/4/2018   | 6.01 |
| 9/19/2018  | 6.09 |
| 3/27/2019  | 6.2  |
| 8/21/2019  | 5.82 |
| 10/9/2019  | 5.96 |

# Sen's Slope Estimator

Constituent: Sulfate (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWA-47 (bg)

|            |      |
|------------|------|
| 8/30/2016  | 160  |
| 11/14/2016 | 150  |
| 2/24/2017  | 120  |
| 5/8/2017   | 120  |
| 7/11/2017  | 110  |
| 10/10/2017 | 93   |
| 4/2/2018   | 88.8 |
| 9/19/2018  | 75   |
| 3/27/2019  | 65.9 |
| 10/8/2019  | 52.3 |

# Sen's Slope Estimator

Constituent: Sulfate (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-45

|            |     |
|------------|-----|
| 8/31/2016  | 190 |
| 11/14/2016 | 200 |
| 2/27/2017  | 190 |
| 5/9/2017   | 190 |
| 7/13/2017  | 180 |
| 10/10/2017 | 180 |
| 4/3/2018   | 183 |
| 9/19/2018  | 192 |
| 3/27/2019  | 188 |
| 10/9/2019  | 183 |

# Sen's Slope Estimator

Constituent: Total Dissolved Solids (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWA-47 (bg)

|            |     |
|------------|-----|
| 8/30/2016  | 319 |
| 11/14/2016 | 280 |
| 2/24/2017  | 162 |
| 5/8/2017   | 194 |
| 7/11/2017  | 193 |
| 10/10/2017 | 175 |
| 4/2/2018   | 192 |
| 9/19/2018  | 186 |
| 3/27/2019  | 170 |
| 10/8/2019  | 172 |

# Sen's Slope Estimator

Constituent: Total Dissolved Solids (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-44

|            |     |
|------------|-----|
| 8/31/2016  | 332 |
| 11/15/2016 | 356 |
| 2/28/2017  | 483 |
| 5/8/2017   | 296 |
| 7/13/2017  | 345 |
| 10/10/2017 | 311 |
| 4/4/2018   | 313 |
| 9/19/2018  | 326 |
| 3/27/2019  | 302 |
| 10/8/2019  | 324 |

# Sen's Slope Estimator

Constituent: Total Dissolved Solids (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

YGWC-45

|            |     |
|------------|-----|
| 8/31/2016  | 402 |
| 11/14/2016 | 445 |
| 2/27/2017  | 346 |
| 5/9/2017   | 388 |
| 7/13/2017  | 433 |
| 10/10/2017 | 396 |
| 4/3/2018   | 418 |
| 9/19/2018  | 413 |
| 3/27/2019  | 383 |
| 10/9/2019  | 432 |

# Sen's Slope Estimator

Constituent: Total Dissolved Solids (mg/L) Analysis Run 2/11/2020 5:44 PM View: AP-1 Time Series

Plant Yates Client: Southern Company Data: Yates Ash Pond 1

---

|            | YGWC-46 |
|------------|---------|
| 9/1/2016   | 1240    |
| 11/16/2016 | 1220    |
| 2/27/2017  | 1060    |
| 5/8/2017   | 1160    |
| 7/13/2017  | 996     |
| 10/11/2017 | 835     |
| 4/4/2018   | 1470    |
| 9/19/2018  | 702     |
| 3/27/2019  | 641     |
| 10/9/2019  | 809     |



**ATLANTIC COAST  
CONSULTING, INC.**

Roswell, GA  
630 Colonial Park Drive  
Suite 110  
Roswell, GA 30075  
Phone: 770.594.5998

Savannah, GA  
7 East Congress Street  
Suite 801  
Savannah, GA 31401  
Phone: 912.236.3471

Knoxville, TN  
212 S. Peters Road  
Suite 203  
Knoxville, TN 37923  
Phone: 865.531.9143