§ 257.100(f)(3)(iv) as set forth by §257.83(b)	REPORT OF ANNUA	AL INSPECTION OF CCI	R SURFACE	IMPO	UNDMENT	
	FACILITY NAME: Plant Branch Ash Pond E (AP-E)					
	OWNER/OPERATOR OF FACILITY: Georgia Power Company					
	INSPECTION DATE: October 30, 2024					
	INSPECTING ENGINEER: Patrick B. Rhodes, P.E. (Georgia P.E. License #24586)					
(i)	ANY CHANGES IN GEOMETRY OF THE IMPOUNDING STRUCTURE SINCE THE PREVIOUS ANNUAL INSPECTION?				N/A ⁽¹⁾	
	(IF YES, DESCRIBE):					
(ii)	LOCATION AND TYPE OF			See	Attached Plan	
(ii)	MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION N/A ⁽¹⁾			N/A ⁽¹⁾		
(iii)	APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION (1)				VATION OF THE	
	MIN. DEPTH: N/A	MAX. DEPTH: N/A	PRESENT D	EPTH: 2	ft	
	MIN. ELEVATION: N/A	MAX. ELEVATION: N/A	PRESENT EI	LEVATIO	N: 412 ft	
(iii)	APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVAL SINCE PREVIOUS ANNUAL INSPECTION (1)				VATION OF CCR	
	MIN. DEPTH: N/A MAX. DEPTH: N/A PRESENT DEPTH: Up to 62 ft			Jp to 62 ft		
	MIN. ELEVATION: N/A	MAX. ELEVATION: N/A	PRESENT ELEVATION: Up to 428		ON: Up to 428 ft	
(iv)	APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 12,768,000 yd ^{3 (2)} INSPECTION			00 yd ^{3 (2)}		
(v)	APPROXIMATE VOLUME OF IMPOUNDED		WATER:	C	CR:	
	WATER AND CCR AT TIMI	E OF INSPECTION	25,000 yd ³	10),893,000 yd ³	
(vi)	ANY APPEARANCE OF AN ACTUAL OR POTENTIAL STRUCTURAL WEAKNESS OF THE CCR UNIT, IN ADDITION TO ANY EXISTING CONDITIONS THAT ARE DISRUPTING OR HAVE THE POTENTIAL TO DISRUPT THE OPERATION AND SAFETY OF THE CCR UNIT AND APPURTENANT STRUCTURES?					
	(IF YES, DESCRIBE):					
(vii)	ANY OTHER CHANGE(S) WHICH MAY HAVE AFFECTED THE STABILITY OR OPERATION SINCE THE PREVIOUS ANNUAL INSPECTION?			No		
	(IF YES, DESCRIBE):					

⁽¹⁾ This is the first Annual inspection by a qualified professional engineer' performed in accordance with 40 CFR Part 257.100(f)(3)(iv). This information will be included in subsequent annual inspection reports.

(2) Approximate storage capacity of impounding structure is estimated as the total storage volume of the pond up to the auxiliary spillway crest elevation of 430 feet.

INSTRUMENTATION PLAN PLANT BRANCH ASH POND E



LOCATION, TYPE, & MAXIMUM RECORDED READINGS OF INSTRUMENTATION PLANT BRANCH ASH POND E PIEZOMETERS

	FIEZOWETERS					
Instrument	Location		Maximum Elevation			
Instrument	Latitude	Longitude	Since Last Inspection (ft) (1)			
PZ-1 ⁽²⁾	33.20580929	-83.32476293	N/A			
PZ-2 ⁽²⁾	33.20419757	-83.32441830	N/A			
PZ-3 ⁽²⁾	33.20420819	-83.32434329	N/A			
PZ-4 ⁽²⁾	33.20424460	-83.32414624	N/A			
PZ-5 ⁽²⁾	33.20430657	-83.32378522	N/A			
PZ-6 ⁽²⁾	33.20271879	-83.32409875	N/A			
PZ-7 ⁽²⁾	33.20281515	-83.32352099	N/A			
PZ-8 ⁽²⁾	33.20428014	-83.32378146	N/A			
PZ-9 ⁽²⁾	33.20540444	-83.32391417	N/A			
PZ-10 ⁽²⁾	33.20604602	-83.32413766	N/A			
PZ-11 ⁽²⁾	33.20496699	-83.32378331	N/A			
PZ-12 ⁽²⁾	33.20326214	-83.32340341	N/A			
PZ-13 ⁽²⁾	33.20698095	-83.32451821	N/A			
PZ-14 ⁽²⁾	33.20718234	-83.32458598	N/A			
PZ-15 ⁽²⁾	33.20651972	-83.32410928	N/A			
PZ-16 ⁽²⁾	33.20640653	-83.32399911	N/A			
PZ-17 ⁽²⁾	33.20603278	-83.32381761	N/A			
PZ-18 ⁽²⁾	33.20557398	-83.3237189	N/A			
PZ-19 ⁽²⁾	33.20555105	-83.32370188	N/A			

- (1) This is the first 'Annual inspection by a qualified professional engineer' performed in accordance with 40 CFR Part 257.100(f)(3)(iv). This information will be included in subsequent annual inspection reports.
- (2) The location (latitude/longitude) has been updated from the February 10, 2025, submittal.

DRAIN FLOWS

Drain	Location		Maximum Flow Since Last Inspection
	Latitude	Longitude	(gpm) ⁽¹⁾
FG-1 ⁽²⁾	33.20748986	-83.32475475	N/A
FG-2 ⁽²⁾	33.20708146	-83.32460902	N/A
FG-3 ⁽²⁾	33.20646124	-83.32439091	N/A
FG-4 ⁽²⁾	33.20588791	-83.32415227	N/A
FG-5 ⁽²⁾	33.20547361	-83.32400495	N/A
FG-6 ⁽²⁾	33.20476784	-83.32378386	N/A
FG-7 ⁽²⁾	33.20470185	-83.32376770	N/A
FG-8 ⁽²⁾	33.20415687	-83.32362897	N/A
FG-9 ⁽²⁾	33.20361973	-83.32350809	N/A
FG-9A ⁽²⁾	33.20324104	-83.32345802	N/A
FG-10 ⁽²⁾	33.20313071	-83.32343776	N/A
FG-11 ⁽²⁾	33.202516356	-83.32331255	N/A

- (1) This is the first 'Annual inspection by a qualified professional engineer' performed in accordance with 40 CFR Part 257.100(f)(3)(iv). This information will be included in subsequent annual inspection reports.
- (2) The location (latitude/longitude) has been updated from the February 10, 2025, submittal.

RELIEF WELL FLOWS

Relief Well	Location		Maximum Flow Since Last Inspection
	Latitude	Longitude	(gpm) ⁽¹⁾
W-1 ⁽²⁾	33.20542838	-83.32390451	N/A
W-2 ⁽²⁾	33.20516958	-83.32382802	N/A
W-3 ⁽²⁾	33.20499199	-83.32377080	N/A
W-4 ⁽²⁾	33.20481944	-83.32372247	N/A
W-5 ⁽²⁾	33.20464231	-83.32368336	N/A
W-6 ⁽²⁾	33.20445903	-83.32363479	N/A
W-7 ⁽²⁾	33.20424880	-83.32357356	N/A
W-8 ⁽²⁾	33.20414244	-83.32354710	N/A
W-9 ⁽²⁾	33.20403149	-83.32351424	N/A
W-10 ⁽²⁾	33.20347660	-83.32341737	N/A

⁽¹⁾ This is the first 'Annual inspection by a qualified professional engineer' performed in accordance with 40 CFR Part 257.100(f)(3)(iv). This information will be included in subsequent annual inspection reports.

⁽²⁾ The location (latitude/longitude) has been updated from the February 10, 2025, submittal.